



# New Standards. Together

Presented by  
Helge Hicken / ESMNG




# Introduction - AIRBUS sandwich structures

The NDT procedures are valid for flat or shallow curved undisturbed honeycomb sandwich structures.

## Challenge:

Single sided access for In Service A/C. Need to inspect the opposite side of the sandwich structure for defects.



CL: FOR DAMAGE TYPES A, B, C, D, E AND F HORIZONTAL

COVER LAYER, MATERIAL CFRP OR GFRP, T3 = THICKNESS OF COVER LAYER, THICKNESS: MINIMUM = 0.4 mm (0.016 in), MAXIMUM = 2.5 mm (0.098 in).

CL: FOR DAMAGE TYPE F VERTICAL

COVER LAYER, MATERIAL CFRP OR GFRP, T3 = THICKNESS OF COVER LAYER, THICKNESS: MINIMUM = 0.4 mm (0.016 in), MAXIMUM = 6.5 mm (0.256 in).



HC: HONEYCOMB CORE, MATERIAL NOMEK HONEYCOMB WITH THE FOLLOWING CELL WIDTH (CW) AND STIFFNESS (S):

- CW = 3.2 mm (0.126 in) AND S = 48 kg/m<sup>3</sup>
- CW = 4.8 mm (0.189 in) AND S = 32 kg/m<sup>3</sup>
- CW = 4.8 mm (0.189 in) AND S = 48 kg/m<sup>3</sup>
- CW = 4.8 mm (0.189 in) AND S = 64 kg/m<sup>3</sup>
- CW = 6.4 mm (0.252 in) AND S = 24 kg/m<sup>3</sup>
- CW = 6.4 mm (0.252 in) AND S = 32 kg/m<sup>3</sup>
- CW = 6.4 mm (0.252 in) AND S = 48 kg/m<sup>3</sup>

T1: MINIMUM HONEYCOMB HEIGHT = 30 mm (1.181 in).

T2: MAXIMUM HONEYCOMB HEIGHT = 40 mm (1.575 in).

# Possible Damage of FRP Sandwich Structures



Type A: Delamination between the layers of the outer composite skin, parallel to the inspection surface

Type B: Disbond between the outer skin and the honeycomb core

Type C: Cracked honeycomb core parallel to the inspection surface

Type D: Crushed honeycomb core in the parallel area




Type E: Disbond between the inner skin and the honeycomb core

Type F (horizontal / vertical): Fluid ingress into the honeycomb core

# Manual Tap Test / WOODPECKER Inspection


Detection of outer skin delamination / disbonding and cracked core (outer skin thickness max. 2 mm, > 25 x 25 mm detectable damage size in max. 25 mm depth)

## Manual Tap Test



# ELCH (Elasticity Laminate Checker) Inspection

Detection of outer / inner skin disbonding and cracked core (outer skin thickness max. 1.5 mm, > Ø 110 mm detectable damage size, test grid 50 x 50 mm)




ELCH puts a defined force perpendicular to the surface, all expected disbonding cases will be detected as a stiffness loss comes with the disbonding.




# ELCH Inspection Principle

- Loading with a defined vacuum
- Deformation measurement under load
- Max. skin thickness 1.5 mm




# X-Ray Inspection

Detection of fluids in honeycomb cells (very sensitive to fluid accumulation, weak radiation 25 kV is mandatory, big effort to perform inspection)



**NOTE:**


DUE TO THE CAPILLARITY AND THE FORCE OF GRAVITY THE FLUIDITY SHAPES IN THE AIRFRAMES, SHOWN ON SECTION OF A-A, RESULT. SEE ALSO TO THE TYPICAL X-RAY INDICATIONS OF FLUIDITY SHOWN IN THE EXAMPLE OF RADIOGRAPHS







# Infra Red Thermography Inspection / Fluid

Detection of fluid in honeycomb core cells (outer skin thickness max. 1.5 mm, detectable damage > 6 ml fluid in sandwich structures up to 40 mm, composite must not be damaged by overheating, new inspection Levels IRT required as per EN 4179 and NAS 410)






# Infra Red Thermography Inspection Example / Fluid




# Infra Red Thermography Inspection Additional FRP Layers

Infra Red „GECKO“ to detect additional FRP layers

Infra Red Camara, 9 Hz,  
Spectral range 7.5 - 13.5  $\mu m$





Halogen Lamp  
850 - 1250 W




# Infra Red Thermography Inspection Additional FRP Layers

Detection of additional FRP layers (max. paint thickness incl. decal foils < 800  $\mu\text{m}$ , *additional 0.25 mm GFRP layer detectable, surface maybe painted matt black (removable)*)



# Ultrasonic Impulse Echo Inspection

Detection of delamination on the outer composite skin, outer / inner skin disbonding, cracked honeycomb core, crushed honeycomb core and fluid ingress (outer skin thickness up to  $> 5$  mm,  $> 25 \times 25$  mm detectable damage size, sandwich thickness up to  $> 40$  mm)






# Ultrasonic Impulse Echo Inspection Principle


The UT Impulse Echo Procedure uses a kind of guided waves.

The System must be tuned to the core height (membrane length =  $\frac{1}{2} \lambda$ )

Transducer operates with a certain bandwidth – disbonding causes a resonance shift to longer wavelength  $\lambda$  -> lower frequency, echoes with lower frequency excite only reduced amplitude in transducer.



Amplitude reduction  
by resonance change



# Ultrasonic Phased Array Impulse Echo Inspection

Impulse Echo  
Ultrasonic Phased  
Array (PAUT) scan  
configuration.  
(PAUT equipment,  
1 MHz probe with  
water delay and  
wheel encoder)



It is possible to  
inspect moderate  
tapered areas by  
adapted ultrasonic  
beam forming.






# Principle of linear electronic scanning

The linear scan is achieved by multiplexing of a single, constant *Focal Law* along a Linear-Array



# Ultrasonic Phased Array Inspection Results

Test Specimen  
with  
Honeycombcore  
Cracks



PAUT Results:  
clear indication of  
affected areas  
(Results also  
confirmed with  
conventional single  
UT probe  
inspection)

# Conclusion

- UT & ELCH were developed to detect disbanded or cracked core of the far side of the sandwich structure under maintenance conditions with the required level of inspection sensitivity.
- New NDI Infra Red Thermography method and training was established to detect fluid ingress and repairs.
- These new NDI procedures guarantee the airworthy condition of the inspected parts.



© AIRBUS Operations GmbH. All rights reserved. Confidential and proprietary document. This document and all information contained herein is the sole property of AIRBUS Operations GmbH. No intellectual property rights are granted by the delivery of this document or the disclosure of its content. This document shall not be reproduced or disclosed to a third party without the express written consent of AIRBUS Operations GmbH. This document and its content shall not be used for any purpose other than that for which it is supplied. The statements made herein do not constitute an offer. They are based on the mentioned assumptions and are expressed in good faith. Where the supporting grounds for these statements are not shown, AIRBUS Operations GmbH will be pleased to explain the basis thereof. AIRBUS, its logo, A300, A310, A318, A319, A320, A321, A330, A340, A350, A380, A400M are registered trademarks.