



# **Metallic Duct Fitting**

using Additive Manufacturing

Jan Nelle | AM-Center | 09.11.2021




**Lufthansa Technik**

# Duct Fitting (generic)

## Part Description

- The **considered fitting** is part of the **engine bleed system**
- It connects the **bleed air tube** to the **airframe**
- Affected tube leads the **hot bleed air** of the engine to supply hot air **for anti icing** function
- It is located in a **non-pressurized area**



### Dimensions and Weight (approx.)

- **100mm x 50mm x 10mm**
- **< 500 gram**

# Duct Fitting

## Safety Assessment

### Expected Loads

Maximum Flight loads, Emergency Landing Loads

### Worst Failure Scenario

Crack, looseness, loss ... When? (Flight Phase)

### Effects on related Systems

E.g. due to loose remains of damaged part

### Failure Detection

Regular inspection, threshold, location ...


### Resulting Effect on Aircraft Level

CS-25.1309 Equipment, systems and installations.

Can differ to effect on Engine Level, e.g. depending on number of engines

### Secondary or Primary Structure

Acc. Structural Classification



### Possible Part Failures

Wear, tear, elongation, cracks ..

### Failure Affect on the System

No effect, limited, total system loss ...

### Effect on Engine Level

CS-E 510 - Safety Analysis, a safe engine shut down is considered as minor safety effect on engine level

### Impact on the Flight Operation

Impact on aircraft operation, crew or passengers

### Different Failure Mode due to AM ?

Failures because of new manufacturing method, material or design

# Duct Fitting

## LHT Design Classification Guideline

Structural function of AM part


### Consequence of failure

	No Safety effect	Minor	Major	Hazardous/ Catastrophic
Principle structural elements or fatigue critical				
Significantly loaded secondary structure parts				
Novelty (cavities, bionic-design optimization, novel application, new materials)				
Low loaded secondary structure parts				
Non loaded/decorative parts >500 gram				
Non loaded/decorative parts < 500 gram				

**Criticality**

# Duct Fitting




## Requirements acc. Classification Guideline



# Duct Fitting

## Resulting Qualification Program

- (FEM) Analysis performed in order to find the occurring loads and most loaded areas
- Material Specification and Material Qualification available. Provided by 21/G and verified by 21/J
- Part Qualification Program carried out. Three qualification builds performed. Build jobs include parts and specimens
- Test for tensile strength, fatigue and hardness performed
- Part Inspection by FPI and X-Ray
- Parts have been cut and microstructure analyzed
- Destructive test of additive manufactured part to compare results with original design



- Part Qualification program confirmed the material specification properties
- Constant quality (porosity and hardness) over the whole part



# Thank you for your attention!

Copyright © 2021 Lufthansa Technik AG. All rights reserved.

The information contained in this presentation is proprietary to Lufthansa Technik AG and is disclosed in confidence. The presentation and the information contained herein shall be kept strictly confidential and shall not be used, disclosed to others or reproduced without the expressed written consent of Lufthansa Technik AG. Nothing contained in this publication shall constitute any warranty, guarantee or liability for Lufthansa Technik AG, its subsidiaries and affiliates, but is for information purposes only. Accordingly, Lufthansa Technik AG, its subsidiaries and affiliates neither expressly nor conclusively accept responsibility or liability for the actuality, accuracy and completeness of the statements and information contained in this publication.



**Lufthansa Technik**