

EOFDM 3rd conference

Géraud de RIVALS
Flight Operations Analysis

Landing Trajectory Computation



Introduction

- Flight Data Monitoring programs use **trajectories** for
 - Touch-down location
 - Approach monitoring
 - Runway overrun risk monitoring
 - Comparisons with remaining runway lengths
 - Detection of poor landing performances
- Common assumption of these programs: good **accuracy** of the trajectory
 - Is it true?
 - How to assess the accuracy?
 - How to improve the accuracy?

Introduction



**Trajectory Computation
+
Trajectory accuracy assessment**


Contents

- Trajectories available on board
- Recorded trajectories
- Post treatment trajectory computation
- Accuracy assessment
- Vertical Speed computation and Touch down detection
- Conclusion

Contents

- Trajectories available on board
- Recorded trajectories
- Post treatment trajectory computation
- Accuracy assessment
- Vertical Speed computation and Touch down detection
- Conclusion

Trajectories available on board



IRS


- Needs initialization (at the gate)
- Short term good accuracy
- Long term poor accuracy (2Nm/h)



GPS

- Good accuracy (GPS Primary 0.056Nm)
- Depends on Satellite configuration

Trajectories available on board




Trajectories available on board



GPS



GPIRS



IRS



FMS



DMC/EFIS

Displays the FMS trajectory


Trajectories available on board



GPS



GPIRS



IRS



FMS




DMC/EFIS

Contents

- Trajectories available on board
- Recorded trajectories
- Post treatment trajectory computation
- Accuracy assessment
- Vertical Speed computation and Touch down detection
- Conclusion

Recorded IRS Trajectories Landings on the same runway

8Nm



Recorded trajectory per airline

Airline 1

Source	IRS 
Nb bits	20
Latitude Resolution	38m
Sampling rate	$\frac{1}{4}$ Hz



Recorded trajectory per airline

Airline 2


Source	IRS 	GPS 
Nb bits	20	21
Latitude Resolution	38m	19m
Sampling rate	$\frac{1}{4}$ Hz	1Hz



Recorded trajectory per airline

Airline 3


Source	IRS 	GPS 	FMS 
Nb bits	20	21	21
Latitude Resolution	38m	19m	19m
Sampling rate	$\frac{1}{4}$ Hz	1Hz	1Hz



Recorded trajectory per airline


Airline 4

Source	IRS 	GPS 	FMS 	DMC 
Nb bits	20	21	21	21
Latitude Resolution	38m	19m	19m	19m
Sampling rate	¼ Hz	1Hz	1Hz	½ Hz



Recorded trajectory per airline

Airline 5

Source	IRS 	GPS 	FMS 	DMC 	GPS 
Nb bits	20	21	21	21	32
Latitude Resolution	38m	19m	19m	19m	1cm
Sampling rate	$\frac{1}{4}$ Hz	1Hz	1Hz	$\frac{1}{2}$ Hz	4 Hz



Recorded trajectory per airline: comparison of the selections

Source	IRS 	GPS 	FMS 	DMC 	GPS 
Nb bits	20	21	21	21	32
Latitude Resolution	38m	19m	19m	19m	1cm
Sampling rate	¼ Hz	1Hz	1Hz	½ Hz	4 Hz



Recommendation for the selection of the recorded trajectory:


Source: **FMS or DMC**

Nb bits: **21**

Sampling rate: **4Hz**

GS = 140kts \approx 70m/s

Resolution & Sampling Rate: impact on the trajectory accuracy



Impact of Sampling Rate:

- Recorded Point = **True Point**
- Between True Points: unknown values


Impact of Resolution (most of the cases):

e.g. Actual Ground Speed = 138.8kts, resolution 1kt => recorded GS = 138kts


→ **Our recommendation to reduce the impact of the resolution:**
Add half of a Resolution

Accumulation of errors in the signal chain

- **Recorded Data** gives an **approximation** of the **measured Data** on board (which is an approximation of the actual data)



Example: Touch down location from recorded data



Contents


- Trajectories available on board
- Recorded trajectories
- **Post treatment trajectory computation**
- Accuracy assessment
- Vertical Speed computation and Touch down detection
- Conclusion

Post treatment trajectory computation

- Available trajectories on board may have poor accuracy
- **Post treatment computation** thanks to the available parameters?
 - Lateral
 - Longitudinal
 - And time: link with events (e.g. touch down)
- A 3-step method is presented here

Post treatment: trajectory computation step 1

Step 1 - $f(\text{Ground speed, route})$




- Needs good initialization at t_0 (position)
- Easy to compute
- Needs route (or heading & drift angle)
- Adds up the errors along the integration




Post treatment: trajectory computation step 2

Step 2 - ILS



Post treatment: trajectory computation step 3

Step 3 – (GS, Route) + ILS + applying corrections



ILS trajectory


Used for the initialization of the trajectory

Too far from the runway:
ILS perturbed

Post treatment: trajectory computation step 3

Step 3 – (GS, Route) + ILS + applying corrections


Y



X

Post treatment: trajectory computation step 3

Step 3 – (GS, Route) + ILS + applying corrections



Twisted trajectory:
final result

Contents

- Trajectories available on board
- Recorded trajectories
- Post treatment trajectory computation
- **Accuracy assessment**
- Vertical Speed computation and Touch down detection
- Conclusion

Accuracy assessment using visual technique

Recorded trajectory + ½ resolution

Source = DMC

585 flights


Coverage = 70m



Accuracy assessment using visual technique

Post Treatment computation

102 flights



Accuracy assessment: cross check using Flight Test data

- Flight Test Data (A380 MSN1):
 - DGPS position (30cm accuracy) => set as the reference
 - Post Treatment computation compared to the reference

Post Treatment Computation

Inaccuracy = 180m

Differential GPS


X, Y Check



Accuracy assessment: cross check using Flight Test data

- Flight Test Data (A380 MSN1):
 - DGPS position (30cm accuracy) => set as the reference
 - Post Treatment computation compared to the reference



Time Check



Contents

- Trajectories available on board
- Recorded trajectories
- Post treatment trajectory computation
- Accuracy assessment
- Vertical Speed computation and Touch down detection
- Conclusion

Touchdown detection - VZ post computation



Objective:

Compute an accurate vertical speed with sufficient sampling rate for analyzing aircraft's impact on ground.

Problem:

On most common flight data recorders, simple derivation of altitude (or radio-altitude) is not satisfactory because of its sampling rate (1 Hz).


Solution:

Use the accelerometers with a sufficient sampling rate (8 Hz) and combine the results with the recorded altitude above airfield (1Hz) to compute the vertical speed.

Touchdown detection - VZ post computation

1st step:

Computation of elevation above runway = double integration of computed vertical acceleration $ACCZ_C$



$ACCZ_C$ = function(aircraft's attitude and accelerometers)
Vertical acceleration calculated in runway coordinates

VZ_C = Integration of $ACCZ_C$
Computed Vertical speed

1st integration

Z_C = integration of VZ_C
Computed elevation above runway

2nd integration



3 unknown constants:

- Accelerometer bias (**C**)
- **VZ_i** = initial vertical speed
- **Z_i** = initial elevation above runway

Touchdown detection - VZ post computation

2nd step:

Get the unknown constants (C , VZ_i , Z_i).



Height computed out of:

- radio-height
- Altitude
- Static air temperature

Z_R = Height above runway

Z_C = integration of VZ_C
Computed elevation above runway

$Z_R - Z_C$


Least Square Method

C, VZ_i, Z_i

Touchdown detection - VZ post computation

3rd step:

Re-compute Vz thanks to the constants



Zc corrected with(C, VZ_i, Z_i)

2nd integration

Z_C = computed elevation

VZc corrected with(C, VZ_i, Z_i)

1st integration

VZ_C = computed elevation

ACCZc corrected with(C, VZ_i, Z_i)


C, VZ_i, Z_i

ACCZ_C = computed vertical acceleration

Touchdown detection

How to define the impact?

- Wheel spin up
- Gears compressed
- Increase of vertical load factor



Objective:

Compute an **accurate time of touchdown** for characterization of impact on ground.


Problem:

On most common flight data recorders, landing squats are recorded at 1 Hz, which is not satisfactory .

Solution:

Use Vertical Load Factor and **previously calculated Vertical speed** to compute accurate time of impact.

Touchdown detection



1st step:

Computation Time windows:

- [Start time] = rough calculation of impact based on radio altitude and vertical speed at 10 FT above ground.
- [End time] = maximum of Vertical speed after [Start time], provided that vertical speed is above a certain threshold.



2nd step:

Seek in the time windows the point which best fits to the impact:



- Maximum positive rate of VRTG, provided that radio altitude is below a certain threshold.

Touchdown detection - Method Comparison

Air/Ground switch method




VRTG- VZ method




Touchdown detection – Impact position on ground

Touch down location with Air/Ground switch method



Touch down location with Vz method




MINIMUM	MAXIMUM	NB flights
50cm	285m	1662

Contents

- Trajectories available on board
- Recorded trajectories
- Post treatment trajectory computation
- Accuracy assessment
- Vertical Speed computation and Touch down detection
- **Conclusion**


Conclusion

Recorded Touch Down locations



Source: DMC

Recorded Touch Down locations
+ 300m inaccuracy



Source: DMC

Conclusion

- Trajectory **inaccuracy** has to be taken into account to draw any conclusion about:
 - Touch down location, long flare
 - Overrun risk
- Accurate **touch-down location** requires complex computation
- Trajectory **computation** afterwards is **complex** and not as accurate as available trajectory on board
 - Way forward: improve this computation, better assess the accuracy
- Alternatively, whenever possible **record FMS trajectory**, 21 bits, 4Hz

Lucky you: record the FMS Trajectory!

© Airbus India Operations Pvt. Ltd. All rights reserved. Confidential and proprietary document. This document and all information contained herein is the sole property of Airbus India Operations Pvt. Ltd. No intellectual property rights are granted by the delivery of this document or the disclosure of its content. This document shall not be reproduced or disclosed to a third party without the express written consent of Airbus India Operations Pvt. Ltd. This document and its content shall not be used for any purpose other than that for which it is supplied. The statements made herein do not constitute an offer. They are based on the mentioned assumptions and are expressed in good faith. Where the supporting grounds for these statements are not shown, Airbus India Operations Pvt. Ltd. will be pleased to explain the basis thereof. AIRBUS, its logo, A300, A310, A318, A319, A320, A321, A330, A340, A350, A380, A400M are registered trademarks.