



**TYPE-CERTIFICATE
DATA SHEET**

No. EASA.A.064

for

AIRBUS A318 – A319 – A320 – A321

Type Certificate Holder:

AIRBUS S.A.S.

2 rond-point Emile Dewoitine

31700 BLAGNAC

FRANCE

For Models:	A318 – 111	A319 – 111	A320 – 211	A321 – 111
	A318 – 112	A319 – 112	A320 – 212	A321 – 112
	A318 – 121	A319 – 113	A320 – 214	A321 – 131
	A318 – 122	A319 – 114	A320 – 215	A321 – 211
		A319 – 115	A320 – 216	A321 – 212
		A319 – 131	A320 – 231	A321 – 213
		A319 – 132	A320 – 232	A321 – 231
		A319 – 133	A320 – 233	A321 – 232
		A319 – 151N	A320 – 271N	A321 – 271N
		A319 – 153N	A320 – 251N	A321 – 251N
		A319 – 171N	A320 – 252N	A321 – 253N
		A319 – 173N	A320 – 272N	A321 – 272N
			A320 – 253N	A321 – 252N
			A320 – 273N	A321 – 251NX
				A321 – 252NX
				A321 – 253NX
				A321 – 271NX
				A321 – 272NX



Intentionally left blank



TABLE OF CONTENTS

SECTION 1: A320 SERIES	8
I. General 8	
1. Type/ Model/ Variant	8
2. Performance Class	8
3. Certifying Authority	8
4. Manufacturer.....	9
5. State of Design Authority Certification Application Date.....	9
6. EASA Type Certification Application Date	9
7. State of Design Authority Type Certificate Date	9
8. EASA Type Certification Date	10
II. Certification Basis 10	
1. Reference Date for determining the applicable requirements	10
2. State of Design Airworthiness Authority Type Certification Data Sheet No.	10
3. State of Design Airworthiness Authority Certification Basis	10
4. EASA Airworthiness Requirements.....	11
5. Special Conditions	25
6. Exemptions/Deviations	30
7. Equivalent Safety Findings.....	30
8. Environmental Protection	32
III. Technical Characteristics and Operational Limitations 33	
1. Type Design Definition	33
2. Description	34
3. Equipment	34
4. Dimensions	34
5. Engines.....	34
6. Auxiliary Power Unit	37
7. Propellers.....	38
8. Fluids (Fuel, Oil, Additives, Hydraulics)	38
9. Fluid Capacities.....	40
10. Airspeed Limits (Indicated Airspeed – IAS – unless otherwise stated)	43
11. Flight Envelope	43
12. Operating Limitations	44
13. Maximum Certified Masses	46
14. Centre of Gravity Range	50
15. Datum	50
16. Mean Aerodynamic Chord (MAC)	50
17. Levelling Means	50
18. Minimum Flight Crew	50
19. Minimum Cabin Crew	50
20. Maximum Seating Capacity	50
21. Baggage/ Cargo Compartment	52
22. Wheels and Tyres	52
23. ETOPS.....	52
IV. Operating and Service Instructions 53	
1. Airplane Flight Manual (AFM)	53
2. Instructions for Continued Airworthiness and Airworthiness Limitations	53
3. Weight and Balance Manual (WBM)	54



V. Operational Suitability Data (OSD)	54
1. Master Minimum Equipment List	54
2. Flight Crew Data	54
3. Cabin Crew Data	54
VI. Part-26 compliance information	55
VII. Notes	55
SECTION 2: A321 SERIES	56
I. General	56
1. Type/ Model/ Variant	56
2. Performance Class	57
3. Certifying Authority	57
4. Manufacturer	57
5. State of Design Authority Certification Application Date	57
6. EASA Type Certification Application Date	57
7. State of Design Authority Type Certificate Date	57
8. EASA Type Certification Date	58
II. Certification Basis	58
1. Reference Date for determining the applicable requirements	58
2. State of Design Airworthiness Authority Type Certification Data Sheet No.	58
3. State of Design Airworthiness Authority Certification Basis	58
4. EASA Airworthiness Requirements	59
5. Special Conditions	75
6. Exemptions/Deviations	80
7. Equivalent Safety Findings	80
8. Environmental Protection	83
III. Technical Characteristics and Operational Limitations	84
1. Type Design Definition	84
2. Description	85
3. Equipment	85
4. Dimensions	86
5. Engines	86
6. Auxiliary Power Unit	89
7. Propellers	89
8. Fluids (Fuel, Oil, Additives, Hydraulics)	89
9. Fluid Capacities	91
10. Airspeed Limits (Indicated Airspeed – IAS – unless otherwise stated)	92
11. Flight Envelope	93
12. Operating Limitations	94
13. Maximum Certified Masses	96
14. Centre of Gravity Range	100
15. Datum	100
16. Mean Aerodynamic Chord (MAC)	100
17. Levelling Means	100
18. Minimum Flight Crew	100
19. Minimum Cabin Crew	101
20. Maximum Seating Capacity	101
21. Baggage/ Cargo Compartment	103
22. Wheels and Tyres	103
23. ETOPS	103
IV. Operating and Service Instructions	104



1. Airplane Flight Manual (AFM)	104
2. Instructions for Continued Airworthiness and Airworthiness Limitations	104
3. Weight and Balance Manual (WBM)	105
V. Operational Suitability Data (OSD) 105	
1. Master Minimum Equipment List.....	105
2. Flight Crew Data	105
3. Cabin Crew Data	106
VI. Part-26 compliance information 106	
VII. Notes 106	
SECTION 3: A319 SERIES 108	
I. General 108	
1. Type/ Model/ Variant	108
2. Performance Class	108
3. Certifying Authority	109
4. Manufacturer.....	109
5. State of Design Authority Certification Application Date.....	109
6. EASA Type Certification Application Date	109
7. State of Design Authority Type Certificate Date	109
8. EASA Type Certification Date	110
II. Certification Basis 110	
1. Reference Date for determining the applicable requirements	110
2. State of Design Airworthiness Authority Type Certification Data Sheet No.	110
3. State of Design Airworthiness Authority Certification Basis	110
4. EASA Airworthiness Requirements.....	110
5. Special Conditions	126
6. Exemptions/Deviations	130
7. Equivalent Safety Findings.....	130
8. Environmental Protection	132
III. Technical Characteristics and Operational Limitations 132	
1. Type Design Definition	132
2. Description	133
3. Equipment	133
4. Dimensions	134
5. Engines.....	134
6. Auxiliary Power Unit.....	137
7. Propellers.....	137
8. Fluids (Fuel, Oil, Additives, Hydraulics)	137
9. Fluid Capacities.....	139
10. Airspeed Limits (Indicated Airspeed – IAS – unless otherwise stated)	146
11. Flight Envelope	147
12. Operating Limitations	148
13. Maximum Certified Masses.....	151
14. Centre of Gravity Range	152
15. Datum	152
16. Mean Aerodynamic Chord (MAC)	152
17. Levelling Means.....	153
18. Minimum Flight Crew	153
19. Minimum Cabin Crew	153
20. Maximum Seating Capacity	153
21. Baggage/ Cargo Compartment	155



22.	Wheels and Tyres	155
23.	ETOPS.....	155
IV. Operating and Service Instructions		156
1.	Airplane Flight Manual (AFM)	156
2.	Instructions for Continued Airworthiness and Airworthiness Limitations	156
3.	Weight and Balance Manual (WBM)	157
V. Operational Suitability Data (OSD)		157
1.	Master Minimum Equipment List.....	157
2.	Flight Crew Data	157
3.	Cabin Crew Data	158
VI. Part-26 compliance information		158
VII. Notes		158
SECTION 4: A318 SERIES		159
I. General		159
1.	Type/ Model/ Variant	159
2.	Performance Class	159
3.	Certifying Authority	159
4.	Manufacturer.....	159
5.	State of Design Authority Certification Application Date.....	159
6.	EASA Type Certification Application Date	159
7.	State of Design Authority Type Certificate Date	159
8.	EASA Type Certification Date	159
II. Certification Basis		160
1.	Reference Date for determining the applicable requirements	160
2.	State of Design Airworthiness Authority Type Certification Data Sheet No.	160
3.	State of Design Airworthiness Authority Certification Basis	160
4.	EASA Airworthiness Requirements.....	160
5.	Special Conditions	163
6.	Exemptions/Deviations	166
7.	Equivalent Safety Findings.....	166
8.	Environmental Protection	167
III. Technical Characteristics and Operational Limitations		167
1.	Type Design Definition	167
2.	Description	167
3.	Equipment	168
4.	Dimensions	168
5.	Engines.....	168
6.	Auxiliary Power Unit	169
7.	Propellers.....	170
8.	Fluids (Fuel, Oil, Additives, Hydraulics)	170
9.	Fluid Capacities.....	170
10.	Airspeed Limits (Indicated Airspeed – IAS – unless otherwise stated)	171
11.	Flight Envelope	172
12.	Operating Limitations	172
13.	Maximum Certified Masses.....	173
14.	Centre of Gravity Range	174
15.	Datum	174
16.	Mean Aerodynamic Chord (MAC)	174
17.	Levelling Means	174
18.	Minimum Flight Crew	174



19.	Minimum Cabin Crew	174
20.	Maximum Seating Capacity	174
21.	Baggage/ Cargo Compartment	175
22.	Wheels and Tyres	175
23.	ETOPS.....	175
IV. Operating and Service Instructions		176
1.	Airplane Flight Manual (AFM)	176
2.	Instructions for Continued Airworthiness and Airworthiness Limitations	176
3.	Weight and Balance Manual (WBM)	176
V. Operational Suitability Data (OSD)		177
1.	Master Minimum Equipment List.....	177
2.	Flight Crew Data	177
3.	Cabin Crew Data	177
VI. Part-26 compliance information		177
VII. Notes		178
SECTION: ADMINISTRATIVE		179
I. Acronyms and Abbreviations		179
II. Type Certificate Holder Record		179
III. Change Record		179



SECTION 1: A320 SERIES**SECTION 1: A320 SERIES****I. General**

1. Type/ Model/ Variant

A320-211
 A320-212
 A320-214
 A320-215
 A320-216
 A320-231
 A320-232
 A320-233
 A320-271N
 A320-251N
 A320-252N
 A320-272N
 A320-273N
 A320-253N

Significant Product Level Changes i.a.w. 21.A.101:

MOD 160500 Sharklet applicable on	A320-214/-215/-216/-232/-233
MOD 156723 Max Pax applicable on	A320-214/-215/-216/-232/-233/-251N/ -252N/-253N/-271N/-272N/-273N
MOD 160080 applicable on	A320-214/-215/-216/-232/-233
MOD 161000	A320-271N
MOD 161003	A320-251N
MOD 158708 Max Pax applicable on	A320-211/-212/-214/-215/-216/-231/ -232/-233
MOD 158819 Max Pax applicable on	A320-214/-215/-216/-232/-233
ACJ320 NEO*	A320-251N/-271N/-272N
A320 CEO*	A320-211/-212/-214/-215/-216/-231/-232/-233
A320 NEO*	A320-251N/-252N/-253N/-271N/-272N/-273N

*Commercial designation only

2. Performance Class

A

3. Certifying Authority

European Union Aviation Safety Agency (EASA)



SECTION 1: A320 SERIES

Postfach 101253
D-50452 Köln
Deutschland

4. Manufacturer

AIRBUS
2 rond-point Emile Dewoitine
31700 BLAGNAC – France

5. State of Design Authority Certification Application Date

A320-111	
A320-211	
A320-212	31 January 1990
A320-214	10 May 1992
A320-231	16 June 1988
A320-232	10 May 1992
A320-233	23 February 1995

6. EASA Type Certification Application Date

A320-215	22 December 2005
A320-216	22 December 2005
A320-271N	29 February 2012
MOD 160500	08 April 2010
MOD 156723 iss 1	31 July 2013
MOD 160080	24 April 2012
MOD 156723 iss 4	23 September 2015
A320-251N	29 February 2012
MOD 156723 iss 5	16 June 2016
MOD 158708 iss 1	7 December 2015
MOD 158819 iss 1	12 July 2016
A320-252N	9 August 2017
A320-272N	20 March 2018
ACJ320 NEO	10 June 2015
A320-253N	8 July 2016
A320-273N	21 November 2016
MOD 156723 iss 7	14 October 2019

7. State of Design Authority Type Certificate Date

A320-211	November 08, 1988
A320-212	November 20, 1990
A320-214	March 10, 1995
A320-231	April 20, 1989



SECTION 1: A320 SERIES

A320-232	September 28, 1993
A320-233	October 26, 1995

Note: For A320-211/-212/-214/-231/-232/-233 produced before December 21, 2005 DGAC-F TC 180 remains a valid reference for individual Certificate of Airworthiness. The content DGAC F TC 180 is replaced by this current TCDS.

8. EASA Type Certification Date

EASA TCDS issue 1 issued December 21, 2005

A320-215	June 22, 2006
A320-216	June 14, 2006
A320-271N	November 24, 2015
A320-251N	May 31, 2016
A320-252N	December 18, 2017
A320-272N	October 17, 2018
A320-273N	January 30, 2019
A320-253N	February 5, 2019
MOD 160500 iss 1	November 30, 2012 (A320-214, -215, -216)
MOD 160500 iss 2	December 21, 2012 (A320-232, -233)
MOD 156723 iss 1	March 5, 2015 (A320-214, -215, -216, -232, -233)
MOD 160080 iss 1	October 15, 2015 (A320-214, -215, -216, -232, -233)
MOD 161000 iss 1	November 24, 2015 (A320-271N)
MOD 160080 iss 2	December 17, 2015 (A320-214, -215, -216, -232, -233)
MOD 156723 iss 4	March 17, 2016 (A320-271N)
MOD 158708 iss 1	June 13, 2016 (A320-211, -212, -214, -215, -216, -231, -232, -233)
MOD 156723 iss 5	June 24, 2016 (A320-251N)
MOD 158819 iss 1	February 24, 2017, 2017 (A320-214, -215, -216, -232, -233)
ACJ320 NEO	December 19, 2018 (A320-251N, -271N, -272N)
MOD 156723 iss 7	November 26, 2019 (A320-252N, -253N, -272N, -273N)

II. Certification Basis**1. Reference Date for determining the applicable requirements**

Application date of the A320-111 model.

2. State of Design Airworthiness Authority Type Certification Data Sheet No.

Original French TCDS DGAC no. 180 was replaced by the EASA TCDS A.064.

3. State of Design Airworthiness Authority Certification Basis

See paragraph 4.



SECTION 1: A320 SERIES**4. EASA Airworthiness Requirements**

Hereafter are listed the certification bases for the different A320 models. The amendments made to a particular basis at the occasion of further A320 model certification are identified per model.

4.1 The applicable technical conditions for models A320-211-212/-213/-214/-215/-216/-231/-232/233 and weight variants up to 006 (DGAC letter 53170 SFACT/TC) are defined as follows:

- JAR 25 Change 11 (except paragraph 25.207 which remains at Change 10 and 25.853(a) and (b) which are at Change 13 since MSN 118) as elected by the Manufacturer
- A320 Special Conditions, Experience Related Conditions and Harmonization Conditions.

4.2 ETOPS:

For the Extended Range Twin Engine Airplane Operations the applicable technical conditions are contained in AMC 20-6 (as initially published in AMJ 120-42/IL 20 and CAP 513) and A320 ETOPS EtC G-1006.

4.3 JAR AWO Change 1 for auto-land and operations in low visibility.

4.4 Certification basis has been revised for MOD 160500 and 160080 "Sharklet".

The certification basis is that of the A320-214,-215,-216,-232,-233 amended by the following:

CS 25 Amdt 8 for

§ 25.23	§ 25.481(a)(c) amended by SC A-2 for § 25.481(a)
§ 25.25	§ 25.483
§ 25.117	§ 25.485
§ 25.147	§ 25.489
§ 25.161	§ 25.491
§ 25.177 amended by SC-F16	§ 25.571(a)(b)(e)
§ 25.235	§ 25.581
§ 25.251	§ 25.601
§ 25.301	§ 25.603
§ 25.302	§ 25.605
§ 25.303	§ 25.607
§ 25.305(a)(b)(c)(e)(f)	§ 25.609
§ 25.307(a)(d)	§ 25.613
§ 25.321(a)(b)(c)(d)	§ 25.619
§ 25.331(a)(b)(c)	§ 25.623
§ 25.333(a)(b)	§ 25.625
§ 25.335(a)(c)(d)(e)(f) amended by SC A-5003 for (b) and SC A-2 for (e)	§ 25.629
§ 25.337	§ 25.631
§ 25.341(a)(b)	§ 25.651



SECTION 1: A320 SERIES

§ 25.343(a)(b)	§ 25.683
§ 25.345(a)(b)(c)(d)	§ 25.899
§ 25.349(a)(b) amended by SC A-2.2.2 for 25.349(a)	§ 25.903(d)(1)
§ 25.351	§ 25.1385
§ 25.365(a)(b)(d)	§ 25.1387
§ 25.367	§ 25.1389
§ 25.371	§ 25.1391
§ 25.373	§ 25.1393
§ 25.391	§ 25.1395
§ 25.393(b)	§ 25.1397
§ 25.427	§ 25.1401
§ 25.445	§ 25.1505
§ 25.457	§ 25.1511
§ 25.459	§ 25.1515
§ 25.471(a)(b)	§ 25.1527
§ 25.473	§ 25.1587
§ 25.479(a)(c)(d) amended by SC A-2 for § 25.479(a)	§ 25.1591

CS 25 Amdt 2 for

§ 25.253

JAR 25 Chg 15 for

§ 25.1517

JAR 25 Chg 14 for

§ 25.21 amended by A318 SC F-5001 (for b)	§ 25.149 + OP96/1
§ 25.101 amended by SC F-11/S-79	§ 25.171 replaced by SC F-5004
§ 25.103 replaced by A318 SC F-5001	§ 25.173 replaced by SC F-5004
§ 25.105 amended by SC F-11/S-79	§ 25.175 replaced by SC F-5004
§ 25.107 amended by A318 SC-F-5001	§ 25.181
§ 25.109 amended by SC F-11/S-79	§ 25.201 + OP96/1, replaced by SC F-5001
§ 25.111	§ 25.203 + OP96/1, replaced by SC F-5001
§ 25.113 + OP96/1 amended by SC F-11/S-79	§ 25.207 amended by SC F-5001
§ 25.115 amended by SC F-11/S-79	§ 25.231
§ 25.119 + OP96/1 amended by A318 SC F-5001 (for b)	§ 25.233
§ 25.121 + OP96/1, amended by A318 SC F-5001 (for c & d)	§ 25.237
§ 25.123	§ 25X261
§ 25.125 + OP96/1, amended by A318 SC F-5001	§ 25.1533
§ 25.143 + OP96/1, amended by SC F-3, F-7 & F-8	§ 25.1581
§ 25.145 + OP96/1	§ 25.1585(a)



SECTION 1: A320 SERIESJAR 25 Chg 11 for

§ 25.671
 § 25.672
 § 25.1001
 § 25.1301
 § 25.1309
 § 25.1419

ETOPS

AMC 20-6 Rev 1 paragraphs related to operation in icing conditions 8.b.(11) for ice shapes on the Sharklet device.

AMC 20-6 Rev 1 paragraphs related to performance data in the AFM supplement for ETOPS 8.f.(1) (iii).

AMJ 120-42 for ETOPS for non-affected areas.

Note: This corresponds to the certification basis used for the initial ETOPS demonstration (refer to A320 EtC G-1006).

4.5 Certification basis has been revised for MOD 156723 issue 1 “Max Pax”.

The certification basis is that of the A320-200 equipped with Sharklets amended by the following:

CS 25 Amdt 13 for

§25.23	§25.489
§25.321	§25.801(d)
§25.331	§25. 803(c)
§25.341(a)(b)	§25. 807(g) amended by ESF E-2107 and demonstrated through ESF D-01
§25.351	§25.1519
§25.473	§25.1529
§25.479(a)(c)(d) amended by SC A-2 for § 25.479(a)	§25.1541(a)(b)
§25.481(a)(c) amended by SC A-2 for § 25.481(a)	§25.1557(a)

JAR 25 change 13

§25 .812(e)	§25 .853(a)1 amended by SC D-0306-000
§25 .812(k)(l)	

JAR 25 change 12

§25 .853(c)

JAR 25 change 11

§25.305(a)(b)	§25.1301
---------------	----------



SECTION 1: A320 SERIES

§25.307(a)	§25.1351(a)
§25.365(a)	§25.1353(a)(b)
§25.561	§25.1359(a)(d)
§25.571(a)(b)	§25.1413
§25.787(a)(b)	§25.1415(b)(c)(d)
§25.789(a)	§25.1431(c)
§25.791	§25.1447(c)(1)
§25.853(a)(b)	

4.6 Certification basis for A320-271N, -272N, -273N, -251N, -252N, -253N

The certification basis has been revised for the A320-271N, -272N, -273N, -251N, -252N, -253N. The certification basis is that of the A320-200 with modification 160500 (Sharklets) amended by the following:

CS 25 Amdt 11 for

25.23 (a) (b)	25.952 (a) (b) (for pylon area)
25.25 (a) (b)	25.954
25.27	25.955 (a)
25.101	25.961 (a) (b)
25.109	25.963 (a)
25.113	25.969
25.115	25.971 (a) (b) (c)
25.117	25.981 for pylon area only
25.145 (a)	25.993 (a) (b) (c) (d) (e) for Engines and Pylon area only.
25.147	25.994 for fuel system component in the pylon and powerplant system area
25.149	25.995 for engine and pylon areas only
25.161	25.997 (a) (b) (c) (d)
25.171 replaced by SC B-04 (Static Directional, Lateral and Longitudinal Stability and Low Energy awareness)	25.999 (a) (b)
25.173 replaced by SC B-04 (Static Directional, Lateral and Longitudinal Stability and Low Energy awareness)	25.1001
25.175 replaced by SC B-04 (Static Directional, Lateral and Longitudinal Stability and Low Energy awareness)	25.1011 (a) (b)
25.177 with subparagraphs (b) and (c) replaced by SC B-04 (Static Directional, Lateral and Longitudinal Stability and Low Energy awareness)	25.1013 (a) (b) (c) (d) (e) (f)
25.181	25.1015 (a) (b)
25.201 replaced by SC B-01 (Stalling and scheduled operating speeds),	25.1017 (a) (b)



SECTION 1: A320 SERIES

25.203 replaced by SC B-01 (Stalling and scheduled operating speeds),	25.1019 (a)
25.231	25.1021 (a) (b)
25.233	25.1023 (a) (b)
25.235	25.1025 (a) (c)
25.251	25.1041
25.301 (a) (b) (c)	25.1043 (a) (b) (c)
25.302 (for new or modified parts)	25.1045 (a) (b) (c)
25.303 (for new or modified parts)	25.1091 (a) (b) (c) (d) (e)
25.305 (a) (b) (c) (e) (f) (for new or modified parts)	25.1093 (b)
25.307 (a) (d) (for new or modified parts)	25.1103 (b) (c) (d)
25.321 (a) (b) (c) (d)	25.1121 (a) (b) (c) (d) (f) (g)
25.331 (a) (b) (c)	25.1123 (a) (b) (c)
25.333 (a) (b)	25.1141 (a) (b) (c) (d) (e) (f)
25.335 (a) (b) (c) (d) (e) (f) with sub-paragraph (b) replaced by Legacy SC A-5003 (Design Dive Speed Vd) and sub-paragraph (e) amended by Legacy SC A-2 (Stalling speeds for structural design)	25.1143 (a) (b) (c) (d) (e)
25.337 (a) (b) (c) (d)	25.1145 (a) (b) (c)
25.341 (a) (b) (c)	25.1155 (a) (b) (c) (d) (e)
25.343 (a) (b) (for new or modified parts)	25.1163 (a) (b) (c)
25.345 (a) (b) (c) (d)	25.1165 (a) (b) (c) (e) (f) (h)
25.349 (a) (b)	25.1167 (a) (b) (c)
25.351 (a) (b) (c) (d)	25.1181 (a) (b) amended by ESF E-44 (Fan Zone non-fire zone)
25.361 (a) (b)	25.1182 (a) (b)
25.362 (a) (b) (for new or modified parts)	25.1183 (a) (b) (c)
25.363 (a) (b)	25.1185 (a) (b) (c)
25.365 (a) (b) (c) (d) (e)(1) (for new or modified parts)	25.1187 (a) (b) (c) (d) (e)
25.367 (a) (b)	25.1189 (a) (b) (d) (e) (f)
25.371	25.1191 (a) (b)
25.373 (a) (b)	25.1193 (a) (b) (c) (d) (e) amended by SC E-45 (Engine Cowl Retention)
25.391 (a) (b) (c) (d) (e)	25.1195 (a) (b) (c)
25.427 (a) (b) (c) (d)	25.1197 (a) (b)
25.445 (a) (b)	25.1199 (a) (b) (c) (d) (e)
25.457	25.1201 (a) (b)
25.459	25.1203 (a) (b) (c) (d) (e) (f) (g)
25.471 (a) (b)	25.1207 (a) (b) (c) (d)
25.473 (a) (b) (c) (d) (e)	25.1301 amended by Legacy SC S-30 (Automatic Flight/Flight Management Functions), for newly designed systems only.



SECTION 1: A320 SERIES

25.479 (a) (c) (d) amended by Legacy SC A-2 for § 25.479(a)	25.1305 (a) (c) (d) amended by SC F-13 (Fuel System Low Level Indication – Fuel Exhaustion)
25.481 (a) (c) amended by Legacy SC A-2 for § 25.481(a)	25.1309 (for newly designed systems) amended by: Legacy SC SE-2001 (SC S-76 – Effects of external radiations upon aircraft systems), Legacy IM SE-14 (SC S-76-1 – Protection from the effects of HIRF)
25.483 (a) (b)	25.1316 (a) (b) (c)
25.485 (a) (b)	25.1337 (a) (c) (d)
25.489	25.1353 (a) (b) (for engine and pylon areas)
25.491	25.1355 (c)
25.493 (b) (c) (d) (e)	25.1357 (a) (for newly designed systems)
25.495	25.1401 (b)
25.499 (a) (b) (c) (d) (e)	25.1403
25.503 (a) (b)	25.1419 (a) (b) (c) (d) (e) (f) (g) (h) for engine air intake protection
25.507 (a) (b) (c)	25.1431 amended by Legacy SC S-76 - Effects of external radiations upon aircraft systems Legacy SC S76-1 – Protection from the effect of HIRF For newly designed equipment only
25.509 (a) (c) (d)	25.1438 (for newly designed equipment)
25.511	25.1459 (a) (b) (c) (d) amended by Legacy SC S-72 (HC S-72 – Flight recorders
25.519 (a) (b) (c)	25.1461 (a) (b) (c) (d) For newly designed equipment
25.571 (a) (b) (c) (d) (e) (for new or modified parts)	25.1501
25.581 amended by Legacy SC S-75 – Lightning protection indirect effects for pylon and nacelle areas	25.1503
25.601 (for new or modified parts)	25.1507
25.603 (a) (b) (c) (for new or modified parts)	25.1511
25.605 (a) (b) (for new or modified parts)	25.1513
25.607 (a) (b) (for new or modified parts)	25.1515
25.609 (a) (b) (for new or modified parts)	25.1517
25.611 (a)	25.1519
25.613 (a) (b) (c) (d) (e) (f) (for new or modified parts)	25.1521 (a) (c) (d)
25.619 (a) (b) (c) (for new or modified parts)	25.1525
25.623 (a) (b) (for new or modified parts)	25.1527
25.625 (a) (b) (c) (d) (for new or modified parts)	25.1531
25.629 (a) (b) (c) (d) (e)	25.1533
25.631 (for new or modified parts)	25.1535 (a) (b) (c)



SECTION 1: A320 SERIES

25.651 (for new or modified parts)	25.1549 (a) (b) (c) (d) amended by ESF E-51 (Oil temperature indication)
25.671 (a) (b) (c) (d) amended by legacy SC F-7 (SC F-9 - Dual Control System)	25.1551
25.731 (a) (b) (c)	25.1553
25.733 (b) (c) (d)	25.1557 (b)
25.779	25.1581
25.831 (a) (e)	25.1583 (a) (b) (c) (d) (e) (f) (h) (i) (k)
25.841 (a)	25.1585
25.851 (b)	25.1587
25.855 (c)	25.1591
25.863 (a) (b) (c) (d)	25.1701 (a) (b) (c) for engines and pylon areas
25.865	25.1703 (a) (b) (d) (e) for engines and pylon areas
25.867 (a) (b)	25.1705 (a) (b) for engines and pylon areas
25.869 (a) (b) (c)	25.1707 (a) (b) (c) (d) (e) (f) (g) (h) (i) (j) (k) (l) for engines and pylon areas
25.899 amended by Legacy SC S-75 – Lightning protection indirect effects, for Pylon and Nacelle areas only	25.1709 (a) (b) for engines and pylon areas
25.901 (a) (b) (c) amended by SC E-45 (Engine Cowl Retention),	25.1711 (a) (b) (c) (d) (e) for engines and pylon areas
25.903 (a) (b) (c) (d) (e)	25.1713 (a) (b) (c) for engines and pylon areas
25.904	25.1715 (a) (b) for engines and pylon areas
25.933 (a)	25.1717 for engines and pylon areas
25.934 amended by ESF E-43 (Thrust Reverser Testing).	25.1719 for engines and pylon areas
25.939 (a) (c)	25.1723 for engines and pylon areas
25.943	25.1725 (a) (b) for engines and pylon areas
25.951 (a) (b) (c) amended by SC E-37 (Water/Ice in Fuel System), for pylon area only.	25.1727 for engines and pylon areas 25.1731 (a) (b)

CS25 Amdt 8 for:

25.683 (b)

CS 25 Amdt 2 for:

25.21 with sub-paragraph (b) added by SC B-01 (Stalling and Scheduled Operating Speeds)	25.123
25.103 replaced by SC B-01 (Stalling and Scheduled Operating Speeds)	25.125
25.105	25.143 Sub-Paragraphs (j), (k), (l) added by SC B-03 (Motion and Effect of Cockpit control), Sub-paragraph (h) added by SC B-07 (Flight envelope protection), Sub paragraph (i) added by SC B-08 (Normal Load factor limiting System).



SECTION 1: A320 SERIES

25.107	25.207 replaced by SC B-01 (Stalling and scheduled operating speeds).
25.111	25.237
25.119	25.253
25.121	25.1419

CS25 Amdt 1:

25.981 (a) (3) amended by generic SC E-48 – Fuel Tank Safety for all areas except engine and pylon areas

JAR 25 Chg 14 for:

25.145 (b) (c)
25.365 (e)(2), (e)(3)
25.1423 (a) (b) (c) (d) (e) (f) (g)
25.1583 (j)

JAR 25 Chg 13 for

25.365 (f) (g)
25.735 (a) (f) (g) (h) amended by
Legacy SC F-11 – Accelerate-stop distances and related performances, worn brakes
Legacy SC S-79 - Brake requirements, qualification and testing – A321
25.853(a)(1)

JAR 25 Chg 12 for

25.853(c)

JAR 25 Chg 11 for:

25.561 (a) (b) (c)	25.1309 amended by Generic SC D-0332-001 (Towbarless Towing) For systems adaptations.
25.563	25X1315
25.672 (a) (b) (c)	25.994 for all areas except engine and pylon areas
25.677 (b)	25.1301
25.703 (a) (b) (c)	25.1321 (d)
25.721 (a) (b) (c)	25.1322 (a) (b) (c) (d) amended by generic SC D-0332-001 (Towbarless Towing)
25.729 (b) (c) (d) (e) (f)	25.1323 (a) (b) (c)
25.735 (b) (c)	25.1325 (b) (d) (e)
25.771 (e)	25.1329 (f) amended by: Legacy SC S-30 (Automatic Flight/Flight Management Functions),
25.777 Sub-paragraph (b) amended by SC B-03 (Motion and Effect of Cockpit Control)	25.1337 (b)
25.783 (a) (b) (c) (e) (f) (g)	25.1351 (a) (b) (d) where (d) is replaced by Legacy SC S-52 (Operation without normal Electrical power)



SECTION 1: A320 SERIES

25.791	25.1353 (a) (b) (for all areas except pylon and engine)
25.801	25.1359
25.807 (a) (b) (c) (d)	25.1363 (a) (b)
25.809 (a) (b) (c) (d) (e) (f)	25.1419 (a) (b) (c) (d)
25.843 (a)	25.1431 (for system adaptations)
25.853 (a)	25.1435 (a) (b) (c) (d)
25X899 amended by Legacy SC S-75 – Lightning protection indirect effects	25.1457 (a) (b) (c) (d) (e) (f) (g)
25.959	25.1529 amended by SC H-01
25.963 (d) (e)	25.A.901 (c)
25.967 (d)	25.A.939 (a)
25.975 (a)	25.A.1521
25.981 for all paragraph except (a) (3) in all areas except engine and pylon areas	25.A.1527

4.7 Certification basis has been revised for MOD 156723 issue 4 and issue 5 “Max Pax”.

The certification basis is that of the A320-271N/-251N amended by the following:

CS 25 Amdt 17 for

§25.23	§25.481(a)(c) amended by SC A-2 for § 25.481(a)
§25.305(a)(b)	§25.489
§25.307(a)	§25.571(a)(b)
§25.321	§25.801(d)
§25.331	§25.803(c)
§25.341(a)(b)	§25.807(g) amended by ESF E-2107 and demonstrated through ESF D-01
§25.351	§25.1519
§25.365(a)	§25.1541(a)(b)
§25.473	§25.1557(a)
§25.479(a)(c)(d) amended by SC A-2 for § 25.479(a)	

CS 25 Amdt 11

§25.1357(a)	§25.1431(c)
-------------	-------------

JAR 25 change 13

§25.812(e)	§25.812(k)(l)
§25.853(a)1 amended by SC D-0306-000	

JAR 25 change 12

§25.853(c)

JAR 25 change 11

§25.561	§25.1351(a)
---------	-------------



SECTION 1: A320 SERIES

§25.787(a)(b)	§25.1353(a)(b)
§25.789(a)	§25.1359(a)(d)
§25.791	§25.1413
§25.853(a)(b)	§25.1415(b)(c)(d)
§25.1301	§25.1447(c)(1)

- 4.8 Certification basis has been revised for MOD 158708 issue 1 “Max Pax” for aircraft with wing tip fence modification (20268 or 21999).

The certification basis is that of the A320-211,-212,-214,-215,-216,-231,-232,-233 amended by the following:

CS 25 Amdt 17 for

§25.23	§25.489
§25.321	§25.801(d)
§25.331(a)(b)(c1)	§25.803(c)
§25.341(a)	§25.807(g) amended by ESF E-2107 and demonstrated through ESF D-01
§25.351	§25.1519
§25.473	§25.1541(a)(b)
§25.479(a)(c)(d) amended by SC A-2 for §25.479(a)	§25.1557(a)
§25.481(a)(c) amended by SC A-2 for §25.481(a)	§25.1529

JAR 25 change 14

§25.305 (a)(b)	§25.341(b)
§25.331(c2)	§25.571(a)(b)

JAR 25 change 13

§25.812(e)(1)(2)	§25.812(k)(l)
§25.853(a)1 amended by SC D-0306-000	

JAR 25 change 12

§25.853(c)

JAR 25 change 11

§25.307(a)	§25.1351(a)
§25.561	§25.1353(a)(b)
§25.785	§25.1357(a)
§25.787(a)(b)	§25.1359(a)(d)
§25.789(a)	§25.1413
§25.791	§25.1415(b)(c)(d)
§25.853(a)(b)	§25.1431(c)
§25.1301	§25.1447(c)(1)
§25.365(a)	



SECTION 1: A320 SERIES

- 4.9 Certification basis has been revised for MOD 158819 issue 1 “Max Pax for Sharklet in service retrofit”.

The certification basis is that of the A320-200 equipped with Sharklets (modification 160080) amended by the following:

CS 25 Amdt 18 for

§25.23	§25.489
§25.321	§25.801(d)
§25.331	§25.803(c)
§25.341(a)(b)	§25.807(g) amended by ESF E-2107 and demonstrated through ESF D-01
§25.351	§25.1519
§25.473	§25.1529
§25.479(a)(c)(d) amended by SC A-2 for § 25.479(a)	§25.1541(a)(b)
§25.481(a)(c) amended by SC A-2 for § 25.481(a)	§25.1557(a)

JAR 25 change 14

§25.305(a)(b)	§25.571(a)(b)
---------------	---------------

JAR 25 change 13

§25.812(e)	§25.853(a)1 amended by SC D-0306-000
§25.812(k)(l)	

JAR 25 change 12

§25.853(c)

JAR 25 change 11

§25.307	§25.1351(a)
§25.365(a)	§25.1353(a)(b)
§25.561	§25.1357(a)
§25.785	§25.1359(a)(d)
§25.787(a)(b)	§25.1413
§25.789(a)	§25.1415(b)(c)(d)
§25.791	§25.1431(c)
§25.853(a)(b)	§25.1447(c)(1)
§25.1301	

- 4.10 Certification basis revised for ACJ320 NEO.

The certification basis is that of the A320-271N, -272N, -251N amended by the following:

CS25 Amdt 16

§25.23	§25.952 (a)
--------	-------------



SECTION 1: A320 SERIES

§25.25	§25.954 (a) (b) (c)
§25.27	§25.957
§25.29	§25.959
§25.301 (a)	§25.963 (a) (b) (c) (d1) (d3) (d4) (e1)(e2) (f)
§25.302	§25.965 (a) (b) (c) (d)
§25.303	§25.967 (a) (b) (e)
§25.305(a) (b) (c)	§25.969
§25.307 (a)	§25.971 (a) (b) (c)
§25.321	§25.975 (a)
§25.331	§25.977 (a) (c) (d)
§25.341 (a) (b)	§25.979 (b) (c) (d) (e)
§25.343 (a) (b3)	§25.981 (a) (b) (d)
§25.351	§25.993 (a) (b) (c) (d) (e) (f)
§25.365 (a) (b) (d) (e) (f)	§25.994
	§25.995 (b)
§25.473	§25.999 (a) (b)
§25.479 (a) (c) (d)	§25.1141 (a) (f)
§25.481 (a) (c)	§25.1189 (h)
§25.489	§25.1301 (a) (b)
	§25.1302 (a) (b) (c)
§25.519 (a) (b)	§25.1305 (a)(2)
§25.561	§25.1309 (a) (b) (c) (d)
§25.571 (a) (b) (c) (e1) (e4)	§25.1310 §25.1315 §25.1316 (a) (b) (c)
§25.581 (a) (b) (c)	§25.1337 (b) §25.1353 (a)
§25.611	§25.1381 (a) (b) §25.1431 (a) (c) (d)
§25.619	§25.1519
§25.625	§25.1535
§25.629 (a) (b) (c) (d) (e) §25.631	§25.1543 (b)
§25.721 (b)	§25.1553
§25.723 (b) §25.777 (a)	§25.1555 (a) (c)
§25.843 (a) §25.851 (b2) §25.855 (a) (c) (e) (f) (g)(h1)(h2)(h3) §25.857 §25.858 §25.863 (a) (b) (c) (d) §25.869	§25.1581 (a) (b) (d)
§25.899 (a) (b)	§25.1583 (c) (f) (h)



SECTION 1: A320 SERIES

§25.901 (c)	§25.1585 (a) (b) (c) (e)(f)
§25.903 (c) (d1)	§25.1703 (a1)(a2)a(3)(a4) (b) (d)
§25.943	§25.1705 (a) (b4) (b9) (b16) §25.1707 (a) (b) (c) (e) (l)
§25.951 (c)	§25.1709 (a) (b) §25.1711 (a) (b) (c) (d) (e) §25.1713 §25.1715 (a) (b) §25.1719 §25.1721 §25.1723 §25.1725 (b)

CS25 Amdt 11

§25.251	§25.855 (c)
§25.305 (a) (b)	
§25.307 (a)	
§25.335 (b)	§25.901 (b) (c) §25.1301 (a1)(a2)(a3) §25.1309 (a) (b) (g) §25.1519 §25.1527 §25.1541 §25.1557 (a)
§25.365 (e) §25.561 (b3)	
§25.601	
§25.671	

CS25 Amdt 2

§25.21 (c)
§25.123 (a)

JAR25 Change 13

§25.365 (e)(2)(3)(f)(g)

JAR25 Change 11

§25.689 (f)	§25.1322 (a) (b) (c) (d)
§25.803 (d)	§25.1351 (a)
§25.807 (a) (c)	§25.1541
§25.1301 (a) (b) (c)	§25.1557 (a)
§25.1309 (a) (b) (c) (d)	

4.11 Certification basis has been revised for MOD 156723 issue 7 “Max Pax”.

The certification basis is that of the A320-252N/-253N/-272N/-273N amended by the following:

CS 25 Amdt 23 for

SECTION 1: A320 SERIES

§25.23	§25.489
§25.321	§25.801(d)
§25.331	§25.803(c)
§25.341(a)(b)	§25.807(g) amended through ESF D-01
§25.351	§25.901(c)
§25.473	§25.1519
§25.479(a)(c)(d) amended by SC A-2 for §25.479(a)	§25.1529
§25.481(a)(c) amended by SC A-2 for §25.481(a)	§25.1541(a)(b)
	§25.1557(a)

CS 25 Amdt 17 for

§25.305(a)(b)	§25.365(a)
§25.307(a)	§25.571(a)(b)

CS 25 Amdt 11

§25.1357(a)	§25.1431(c)
-------------	-------------

JAR 25 change 13

§25.812(e)	§25.812(k)(l)
§25.853(a)1 amended by SC D-0306-000	

JAR 25 change 12

§25.853(c)

JAR 25 change 11

§25.561	§25.1351(a)
§25.785	§25.1353(a)(b)
§25.787(a)(b)	§25.1359(a)(d)
§25.789(a)	§25.1413
§25.791	§25.1415(b)(c)(d)
§25.853(a)(b)	§25.1447(c)(1)
§25.1301	

4.12 Post TC changes

4.12.1 For cabin and/or passengers improved seats (see EtC E-31), CS 25.562 is at amendment initial issue.

4.12.2 When halon free hand-held fire extinguishers are installed, CS25.851(a),(c) is at Amdt 17 (see EtC D-GEN-AIRBUS-01).

4.12.3 When reinforced cockpit door is installed (see EtC E-12), 14 CFR Part 25.772(a) and (c) and 25.795 are at amendment 106.



SECTION 1: A320 SERIES**4.12.4 Airbus complies with CS-ACNS:**

- Subpart B, Section 2 – for optional modifications (Post TC) installing FANS aiming at answering to SES mandate as defined in (EU) N° 29/2009 and amended by (EU) N° 310/2015 of 26 February 2015.

Note: For compliance to CS-ACNS Subpart B, Section 2, a deviation to CS-ACNS.B.DLS.B1.075 is accepted by DEV ACNS-B-GEN-01 to not include DM89 MONITORING [unit name] [frequency] in the downlink message set installed.

- Subpart D – for optional modifications installing transponders aiming at answering to SES mandate as defined in (EU) No 1207/2011 and amended by (EU) No 1028/2014 of 26 September 2014.

4.12.5 When Mod 160139 “Passenger information signs and placards” is installed CS25-791 is at Amdt 20.**4.12.6 When modifications 26334/26335 is installed on A320-200 series, JAR 25.341(a) is modified with the new discrete gust requirements of JAR 25 Change 14 as amended by NPA 25C-282.****4.12.7 For weight variant 007 and subsequent and for all models except A320-211/-212/-214/-231, the following JAR 25 paragraphs are at change 13 . This is related to DGAC letter 60667/SFACT/N.AT:**

JAR 25.305	JAR 25.349(b)
JAR 25.321	JAR 25.351
JAR 25.331	JAR 25.365(e)
JAR 25.333	JAR 25.371
JAR 25.335(d)	JAR 25.373
JAR 25.341	JAR 25.391
JAR 25.343(b)(1)(ii)	JAR 25.427
JAR 25.345(a)(c)	JAR 25.571(b)(2)

4.12.8 When Mod 1675567 “Define modified airspace Lavatory A” is installed, CS 25.795(a)(1), 25.795(a)(2) and §25.795(c)(3)(ii) are at amendment 22 (see ESF D-31).**4.12.9 For A320 series aircraft except those configured for Corporate Jet use (refer to note in section III paragraph 9):**

For all changes installing lavatory or galley adjacent to flight crew compartment on aircraft delivered after June 2026, where application for change is received after 02 June 2023 (date of Issue 51), CS 25.795(a)(1), 25.795(a)(2) are at Amendment 22.

4.12.10 For A/C configuration with ELT-DT equipment MOD 166219: CS-ACNS is at Issue 3 Subpart E Section 3.**4.12.11 From 14 December 2023, CS-FCD is at issue 2 for CS FCD.300, CS FCD.310, CS FCD.400, CS FCD.410, CS FCD.415.****5. Special Conditions**

Reminder: Within the scope of the establishment of the A320 Joint Certification Basis, three types of special conditions were developed:



SECTION 1: A320 SERIES

- Special conditions: rose to cover novel or unusual features not addressed by the JAR.
- Experience related conditions: rose to record an agreed text for the A320 Joint Certification Basis when evolution of JAR was in progress under the NPA procedure.
- Harmonization conditions: to record, for the purpose of the A320 Joint Certification Basis, a common understanding with respect to National variant. This should not be confused with the FAA/JAA harmonized regulations.

Compulsory

EC G-11	Turbine Engine - Maximum Take-Off Power and/or Thrust Duration - General Definitions
(DGAC-F) SC G-17	Operational proving flights
(CAA-UK) SC G-17	Operational flight before certification
SC F-1	Stalling and Scheduled operating Speeds
SC F-3	Cockpit control - motion and effect of cockpit control
SC F-4	Static longitudinal stability
SC F-6	Static directional and lateral stability
SC F-7	Flight envelope protection
SC F-8	Normal load factor limiting
SC F-9	Dual control system
HC F-103	Accelerate Stop Distance, Take-Off Distance and Take-Off Run on a Wet Runway
HC F-114	Approach and Target Threshold Speeds
SC A-2.1.1	Certification Criteria of Aircraft Designed with Systems Interacting with Structural Performance
SC A-2.2.2	Design manoeuvre requirement
SC A-2.2.3	Design dive speed
EC A-3.6.1	High Lift Devices
(CAA-UK) SC A-4.3	Tuned Gust Loads
HC A-4.4	Manoeuvre Loads - High Lift Devices Deployed
HC A-4.5	Braked roll conditions
HC A-4.6	Speed control device
SC S-11	Limit pilot forces and torques
HC S-23	Standby gyroscopic horizon
HC S-24	VMO/MMO Warning (setting)
EC S-30	Autoflight system
SC S-33	Autothrust system
SC S-52	Operation without normal electrical power
EC S-54	Circuit protective devices
HC S-61	Design Landing Brakes Kinetic Energy
HC S-62	Rejected Take-Off Brakes Kinetic Energy
HC S-72	Flight recorder



SECTION 1: A320 SERIES

SC S-74	Abnormal attitudes
SC S-75	Lightning protection indirect effects
SC S-76	Effect of external radiations up on aircraft systems
SC S-77	Integrity of control signal
SC P-01	Full Authority Engine Control System (FADEC)
SC E-1005	Resistance to fire terminology

- 5.1 For weight variant 007 and subsequent and for all new models from and including A320-232, the following A320 Special Conditions and Interpretative Materials are deleted by application of JAR 25 amendment 91/1:

SC A-4.3	Tuned gust loads
HC A-4.4	Manoeuvre loads high lift devices deployed

- 5.2 The following Special Conditions have been developed for the A320-233:

SC F-11	Accelerate-Stop distances and related performances, worn brakes (see SC F-2012 dated June 4, 1996)
SC S-79	Brakes requirements, qualification and testing (see SC SE-2003 dated June 4, 1996), for which the requirements are met by installation of MOD 24946 (Messier-Bugatti SEPCARB III brakes)

- 5.3 For A320-233 and all A320-200 with OCTOPUS AFM (see EtC F-2013), the JAR 25 paragraphs are modified following the Elect-to-comply with SC F-11 and SC S-79

The following JAR Change 11 paragraphs are deleted:

JAR 25x131
JAR 25x132
JAR 25x133
JAR 25x135
JAR 25x1588

The following A320 Harmonization Conditions are deleted:

HC F-103	Accelerate-Stop distance, Take-off distance, Take-off run on wet runway
HC S-61	Design landing brakes kinetic energy
HC S-62	Rejected take-off brakes kinetic energy

The following JAR 25 paragraphs are upgraded at Change 13 and amended by SC F-11 and SC S-79:

JAR 25.101
JAR 25.105
JAR 25.109
JAR 25.113
JAR 25.115
JAR 25.735



SECTION 1: A320 SERIES

JAR 25x1591

- 5.4 For any new application (new or modified aeroplane system and associated components) after July 10, 1998, SC S-76 (Effect of external radiations upon aircraft systems) are superseded by SC S-76-1 (SC SE-14)
- 5.5 For any further variant certification after Aug. 10, 1998, the HC A-4.5 (Braked roll conditions) is superseded by JAR 25.493(d) at Change 14 (EtC A-7)
- 5.6 The following special conditions have been developed post Type Certification:

SC D-0306	Heat release and smoke density requirements to seat material (applicable from June 2010)
SC E-48	Fuel Tank Safety (applicable from October 2013)
SC F-0311-001	Flight Recorders including Data Link Recording (applicable as per operational regulations)
F-GEN-01	Installation of non-rechargeable lithium battery (applicable from March 2019)
SC H-01	Enhanced Airworthiness Programme for Aeroplane Systems - ICA on EWIS (applicable from May 2010)
SC P-27	Flammability Reduction System If fitted, the centre fuel tank of aircraft which have made their first flight after 1st of January 2012 must be equipped in production with a fuel tank Flammability Reduction System (modification 38062). This system shall remain installed and operative and can only be dispatched inoperative in accordance with the provisions of the MMEL revision associated with modification 38062. If modification 38062 (Fuel Tank Inerting System (FTIS)) is embodied on A318, A319, A320, or A321 airplanes, the airplane is compliant with paragraph FR Section 25.981(a) & (b) at amendment 25-102, Part 25 appendix M & N at amendment 25-125, and Section 26.33 at amendment 26-3.

- 5.7 Special Conditions for aircraft equipped with MOD 160500 and 160080

SC F-16	Static directional and lateral stability
SC F-5001	Stalling and scheduled operating speeds
SC F-5004	Static Longitudinal Stability and Low energy awareness
SC A-5003*	Design Dive Speed V_D

Note: All other original Special Conditions applicable to each model remain effective.

*From 07th December 2018 SC B-14 is replacing SC A-5003

- 5.8 Special Conditions for A320-271N, -272N, -273N, -251N, -252N, -253N



SECTION 1: A320 SERIES

B-01	Stalling and Scheduled Operating Speeds
B-03	Motion and effect of cockpit control
B-04	Static Directional, Lateral and Longitudinal Stability and Low energy awareness
B-07	Flight Envelope Protection
B-08	Normal Load Factor limiting System
E-37	Water/Ice in Fuel System
E-45	Engine Cowl Retention
F-13	Fuel System Low Level Indication - Fuel Exhaustion
E-55*	Fan Blade Loss

*Only applicable to CFM models

The following special conditions developed for previous models are also applicable to the A320-271N/-272N/-273N/-251N/-252N/-253N affected areas:

A-2.2.2	Design Manoeuvre requirement
SC A-1	Interaction of systems and structure
SC A-2	Stalling Speeds for structural design (A321)
A-5003*	Design dive speed Vd
D-0332-001	Towbarless Towing
E-48	Fuel Tank Safety
SC F-11	Accelerate-stop distances and relates performances, worn brakes
SC F-9	Dual Control System
H-01	Enhanced Airworthiness Programme for Aeroplane Systems - ICA on EWIS
P-27	Flammability Reduction System (consisting of Cooled Serviced Air System and Inert Gas Generation System)
S11	Limit Pilot forces and torques
S30	Automatic Flight/Flight Management Functions
S-33	Autothrust system
HC S-72	Flight recorders
SC S-76-1	Protection from the effect of HIRF
SC S-75	Lightning protection indirect effects
SC S-79	Brake requirements, qualification and testing (A321)

*From 07th December 2018 SC B-14 is replacing SC A-5003

Additional Special Conditions part of the Certification Basis (added post TC):

The following Special Conditions are additionally applicable when an A/C configuration includes the subject design change(s):

B-12	Soft Go Around
D-0322-001	Installation of suite type seating
D-0332-001	Towbarless Towing



SECTION 1: A320 SERIES

D-08	Installation of Personal Electronic Device charging stowage for cabin crew use
D-15	Pilot Control Mode TaxiBot Operations
D-19	Incorporation of Inertia Locking Device in Dynamic Seats
D-24	Installation of Airbags in the backrest of seats
D-25	Installation of structure mounted airbag
D-27	Installation of Three Point Restraint & Pretensioner System
D-28	Installation of oblique seats
E-10	High Altitude airport operations (up to 14,100ft)
E-13	Installation of inflatable restraints
E-34	Seat with inflatable restraints
E-21	Flight Instrument External Probes – Qualification in Icing Conditions New UTAS Pitot Probes
F-119	Security Protection of Aircraft Systems and Networks
D-33	Cabin attendant seat mounted on movable part of an interior monument
F-MULTI-04	Rechargeable Lithium Battery Installations
F-37	ATN over SATCOM

6. Exemptions/Deviations

ACNS-B-GEN-01 Deviation to CS-ACNS Initial Issue Subpart B, Section 2 (See Note in §II-4.12.4)

7. Equivalent Safety Findings**Compulsory**

7.1 The following paragraphs have been complied with through equivalent safety demonstrations:

JAR 25.783 (e)	cargo doors (see ESF SM-2005)
JAR 25.783 (f)	passenger doors and bulk cargo door (MOD 20029) (see ESF SM-2004 and SM-2007)
JAR 25.813 (c)	emergency exits (see ESF E-2105 issue 3 "Type III overwing emergency exit access", seat cushion height)
JAR 25.807	maximum number of passengers (180 PAX) (see ESF E-2107 "Passenger extension to 180")
JAR 25.933 (a)	thrust reverser autorestore function (see ESF P-1002).
JAR 25.791	Passenger information signs (ESF S-53)

7.2 Equivalent Safety Findings for aircraft equipped with MOD 160500 and 160080

25.1419 (c)	ESF F-19	Flight in natural icing condition
-------------	----------	-----------------------------------



SECTION 1: A320 SERIES

7.3 The following Equivalent Safety Findings have been developed for the A320-271N/-272N/-273N/-251N/-252N/-253N:

CS25.934, CS-E 890	E-43	Thrust Reverser Testing
CS25.1181(a)	E-44**	Fan Zone as non fire zone
CS25.1549(a)	E-51	Oil temperature indication
CS25.1181, CS25.1182	E-52	Nacelle area adjacent to fire
CS25.997(d)	E-49*	Fuel Filter Location

*Applicable to CFM models only

**Applicable to IAE models only

7.4 The following ESF developed for previous models are also applicable to the A320-271N/-272N/-273N/-251N/-252N/-253N affected areas:

JAR AWO 313	SE-4005	Revised strategy for demonstrating a safe go-around 'Minimum Approach Break-off Height (MABH) (issued for A319)
JAR AWO 236	SE-5005	Cat III operations - Excess Deviation Alerts
JAR 25.1441(c)	F-21	Crew Determination of Quantity of Oxygen in Passenger Oxygen System
14CFR Part 25.856(a)	E-18	Improved flammability standards for thermal / acoustic insulation materials

7.5 Additional ESF part of the Certification Basis (added post TC):

The following ESF are additionally applicable when an A/C configuration includes the subject design change(s):

CS 25.251(b)	B-17	Vibration/buffeting compliance criteria for large external antenna installation applicable from February 2021.
JAR 25.785(c)	D-0329-001	Forward facing seats with more than 18° to aircraft centreline.
CS 25.795(a)(1)	D-31	Application of reduced Intrusion Loads in certain areas of the flight deck boundaries
CS25.811(e)(4)	SE-63	Green Arrow and "Open" placard for Emergency Exit Marking
JAR 25.811(f)	E-16	Emergency exit marking reflectance
JAR 25.812(b)(1)(ii)	E-14	Photo-luminescent EXIT sign for MCD (Moveable Class Divider)
JAR 25.812(b)(1)(i)(ii)	SE-42	Symbolic EXIT signs as an alternative to red EXIT signs for passenger aircraft
FAR 25.856(b)	E-32 E-28	Fuselage burnthrough protection in bilge area, see note below



SECTION 1: A320 SERIES

		If modifications 150700, and 37270 (with CLS option only), 37048 and 36985 are embodied in production on A318, A319, A320, or A321 airplanes, the airplane is compliant with Fuselage Flame Penetration "Burnthrough" requirements addressed by paragraph 14 CFR Part 25.856(b) Amdt 25-111 (applicable as per operational regulations)
14CFR Part 25.856(a)	E-18	Improved flammability standards for insulation materials (applicable as per operational regulations)
JAR 25.1441(c)	F-21	Crew Determination of Quantity of Oxygen in Passenger Oxygen System
JAR 25.1443(c)	F-20	Minimum Mass Flow of Supplemental Oxygen
CS FCD.425(g)	FCD-MULTI-01	CS-FCD T3 Evaluation Process
25.795(a)(1) Amdt 22	D-31	Mod 167557 "Define Modified Airspace Lavatory A Option for 25.795 Compliance"
JAR 25.1441(c)	F-122	Crew Determination of Quantity of Oxygen in Passenger Oxygen System

7.6 Equivalent Safety Findings for aircraft equipped with MOD 156723, 158819 and 158708

CS25.807(g)	ESF D-01	Over-performing Type I exit
-------------	----------	-----------------------------

Note: The original ESFs applicable to each model remain effective.

8. Environmental Protection

ICAO Annex 16:

Vol. I, Part II	Noise Requirements
Vol. II, Part II	Fuel Venting
Vol. II, Part III Chapter 2	Emissions

Notes: Further details are defined within TCDSN EASA.A.064



SECTION 1: A320 SERIES**III. Technical Characteristics and Operational Limitations****1. Type Design Definition**

- 1.1 Certificated model: A320-211
Definition of reference airplane by AIRBUS INDUSTRIE document AI/EA-A-413.630/88
- 1.2 Certificated model: A320-212
Definition of reference airplane by AIRBUS INDUSTRIE document AI/EA-A 412.1589/90 (00D000A0004/C05)
- 1.3 Certificated model: A320-214
Definition of reference airplane by AIRBUS INDUSTRIE document AI/EA-S 413.0150/95 (00D000A0006/C21)
- 1.4 Certificated model: A320-215
Definition of reference airplane by AIRBUS INDUSTRIE document D00D06006382 (00D000A0215/C21)
- 1.5 Certificated model: A320-216
Definition of reference airplane by AIRBUS INDUSTRIE document D00D06011383 (00D000A0216/C21)
- 1.6 Certificated model: A320-231
Definition of reference airplane by AIRBUS INDUSTRIE document AI/EA-A 414.301/89
- 1.7 Certificated model: A320-232
Definition of reference airplane by AIRBUS INDUSTRIE document AI/EA-AC 414.0502/93 (00D000A0005/C21)
- 1.8 Certificated model: A320-233
Definition of reference airplane by AIRBUS INDUSTRIE document AI/EA-S 413.1984/95 (00D000A0007/C21)
- 1.9 Certified model: A320-271N
Definition of reference airplane by Airbus document 00D000A5021/C20
- 1.10 Certified model: A320-251N
Definition of reference airplane by Airbus document 00D000A5024/C20
- 1.11 Certified model: A320-252N
Definition of reference airplane by Airbus document 00D000A5188/C20
- 1.12 Certified model: A320-272N
Definition of reference airplane by Airbus document 00D000A5204/C00
- 1.13 Certified model: A320-273N
Definition of reference airplane by Airbus document 00D000A5155/C00
- 1.14 Certified model: A320-253N
Definition of reference airplane by Airbus document 00D000A5153C00

Notes:**a. Model conversions:**

- If modification 34647 is embodied on A320-212 model powered with CFM56-5A3 engines, it is converted into A320-211 model, powered with CFM56-5A1 engines
- If modification 35962 is embodied on A320-211 model powered with CFM56-5A1 engines, it is converted into A320-212 model, powered with CFM56-5A3 engines
- If modification 153177 is embodied on A320-233 model powered with IAE V2527E-A5 it is converted into A320-232 model, powered with IAE V2527-A5 engines



SECTION 1: A320 SERIES

- If modification 36563 is embodied on A320-216 model powered with CFM56-5B6/3 or /P engines, it is converted into A320-214 model, powered with CFM56-5B4/3 or /P engines
 - If modification 36885 is embodied on A320-214 model powered with CFM56-5B4/3 or /P engines, it is converted into A320-216 model, powered with CFM56-5B6/3 or /P engines
 - If modification 150847 is embodied on A320-232 model powered with IAE V2527-A5 engines, it is converted into A320-233 model, powered with IAE V2527E-A5 engines
- b. A320-216 model results of the embodiment of modification 36311 on A320-214 model.
- c. A320-215 model results of the embodiment of modification 36297 on A320-214 model.

2. Description

Twin turbo-fan, short to medium range, single aisle, transport category airplane.

3. Equipment

Equipment approved for installation is listed in the Certification Standard Equipment List ref. 00D000A0101/C1S (not applicable for A320-216, A320-215, A320-251N, A320-252N, A320-253N, A320-271N, A320-272N and A320-273N).

Cabin furnishings, equipment and arrangement shall be in conformance to the following specifications:

Cabin seats	2521M1F10000 at latest approved issue.
Galleys	2530M1F000900 at latest approved issue.

4. Dimensions

Principal dimensions of A320 Aircraft:

- Length:	37.57 m
- Width:	34.10 m
(if MOD 160500 or 160080 is installed)	35.80 m
- Height:	11.76 m
- Width at horizontal stabilizer:	12.45 m
- Outside fuselage diameter:	3.95 m
- Distance between engines axis:	11.51 m
- Distance between main landing gear:	7.59 m
- Distance between nose and main landing gear:	12.64 m

5. Engines

The list below lists the basic engines fitted on the aircraft models. The notes describe usual names and certified names as well as new engines variants.

A320-211

Two CFMI CFM 56-5A1 jet engines (MOD 20141), or
CFM 56-5A1/F jet engines (MOD 23755)



SECTION 1: A320 SERIES**A320-212**

Two CFMI CFM 56-5A3 jet engines (MOD 22093)

A320-214Two CFMI CFM 56-5B4 jet engines (MOD 24251), or
CFM 56-5B4/2 jet engines (MOD 24405)**A320-215**

Two CFMI CFM 56-5B5/P jet engines (MOD 25800)

A320-216

Two CFMI CFM 56-5B6/P jet engines (MOD 25800)

A320-231

Two IAE V2500-A1 jet engines (MOD 20165)

A320-232

Two IAE V2527-A5 jet engines (MOD 23008)

A320-233

Two IAE V2527E-A5 jet engines (MOD 25068)

A320-271N

Two IAE PW1127G-JM Geared Turbo Fan jet engines (MOD 161000)

A320-251N

Two CFMI LEAP-1A26 jet engines (MOD 161003)

A320-252N

Two CFMI LEAP-1A24 jet engines (MOD 162680)

A320-272N

Two IAE PW1124G1-JM Geared Turbo Fan jet engines (MOD 163955)

A320-253N

Two CFMI LEAP-1A29 jet engines (MOD 161860)

A320-273N

Two IAE PW1129G-JM Geared Turbo Fan jet engines (MOD 162512)

ACJ320 NEOTwo CFMI LEAP-1A26CJ jet engines (MOD 165333)
Two IAE PW1127G-JM Geared Turbo Fan jet engines (MOD 161000)
Two IAE PW1124G1-JM Geared Turbo Fan jet engines (MOD 163955)
Two IAE PW1129G-JM Geared Turbo Fan jet engines (MOD 173371)

SECTION 1: A320 SERIES**Notes:**

- 1 Whereas it is common use to apply the name of CFMI engines CFM56-5A1 and CFM56-5A1/F, the correct names of the certified engines are:
 - CFM56-5 is the certified engine name, when CFM56-5A1 is the usual name.
 - CFM56-5-A1/F is the certified engine name, when CFM56-5A1/F is the usual name.
- 2 A320-211 CFM 56-5A1 engine can be intermixed with CFM 56-5A1/F engine (MOD 23755) on the same aircraft.
- 3 From March 31st, 2008, there is no longer any CFM56-5B/2 non /P in field or in production. CFM56-5B4/2 engine model has been removed from CFM56-5B Type Certificate Data Sheet.
- 4 If modification 25800 is embodied on models with CFM56-5B engines, the engine performance is improved. The engine's denomination changes to /P.

The modification is currently applicable for:

A320-214: CFM56-5B4 (SAC) which changes to CFM56-5B4/P

CFM 56-5B/"non-P" engine can be intermixed with CFM 56-5B/P engine on the same aircraft.

Note: modification 25800 is basically embodied for A320-215 and -216 models.

- 5 If modification 26610 is embodied on models with CFM-5B/2 (DAC) engines, the engine performance and gaseous emission levels are improved. The modification is currently applicable for:

A320-214: CFM 56-5B4/2(DAC) which changes to CFM 56-5B4/2P(DAC II C).

CFM 56-5B/2 "non-P" (DAC) engine can be intermixed with CFM 56-5B/2P(DAC II C) engine on the same aircraft (AFM supplement).

CFM 56-5B/P or / "non-P" (SAC) engine can be intermixed with CFM 56-5B/2P (DAC II C) engine on the same aircraft (AFM supplement).

Modification 26610 is not compatible with modification 160080 (sharklet retrofit).

- 5 A320-214 CFM 56-5B4 engine can be intermixed with CFM 56-5B4/2 engine (MOD 24405) on the same aircraft (AFM supplement).
- 6 Introduction of CFM56-5Bx/3 "Tech Insertion" engine is done through embodiment of modification 37147 in production or 38770 in field.
This modification is only applicable on CFM56-5Bx /P SAC engines.
If modification 37147 is embodied on models with CFM-5B engines, the engine's denomination changes to /3.

The modification is currently applicable for:

A320-214: CFM 56-5B4 (SAC) which changes to CFM 56-5B4/3



SECTION 1: A320 SERIES

- A320-215: CFM 56-5B5 (SAC) which changes to CFM 56-5B5/3
 A320-216: CFM 56-5B6 (SAC) which changes to CFM 56-5B6/3

Modification 37147 has been demonstrated as having no impact on previously certified noise levels.

The engine characteristics remain unchanged.

CFM56-5Bx/3 engine can be intermixed with CFM56-5Bx/P engine under considerations as prescribes in modification 38573.

- 7 Introduction of “BUMP” function is done through embodiment of modification 38946.
 If modification 38946 is embodied on models with CFM-5B engines, the engine denomination changes to /P1 (SAC) or /2P1 (DAC) or /3B1 (Tech Insertion).

The modification is currently applicable for:

- A320-214: CFM 56-5B4 (SAC) which changes to CFM 56-5B4/P1

Modification 38946 has been demonstrated as having no impact on previously certified noise levels.

The engine characteristics remain unchanged.

Intermix at aircraft level between “non-Bump” engine and “Bump” engine is not allowed.

- 8 CFM56-5B engines are not compatible with modification 160080 (Sharklet retrofit) unless modification 37147 or modification 38770 are installed.
- 9 If modification 161562 (alternate climb) is installed on the A320-271N equipped with IAE PW1127G-JM, then the engine model is changed to PW1127GA-JM.
- 10 If modification 161925 (extended corner point) is installed on the A320-251N equipped with CFM LEAP-1A26 engines, then the engine model is changed to LEAP-1A26E1.
- 11 If modification 165333 is installed on the A320-251N equipped with CFM LEAP-1A26 engines, then the engine model is changed to LEAP-1A26CJ

6. Auxiliary Power Unit

APU GARRETT

The APU GARRETT AIRESEARCH GTCP 36-300 (A) installation is defined by MOD 20020 (Specification 31-5306B)

Approved oils: see GARRETT REPORT GT. 7800

APU Pratt & Whitney Rzeszow S.A.

The APU Pratt & Whitney Rzeszow S.A. installation is defined by MOD 22562 or MOD 35864.

Pratt & Whitney Rzeszow S.A. APS 3200 (Specification ESR 0802, Rev. A)

Approved oils: in conformance to MIL-L-7808, MIL-L-23699 or DERD 2487



SECTION 1: A320 SERIES**APU AlliedSignal**

The APU Honeywell International installation is defined by MOD 25888 or 37987
Honeywell International 131-9[A] (Specification 4900 M1E 03 19 01)
Approved oils: according to model Specification 31-12048A-3A

7. Propellers

N/A

8. Fluids (Fuel, Oil, Additives, Hydraulics)

Fuel**Fuel Specification**

ENGINES	KEROSENE DESIGNATION
CFM56: Installation document CFM 2026 or CFM 2129)	JET A, JET A-1, JP5, JP8, N°3 Jet Fuel, JET B**, JP 4**, TS-1, RT(GOST), F44, F34, AVTUR, AVTUR/FSII, AVTAG/FSII, AVCAT/FSII
IAE V2500: IAE Standard Practices and processes Manual IAE 0043	JET A, JET A-1, JP5, JP8, N°3 Jet Fuel, JET B**, JP 4**, TS-1*, RT(GOST), F44, F34, AVTUR, AVTUR/FSII, AVTAG/FSII, AVCAT/FSII
IAE PW1100G-JM: (Service Bulletin PW1000G - 100-73 00-0002-00A930AD)	JET A, JET A-1, JP5, JP8, N°3 Jet fuel, TS-1(GOST), RT(GOST), AVTUR, AVTUR/FSII, AVCAT/FSII
CFMI LEAP-1A: Service Bulletin LEAP-1A S/B 73-0001	JET A, JET A-1, JP5, JP8, N°3 Jet fuel, TS-1(GOST), RT(GOST), AVTUR, AVTUR/FSII, AVCAT/FSII

The above-mentioned fuels are also suitable for the APU.

Refer to Consumable Material List (CML) for details on approved fuel specifications

- * For IAE V2500 engines, TS-1 is cleared for transient use (less than 50% of operations)
- ** JET B and JP 4 fuels are not authorized for use in aircraft fitted with jet pumps (modification 154327)

OIL

For oil specification:

Engine	CFM56-5B5/P CFM56-5B6/P CFM56-5A1 CFM56-5A1/F CFM56-5A3 CFM56-5B4 CFM56-5B4/2	IAE V2500-A1 IAE V2527-A5 IAE V2527E-A5	PW1127G-JM PW1124G1-JM PW1129G-JM	LEAP-1A26 LEAP-1A26E1 LEAP-1A24 LEAP-1A26CJ LEAP-1A29
--------	---	---	---	---



SECTION 1: A320 SERIES

Approved Oils	SB CFMI 79-001	See doc IAE 0043 Sect 4.9 (MIL-L- 23699)	Service Bulletin PW1000G – 1000 – 79 – 00 – 0002 - 00A - 930A – D	SB LEAP-1A S/B 79- 0001
---------------	----------------	--	--	----------------------------

Additives:

Refer to Airbus Consumable Material List (CML).

Hydraulics

Hydraulic fluids: Type IV or Type V - Specification NSA 30.7110



SECTION 1: A320 SERIES

9. Fluid Capacities

Fuel quantity (0.8 kg/litre)**A320-211/-212/-214/-215/-216/-231/-232/-233 (without MOD 160001)**

TANK	3 TANK AIRPLANE		4 TANK AIRPLANE		4 or 5 TANK AIRPLANE *	
	Usable fuel litres (kg)	Unusable fuel litres (kg)	Usable fuel litres (kg)	Unusable fuel litres (kg)	Usable fuel litres (kg)	Unusable fuel litres (kg)
WING	15 609 (12 487)	58.9 (47.1)	15 609 (12 487)	58.9 (47.1)	15 609 (12 487)	58.9 (47.1)
CENTRE	8 250 (6 600)	23.2 (18.6)	8 250 (6 600)	23.2 (18.6)	8 250 (6 600)	23.2 (18.6)
ACT (*)			2992 (2 393)	17 (13.6)	2 992 / 5 984 (2 393 / 4 786)	17 / 34 (13.6 / 27.2)
TOTAL	23 859 (19 087)	82.1 (65.7)	26 851 (21 480)	99.1 (79.3)	26 851 / 29 843 (21 480 / 23 873)	99.1 / 116.1 (79.3 / 92.9)

On the series A320-200, the certification of installing one or two Additional Centre Tanks (ACT) in bulk version is defined by modification 28378.

An alternative is the installation of one ACT only (with the provisions for only one ACT), as defined by modification 34456.

A320-211/-212/-214/-215/-216 (with MOD 37331 and without MOD 160001)

TANK	3 TANK AIRPLANE		4 TANK AIRPLANE		4 or 5 TANK AIRPLANE *	
	Usable fuel litres (kg)	Unusable fuel litres (kg)	Usable fuel litres (kg)	Unusable fuel litres (kg)	Usable fuel litres (kg)	Unusable fuel litres (kg)
WING	15 959 (12 767)	58.9 (47.1)	15 959 (12 767)	58.9 (47.1)	15 959 (12 767)	58.9 (47.1)
CENTRE	8 250 (6 600)	23.2 (18.6)	8 250 (6 600)	23.2 (18.6)	8 250 (6 600)	23.2 (18.6)
ACT (*)			2992 (2 393)	17 (13.6)	2 992 / 5 984 (2 393 / 4 786)	17 / 34 (13.6 / 27.2)
TOTAL	24 209 (19 367)	82.1 (65.7)	27 201 (21 761)	99.1 (79.3)	27 201 / 30 193 (21 761 / 24 154)	99.1 / 116.1 (79.3 / 92.9)

On the series A320-200, the certification of installing one or two Additional Centre Tanks (ACT) in bulk version is defined by modification 28378.

An alternative is the installation of one ACT only (with the provisions for only one ACT), as defined by modification 34456.



SECTION 1: A320 SERIES**A320-211/-212/-214/-215/-216/-231/-232/-233 (without MOD 37331 and with MOD 160001)**

TANK	3 TANK AIRPLANE		4 TANK AIRPLANE		4 or 5 TANK AIRPLANE *	
	Usable fuel litres (kg)	Unusable fuel litres (kg)	Usable fuel litres (kg)	Unusable fuel litres (kg)	Usable fuel litres (kg)	Unusable fuel litres (kg)
WING	15 569 (12 455)	58.9 (47.1)	15 569 (12 455)	58.9 (47.1)	15 569 (12 455)	58.9 (47.1)
CENTRE	8 248 (6 598)	23.2 (18.6)	8 248 (6 598)	23.2 (18.6)	8 248 (6 598)	23.2 (18.6)
ACT (*)			2992 (2 393)	17 (13.6)	2 992 / 5 984 (2 393 / 4 786)	17 / 34 (13.6 / 27.2)
TOTAL	23 817 (19 054)	82.1 (65.7)	26 809 (21 447)	99.1 (79.3)	26 809 / 29 801 (21 447 / 23 841)	99.1 / 116.1 (79.3 / 92.9)

*On the series A320-200, the certification of installing one or two Additional Centre Tanks (ACT) in bulk version is defined by modification 28378.

An alternative is the installation of one ACT only (with the provisions for only one ACT), as defined by modification 34456.

On the series A320-200 equipped with IAE engines, introduction of standard of wingbox with dry bay (modification 37332) will decrease the fuel capacity by 350 litres.

A320-214/-215/-216 (with MOD 37331 and MOD 160001)

TANK	3 TANK AIRPLANE		4 TANK AIRPLANE*		4 or 5 TANK AIRPLANE *	
	Usable fuel litres (kg)	Unusable fuel litres (kg)	Usable fuel litres (kg)	Unusable fuel litres (kg)	Usable fuel litres (kg)	Unusable fuel litres (kg)
WING	15 919 (12 735)	58.9 (47.1)	15 919 (12 735)	58.9 (47.1)	15 919 (12 735)	58.9 (47.1)
CENTRE	8 248 (6 598)	23.2 (18.6)	8 248 (6 598)	23.2 (18.6)	8 248 (6 598)	23.2 (18.6)
ACT (*)			2992 (2 393)	17 (13.6)	2 992 / 5 984 (2 393 / 4 786)	17 / 34 (13.6 / 27.2)
TOTAL	24 167 (19 334)	82.1 (65.7)	27 159 (21 727)	99.1 (79.3)	27 159 / 30 151 (21 727 / 24 121)	99.1 / 116.1 (79.3 / 92.9)

*On the series A320-200, the certification of installing one or two Additional Centre Tanks (ACT) in bulk version is defined by modification 28378.

An alternative is the installation of one ACT only (with the provisions for only one ACT), as defined by modification 34456.



SECTION 1: A320 SERIES**A320-271N/-272N/-273N/-251N/-252N/-253N**

TANK	3 TANK AIRPLANE	
	Usable fuel litres (kg)	Unusable fuel litres (kg)
WING	15476.7 (12427.8)	58.9 (47.3)
CENTRE	8248.0 (6623.1)	23.2 (18.6)
TOTAL	23724.7 (19050.9)	82.1 (65.9)

A320-271N/-272N/-251N equipped with modification 163215 (ACJ320 NEO)

TANK	3 TANK AIRPLANE		4 TANK AIRPLANE		5 TANK AIRPLANE	
	Usable fuel litres (kg)	Unusable fuel litres (kg)	Usable fuel litres (kg)	Unusable fuel litres (kg)	Usable fuel litres (kg)	Unusable fuel litres (kg)
WING	15476.7 (12427.8)	58.9 (47.3)	15476.7 (12427.8)	58.9 (47.3)	15476.7 (12427.8)	58.9 (47.3)
CENTRE	8248.0 (6623.1)	23.2 (18.6)	8248.0 (6623.1)	23.2 (18.6)	8248.0 (6623.1)	23.2 (18.6)
AFT 1	-	-	3138.0 (2510.4)	17.0 (13.6)	3138.0 (2510.4)	17.0 (13.6)
AFT 2	-	-	-	-	3138.0 (2510.4)	17.0 (13.6)
TOTAL	23724.7 (19050.9)	82.1 (65.9)	26862.7 (21561.3)	99.1 (79.5)	30000.7 (24071.7)	116.1 (93.1)

TANK	6 TANK AIRPLANE		7 TANK AIRPLANE	
	Usable fuel litres (kg)	Unusable fuel litres (kg)	Usable fuel litres (kg)	Unusable fuel litres (kg)
WING	15476.7 (12427.8)	58.9 (47.3)	15476.7 (12427.8)	58.9 (47.3)
CENTRE	8248.0 (6623.1)	23.2 (18.6)	8248.0 (6623.1)	23.2 (18.6)
AFT 1	3138.0 (2510.4)	17.0 (13.6)	3138.0 (2510.4)	17.0 (13.6)
AFT 2	3138.0 (2510.4)	17.0 (13.6)	3138.0 (2510.4)	17.0 (13.6)
AFT 3	2208.0 (1766.4)	22.0 (17.6)	2208.0 (1766.4)	22.0 (17.6)



SECTION 1: A320 SERIES

FWD	-	-	2208.0 (1766.4)	22.0 (17.6)
TOTAL	32208.7 (25838.1)	138.1 (110.7)	34416.7 (27604.5)	160.1 (128.3)

Notes

A320-251N, -271N, -272N for Corporate Jet use (commercially identified as ACJ320 NEO) are defined through the following set of modifications:

modification 163215:	Installation of up to 4 ACTs
modification 162744:	Extension of the flight envelope up to 41000 ft
modification 23398:	Install stairs at fwd pax door.
modification 162193:	Lower Cabin Altitude activation
modification 162339:	Certify Envelope for design weight of ACJ320 NEO

10. Airspeed Limits (Indicated Airspeed – IAS – unless otherwise stated)

Maximum Operating Mach (MMO):	0.82
Maximum Operating Speed (VMO):	350 kt
Manoeuvring Speed VA:	See Limitations Section of the EASA approved Flight Manual

Extended Flaps / Slats Speed (VFE): see table below

Configuration	Slats/Flaps (°)	VFE (kt)	
1	18/0 *18/10	230 215	Intermediate approach Take-off
2	22/15	200	Take-off and approach
3	22/20	185	Take-off, approach, landing
Full	27/35**	177	Landing

*Auto flap retraction at 210 kt in take-off configuration

**27/40 for A320 equipped with IAE or CFM LEAP-1A engines

Landing gear:	
VLE - Extended:	280 kt/Mach 0.67
VLO - Extension:	250 kt
Retraction:	220 kt
Tyres limit speed (ground speed):	195.5 kt (225 mph)

11. Flight Envelope

Maximum Operating Altitude:
39 100 ft (pressure altitude)



SECTION 1: A320 SERIES

39 800 ft (pressure altitude) if modification 30748 is embodied
 41 000 ft (pressure altitude) if modification 162744 is embodied

See the appropriate EASA approved Airplane Flight Manual

12. Operating Limitations

See the appropriate EASA approved Airplane Flight Manual.

Powerplant (2.2482 lb/daN)

Engine	CFM56-5B5/P	CFM56-5B6/P	CFMI		
			CFM56-5A1 CFM56-5A1/F (**)	CFM56-5A3	CFM56-5B4 CFM56-5B4/2 (***)
Data sheets	E37NE (FAA) E38NE (FAA) EASA.E.003	E37NE (FAA) E38NE (FAA) EASA.E.003	E28NE (FAA) EASA.E.067	E28NE (FAA) EASA.E.067	E37NE (FAA) E38NE (FAA) EASA.E.003
Static thrust at sea level					
Take-off (5 min)* (Flat rated 30° C)	9 786 daN (22 000 lbs)	10 453 daN (23 500 lbs)	11 120 daN (25 000 lb)	11 787 daN (26 500 lbs)	12 010 daN (27 000 lbs)
Maximum continuous (Flat rated 25° C)	9 008 daN (20 250 lbs)	9 008 daN (20 250 lbs)	10 542 daN (23 700 lbs)	10 542 daN (23 700 lbs)	10 840 daN (24 370 lbs)

(**): see note 1 chapter 5 for usual names and certified names

(***): see note 3 chapter 5 for engine models no longer in prod/service.

Engine	IAE V2500-A1	IAE V2527-A5 IAE V2527E-A5
Data sheets	E31NE (FAA) M-IM22 (DGAC)	E40NE (FAA) EASA.E.069
Static thrust at sea level		
Take-off (5 min)* (Flat rated 30° C)	11 031 daN (24 800 lbs)	11 031 daN (24 800 lbs)
Maximum continuous (Flat rated 25° C)	9 893 daN (22 240 lbs)	9 893 daN (22 240 lbs)

* 10 minutes at take-off thrust allowed only in case of engine failure (at take-off or during go-around) in accordance with DGAC "Fiche de Caractéristiques Moteur"



SECTION 1: A320 SERIES

Engine	CFM LEAP-1A26 LEAP-1A26E1 LEAP-1A26CJ	CFM LEAP-1A24	CFM LEAP-1A29
Data sheets	E00089EN (FAA) EASA.E.110	E00089EN (FAA) EASA.E.110	E00089EN (FAA) EASA.E.110
Static thrust at sea level			
Take-off (5 min)* (Flat rated 30° C)	12 064 daN (27 120 lbs)	10 680 daN (24 010 lbs)	13 029 daN (29 290 lbs)
Maximum continuous (Flat rated 25° C)	11 868 daN (26 680 lbs)	10 676 daN (24 000 lbs)	11 868 daN (26 680 lbs)

Engine	PW1127G-JM/ PW1127GA-JM	PW1124G1-JM	PW1129G-JM
Data sheets	E87NE (FAA) EASA.IM.E.093	E87NE (FAA) EASA.IM.E.093	E87NE (FAA) EASA.IM.E.093
Static thrust at sea level			
Take-off (5 min)* (Flat rated 30° C)	12 043 daN (27 075 lbs)	10 782 daN (24 240 lbs)	13 000 daN (29 245 lbs)
Maximum continuous (Flat rated 25° C)	11 718 daN (26 345 lbs)	10 691 daN (24 035 lbs)	11 719 daN (26 345 lbs)

Other engine limitations: see the relevant Engine Type Certificate Data Sheet

Notes:

- A320-212 (CFM 56-5A3 engines) - A320-211 (CFM 56-5A1/F engines, see note 1 in Chapter 5 "engines" for usual names and certified names). The maximum permissible gas temperature at take-off and max continuous is extended to 915° C and 880° C respectively. However, the ECAM indication remains at 890° C and 855° C.
- A320-231 with modification 23872 (EGT redline increase for IAE engines):
 - for consolidated bump rating operation (MOD 23408), the maximum permissible gas temperature is extended to 650° C at take-off. The ECAM indication remains at 635° C.
 - for non-rating bump operation, the maximum permissible gas temperature is extended to 640° C at take-off. The ECAM indication remains at 635° C.
 - for maximum continuous and take-off operation, the maximum permissible gas temperature is extended to 615° C. The ECAM indication remains at 610° C.
- A320-231 with modification 25000 (FADEC Standard SCN12C for IAE engines):



SECTION 1: A320 SERIES

- for take-off operation, the maximum permissible gas temperature is extended to 650° C. The ECAM indication remains at 635° C.
- for maximum continuous operation, the maximum permissible gas temperature is extended to 625° C. The ECAM indication remains at 610°C.

12.1 Approved Operations

Transport commercial operations.

12.2 Other Limitations

For a complete list of applicable limitations see the appropriate EASA approved Airplane Flight Manual.

13. Maximum Certified Masses**A320-211/A320-212/A320-231**

VARIANT	000 (BASIC (MOD 20802)	001 (MOD 20966)	002 (MOD 21601)	003 (MOD 22269)	004 (MOD 21532)	005 (MOD 21711)
WEIGHT (Kg)						
Max. Ramp Weight	73 900	68 400	70 400	75 900	71 900	67 400
Max. Take-off Weight	73 500	68 000	70 000	75 500	71 500	67 000
Max. Landing Weight	64 500	64 500	64 500	64 500	64 500	64 500
Max. Zero Fuel Weight	60 500	60 500	60 500	60 500	60 500	60 500
Minimum Weight	37 230	37 230	37 230	37 230	37 230	37 230

VARIANT	006 (MOD 22436)	007 (MOD 23264)	008 (MOD 23900)	009 (MOD 23900 & 22269)	010 (MOD 23900 & 23264)	011⁽⁵⁾ (MOD 30307)
WEIGHT (Kg)						
Max. Ramp Weight	66 400	77 400	73 900	75 900	77 400	75 900
Max. Take-off Weight	66 000	77 000	73 500	75 500	77 000	75 500
Max. Landing Weight	64 500	64 500	64 500	64 500	64 500	66 000
Max. Zero Fuel Weight	60 500	60 500	61 000	61 000	61 000	62 500
Minimum Weight	37 230	37 230	37 230	37 230	37 230	37 230

VARIANT	012⁽⁵⁾ (MOD 30479)	013 (MOD 31132)	014 (MOD 31385)	016⁽⁵⁾ (MOD 34094)	018⁽⁵⁾ (MOD 151710)	019 (MOD 156523)
WEIGHT (Kg)						
Max. Ramp Weight	77 400	71 900	73 900	73 900	71 900	70 400
Max. Take-off Weight	77 000	71 500	73 500	73 500	71 500	70 000
Max. Landing Weight	66 000	64 500	64 500	66 000	66 000	64 500
Max. Zero Fuel Weight	62 500	61 000	61 500	62 500	62 500	61 000
Minimum Weight	37 230	37 230	37 230	37 230	37 230	37 230



SECTION 1: A320 SERIES**A320-214/A320-232/A320-233**

VARIANT	000	001	002	003*	005	007*
WEIGHT (Kg)	(BASIC)	(MOD	(MOD	(MOD	(MOD	(MOD
		20966)	21601)	22269)	21711)	23264)
Max. Ramp Weight	73 900	6 8400	70 400	75 900	67 400	77 400
Max. Take-off Weight	73 500	68 000	70 000	75 500	67 000	77 000
Max. Landing Weight	64 500	64 500	64 500	64 500	64 500	64 500
Max. Zero Fuel Weight	60 500	60 500	60 500	60 500	60 500	60 500
Minimum Weight	37 230	37 230	37 230	37 230	37 230	37 230

VARIANT	008*(3)(4)	009*(3)(4)	010*(3)(4)	011*(3)(4)(5)	012*(3)(4)(5)	013*(3)(4)
WEIGHT (Kg)	(MOD	(MOD	(MOD	(MOD	(MOD	(MOD
	23900)	23900)	23900)	30307)	30479)	31132)
		(MOD	(MOD			
		22269)	23264)			
Max. Ramp Weight	73 900	75 900	77 400	75 900	77 400	71 900
Max. Take-off Weight	73 500	75 500	77 000	75 500	77 000	71 500
Max. Landing Weight	64 500	64 500	64 500	66 000	66 000	64 500
Max. Zero Fuel Weight	61 000	61 000	61 000	62 500	62 500	61 000
Minimum Weight	37 230	37 230	37 230	37 230	37 230	37 230

VARIANT	014*(3)(4)	015*(3)	016*(3)(4)(5)	017*(3)(5)	018*(3)(4)(5)	019*(3)(4)
WEIGHT (Kg)	(MOD	(MOD	(MOD	(MOD	(MOD	(MOD
	31385)	34047)	34094)	151634)	151710)	156523)
Max. Ramp Weight	73 900	78 400	73 900	78 400	71 900	70 400
Max. Take-off Weight	73 500	78 000	73 500	78 000	71 500	70 000
Max. Landing Weight	64 500	64 500	66 000	66 000	66 000	64 500
Max. Zero Fuel Weight	61 500	61 000	62 500	62 500	62 500	61 000
Minimum Weight	37 230	37 230	37 230	37 230	37 230	37 230

A320-215/A320-216

VARIANT	000	001*(1)	002*	003*	005(2)	008*(3)(4)
WEIGHT (Kg)	(BASIC)	(MOD	(MOD	(MOD	(MOD	(MOD
	(MOD	20966)	21601)	22269)	21711)	23900)
	20802)					
Max. ramp weight	73 900	68 400	70 400	75 900	67 400	73 900
Max. Take-off Weight	73 500	68 000	70 000	75 500	67 000	73 500
Max. Landing Weight	64 500	64 500	64 500	64 500	64 500	64 500
Max. Zero Fuel Weight	60 500	60 500	60 500	60 500	60 500	61 000
Minimum Weight	37 230	37 230	37 230	37 230	37 230	37 230

VARIANT	009*(3)(4)	011*(3)(4)(5)	013*(3)(4)	014*(3)(4)	016*(3)(4)(5)	018*(3)(4)(5)
WEIGHT (Kg)		(MOD	(MOD	(MOD	(MOD	(MOD
		30307)	31132)	31385)	34094)	151710)



SECTION 1: A320 SERIES

	(MOD 23900 & 22269)					
Max. ramp weight	75 900	75 900	71 900	73 900	73 900	71 900
Max. Take-off Weight	75 500	75 500	71 500	73 500	73 500	71 500
Max. Landing Weight	64 500	66 000	64 500	64 500	66 000	66 000
Max. Zero Fuel Weight	61 000	62 500	61 000	61 500	62 500	62 500
Minimum Weight	37 230	37 230	37 230	37 230	37 230	37 230

VARIANT	019⁽³⁾⁽⁴⁾ (MOD 156523)
Max. ramp weight	70 400
Max. Take-off Weight	70 000
Max. Landing Weight	64 500
Max. Zero Fuel Weight	61 000
Minimum Weight	37 230

Notes:

- * WV option certified concurrently with the basic WV at the time of the model's approval
- (1) WV001 applicable to A320-215 (and –216) model only from MSN 530 (Introduction of A320-214 model)
- (2) WV005 applicable to A320-215 (and –216) models only for a/c having modification 28154 embodied
- (3) MOD 160500 is approved for WV 008 to WV 019, only.
- (4) MOD 160080 is approved for WV 008 to 014, 016 & 018-019 only
- (5) MOD 158708 is approved for WV 011, 012, 016-018 only

A320-271N/-272N/-273N/-251N/-252N/-253N

VARIANT	050 BASIC (MOD 161248)	051* (MOD 161380)	052* (MOD 161379)	053* (MOD 161384)	054 * (MOD 161381)
Max. ramp weight	73 900	73 900	77 400	77 400	79 400
Max. Take-off Weight	73 500	73 500	77 000	77 000	79 000
Max. Landing Weight	66 300	67 400	66 300	67 400	66 300
Max. Zero Fuel Weight	62 800	64 300	62 800	64 300	62 800



SECTION 1: A320 SERIES

VARIANT	055* (MOD 161249)	056* (MOD 161383)	057* (MOD 161382)	069 (MOD 157908)	071 (MOD 157910)	075** (MOD 157914)
Max. ramp weight	79 400	70 400	70 400	75 900	75 400	74 400
Max. Take-off Weight	79 000	70 000	70 000	75 500	75 000	74 000
Max. Landing Weight	67 400	66 300	67 400	67 400	67 400	67 400
Max. Zero Fuel Weight	64 300	62 800	64 300	64 300	64 300	64 300

VARIANT	083 (MOD 157922)	085 (MOD 157924)	103 (MOD 169007)
Max. ramp weight	71 900	71 400	79 400
Max. Take-off Weight	71 500	71 000	79 000
Max. Landing Weight	67 400	67 400	68 400
Max. Zero Fuel Weight	64 300	64 300	65 300

In addition, the following weight variants are also certified for the A320-271N/-272N/-251N

VARIANT	068 (MOD 157907)			078 (MOD 157917)	082 (MOD 157921)
Max. ramp weight	75 900			72 900	71 900
Max. Take-off Weight	75 500			72 500	71 500
Max. Landing Weight	66 300			66 300	66 300
Max. Zero Fuel Weight	62 800			62 800	62 800

In addition, the following weight variants are also certified for the A320-271N/-272N/-251N equipped with modifications 162744, 163215 and 23398 (ACJ320 NEO specific weight variants)

VARIANT	110 (MOD 160808)	111 (MOD 160809)	112 (MOD 160810)
Max. ramp weight	79 400	78 400	77 400
Max. Take-off Weight	79 000	78 000	77 000
Max. Landing Weight	67 400	67 400	67 400
Max. Zero Fuel Weight	55 300	55 300	55 300

Notes:

- * WV option certified concurrently with the basic WV at the time of the model's approval
- ** WV 075 is not approved for the A320-272N, -273N, -253N

A320-251N/-252N/-253N have a Minimum Weight of 40600.

A320-271N/-272N/-273N have a Minimum Weight of 40300.



SECTION 1: A320 SERIES

14. Centre of Gravity Range

See approved Airplane Flight Manual.

15. Datum

Station 0.0, located 2.540 meters forward of airplane nose.

16. Mean Aerodynamic Chord (MAC)

4.1935 meters.

17. Levelling Means

The A/C can be jacked on three primary jacking points.
See the appropriate EASA approved Weight and Balance Manual.

18. Minimum Flight Crew

2 pilots.

19. Minimum Cabin Crew

See paragraph 20.

20. Maximum Seating Capacity

The table below provides the certified Maximum Passenger Seating Capacities (MPSC), the corresponding cabin configuration (exit arrangement and modifications) and the associated minimum numbers of cabin crew members used to demonstrate compliance with the certification requirement:



SECTION 1: A320 SERIES

MPSC	Cabin configuration	Modification	Minimum CC
195	C*-III-III-C*	156723, 158708 or 158819	4
180	C-III-III-C		4
165	C*-III-C*	164024	4
150	C-III-III-C	150364	3
145	C-III-C	150016 or 35177	3

Note: C* is the over-performing exit according to modification 156723/158708/158819

The original maximum passenger seating capacity is 180.

The Modifications 156723, 158708 or 158819 enable the maximum seating capacity to be increased from 180 up to 195. These modifications define a virtual envelope of the Layout of Passenger Accommodations (LOPA) and do not constitute an authorization for the installation of seats in excess of 180. A separate approval is needed for the installation of the individual customized cabin layout and the necessary cabin adaptations up to 195 seats.

Note: The second Type III emergency exit can be de-activated by embodiment of modification 35177 (aft overwing exit) or modification 150016 (forward overwing exit). The maximum number of passengers between any of the overwing exit doors and rear door is 90.

When modification 164024 applies: If modification 35177 or modification 150016 is installed with modification 156723 or 158708 or 158819 the maximum number of passengers between the overwing exit doors and the forward or rear door is 100.

For modification 164024 in combination with 150364 the MPSC is 150, the minimum cabin crew is 3.

With MOD 153648 "EQUIPMENT/FURNISHINGS - GENERAL - DELIVER AIRCRAFT WITH INCOMPLETE CABIN" embodied, the cabin is limited to zero occupancy and no cargo (i.e. no occupancy and no cargo in cabin) during all phases of flight, unless a separate approved Modification is embodied to remove the limitation.



SECTION 1: A320 SERIES**21. Baggage/ Cargo Compartment**

CARGO COMPARTMENT	MAXIMUM LOAD (kg)
Forward	3 402
Aft	4 536
Rear (bulk)	1 497

For the positions and the loading conditions authorized in each position (references of containers, pallets and associated weights) see Weight and Balance Manual, ref. 00E080A0001/C1S Chapter 1.10.

22. Wheels and Tyres

See SB A320 32 1007 for A320-211/-212/-214/-215/-216/-231/-232/-233
SB A320 32 1439 for 320-271N/-272N/-273N/-251N/-252N/-253N

Aircraft incorporating modification 20139 and without modification 22129, are equipped with a four-wheel bogie landing gear (up to 73.5 T MTOW).

23. ETOPS

The Type Design, system reliability and performance of A320 models were found capable for Extended Range Operations when configured, maintained and operated in accordance with the current revision of the ETOPS Configuration, Maintenance and Procedures (CMP) document, SA/EASA: AMC 20-6/CMP.

This finding does not constitute an approval to conduct Extended Range Operations (operational approval must be obtained from the responsible Authority).

The following table provides details on the ETOPS approvals.

Aircraft model	Engine Type	120 min Approval Date	180 min Approval Date
A320-211	CFM56-5A1	17 September 1991	11 March 2004
A320-212	CFM56-5A3	17 September 1991	11 March 2004
A320-214	CFM56-5B4	28 April 1995	11 March 2004
A320-215	CFM56-5B5	N/A	06 November 2006
A320-216	CFM56-5B6	N/A	06 November 2006
A320-231	V2500-A1	13 January 1992	11 March 2004
A320-232	V2527-A5	28 April 1995	11 March 2004
A320-233	V2527E-A5	14 February 1997	11 March 2004
A320-271N	PW1127G-JM	27 June 2017	27 June 2017 (10 Jan 2019 for ACJ320 NEO)
A320-251N	CFM LEAP-1A26	10 July 2017	10 July 2017 (10 Jan 2019 for ACJ320 NEO)
A320-251N	CFM LEAP-1A26E1	07 May 2020	07 May 2020



SECTION 1: A320 SERIES

			(Including ACJ320 NEO)
A320-252N	CFM LEAP-1A24	17 January 2018	17 January 2018
A320-253N	CFM LEAP-1A29	19 August 2019	19 August 2019
A320-272N	PW1124G1-JM	19 August 2019	19 August 2019
A320-273N	PW1129G-JM	19 August 2019	19 August 2019

Note:

The Configuration, Maintenance and Procedure Standards for extended range twin-engine airplane operations are contained in ETOPS CMP document reference SA/EASA: AMC 20-6/CMP at latest applicable revision. Certificated models are A320-211/-212/-214/-215/-216/-231/-232/-233/-271N/-251N/-252N/-253N/-272N/-273N, with all applicable engines

Embodiment of modification:

36666 provides ETOPS 120 mn capability for EASA

32009 provides ETOPS 180 mn capability for EASA

IV. Operating and Service Instructions**1. Airplane Flight Manual (AFM)**

EASA approved Airplane Flight Manual for A320.

2. Instructions for Continued Airworthiness and Airworthiness Limitations

The complete set of Instructions for Continued Airworthiness is identified in paragraph 2 of the Aircraft Maintenance Manual introduction.

Airworthiness Limitations

- Limitations applicable to Safe Life Airworthiness Limitation Items are provided in the A318/A319/A320/A321 approved Airworthiness Limitations Section (ALS) sub-parts 1-2 and 1-3.
- Limitations applicable to Damage Tolerant Airworthiness Limitation Items are provided in the A318/A319/A320/A321 approved Airworthiness Limitations Items document (ALS Part 2).
- Certification Maintenance Requirements are provided in the A318/A319/A320/A321 approved Airworthiness Limitations Section (ALS) Part 3.
- System Equipment Maintenance Requirements are provided in the A318/A319/A320/A321 approved Airworthiness Limitations Section (ALS) Part 4.
- Fuel Airworthiness Limitations are provided in the A318/A319/A320/A321 approved Fuel Airworthiness Limitations document (ALS Part 5).
- Maintenance Review Board Report



SECTION 1: A320 SERIES**Note:**

For A320-211, -212, -231, -232 and -233 models, the embodiment of modification 37734 leads to change the maintenance program and its associated Maintenance Programme Publication Trigger (MPPT) from 48,000FC/60,000FH to 37,500FC/80,000FH (whichever occurs first).
For A320-211, -212, -214, -215, -216, -231, -232, -233 models without sharklets, the embodiment of modification 39020 leads to change the maintenance program and its associated Maintenance Programme Publication Trigger (MPPT) from 48,000FC/60,000FH to 60,000FC/120,000FH (whichever occurs first).

Other limitations

See EASA approved Flight Manual.

3. Weight and Balance Manual (WBM)

Airbus Compliance Document 00D80A0001/C1S

V. Operational Suitability Data (OSD)

The Operational Suitability Data elements listed below are approved by the European Union Aviation Safety Agency under the EASA Type Certificate EASA.A.064 as per Commission Regulation (EU) 748/2012 as amended by Commission Regulation (EU) No 69/2014.

1. Master Minimum Equipment List

- a. The Master Minimum Equipment List has been approved as per the defined Operational Suitability Data Certification Basis (JAR-MMEL/MEL – Subpart B – MMEL at Amendment 1) and as documented in A320 MMEL reference “MMEL STL11000” at the latest applicable revision.
- b. Required for entry into service by EU operator.

2. Flight Crew Data

- a. The Flight Crew data has been approved as per the defined Operational Suitability Data Certification Basis (CS-FCD, initial issue) and as documented in reference “A320 Operational Suitability Data Flight Crew - SA01RP1536744” at the latest applicable revision.
- b. Required for entry into service by EU operator.
- c. The aircraft models: A318, A319, A321 are determined to be variants to the A320 aircraft model.

3. Cabin Crew Data

- a. The Cabin Crew data has been approved as followed and as documented in reference “A320 Operational Suitability Data Cabin Crew - SA01RP1534113” at the latest applicable revision.



SECTION 1: A320 SERIES

1. Until 20 Jan 2022 (date of MOD 165947 iss 1 Adapt lavatory SpaceFlex V2 for Airspace Cabin):
A318, A319, A320: Certification Basis/SC CCD-01
A321 except A321NX: Certification Basis/SC CCD-01
A321NX (A321-271NX,-272NX,-251NX,-252NX,-253NX): SC CCD-01 + CS-CCD.400(a) at initial issue
 2. After 20 Jan 2022 (date of MOD 165947 iss 1 Adapt lavatory SpaceFlex V2 for Airspace Cabin): A318, A319, A320, A321: Certification Basis/SC CCD-01 + CS-CCD.400 at initial issue
- b. Required for entry into service by EU operator.
 - c. The aircraft models: A318, A319, A321 are determined to be variants to the A320 aircraft model.

VI. Part-26 compliance information

For all models, compliance with point 26.300(a) of Part-26 is demonstrated by complying with points

- 26.301 Compliance Plan for (R)TC holders
- 26.302 Fatigue and damage tolerance evaluation
- 26.303 Limit of Validity
- 26.304 Corrosion prevention and control programme
- 26.306 Fatigue critical baseline structure
- 26.307 Damage tolerance data for existing changes to fatigue-critical structure
- 26.308 Damage tolerance data for existing repairs to fatigue-critical structure
- 26.309 Repair Evaluation Guidelines

VII. Notes

1. For models A320-211 and A320-212, modification 21038 shall be installed to enable Cat IIIB precision approach.
For model A320-231, modification 21039 shall be installed to enable Cat IIIB precision approach.

A320-214, -215, -216, -232, -233 are qualified for Cat IIIB precision approach per basic design definition.

For A320-251N/-252N/-253N/-271N/-272N/-273N modification 161765 shall be installed to enable Cat IIIB precision approach.



SECTION 2: A321 SERIES**SECTION 2: A321 SERIES****I. General**

1. Type/ Model/ Variant

A321-111
 A321-112
 A321-131
 A321-211
 A321-212
 A321-213
 A321-231
 A321-232
 A321-271N
 A321-251N
 A321-253N
 A321-272N
 A321-252N
 A321-251NX
 A321-252NX
 A321-253NX
 A321-271NX
 A321-272NX

Significant Product Level Changes i.a.w. 21.A.101:

MOD 160023 Sharklet applicable on	A321-211, A321-212, A321-213, A321-231, A321-232
MOD 157272 Iss 1 Max Pax applicable on	A321-211, A321-212, A321-213, A321-231, A321-232
MOD 161002 Iss 1	A321-271N
MOD 161005 Iss 1	A321-251N
MOD 157272 Iss 2 Max Pax applicable on	A321-271N
MOD 157272 Iss 3 Max Pax applicable on	A321-251N, A321-253N
MOD 159536 Iss 1 Max Pax applicable on	A321-211,-212,-213,-231,-232
MOD 160766 Iss 1	A321-251NX,-252NX,-253NX,-271NX,-272NX
MOD 157272 Iss 4 Max Pax applicable on	A321-252N, A321-272N
A321 CEO*	A321-111/-112/-131/-211/-212/-213/-231/-232
A321 NEO*	A321-271N/-251N/-253N/-272N/-252N/-251NX/-252NX/-253NX/-271NX/-272NX

*Commercial designation only



SECTION 2: A321 SERIES

2. Performance Class

A

3. Certifying Authority

European Union Aviation Safety Agency (EASA)
Postfach 101253
D-50452 Köln
Deutschland

4. Manufacturer

AIRBUS
2 rond-point Emile Dewoitine
31700 BLAGNAC – France

5. State of Design Authority Certification Application Date

A321-111:	November 30, 1989
A321-112:	November 30, 1989
A321-131:	November 30, 1989
A321-211:	July 17, 1996
A321-212:	February 22, 2001
A321-213:	February 22, 2001
A321-231:	July 17, 1996
A321-232:	September 15, 2000

6. EASA Type Certification Application Date

Mod 160023	08 April 2010
Mod 157272 Iss 1	20 October 2014
Mod 161002	29 February 2012
Mod 161005	29 February 2012
Mod 161006	10 November 2016
Mod 157272 Iss 2	28 October 2016
Mod 162038	10 November 2016
Mod 157272 Iss 3	22 December 2016
Mod 162681	10 November 2016
Mod 159536	01 July 2016
Mod 160766	11 February 2015
Mod 157272 Iss 4	14 October 2019

7. State of Design Authority Type Certificate Date

A321-111:	May 27, 1994
-----------	--------------



SECTION 2: A321 SERIES

A321-112:	February 15, 1994
A321-131:	December 17, 1993
A321-211:	March 20, 1997
A321-212:	August 31, 2001
A321-213:	August 31, 2001
A321-231:	March 20, 1997
A321-232:	August 31, 2001

Note: For A321 produced before December 21, 2005 DGAC-F TC 180 remains a valid reference.

8. EASA Type Certification Date

EASA TCDS issue 1 issued December 21, 2005

Mod 160023 issue 1	17 July 2013 (A321-211)
Mod 160023 issue 2	30 July 2013 (A321-231)
Mod 160023 issue 4	16 June 2014 (A321-212, -213, -232)
Mod 157272 issue 1	19 June 2015 (A321-211/-212/-213/-231/-232)
Mod 161002 issue 1	15 December 2016 (A321-271N)
Mod 161005 issue 1	1 March 2017 (A321-251N)
Mod 161006 issue 1	3 March 2017 (A321-253N)
Mod 157272 issue 2	6 March 2017 (A321-271N)
Mod 162038 Issue 1	23 May 2017 (A321-272N)
Mod 157272 issue 3	31 May 2017 (A321-251N/-253N)
Mod 162681 issue 1	18 December 2017 (A321-252N)
Mod 159536 issue 1	24 November 2017 (A321-211/-212/-213/-231/-232)
Mod 160766 issue 1	22 March 2018 (A321-251NX/-252NX/-253NX/-271NX/-272NX)
Mod 157272 issue 4	07 May 2020 (A321-252N/-272N)

II. Certification Basis**1. Reference Date for determining the applicable requirements**

AIRBUS INDUSTRIE has applied for A321-100 certification on November 30, 1989 by letter AI/EA-410.106/89.

2. State of Design Airworthiness Authority Type Certification Data Sheet No.

Original French TCDS DGAC no. 180 was replaced by the EASA TCDS A.064

3. State of Design Airworthiness Authority Certification Basis

See below



SECTION 2: A321 SERIES**4. EASA Airworthiness Requirements**

Hereafter are listed the certification basis for the different A321 models. The amendments made to a particular basis at the occasion of further A321 models certification are identified per model.

4.1 JAR 25 Change 11 as amended by the following JAR 25 Change 13 paragraphs effective on the reference date November 30, 1989:

JAR 25X20	JAR 25.345(a)
JAR 25.101	JAR 25.365
JAR 25.105	JAR 25.812(e)
JAR 25.107(d)	JAR 25.853 (a)(b) since MSN 118
JAR 25.109(a)	JAR 25.857(d)(6)
JAR 25.113	JAR 25.1501(c)
JAR 25.119(b)	JAR 25.1533(b)
JAR 25.121	JAR 25.1581(b)
JAR 25.125	JAR 25.1583(k)
JAR 25.143(f)	JAR 25.1587
JAR 25.207	JAR 25X1591
JAR 25.253	

Associated to JAR 25 Change 13, the following paragraphs are deleted:

JAR 25X131	Change 11
JAR 25X132	Change 11
JAR 25X133	Change 11
JAR 25X135	Change 11
JAR 25X1588	Change 11

4.2 Airbus Industrie has applied for A321-200 certification on July 17, 1996 by letter AI/EA-S 413.1938/96.

The previous certification basis of the A321-100 remains applicable, except 4.3.b which is superseded by the Airbus Industrie elect-to-comply (letter AI/EA-S 413.0278/97 dated January 29, 1997) with NPA 25 BDG 244 dated January 1996, amended 24/04/96, 22/05/96, 07/06/96, 04/07/96) (see EtC F-3012).

4.3 JAR AWO Change 1 for autoland and operations in low visibility.

4.4 For the Extended Twin Engine Airplane Operations, the applicable technical conditions are contained in AMC 20-6 (as initially published in AMJ 120-42/IL 20) and:

G-3006	ETOPS
G-3007	ETOPS One engine inoperative cruise speed.

4.5 Certification basis has been revised for MOD 160023 "Sharklet".

The certification basis is that of the A321-211,-212,-213,-231,-232 amended by the following:



SECTION 2: A321 SERIES**CS 25 Amdt 8 for**

§ 25.23	§ 25.481(a)(c) amended by SC A-2 for § 25.481(a)
§ 25.25	§ 25.483
§ 25.117	§ 25.485
§ 25.147	§ 25.489
§ 25.161	§ 25.491
§ 25.177 amended by SC F-16	§ 25.571(a)(b)(e)
§ 25.235	§ 25.581
§ 25.251	§ 25.601
§ 25.301	§ 25.603
§ 25.302	§ 25.605
§ 25.303	§ 25.607
§ 25.305(a)(b)(c)(e)(f)	§ 25.609
§ 25.307(a)(d)	§ 25.613
§ 25.321(a)(b)(c)(d)	§ 25.619
§ 25.331(a)(b)(c)	§ 25.623
§ 25.333(a)(b)	§ 25.625
§ 25.335(a)(c)(d)(e)(f) amended by SC A-5003 for (b) and SC A-2 for (e)	§ 25.629
§ 25.337	§ 25.631
§ 25.341(a)(b)	§ 25.651
§ 25.343(a)(b)	§ 25.683
§ 25.345(a)(b)(c)(d)	§ 25.899
§ 25.349(a)(b) amended by SC A-2.2.2 for 25.349(a)	§ 25.903(d)(1)
§ 25.351	§ 25.1385
§ 25.365(a)(b)(d)	§ 25.1387
§ 25.367	§ 25.1389
§ 25.371	§ 25.1391
§ 25.373	§ 25.1393
§ 25.391	§ 25.1395
§ 25.393(b)	§ 25.1397
§ 25.427	§ 25.1401
§ 25.445	§ 25.1505
§ 25.457	§ 25.1511
§ 25.459	§ 25.1515
§ 25.471(a)(b)	§ 25.1527
§ 25.473	§ 25.1587
§ 25.479(a)(c)(d) amended by SC A-2 for § 25.479(a)	§ 25.1591

CS 25 Amdt 2 for

§ 25.253	
----------	--

JAR 25 Chg 15 for

§ 25.1517	
-----------	--



SECTION 2: A321 SERIES**JAR 25 Chg 14 for**

§ 25.21 amended by A318 SC F-5001 (for b)	§ 25.149 + OP96/1
§ 25.101 amended by SC F-11/S-79	§ 25.171 replaced by SC F-5004
§ 25.103 replaced by A318 SC F-5001	§ 25.173 replaced by SC F-5004
§ 25.105 amended by SC F-11/S-79	§ 25.175 replaced by SC F-5004
§ 25.107 amended by A318 SC-F-5001	§ 25.181
§ 25.109 amended by SC F-11/S-79	§ 25.201 + OP96/1, replaced by SC F-5001
§ 25.111	§ 25.203 + OP96/1, replaced by SC F-5001
§ 25.113 + OP96/1 amended by SC F-11/S-79	§ 25.207 amended by SC F-5001
§ 25.115 amended by SC F-11/S-79	§ 25.231
§ 25.119 + OP96/1 amended by A318 SC F-5001 (for b)	§ 25.233
§ 25.121 + OP96/1, amended by A318 SC F-5001 (for c & d)	§ 25.237
§ 25.123	§ 25X261
§ 25.125 + OP96/1, amended by A318 SC F-5001	§ 25.1533
§ 25.143 + OP96/1, amended by SC F-3, F-7 & F-8	§ 25.1581
§ 25.145 + OP96/1	§ 25.1585(a)

JAR 25 Chg 11 for

§ 25.671	§ 25.672
§ 25.1001	§ 25.1301
§ 25.1309	§ 25.1419 amended by AMC-F14

ETOPS

AMC 20-6 Rev 1 paragraphs related to operation in icing conditions 8.b.(11) for ice shapes on the Sharklet device.

AMC 20-6 Rev 1 paragraphs related to performance data in the AFM supplement for ETOPS 8.f.(1) (iii).

AMJ 120-42 for ETOPS for non-affected areas.

Note: This corresponds to the certification basis used for the initial ETOPS demonstration (refer to A320 EtC G-1006).

4.6 Certification basis has been revised for MOD 157272 issue 1 “Max Pax”.

The certification basis is that of the A321-200 equipped with Sharklets amended by the following:

CS 25 Amdt 15 for

§25.23	§25.489
§25.321	§25.801(d)
§25.331	§25. 803(c)
§25.341(a)(b)	§25. 807(g) amended by SC E-3001 and demonstrated through ESF D-02
§25.351	§25.1519
§25.473	§25.1529



SECTION 2: A321 SERIES

§25.479(a)(c)(d) amended by SC A-2 for §25.479(a)	§25.1541(a)(b)
§25.481(a)(c) amended by SC A-2 for §25.481(a)	§25.1557(a)

JAR 25 change 13

§25.305(a)(b)	§25.812(k)(l)
§25.812(e)	§25.853(a)1 amended by SC D-0306-000

JAR 25 change 12

§25.853(c)(d)(e)	
------------------	--

JAR 25 change 11

§25.307(a)	§25.1301
§25.561	§25.1351(a)
§25.571(a)(b)	§25.1353(a)(b)
§25.785	§25.1359(a)(d)
§25.787(a)(b)	§25.1413
§25.789(a)	§25.1415(b)(c)(d)
§25.791	§25.1431(c)
§25.853(a)(b)	§25.1447(c)(1)

4.7 Certification basis for A321-271N, A321-272N, A321-251N, A321-252N and A321-253N

The certification basis has been revised for the A321-271N, A321-272N, A321-251N, A321-252N and A321-253N.

The certification basis is that for A321-200 equipped with Sharklets amended by the following:

CS 25 Amdt 11 for

25.23 (a) (b)	25.952 (a) (b) (for pylon area)
25.25 (a) (b)	25.954
25.27	25.955 (a)
25.101	25.961 (a) (b)
25.109	25.963 (a)
25.113	25.969
25.115	25.971 (a) (b) (c)
25.117	25.981 for pylon area only
25.145 (a)	25.993 (a) (b) (c) (d) (e) for Engines and Pylon area only.
25.147	25.994 for fuel system component in the pylon and powerplant system area
25.149	25.995 for engine and pylon areas only
25.161	25.997 (a) (b) (c) (d)



SECTION 2: A321 SERIES

25.171 replaced by SC B-04 (Static Directional, Lateral and Longitudinal Stability and Low Energy awareness)	25.999 (a) (b)
25.173 replaced by SC B-04 (Static Directional, Lateral and Longitudinal Stability and Low Energy awareness)	25.1001
25.175 replaced by SC B-04 (Static Directional, Lateral and Longitudinal Stability and Low Energy awareness)	25.1011 (a) (b)
25.177 with subparagraphs (b) and (c) replaced by SC B-04 (Static Directional, Lateral and Longitudinal Stability and Low Energy awareness)	25.1013 (a) (b) (c) (d) (e) (f)
25.181	25.1015 (a) (b)
25.201 replaced by SC B-01 (Stalling and scheduled operating speeds), with reference to IM B-06 (Flight in icing conditions)	25.1017 (a) (b)
25.203 replaced by SC B-01 (Stalling and scheduled operating speeds),	25.1019 (a)
25.231	25.1021 (a) (b)
25.233	25.1023 (a) (b)
25.235	25.1025 (a) (c)
25.251	25.1041
25.301 (a) (b) (c)	25.1043 (a) (b) (c)
25.302 (for new or modified parts)	25.1045 (a) (b) (c)
25.303 (for new or modified parts)	25.1091 (a) (b) (c) (d) (e)
25.305 (a) (b) (c) (e) (f) (for new or modified parts)	25.1093 (b)
25.307 (a) (d) (for new or modified parts)	25.1103 (b) (c) (d)
25.321 (a) (b) (c) (d)	25.1121 (a) (b) (c) (d) (f) (g)
25.331 (a) (b) (c)	25.1123 (a) (b) (c)
25.333 (a) (b)	25.1141 (a) (b) (c) (d) (e) (f)
25.335 (a) (b) (c) (d) (e) (f) with sub-paragraph (b) replaced by Legacy SC A-5003 (Design Dive Speed Vd) and sub-paragraph (e) amended by Legacy SC A-2 (Stalling speeds for structural design)	25.1143 (a) (b) (c) (d) (e)
25.337 (a) (b) (c) (d)	25.1145 (a) (b) (c)
25.341 (a) (b) (c)	25.1155 (a) (b) (c) (d) (e)
25.343 (a) (b) (for new or modified parts)	25.1163 (a) (b) (c)
25.345 (a) (b) (c) (d)	25.1165 (a) (b) (c) (e) (f) (h)
25.349 (a) (b)	25.1167 (a) (b) (c)
25.351 (a) (b) (c) (d)	25.1181 (a) (b) amended by ESF E-44 (Fan Zone non-fire zone)
25.361 (a) (b)	25.1182 (a) (b)
25.362 (a) (b) (for new or modified parts)	25.1183 (a) (b) (c)



SECTION 2: A321 SERIES

25.363 (a) (b)	25.1185 (a) (b) (c)
25.365 (a) (b) (c) (d) (e)(1) (for new or modified parts)	25.1187 (a) (b) (c) (d) (e)
25.367 (a) (b)	25.1189 (a) (b) (d) (e) (f)
25.371	25.1191 (a) (b)
25.373 (a) (b)	25.1193 (a) (b) (c) (d) (e) amended by SC E-45 (Engine Cowl Retention)
25.391 (a) (b) (c) (d) (e)	25.1195 (a) (b) (c)
25.427 (a) (b) (c) (d)	25.1197 (a) (b)
25.445 (a) (b)	25.1199 (a) (b) (c) (d) (e)
25.457	25.1201 (a) (b)
25.459	25.1203 (a) (b) (c) (d) (e) (f) (g)
25.471 (a) (b)	25.1207 (a) (b) (c) (d)
25.473 (a) (b) (c) (d) (e)	25.1301 amended by Legacy SC S-30 (Automatic Flight/Flight Management Functions), for newly designed systems only
25.479 (a) (c) (d) amended by Legacy SC A-2 for § 25.479(a)	25.1305 (a) (c) (d) amended by SC F-13 (Fuel System Low Level Indication – Fuel Exhaustion)
25.481 (a) (c) amended by Legacy SC A-2 for § 25.481(a)	25.1309 (for newly designed systems) amended by: Legacy SE-2001 (SC S-76 – Effects of external radiations upon aircraft systems), Legacy SC SE-14 (SC S-76-1 – Protection from the effects of HIRF)
25.483 (a) (b)	25.1316 (a) (b) (c)
25.485 (a) (b)	25.1337 (a) (c) (d)
25.489	25.1353 (a) (b) (for engine and pylon areas)
25.491	25.1355 (c)
25.493 (b) (c) (d) (e)	25.1357 (a) (for newly designed systems)
25.495	25.1401 (b)
25.499 (a) (b) (c) (d) (e)	25.1403
25.503 (a) (b)	25.1419 (a) (b) (c) (d) (e) (f) (g) (h) for engine air intake protection
25.507 (a) (b) (c)	25.1431 amended by Legacy SE-2001(SC S76 - Effects of external radiations upon aircraft systems) Legacy SC SE14 (SC S76-1 – Protection from the effect of HIRF) For newly designed equipment only
25.509 (a) (c) (d)	25.1438 (for newly designed equipment)
25.511	25.1459 (a) (b) (c) (d) amended by Legacy SC S-72 (HC-S72 – Flight recorders)
25.519 (a) (b) (c)	25.1461 (a) (b) (c) (d) For newly designed equipment
25.571 (a) (b) (c) (d) (e) (for new or modified parts)	25.1501



SECTION 2: A321 SERIES

25.581 amended by Legacy SC S-75 – Lightning protection indirect effects for pylon and nacelle areas	25.1503
25.601 (for new or modified parts)	25.1507
25.603 (a) (b) (c) (for new or modified parts)	25.1511
25.605 (a) (b) (for new or modified parts)	25.1513
25.607 (a) (b) (for new or modified parts)	25.1515
25.609 (a) (b) (for new or modified parts)	25.1517
25.611 (a)	25.1519
25.613 (a) (b) (c) (d) (e) (f) (for new or modified parts)	25.1521 (a) (c) (d)
25.619 (a) (b) (c) (for new or modified parts)	25.1525
25.623 (a) (b) (for new or modified parts)	25.1527
25.625 (a) (b) (c) (d) (for new or modified parts)	25.1531
25.629 (a) (b) (c) (d) (e)	25.1533
25.631 (for new or modified parts)	25.1535 (a) (b) (c)
25.651 (for new or modified parts)	25.1549 (a) (b) (c) (d) amended by ESF E-51 (Oil temperature indication)
25.671 (a) (b) (c) (d) amended by SC F-9 - Dual Control System	25.1551
25.731 (a) (b) (c)	25.1553
25.733 (b) (c) (d)	25.1557 (b)
25.779	25.1581
25.831 (a) (e)	25.1583 (a) (b) (c) (d) (e) (f) (h) (i) (k)
25.841 (a)	25.1585
25.851 (b)	25.1587
25.855 (c)	25.1591
25.863 (a) (b) (c) (d)	25.1701 (a) (b) (c) for engines and pylon areas
25.865	25.1703 (a) (b) (d) (e) for engines and pylon areas
25.867 (a) (b)	25.1705 (a) (b) for engines and pylon areas
25.869 (a) (b) (c)	25.1707 (a) (b) (c) (d) (e) (f) (g) (h) (i) (j) (k) (l) for engines and pylon areas
25.899 amended by Legacy SC S-75 – Lightning protection indirect effects, for Pylon and Nacelle areas only	25.1709 (a) (b) for engines and pylon areas
25.901 (a) (b) (c) amended by SC E-45 (Engine Cowl Retention),	25.1711 (a) (b) (c) (d) (e) for engines and pylon areas
25.903 (a) (b) (c) (d) (e)	25.1713 (a) (b) (c) for engines and pylon areas
25.904	25.1715 (a) (b) for engines and pylon areas
25.933 (a)	25.1717 for engines and pylon areas
25.934 amended by ESF E-43 (Thrust Reverser Testing).	25.1719 for engines and pylon areas
25.939 (a) (c)	25.1723 for engines and pylon areas
25.943	25.1725 (a) (b) for engines and pylon areas
25.951 (a) (b) (c) amended by SC E-37 (Water/Ice in Fuel System), for pylon area only.	25.1727 for engines and pylon areas
	25.1731 (a) (b)



SECTION 2: A321 SERIES**CS25 Amdt 8 for:**

25.683 (b)	
------------	--

CS 25 Amdt 2 for:

25.21 with sub-paragraph (b) added by SC B-01 (Stalling and Scheduled Operating Speeds)	25.123
25.103 replaced by SC B-01 (Stalling and Scheduled Operating Speeds)	25.125
25.105	25.143 Sub-Paragraphs (j), (k), (l) added by SC B-03 (Motion and Effect of Cockpit control), Sub-paragraph (h) added by SC B-07 (Flight envelope protection), Sub paragraph (i) added by SC B-08 (Normal Load factor limiting System).
25.107	25.207 replaced by SC B-01 (Stalling and scheduled operating speeds).
25.111	25.237
25.119	25.253
25.121	25.1419

CS25 Amdt 1:

25.981 (a) (3) amended by generic SC E-48 – Fuel Tank Safety for all areas except engine and pylon areas	
--	--

JAR 25 Chg 14 for:

25.145 (b) (c)	25.1423 (a) (b) (c) (d) (e) (f) (g)
25.365 (e)(2), (e)(3)	25.1583 (j)

JAR 25 Chg 13 for

25.365 (f) (g)	25.735 (a) (f) (g) (h) amended by Legacy SC F-11 – Accelerate-stop distances and related performances, worn brakes Legacy SC S-79 - Brake requirements, qualification and testing – A321
25.853(a)(1)	

JAR 25 Chg 12 for

25.853(c)

JAR 25 Chg 11 for:

25.561 (a) (b) (c)	25.1309 amended by Generic SC D-0332-001 (Towbarless Towing) For systems adaptations.
25.563	25X1315



SECTION 2: A321 SERIES

25.672 (a) (b) (c)	25.994 for all areas except engine and pylon areas
25.677 (b)	25.1301
25.703 (a) (b) (c)	25.1321 (d)
25.721 (a) (b) (c)	25.1322 (a) (b) (c) (d) amended by generic SC D-0332-001 (Towbarless Towing)
25.729 (b) (c) (d) (e) (f)	25.1323 (a) (b) (c)
25.735 (b) (c)	25.1325 (b) (d) (e)
25.771 (e)	25.1329 (f) amended by: Legacy SC S-30 (Automatic Flight/Flight Management Functions),
25.777 Sub-paragraph (b) amended by SC B-03 (Motion and Effect of Cockpit Control)	25.1337 (b)
25.783 (a) (b) (c) (e) (f) (g)	25.1351 (a) (b) (d) where (d) is replaced by Legacy SC-S52 (Operation without normal Electrical power)
25.791	25.1353 (a) (b) (for all areas except pylon and engine)
25.801	25.1359
25.807 (a) (b) (c) (d)	25.1363 (a) (b)
25.809 (a) (b) (c) (d) (e) (f)	25.1419 (a) (b) (c) (d)
25.843 (a)	25.1431 (for system adaptations)
25.853 (a)	25.1435 (a) (b) (c) (d)
25X899 amended by Legacy SC S-75 – Lightning protection indirect effects	25.1457 (a) (b) (c) (d) (e) (f) (g)
25.959	25.1529 amended by SC H-01
25.963 (d) (e)	25A901 (c)
25.967 (d)	25A939 (a)
25.975 (a)	25A1521
25.981 for all paragraph except (a) (3) in all areas except engine and pylon areas	25A1527

4.8 Certification basis has been revised for MOD 157272 issue 2 and Issue 3 “Max Pax”.

The certification basis is that of the A321-271N,-251N,-253N amended by the following:

CS 25 Amdt 18 for

§25.23	§25.489
§25.305(a)(b)	§25.571(a)(b)
§25.307(a)	§25.801(d)
§25.321	§25. 803(c)
§25.331	§25. 807(g) amended by SC E-3001 and demonstrated through ESF D-02
§25.341(a)(b)	§25.901(c)
§25.351	§25.1519



SECTION 2: A321 SERIES

§25.365(a)	§25.1529
§25.473	§25.1541(a)(b)
§25.479(a)(c)(d) amended by SC A-2 for § 25.479(a)	§25.1557(a)
§25.481(a)(c) amended by SC A-2 for § 25.481(a)	

CS 25 Amdt 11

§25.1357(a)

JAR 25 change 13

§25.812(e)	§25.853(a)1 amended by SC D-0306-000
§25.812(k)(l)	

JAR 25 change 12

§25.853(c)

JAR 25 change 11

§25.561	§25.1351(a)
§25.785	§25.1353(a)(b)
§25.787(a)(b)	§25.1359(a)(d)
§25.789(a)	§25.1413
§25.791	§25.1415(b)(c)(d)
§25.853(a)(b)	§25.1431(c)
§25.1301	§25.1447(c)(1)

4.9 Certification basis has been revised for MOD 159536 issue 1 “Max Pax”.

The certification basis is that of the A321-200 without modification 160021(reinforced wings) amended by the following:

CS 25 Amdt 18 for

§25.23	§25.489
§25.321	§25.801(d)
§25.331(a)(b)(c1)	§25. 803(c)
§25.341(a)	§25. 807(g) amended by SC E-3001 and demonstrated through ESF D-02
§25.351	§25.1519
§25.365(a)	§25.1529
§25.473	§25.1541(a)(b)
§25.479(a)(c)(d) amended by SC A-2 for § 25.479(a)	§25.1557(a)
§25.481(a)(c) amended by SC A-2 for § 25.481(a)	

JAR 25 Change 14

SECTION 2: A321 SERIES

§25.305(a)(b)	§25.571(b2)
§25.331(c2)	§25.1357(a)
§25.341(b)	

JAR 25 change 13

§25.812(e)	§25.853(a)1 amended by SC D-0306-000
§25.812(k)(l)	

JAR 25 change 12

§25.853(c)	
------------	--

JAR 25 change 11

§25.307(a)	§25.1351(a)
§25.561	§25.1353(a)(b)
§25.571(a)(b)	§25.1357(a)
§25.785	§25.1359(a)(d)
§25.787(a)(b)	§25.1413
§25.789(a)	§25.1415(b)(c)(d)
§25.791	§25.1431(c)
§25.853(a)(b)	§25.1447(c)(1)
§25.1301	

4.10 Certification basis has been revised for MOD 160766 issue 1 A321-251NX, -252NX, -253NX, -271NX, -272NX.

The certification basis is that of the A321-271N,-272N,-251N, -252N,-253N amended by the following.

CS25 Amdt 15

§25.1	§25.623
§25.23	§25.625
§25.25	§25.629
§25.101(c)(d)(e)(f)(h)	§25.631
§25.109	§25.703(b)(c)
§25.113	§25.723
§25.115	§25.729(a)(b)(d)(e)
§25.117	§25.731(a)(b)(c)
§25.147(c)(d)	§25.733(b)(c)(d)
§25.201 as amended by SC B-01	§25.735(a)
§25.203 as amended by SC B-01	§25.735[f(2)]
§25.251(d)(e)	§25.783
§25.301(a)(c)	§25.783[e(4)]
§25.301(b)	§25.787(c)
§25.302	§25.795(c[1])
§25.303	§25.795(c[3](i))
§25.305(a)(b)	§25.801(a)(d)
§25.305(c)(e)(f)	§25.803(a)(c)



SECTION 2: A321 SERIES

§25.307(a)	§25.807(a[3])(a[9])(b)(c)(e)(f)(g)(i) as amended by ESF D-09, ESF D-13, ESF D-14
§25.321	§25.809(a)
§25.331	§25.809(a)
§25.333	§25.809(b)(c)(e)(f)(g)(i)
§25.335(a)(c)(d)(e)(f) as amended by SC A-2	§25.810(a[1])(c)(d)
§25.337(a)(b)(c)	§25.811
§25.341	§25.812(a)(b[1])(c)(d)(e)(f)(g)(h)(i)(j)(k)(l)
§25.343	§25.812(e[1])(e[2])(k)(l)
§25.345(a)(b)(d)	§25.813(a)(b)(c) as amended by ESF D-11, ESF D-14
§25.349 (a1,5)(b)	§25.843(a)(b[4])
§25.351	§25.853(a)(d[1])
§25.361	§25.855(a)(c)
§25.362	§25.856 as amended by ESF E-18
§25.363	§25.857
§25.365(a)(b)(d)	§25.858
§25.365(e1)	§25.863(a)(b)(d)
§25.365(e[2])(e[3])(f)	§25.869(a[1])
§25.367	§25.899 as amended by SC S-75
§25.371	§25.901(c)
§25.373	§25.903(c)(d[1])
§25.391(a)(b)(d)(e)	§25.963(a)
§25.427(a)(b)(d)	§25.1001(a)(b)(c)(d)
§25.445(a)	§25.1301(a)
§25.457	§25.1301(b)
§25.459	§25.1305(c)(6)(7) as amended by ESF E-49
§25.471(a)(b)	§25.1309 as amended by SC S-76-1
§25.473	§25.1316
§25.479(a)(c)(d) as amended by SC A-2	§25.1353(a)(b)(e)
§25.481(a)(c) as amended by SC A-2	§25.1360
§25.483	§25.1411
§25.485	§25.1431(a)(c)(d) as amended by SC S-76-1
§25.489	§25.1511
§25.491	§25.1519
§25.493(b)(c)(d)(e)	§25.1533
§25.495	§25.1535(a)(b)(c)
§25.499	§25.1541
§25.503	§25.1545
§25.507(a)(b)	§25.1557(a)(c)
§25.509(a)(c)(d)	§25.1561
§25.509(b)	§25.1581
§25.511	§25.1583
§25.519	§25.1587
§25.561	§25.1591
§25.562(a)(b)(c[1])(c[2])(c[3])(c[4])(c[7])(c[8])	§25.1703(a)(b)(d)



SECTION 2: A321 SERIES

§25.571(a)(b)	§25.1705(a)
§25.571(c)	§25.1707(a)(d)(l)
§25.571(e)	§25.1709
§25.581	§25.1711(a)(c)(d)(e)
§25.601	§25.1713(a)(c)
§25.603	§25.1715
§25.605	§25.1717
§25.607	§25.1719
§25.609	§25.1721(a)(b)
§25.611(a)	§25.1725(b)
§25.611(b)	§25.J951(a)
§25.613	§25.J952(a)
§25.619	§25.J955(a1)
§25.621	§25.J993
	§25.J994

CS25 Amdt 11

§25.335(b) as amended by SC A-5003	§25.1301(a)[1][3])
§25.809(a)	§25.1309 as amended by SC S-76-1

CS25 Amdt 2

§25.21(a)(d)	§25.111
§25.103	§25.121
§25.105	§25.123
§25.107	§25.143(a)(b[3])(g) as amended by SC B-01, SC B-08

JAR25 Change 14

§25.1423

JAR25 Change 13

§25.853(a[1]) as amended by SC D-0306-000

JAR25 Change 12

§25.853(c)

JAR25 Change 11

§25.561	§25.1309(a)(b)(c)(d) (g) as amended by SC S-76-1
§25.729(f)	§25.1322
§25.785 as amended by ESF D-12, D-14.	§25.1351(a[1])
§25.787(a)(b)	§25.1353(a)(b)
§25.789(a)	§25.1357(a)(c)(g)
§25.791	§25.1359(a)(d)
§25.793	§25.1413
§25.815	§25.1415(a)(b)(c)(d)
§25.817	§25.1431(c)



SECTION 2: A321 SERIES

§25.843(a)(b[4])	§25.1435(a[1])(a[5]) (a[6])
§25.851(a[1])	§25.1438
§25.853(a)(b) as amended by EtC E-28 and ESF E-18	§25.1441
§25.853(c)(d)(e)	§25.1447(a)(c[1]) (c[3])(c[4])
§25.X899 as amended by SC S-75	§25.1450
§25.1103(c)(d)	§25.1529 as amended by SC H-01
§25.1301	

4.11 Certification basis has been revised for MOD 157272 issue 4 “Max Pax”

The certification basis is that of the A321-252N,-272N amended by the following:

CS 25 Amdt 23 for

§25.23	§25.489
§25.321	§25.801(d)
§25.331	§25. 803(c)
§25.341(a)(b)	§25. 807(g) amended by SC E-3001 and demonstrated through ESF D-02
§25.351	§25.901(c)
§25.473	§25.1519
§25.479(a)(c)(d) amended by SC A-2 for § 25.479(a)	§25.1529
§25.481(a)(c) amended by SC A-2 for § 25.481(a)	§25.1541(a)(b)
	§25.1557(a)

CS 25 Amdt 18 for

§25.305(a)(b)	§25.365(a)
§25.307(a)	§25.571(a)(b)

CS 25 Amdt 11

§25.1357(a) §25.1431(c)

JAR 25 change 13

§25.812(e)	§25.853(a)1 amended by SC D-0306-000
§25.812(k)(l)	

JAR 25 change 12

§25.853(c)

JAR 25 change 11

§25.561	§25.1351(a)
§25.785	§25.1353(a)(b)
§25.787(a)(b)	§25.1359(a)(d)
§25.789(a)	§25.1413



SECTION 2: A321 SERIES

§25.791	§25.1415(b)(c)(d)
§25.853(a)(b)	§25.1447(c)(1)
§25.1301	

4.12 Post TC changes

4.12.1 As per Letter AI/EA 412.0033/92 dated March 13, 1992, the following JAR 25 paragraphs are at Change 13 and amended by the NPA 25C205 Unified Discrete Gust Requirements introduced by Orange Paper 91/1:

JAR 25.305	JAR 25.349(b)
JAR 25.321	JAR 25.351
JAR 25.331	JAR 25.365
JAR 25.333	JAR 25.371
JAR 25.335(d)	JAR 25.373
JAR 25.341	JAR 25.391
JAR 25.343(b)(1)(ii)	JAR 25.427
JAR 25.345(a) and (c)	JAR 25.571(b)(2)

4.12.2 JAR 25 paragraphs 25.101(i), 25.105(c), 25.109(a) (e) and (f), 25.113(b) (c), 25.115(a), 25.735 (f)(g)(h)(i)(j), 25X.1591(a)(b)(c)(d) at Change 13 and amended by the NPA 25 BDG 244 Accelerate Stop Distances and Associated Performance.

4.12.3 When reinforced cockpit door is installed (see EtC E-12), 14 CFR Part 25.772(a) and (c) and 25.795 are at amendment 106.

4.12.4 When halon free hand-held fire extinguishers are installed, CS25.851(a),(c) is at Amdt 17 (see EtC D-GEN-AIRBUS-01).

4.12.5 For cabin and/or passengers improved seats (see EtC E-31), CS 25.562 is at amendment initial issue.

4.12.6 When modification 163213 (up to 3 additional central tanks) is installed on A321-251NX, -252NX, -253NX, 271NX & 272NX, the following paragraphs are at CS25 Amendment 15:

25.305 (a)(b)	25.979(b)(c)(d)(e)
25.307 (a)	25.981(a)(b)(d)
25.561(b)(c)(d)	25.993
25.571 (a)(b)	25.994 & 25J994
25.581	25.995(b)
25.601	25.999(a)(b)
25.603	25.1141(a)(b)(c)(d)(f)
25.605	25.1189(h)
25.609	25.1301(a)
25.611 (b)	25.1301(b)



SECTION 2: A321 SERIES

25.613	25.1302(a)(b)(c)
25.619	25.1305(a)(2)
25.625	25.1309 (a)
25.721(b)	25.1309(b)
25.777(a)	25.1309 (c)(d)
25.787(c)	25.1310
25.851(b)(2)	25.1315
25.855(e)(f)(g)(h)	25.1316
25.856(b)	25.1337(b)
25.863(a)(b)(c)(d)	25.1353(a)
25.869(a)(1)	25.1360
25.869(a)(3)	25.1381
25.899	25.1431(a)(c)(d)
25.903(d)(1)	25.1541
25.943	25.1543(b)
25.951(c)	25.1553
25.952(a)	25.1555(a)
25.954	25.1555(c)
25.957	25.1557(a)
25.959	25.1703 (a)(b)(d)
25.963(a)(b)(c)(e)(f)	25.1705(a)(b)
25.963(d)	25.1707 (a) (b)(c)(e)(l)
25.965(a)(b)(c)(d)	25.1709
25.967(a)(b)(e)	25.1711
25.969	25.1717
25.971	25.1719
25.975(a)	25.1721(b)
25.977(a)(c)(d)	25.1723
	25.1725(b)

4.12.7 Airbus complies with CS-ACNS:

- Subpart B, Section 2 – for optional modifications (Post TC) installing FANS aiming at answering to SES mandate as defined in (EU) N° 29/2009 and amended by (EU) N° 310/2015 of 26 February 2015.
Note: For compliance to CS-ACNS Subpart B, Section 2, a deviation to CS-ACNS.B.DLS.B1.075 is accepted by DEV ACNS-B-GEN-01 to not include DM89 MONITORING [unit name] [frequency] in the downlink message set installed.
- Subpart D – for optional modifications installing transponders aiming at answering to SES mandate as defined in (EU) No 1207/2011 and amended by (EU) No 1028/2014 of 26 September 2014.

4.12.8 When Mod 160139 “Passenger information signs and placards” is installed CS25-791 is at Amdt 20

SECTION 2: A321 SERIES

4.12.9 When mod 167557 "Define Modified Airspace Lavatory A Option for 25.795 Compliance" is installed, CS 25.795(a)(1), 25.795(a)(2) and §25.795(c)(3)(ii) are at Amdt 22 (ESF D-31).

4.12.10 When Modification 166104 (Define Hero and welcome effect light for airspace cabin) is installed on A321-251NX/-252NX/253NX/271NX/272NX, CS 25.603(a) is at Amdt 19.

4.12.11 For A321 series aircraft:

For all changes installing lavatory or galley adjacent to flight crew compartment on aircraft delivered after June 2026, where application for change is received after 02 June 2023 (date of Issue 51), CS 25.795(a)(1), 25.795(a)(2) are at Amendment 22.

4.12.12 For A/C configuration with ELT-DT equipment MOD 166219: CS ACNS is at Issue 3 Subpart E Section 3.

4.12.13 From 14 December 2023, CS-FCD is at issue 2 for CS FCD.300, CS FCD.310, CS FCD.400, CS FCD.410, CS FCD.415.

4.12.14 When MOD 163323 (E-Rudder) is installed on A321-251NX/-252Nx and -253NX, CS 25.353, CS 25.1583, CS 25.1581 are at Amdt 22.

5. Special Conditions

Reminder: Within the scope of the establishment of the A320 Joint Certification Basis, three types of special conditions were developed:

- Special conditions: rose to cover novel or unusual features not addressed by the JAR.
- Experience related conditions: rose to record an agreed text for the A320 Joint Certification Basis when evolution of JAR was in progress under the NPA procedure.
- Harmonization conditions: to record, for the purpose of the A320 Joint Certification Basis, a common understanding with respect to National variant. This should not be confused with the FAA/JAA harmonised regulations.

Compulsory

5.1 The following A320 Special Conditions, Experience Related Conditions and Harmonization Conditions are deleted:

- a. Further to application of the updated requirements of above paragraphs 4.1 and 9.1:

HC F-103	ASD-TOD-TOR on wet runways
----------	----------------------------



SECTION 2: A321 SERIES

HC F-114	Approach and Target Threshold Speeds
EC A-3.6.1	High Lift Devices
SC A-4.3	Tuned Gust Loads (UK)
HC A-4.4	Manoeuvre Loads - High Lift Devices Deployed
HC S-61	Design Landing Brake Kinetic Energy
HC S-62	Rejected Take-Off Brake Kinetic Energy

- b. Further to JAR 25 requirements evolution:

EC G-11	Turbine Engine - Maximum Take-Off Power and/or Thrust Duration – General Definition
---------	---

- c. Further to issuance of A321 Special Conditions and Interpretative Materials listed in paragraph 5.2 below:

SC A-2.1.1	Certification criteria for aircraft designed with systems interacting with structural performance
------------	---

5.2 New or updated A321 Special ConditionsFlight

SC F-1	Stalling and Scheduled Operating Speeds
SC F-10	Accelerate - Stop Distance
SC F-4	Static Longitudinal Stability

Structure

SC A-1	Interaction of Systems and Structure
SC A-2	Stalling Speeds for Structural Design

Propulsion

SC P-1	FADEC
--------	-------

Environment

SC E-1	Resistance to Fire Terminology
SC E-3	Exit Configuration

Systems

SC S-79	Brakes requirements qualification and testing
---------	---

5.3 The following A320 Special Conditions and Interpretative Material are validated for A321:

SC G-17 (F)	Operational proving flights
-------------	-----------------------------



SECTION 2: A321 SERIES

SC G-17 (G)	Operational flight for certification
SC F-3	Side Stick - Maximum Forces for Temporary and Prolonged Application
SC F-4	Static Longitudinal Stability
SC F-6	Static Directional and Lateral Stability
SC F-7	Flight Envelope Protection
SC F-8	Normal Load Factor Limiting
SC F-9	Dual Control System
SC A-2.2.2	Design Manoeuvre requirement
SC A-2.2.3	Design Dive Speed
IM A-39	Discrete Source Damage
HC A-4.5	Brake Roll Conditions
HC A-4.6	Speed control device
AMC S-5	Electrical bonding and lightning protection (direct effects)
SC S-11	Limit pilot forces and torques
IM S-21	Landing Gear
HC S-23	Standby Gyroscopic Horizon
HC S-24	VMO/MMO Warning (Setting)
IM/AMC S-27	Altitude Display System
EC S-30	Autoflight System
SC S-33	Autothrust System
SC S-52	Operation without normal electrical power
SC S-54	Circuit protective devices
HC S-72	Flight recorder
SC S-74	Abnormal attitudes
SC S-75	Lightning protection (indirect effects)
SC S-76	Effect of external radiations upon aircraft systems
SC S-77	Integrity of signal control

5.4 For any new application (new or modified aeroplane system and associated components) after July 10, 1998, SC -S-76 (Effect of external radiations upon aircraft systems) are superseded by SC -S-76-1.

5.5 For any further variant certification after Aug. 10, 1998, the HC-A.4.5 (Braked roll conditions) is superseded by JAR 25.493(d) at Change 14 (EtC A-7).

5.6 The following special conditions have been developed post Type Certification:

SC H-01	Enhanced Airworthiness Programme for Aeroplane Systems - ICA on EWIS (applicable from May 2010)
SC D-0306	Heat release and smoke density requirements to seat material (applicable from June 2010)
SC P-27	Flammability Reduction System (see Note below) If fitted, the centre fuel tank of aircraft which have made their first flight after 1st of January 2012 must be equipped in production with a fuel tank Flammability Reduction System



SECTION 2: A321 SERIES

	(modification 38062). This system shall remain installed and operative and can only be dispatched inoperative in accordance with the provisions of the MMEL revision associated with modification 38062. If modification 38062 (Fuel Tank Inerting System (FTIS)) is embodied on A318, A319, A320, or A321 airplanes, the airplane is compliant with paragraph FR Section 25.981(a) & (b) at amendment 25-102, Part 25 appendix M & N at amendment 25-125, and Section 26.33 at amendment 26-3.
SC E-48	Fuel Tank Safety (applicable from October 2013)
SC F-0311-001	Flight Recorders including Data Link Recording (applicable as per operational regulations)
F-GEN-01	Installation of non-rechargeable lithium battery (applicable from March 2019)

5.7 Special Conditions for aircraft equipped with MOD 160023

SC F-16	Static directional and lateral stability
A318 SC F-5001	Stalling and scheduled operating speeds
A318 SC F-5004	Static Longitudinal Stability and Low energy awareness
A318 SC A-5003*	Design Dive Speed V_D

Note: All other original Special Conditions applicable to each model remain effective.

*From 07th December 2018 SC B-14 is replacing SC A-5003

5.8 Special Conditions for A321-271N, A321-272N, A321-251N, A321-252N and A321-253N

B-01	Stalling and Scheduled Operating Speeds
B-03	Motion and effect of cockpit control
B-04	Static Directional, Lateral and Longitudinal Stability and Low energy awareness
B-07	Flight Envelope Protection
B-08	Normal Load Factor limiting System
E-37	Water/Ice in Fuel System
E-45	Engine Cowl Retention
F-13	Fuel System Low Level Indication - Fuel Exhaustion
E-55*	Fan Blade Loss

*Only applicable to CFM models

5.8.1. The following special conditions developed for previous models are also applicable to the A321-271N, A321-272N, A321-251N, A321-252N and A321-253N affected areas:

A-2.2.2	Design Manoeuvre requirement
SC A-1	Interaction of systems and structure
SC A-2	Stalling Speeds for structural design (A321)



SECTION 2: A321 SERIES

A-5003*	Design dive speed Vd
D-0332-001	Towbarless Towing
E-48	Fuel Tank Safety
SC F-11	Accelerate-stop distances and relates performances, worn brakes
SC F-9	Dual Control System
H-01	Enhanced Airworthiness Programme for Aeroplane Systems - ICA on EWIS
P-27	Flammability Reduction System (consisting of Cooled Serviced Air System and Inert Gas Generation System)
S-11	Limit Pilot forces and torques
S-30	Automatic Flight/Flight Management Functions
S-33	Autothrust system
S-72 (HC S-72)	Flight recorders
SC S-76-1	Protection from the effect of HIRF
SC S-75	Lightning protection indirect effects
SC S-79	Brake requirements, qualification and testing (A321)

*From 07th December 2018 SC B-14 is replacing SC A-5003

5.8.2. The following special conditions developed for previous models are also applicable to the A321-271NX, A321-272NX, A321-251NX, A321-252NX and A321-253NX affected areas:

B-01	Stalling and Scheduled Operating Speeds
B-03	Motion and effect of cockpit control
B-04	Static Directional, Lateral and Longitudinal Stability and Low energy awareness
B-07	Flight Envelope Protection
B-08	Normal Load Factor limiting System
E-37	Water/Ice in Fuel System
E-45	Engine Cowl Retention
F-13	Fuel System Low Level Indication - Fuel Exhaustion
E-55*	Fan Blade Loss
SC A-2	Stalling Speeds for structural design (A321)
A-5003**	Design dive speed Vd
D-0332-001	Towbarless Towing
E-48	Fuel Tank Safety
SC F-11	Accelerate-stop distances and relates performances, worn brakes
SC F-9	Dual Control System
H-01	Enhanced Airworthiness Programme for Aeroplane Systems - ICA on EWIS
P-27	Flammability Reduction System (consisting of Cooled Serviced Air System and Inert Gas Generation System)
S-11	Limit Pilot forces and torques
S-30	Automatic Flight/Flight Management Functions
S-33	Autothrust system
S-72 (HC S-72)	Flight recorders



SECTION 2: A321 SERIES

SC S-76-1	Protection from the effect of HIRF
SC S-75	Lightning protection indirect effects

*Only applicable to CFM models

**From 07th December 2018 SC B-14 is replacing SC A-5003

5.9 Additional Special Conditions part of the Certification Basis (added post TC):

The following Special Conditions are additionally applicable when an A/C configuration include the subject design change(s):

B-12	Soft Go Around
D-08	Installation of Personal Electronic Device charging stowage for cabin crew use
D-15	Pilot Control Mode TaxiBot Operations
D-19	Incorporation of Inertia Locking Device in Dynamic Seats
D-24	Installation of Airbags in the backrest of seats
D-25	Installation of structure mounted airbag
D-27	Installation of Three Point Restraint & Pretensioner System
D-28	Installation of oblique seats
D-0322-001	Installation of suite type seating
D-0332-001	Towbarless Towing
E-10	High altitude airport operations (up to 14,100 ft)"
E-13	Installation of inflatable restraints
E-21	Flight Instrument External Probes – Qualification in Icing Conditions New UTAS Pitot Probes
E-34	Seat with inflatable restraints
F-119	Security Protection of Aircraft Systems and Networks
D-33	Cabin attendant seat mounted on movable part of an interior monument
D-35	Airbelt without HIC requirement
F-MULTI-04	Rechargeable Lithium Battery Installations
F-37	ATN over SATCOM

6. Exemptions/Deviations

Optional

ACNS-B-GEN-01 Deviation to CS-ACNS Initial Issue Subpart B, Section 2 (See Note in §II-4.12.7)

7. Equivalent Safety Findings

Compulsory



SECTION 2: A321 SERIES

8.1 The following paragraphs JAR 25 have been complied with through equivalent safety demonstration:

- JAR 25.783 (f) passenger doors and bulk door (see ESF SM-3001, SM-3002 and SM-3004)
JAR 25.933 (a) Thrust reverser auto restow function (see ESF P-3008).

8.2 The following Equivalent Safety Findings have been developed post Type Certification:

- FAR 25.856(b) Fuselage burnthrough protection in bilge area (see ESF E-32), see note below
If modifications 150700, and 37270 (with CLS option only), 37048 and 36985 are embodied in production on A318, A319, A320, or A321 airplanes, the airplane is compliant with Fuselage Flame Penetration "Burnthrough" requirements addressed by paragraph 14 CFR Part 25.856(b) Amdt 25-111(See EtC E-28).
(applicable as per operational regulations)
- 14CFR Part 25.856(a) Improved flammability standards for insulation materials (ESF E-18) (applicable as per operational regulations)

8.3 Equivalent Safety Findings for aircraft equipped with MOD 160023

- CS25.1419(c) F-19 Flight in natural icing condition

Note: The original ESFs applicable to each model remain effective.

8.4 Equivalent Safety Findings for aircraft equipped with MOD 157272 or 159536

- CS25.807(g) D-02 Over-performing Type I exit

8.5 The following Equivalent Safety Findings have been developed for the A321-271N, A321-272N, A321-251N, A321-252N and A321-253N:

CS25.934, CS-E 890	E-43	Thrust Reverser Testing
CS25.1181(a)	E-44*	Fan Zone as non fire zone
CS25.1549(a)	E-51	Oil temperature indication
CS25.1181, CS25.1182	E-52	Nacelle area adjacent to fire
CS25.997(d)	E-49**	Fuel Filter Location

* Applicable to IAE models only

**Applicable to CFM models only

8.5.1 The following ESF developed for previous models are also applicable to the A321-271N, A321-272N, A321-251N, A321-252N and A321-253N affected areas:



SECTION 2: A321 SERIES

JAR AWO 313	SE-4005	Revised strategy for demonstrating a safe go-around 'Minimum Approach Break-off Height (MABH) (issued for A319)
JAR AWO 236	SE-5005	Cat III operations - Excess Deviation Alerts
JAR 25.1441(c)	F-21	Crew Determination of Quantity of Oxygen in Passenger Oxygen System
14CFR Part 25.856(a)	E-18	Improved flammability standards for thermal / acoustic insulation materials

8.6 The following Equivalent Safety Findings have been developed for the A321-271NX, A321-272NX, A321-251NX, A321-252NX and A321-253NX:

CS 25.807(g)	D-09	Increase of seats' credit for oversized Type I (qualified to Type C) floor level exits
CS 25.813(c)(4)(i)] CS 25.813(c)(2)(i)]	D-11	Over wing Type III exit interior arrangement
JAR 25.785(h)	D-12	Single cabin attendant seat at door #3
CS 25.807(g)	D-13	Increase of seats' credit for Type III exit
CS 25.807(c)(g), 25.813(c) JAR 25.785(h)	D-14	De-rating of Door #3 to 45 or 35 passengers

8.6 Additional ESF part of the Certification Basis (added post TC):

The following ESF are additionally applicable when an A/C configuration include the subject design change(s):

CS 25.251(b)	B-17	Vibration/buffeting compliance criteria for large external antenna installation applicable from February 2021.
JAR 25.785(c)	D-0329-001	Forward facing seats with more than 18° to aircraft centreline.
CS 25.795(a)(1)	D-31	Application of reduced Intrusion Loads in certain areas of the flight deck boundaries
FAR 25.856(b)	E-32 EtC E-28	Fuselage burnthrough protection in bilge area, see note below If modifications 150700, and 37270 (with CLS option only), 37048 and 36985 are embodied in production on A318, A319, A320, or A321 airplanes, the airplane is compliant with Fuselage Flame Penetration "Burnthrough" requirements addressed by paragraph 14 CFR Part 25.856(b) Amdt 25-111. (applicable as per operational regulations)
CS 25.811(e)(4)	SE-63	Green Arrow and "Open" placard for Emergency Exit Marking
JAR 25.811(f)	E-16	Emergency exit marking reflectance
JAR 25.812(b)(1)(ii)	E-14	Photo-luminescent EXIT sign for MCD (Moveable Class Divider)
JAR 25.812(b)(1)(i)(ii)	SE-42	Symbolic EXIT signs as an alternative to red EXIT signs for passenger aircraft
CS 25.813(c)(2)	D-21	Over-Wing Exit Interior Arrangement
JAR 25.1441(c)	F-21	Crew Determination of Quantity of Oxygen in Passenger Oxygen System
JAR 25.1443(c)	F-20	Minimum Mass Flow of Supplemental Oxygen (optional)



SECTION 2: A321 SERIES

CS FCD.425(g)	FCD-MULTI-01	CS-FCD T3 Evaluation Process
JAR 25.1441(c)	F-122	Crew Determination of Quantity of Oxygen in Passenger Oxygen System

8. Environmental Protection

ICAO Annex 16:

Vol. I, Part II	Noise Requirements
Vol. II, Part II	Fuel Venting
Vol. II, Part III Chapter 2	Emissions

Notes: Further details are defined within TCDSN EASA.A.064



SECTION 2: A321 SERIES**III. Technical Characteristics and Operational Limitations****1. Type Design Definition**

- 1.1 Certificated model: A321-111
Definition of reference airplane by AIRBUS INDUSTRIE Document AI/EA-A 413.1063/94 (00E000A0008/C21)
- 1.2 Certificated model: A321-112
Definition of reference airplane by AIRBUS INDUSTRIE Document AI/EA-A 414.0118/94 (00E000A0002/C11)
- 1.3 Certificated model: A321-131
Definition of reference airplane by AIRBUS INDUSTRIE Document AI/EA-A 414.0900/93 (00E000A0003/C21)
- 1.4 Certificated model: A321-211
Definition of reference airplane by AIRBUS INDUSTRIE Document AI/EA-S 413.0400/97 (00E000A0211/C21)
- 1.5 Certificated model: A 321-212
Definition of reference airplane by AIRBUS INDUSTRIE Document AI/EA-S 413.1359/01 (00E000A0212/C21)
- 1.6 Certificated model: A321-213
Definition of reference airplane by AIRBUS INDUSTRIE Document AI/EA-S 413.1360/01 (00E000A0213/C21)
- 1.7 Certificated model: A321-231
Definition of reference airplane by AIRBUS INDUSTRIE Document AI/EA-S 413.0388/97 (00E000A0231/C21)
- 1.8 Certificated model: A321-232
Definition of reference airplane by AIRBUS INDUSTRIE Document AI/EA-S 413.1361/01 (00E000A0232/C21)
- 1.9 Certificated model: A321-271N
Definition of reference airplane by AIRBUS Document 00E000A5023/C20
- 1.10 Certificated model: A321-251N
Definition of reference airplane by AIRBUS Document 00E000A5026/C20
- 1.11 Certificated model: A321-253N
Definition of reference airplane by AIRBUS Document 00E000A5113/C20
- 1.12 Certificated model: A321-272N
Definition of reference airplane by AIRBUS Document 00E000A5114/C20
- 1.13 Certificated model: A321-252N
Definition of reference airplane by AIRBUS Document 00E000A5190/C00
- 1.14 Certificated model: A321-251NX
Definition of reference airplane by AIRBUS Document 00E000A5123/C00
- 1.15 Certificated model: A321-252NX
Definition of reference airplane by AIRBUS Document 00E000A5124/C00
- 1.16 Certificated model: A321-253NX
Definition of reference airplane by AIRBUS Document 00E000A5125/C00
- 1.17 Certificated model: A321-271NX
Definition of reference airplane by AIRBUS Document 00E000A5121/C00
- 1.18 Certificated model: A321-272NX



SECTION 2: A321 SERIES

Definition of reference airplane by AIRBUS Document 00E000A5122/C00

NOTES**a. Model conversions:**

- If modification 34368 is embodied on A321-111 model powered with CFM56-5B1/2P engines, it is converted into A321-211 model, powered with CFM56-5B3/2P engines.
- If modification 34818 is embodied on A321-211 model powered with CFM56-5B3/P engines, it is converted into A321-212 model, powered with CFM56-5B1/P engines.
- If modification 35252 is embodied on A321-212 model powered with CFM56-5B1/P engines, it is converted into A321-211 model, powered with CFM56-5B3/P engines.
- If modification 35718 is embodied on A321-131 model powered with V2530-A5 engines, it is converted into A321-231 model, powered with V2533-A5 engines
- If modification 37836 is embodied on A321-232 model powered with V2530-A5 engines, it is converted into A321-231 model, powered with V2533-A5 engines.
- If modification 155204 is embodied on A321-211 model powered with CFM56-5B3/P engines, it is converted into A321-213 model, powered with CFM56-5B2/P engines

2. Description

Twin turbo-fan, short to medium range, single aisle, transport category airplane.

3. Equipment**A321-111**

Equipment approved for installation is listed in the Certification Standard Equipment List ref. 00E000A0007/C1S at latest approved issue.

A321-112

Equipment approved for installation is listed in the Certification Standard Equipment List ref. 00E000A0006/C1S at latest approved issue.

A321-131

Equipment approved for installation is listed in the Certification Standard Equipment List ref. 00E000A0004/C0S at latest approved issue.

A321-211

Equipment approved for installation is listed in the Certification Standard Equipment List ref. 00E000A0211/C0S at latest approved issue.

A321-212

Equipment approved for installation is listed in the Certification Standard Equipment List ref. 00E000A0212/C0S at latest approved issue.

A321-213

Equipment approved for installation is listed in the Certification Standard Equipment List ref. 00E000A0213/C0S at latest approved issue.

A321-231

Equipment approved for installation is listed in the Certification Standard Equipment List ref. 00E000A0231/C0S at latest approved issue.

A321-232

Equipment approved for installation is listed in the Certification Standard Equipment List ref. 00E000A0232/C0S at latest approved issue.



SECTION 2: A321 SERIES

Certification Standard Equipment List is not applicable to the A321-271N, A321-272N, A321-251N, A321-252N, A321-253N, A321-271NX, A321-272NX, A321-251NX, A321-252NX, A321-253NX.

Note:

The type design definitions and certification standard equipment lists are complemented by doc. 00D000A0546/COS "A319-100/A321-200 FMGC Type Std Evolution".

Cabin furnishings, equipment and arrangement shall be in conformance to the following specifications:

Cabin seats	2521M1F10000 at latest approved issue plus technical note SA2521ME1619350 (technical note applicable to A321-251NX, -252NX, -253NX, -271NX, -272NX)
Galleys	2530M1F000900 at latest approved issue.

4. Dimensions

Principal dimensions of A321 Aircraft:

- Length:	44.51 m
- Width:	34.10 m
(If mod 160023 installed)	35.80m
- Height:	11.76 m
- Width at horizontal stabilizer:	12.45 m
- Outside fuselage diameter:	3.95 m
- Distance between engine axis:	11.51 m
- Distance between main landing gear:	7.59 m
- Distance between nose and main landing gear:	16.91 m

5. Engines

The list below lists the basic engines fitted on the aircraft models. The notes describe usual names and certified names as well as new engines variants.

A321-111

Two CFMI CFM 56-5B1 jet engines (MOD 23083), or
CFM 56-5B1/2 jet engines (MOD 24404)

A321-112

Two CFMI CFM 56-5B2 engines (MOD 23152)

A321-131

Two IAE V2530 - A5 jet engines (MOD 22989)

A321-211

Two CFMI CFM 56-5B3/P jet engines (MOD 26359 + 25800), or
CFM 56-5B3/2P jet engines (MOD 27640)

A321-212

SECTION 2: A321 SERIES

Two CFMI CFM 56-5B1 jet engines (MOD 23083), or
CFM 56-5B1/2 jet engines (MOD 24404)

A321-213

Two CFMI CFM 56-5B2 engines (MOD 23152)

A321-231

Two IAE V2533-A5 jet engines (MOD 25643)

A321-232

Two IAE V2530 - A5 jet engines (MOD 22989).

A321-271N/A321-271NX

Two IAE PW1133G-JM Geared Turbo Fan jet engines (MOD 161002)

A321-251N/A321-251NX

Two CFMI LEAP-1A32 jet engines (MOD 161005)

A321-253N/A321-253NX

Two CFMI LEAP-1A33 jet engines (MOD 161006)

A321-272N/A321-272NX

Two IAE PW1130G-JM Geared Turbo Fan jet engines (MOD 162038)

A321-252N/A321-252NX

Two CFMI LEAP-1A30 jet engines (MOD 162681)

Notes:

1. If modification 25800 is embodied on models with CFM-5B engines, the engine performance is improved. The engine denomination changes to /P.

The modification is currently applicable for:

A321-111: CFM 56-5B1 (SAC) which changes to CFM 56-5B1/P
A321-112: CFM 56-5B2 (SAC) which changes to CFM 56-5B2/P
A321-212: CFM 56-5B1 (SAC) which changes to CFM 56-5B1/P
A321-213: CFM56-5B2 (SAC) which changes to CFM 56-5B2/P

CFM 56-5B/"non-P" engine can be intermixed with CFM 56-5B/P engine on the same aircraft.
See notes 3 & 4 below as well.

2. If modification 26610 is embodied on models with CFM-5B/2 (DAC) engines, the engine performance and gaseous emission levels are improved. The engine denomination changes to /2P.

The modification is currently applicable for:



SECTION 2: A321 SERIES

A321-111: CFM 56-5B1/2 (DAC) which changes to CFM 56-5B1/2P (DAC II C)

A321-212: CFM 56-5B1/2 (DAC) which changes to CFM 56-5B1/2P (DAC II C)

CFM 56-5B/2 "non P" (DAC) engine can be intermixed with CFM 56-5B/2P (DAC II C) engine on the same aircraft (AFM supplement).

CFM 56-5B/P or /"non-P" (SAC) engine can be intermixed with CFM 56-5B/2P (DAC II C) engine on the same aircraft (AFM supplement).

3. From March 31st, 2008, there is no longer any CFM56-5B1 non /P in field or in production.
4. From March 31st, 2008, there is no longer any CFM56-5B1/2 non /P in field or in production.
5. A321-111 CFM 56-5B1 engine can be intermixed with CFM 56-5B1/2 engine (MOD 24404) on the same aircraft (AFM supplement).
6. CFM56-5B3/P (SAC) engine (MOD 26359 + 25800) can be intermixed with CFM56-5B3/2P (DAC II C PIP) engine (MOD 27640) on the same aircraft (AFM supplement).
7. Introduction of CFM56-5Bx/3 "Tech Insertion" engine is done through embodiment of modification 37147 in production or 38770 in field. This modification is only applicable on CFM56-5Bx/P SAC engines.
If modification 37147 is embodied on models with CFM-5B engines the engine denomination changes to /3.

The modification is currently applicable for:

A321-111: CFM 56-5B1 (SAC) which changes to CFM 56-5B1/3

A321-112: CFM 56-5B2 (SAC) which changes to CFM 56-5B2/3

A321-211: CFM 56-5B3 (SAC) which changes to CFM 56-5B3/3

A321-212: CFM 56-5B1 (SAC) which changes to CFM 56-5B1/3

A321-213: CFM 56-5B2 (SAC) which changes to CFM 56-5B2/3

The engine characteristics remain unchanged.

Modification 37147 has been demonstrated as having no impact on previously certified noise levels.

CFM56-5Bx/3 engine can be intermixed with CFM56-5Bx/P engine under considerations as prescribes in modification 38573.

8. Introduction of "BUMP" function is done through embodiment of modification 38946.
If modification 38946 is embodied on models with CFM-5B engines, the engine denomination changes to /P1 (SAC) or /2P1 (DAC) or /3B1 (Tech Insertion).

The modification is currently applicable for:

A321-211: CFM 56-5B3 (SAC) which changes to CFM 56-5B3/P1



SECTION 2: A321 SERIES

Modification 38946 has been demonstrated as having no impact on previously certified noise levels.

The engine characteristics remain unchanged.

Intermix at aircraft level between “non-Bump” engine and “Bump” engine is not allowed.

9. If modification 160684 (alternate climb) is installed on the A321-271N or A321-271NX equipped with IAE PW1133G-JM, then the engine model is changed to PW1133GA-JM.
10. If modification 160820 is installed on the A321-253N equipped with CFM LEAP-1A33 then the engine model is changed to LEAP-1A35A.

6. Auxiliary Power Unit

APU GARRETT

The APU GARRETT AIRESEARCH GTCP 36-300 (A) installation is defined by MOD 20020 (Specification 31-5306B)

Approved oils: see GARRETT REPORT GT.7800

APU Pratt & Whitney Rzeszow S.A.

The APU Pratt & Whitney Rzeszow S.A. installation is defined by MOD 22562 or MOD 35864 Pratt & Whitney Rzeszow S.A. APS 3200 (Specification ESR 0802, Rev. A).

Approved oils: in conformance to MIL-L-7808, MIL-L-23699 or DERD 2487

APU Honeywell International

The APU Honeywell International installation is defined by MOD 25888 or 37987

Honeywell International 131-9[A] (Specification 4900 M1E 03 19 01)

Approved oils: according to model Specification 31-12048A-3A

7. Propellers

N/A

8. Fluids (Fuel, Oil, Additives, Hydraulics)

Fuel

ENGINES	KEROSENE DESIGNATION
CFM56: Installation document CFM 2026 or CFM 2129)	JET A, JET A-1, JP5, JP8, N°3 Jet Fuel, JET B, JP 4, TS-1, RT(GOST), F44, F34, AVTUR, AVTUR/FSII, AVTAG/FSII, AVCAT/FSII
IAE V2500: IAE Standard Practices and processes Manual IAE 0043	JET A, JET A-1, JP5, JP8, N°3 Jet Fuel, JET B, JP 4, TS-1*, RT(GOST), F44, F34, AVTUR, AVTUR/FSII, AVTAG/FSII, AVCAT/FSII
IAE PW1100G-JM: (Service Bulletin PW1000G - 100-73 00-0002-00A930AD)	JET A, JET A-1, JP5, JP8, N°3 Jet fuel, TS-1(GOST), RT(GOST), AVTUR, AVTUR/FSII, AVCAT/FSII
CFMI LEAP-1A: Service Bulletin LEAP-1A S/B 73-0001	JET A, JET A-1, JP5, JP8, N°3 Jet fuel, TS-1(GOST), RT(GOST), AVTUR, AVTUR/FSII, AVCAT/FSII



SECTION 2: A321 SERIES

The above-mentioned fuels are also suitable for the APU.
Refer to Consumable Material List (CML) for details on approved fuel specifications

- * For IAE V2500 engines, TS-1 is cleared for transient use (less than 50% of operations)

OIL

Engine	CFMI CFM56-5B1 (**) CFM56-5B1/2 (**) CFM56-5B2 CFM56-5B3 (/P only) CFM56-5B3/2P	IAE V2530-A5 V2533-A5	PW1133G-JM PW1130G-JM	LEAP 1A30 LEAP-1A32 LEAP-1A33 LEAP-1A35A
Approved Oils	SB CFMI 79-001-OX	See doc IAE 0043 Sect 4.9 (MIL-L- 23699)	Service Bulletin PW1000G – 1000 – 79 – 00 – 0002 - 00A - 930A – D	SB LEAP-1A S/B 79-0001

(**): see notes 3 and 4 in chapter 5 for engine models no longer in prod/service.

Additives:

Refer to Airbus Consumable Material List (CML).

Hydraulics

Hydraulic fluids: Type IV or Type V Specification NSA 30.7110



SECTION 2: A321 SERIES

9. Fluid Capacities

Fuel quantity (0.8 kg/litre) (see note 1 below)

For A321-111/-112/-131/-211/-212/-213/-231/-232 the following table applies:

TANK	3 TANK AIRPLANE		4 or 5 TANK AIRPLANE (*) (**)	
	Usable fuel litres (kg)	Unusable fuel litres (kg)	Usable fuel litres (kg)	Unusable fuel litres (kg)
WING	15 500 (12 400)	22.6 (18)	15 500 (12 400)	22.6 (18)
CENTRE	8 200 (6 560)	23.2 (18.6)	8 200 (6 560)	23.2 (18.6)
ACT (*) (**)			2 900 or 2 992 / 5 984 ** (2 320) or (2 393 / 4 786) **	17 / 34 (13.6 / 27.2)
TOTAL	23 700 (18 960)	45.8 (36.6)	26 600 or 26 692 / 29 684 ** (21 280) or (21 353 / 23 746) **	62.8 / 79.8 (50.2 / 63.8)

For A321-271N, A321-272N, A321-251N, A320-252N and A321-253N the following table applies:

TANK	3 TANK AIRPLANE		4 or 5 TANK AIRPLANE (*) (**)	
	Usable fuel litres (kg)	Unusable fuel litres (kg)	Usable fuel litres (kg)	Unusable fuel litres (kg)
WING	15 380 (12 073)	22.6 (18)	15 380 (12 073)	22.6 (18)
CENTRE	8 200 (6 437)	23.2 (18.6)	8 200 (6 437)	23.2 (18.6)
ACT (*) (**)			2 900 or 2 992 / 5 984 ** (2 320) or (2 393 / 4 786) **	17 / 34 (13.6 / 27.2)
TOTAL	23 580 (18 510)	45.8 (36.6)	26 480 or 26 572 / 29 564** (20 830) or (20 903 / 23 296)	62.8 / 79.8 (50.2 / 63.8)

* See notes 2 and 3 below

** 1 ACT high pressure system, 2900 litres on A321-200, on additional centre tanks 1 / 2 ACT low pressure system 2992/5984 litres on A321-200

Note:

1. On series A321-200 equipped with CFM56 engines, introduction of standard of wingbox without dry bay (modification 38616) will increase the fuel capacity by 350 litres.
2. On the series A321-200, one Additional Centre Tank (ACT) in bulk version is defined by modification 25453 (high pressure system). Its approval together with structural and system provisions is subject of Major Change E2-001.
3. On the series A321-200, one or two Additional Centre Tanks (ACT) in bulk version are defined by modification 30422 (low pressure system). Their approval together with structural and system provisions is subject of Major Change E2-002.



SECTION 2: A321 SERIES

For A321-271NX, A321-272NX, A321-251NX, A320-252NX and A321-253NX the following table applies:

TANK	3 TANK AIRPLANE		4 TANK AIRPLANE		5 TANK AIRPLANE	
	Usable fuel litres (kg)	Unusable fuel litres (kg)	Usable fuel litres (kg)	Unusable fuel litres (kg)	Usable fuel litres (kg)	Unusable fuel litres (kg)
WING	15 380 (12 073)	22.6 (18)	15 380 (12 073)	22.6 (18)	15 380 (12 073)	22.6 (18)
CENTRE	8 200 (6 437)	23.2 (18.6)	8 200 (6 437)	23.2 (18.6)	8 200 (6 437)	23.2 (18.6)
AFT ACT 1	-	-	3 121 (2450)	17 (13.6)	3121 (2450)	17 (13.6)
AFT ACT 2	-	-	-	-	3 121 (2450)	17 (13.6)
FWD ACT	-	-	-	-	-	-
TOTAL	23 580 (18 510)	45.8 (36.6)	26 701 (20960)	62.8 (53.6)	29 822 (23410)	79.8 (63.8)

TANK	6 TANK AIRPLANE	
	Usable fuel litres (kg)	Unusable fuel litres (kg)
WING	15 380 (12 073)	22.6 (18)
CENTRE	8 200 (6 437)	23.2 (18.6)
AFT ACT 1	3 121 (2450)	17 (13.6)
AFT ACT 2	3 121 (2450)	17 (13.6)
FWD ACT	3 121 (2450)	17 (13.6)
TOTAL	32 943 (25860)	96.8 (77.4)

10. Airspeed Limits (Indicated Airspeed – IAS – unless otherwise stated)

Maximum Operating Mach (MMO):	0.82
Maximum Operating Speed (VMO):	350 kt
Manoeuvring Speed VA:	see Limitations Section of the EASA approved Flight Manual
Extended Flaps/Slats Speed (VFE):	see table below



SECTION 2: A321 SERIES

For A321-111/-112/-131/-211/-212/-213/-231/-232 the following table applies:

Configuration	Slats/Flaps (°)	VFE (kt)	
1	18/0 18/10	230 ** 215 **	Intermediate approach Take-off
2	22/14	205 215*	Take-off and approach
3	22/21	195	Take-off, approach, landing
Full	27/25	190	Landing

* See note 1

** See note 2

For A321-271N / -272N / -251N /-252N/ -253N/ -271NX/ -272NX/ -251NX/ -252NX/ -253NX the following table applies:

Configuration	Slats/Flaps (°)	VFE (kt)	
1	18/0 18/10	238* 225	Intermediate approach Take-off
2	22/14	215	Take-off and approach
3	22/21	195	Take-off, approach, landing
Full	27/34	186	Landing

*For A321-251NX,-252NX,-253NX,-271NX,-272NX models 243 kt

Landing gear:

VLE - Extended: 280 kt/Mach 0.67

VLO - Extension: 250 kt

Retraction: 220 kt

Tyres limit speed (ground speed): 195.5 kt (225 mph)

Notes:

1. If FWC Standard D2 and FAC Standard BAM 0510 are fitted on A321 aircraft, VFE speed in Configuration 2 is increased from 205 kts to 215 kts (as identified by speed limitation placard installed by modification 24641).
2. On the series A321-200, Weight Variant 001, 002 & 011, VFE speed in Configuration 1 is increased from 230 to 235 kts, and in Configuration 1+F increased from 215 to 225 kts (as identified by speed limitation placard installed by modification 28960 or 28721).

11. Flight Envelope

Maximum Operating Altitude:



SECTION 2: A321 SERIES

39 100 ft (pressure altitude)
39 800 ft (pressure altitude) if modification 30748 is embodied

See the appropriate EASA approved Airplane Flight Manual.

12. Operating Limitations

See the appropriate EASA approved Airplane Flight Manual

Powerplant (2.2482 lb/daN)**A321-111 or -212 / A321-112 or -213 / A321-131 or -232**

Engine	CFMI CFM56-5B1 (**) CFM56-5B1/2 (**)	CFMI CFM56-5B2	IAE V2530-A5
Data sheets	E37NE (FAA) E38NE (FAA) EASA.E.003	E37NE (FAA) E38NE (FAA) EASA.E.003	E40NE (FAA) EASA.E.069
Static thrust at Sea level			
Take-off (5 minutes)* (Flat rated 30° C)	13 344 daN (30 000 lbs)	13 789 daN (31 000 lbs)	13 300 daN (29 900 lbs)
Maximum continuous (Flat rated 25° C)	12 940 daN (29 090 lbs)	12 940 daN (29 090 lbs)	11 988 daN (26 950 lbs)

* 10 minutes at take-off thrust allowed only in case of engine failure (at take-off or during go-around) in accordance with DGAC "Fiche de Caractéristiques moteur"

Other engine limitations: see the relevant Engine Type Certificate Data Sheet

** see notes 3 and 4 in chapter 5 for engine models no longer in prod/service.



SECTION 2: A321 SERIES**A321-211/-231**

Engine	CFMI CFM56-5B3 (/P only) CFM56-5B3/2P	IAE V2533-A5
Data sheets	E37NE (FAA) E38NE (FAA) EASA.E.003	E40NE (FAA) EASA.E.069
Static thrust at Sea level		
Take-off (5 minutes)* (Flat rated 30° C)	14 234 daN (32 000 lbs)	14 055 daN (31 600 lbs)
Maxi continuous (Flat rated 25° C)	12 940 daN (29 090 lbs)	11 988 daN (26 950 lbs))

* 10 minutes at take-off thrust allowed only in case of engine failure (at take-off or during go-around) in accordance with DGAC "Fiche de Caractéristiques Moteur"

Other engine limitations: see the relevant Engine Type Certificate Data Sheet

A321-271N/-272N/-271NX/-272NX

Engine	PW1133G-JM PW1133GA-JM	PW1130G-JM
Data sheets	E87NE (FAA) EASA.IM.E.093	E87NE (FAA) EASA.IM.E.093
Static thrust at sea level		
Take-off (5 min)* (Flat rated 30° C)	14728 daN (33110 lbs)	14728 daN (33110 lbs)
Maximum continuous (Flat rated 25° C)	14581 daN (32780 lbs)	14581 daN (32780 lbs)

A321-251N/-252N/-253N/-251NX/-252NX/-253NX

Engine	LEAP-1A32	LEAP-1A33/-1A35A	LEAP-1A30
Data sheets	E00089EN (FAA) EASA.E.110	E00089EN (FAA) EASA.E.110	E00089EN (FAA) EASA.E.110
Static thrust at sea level			
Take-off (5 min)* (Flat rated 30° C)	14 305 daN (32160lbs)	14 305 daN (32160lbs)	14 305 daN (32160lbs)
	14 096 daN	14 096 daN	14 096 daN



SECTION 2: A321 SERIES

Engine	LEAP-1A32	LEAP-1A33/-1A35A	LEAP-1A30
Maximum continuous (Flat rated 25° C)	(31690lbs)	(31690lbs)	(31690lbs)

12.1 Approved Operations

Transport commercial operations.

12.2 Other Limitations

For a complete list of applicable limitations see the appropriate EASA approved Airplane Flight Manual.

13. Maximum Certified Masses**A321-111/A321-112**

VARIANT	000 (BASIC)	002 (MOD 24178)	003 (MOD 24899)	004 (MOD 24308)	005 (MOD 25649)	006 (MOD 26600*)	007 (MOD 26888)	008 (MOD 30334)
WEIGHT (Kg)								
Max. Ramp Weight	83 400	83 400	85 400	78 400	83 400	78 400	80 400	89 400
Max. Take-off Weight	83 000	83 000	85 000	78 000	83 000	78 000	80 000	89 000
Max. Landing Weight	73 500	74 500	74 500	73 500	75 000	74 500	73 500	75 500
Max. Zero Fuel Weight	69 500	70 500	70 500	69 500	71 000	70 500	69 500	71 500
Minimum Weight	47 500	47 500	47 500	47 500	47 500	47 500	47 500	47 500

A321-131

VARIANT	000 (BASIC)	002 (MOD 24178)	003 (MOD 24899)	004 (MOD 24308)	006 (MOD 26600*)	007 (MOD 26888)	008 (MOD 30334)
WEIGHT (Kg)							
Max. Ramp Weight	83 400	83 400	85 400	78 400	78 400	80 400	89 400
Max. Take-off Weight	83 000	83 000	85 000	78 000	78 000	80 000	89 000
Max. Landing Weight	73 500	74 500	74 500	73 500	74 500	73 500	75 500
Max. Zero Fuel Weight	69 500	70 500	70 500	69 500	70 500	69 500	71 500
Minimum Weight	47 500	47 500	47 500	47 500	47 500	47 500	47 500

Note:

On the series A321-100, Weight Variant 006 is defined either by MOD 26600, building up on Weight Variant 003, or MOD 30310, building up on Weight Variant 000.

A321-211/A321-231

VARIANT	000 (BASIC)	001	002	003	004	005	006	008	010
---------	----------------	-----	-----	-----	-----	-----	-----	-----	-----



SECTION 2: A321 SERIES

WEIGHT (Kg)		(MOD 28960)	(MOD 28721)	(MOD 31613)	(MOD 31614)	(MOD 27553)	(MOD 31616)	(MOD 31618)	(MOD 31321)
Max. Ramp Weight	89 400	93 400	89 400	91 400	87 400	85 400	83 400	80 400	85 400
Max. Take-off Weight	89 000	93 000	89 000	91 000	87 000	85 000	83 000	80 000	85 000
Max. Landing Weight	75 500	77 800	77 800	77 800	75 500	75 500	75 500	73 500	77 800
Max. Zero Fuel Weight	71 500	73 800	73 800	73 800	71 500	71 500	71 500	69 500	73 800
Minimum Weight	47 500	47 500	47 500	47 500	47 500	47 500	47 500	47 500	47 500

VARIANT WEIGHT (Kg)	011 (MOD 32456)
Max. Ramp Weight	93 900
Max. Take-off Weight	93 500
Max. Landing Weight	77 800
Max. Zero Fuel Weight	73 800
Minimum Weight	47 500

Notes:

(1) MOD 160023 is approved for WV 000 to WV11.



SECTION 2: A321 SERIES**A321-212/A321-213/A321-232**

VARIANT WEIGHT (Kg)	000 BASIC	001* (MOD 28960)	002* (MOD 28721)	003* (MOD 31613)	004* (MOD 31614)	005* (MOD 31615)	006* (MOD 31616)	007* (MOD 31617)	008* (MOD 31618)	009* (MOD 31619)	010* (MOD 31321)	011 (MOD 32456)
Max. Ramp Weight	89 400	93 400	89 400	91 400	87 400	85 400	83 400	83 400	80 400	78 400	85 400	93 900
Max. Take-off Weight	89 000	93 000	89 000	91 000	87 000	85 000	83 000	83 000	80 000	78 000	85 000	93 500
Max. Landing Weight	75 500	77 800	77 800	77 800	75 500	75 500	75 500	73 500	73 500	73 500	77 800	77 800
Max. Zero Fuel Weight	71 500	73 800	73 800	73 800	71 500	71 500	71 500	69 500	69 500	69 500	73 800	73 800
Minimum Weight	47 500	47 500	47 500	47 500	47 500	47 500	47 500	47 500	47 500	47 500	47 500	47 500

Notes:

- * WV option certified concurrently with the basic WV at the time of the model's approval
- (2) MOD 160023 is approved for WV 000 to WV11.

A321-271N / -272N / -251N / -252N/ -253N

VARIANT WEIGHT (Kg)	50 BASIC (MOD 161448)	51* (MOD 161555)	52* (MOD 161556)	53* (MOD 161557)	56 (MOD 158238)	57 (MOD 158239)	63 (MOD 158245)	65 (MOD 158247)	67 (MOD 158249)
Max. Ramp Weight	89 400	89 400	93 900	93 900	92 900	92 900	91 400	90 900	90 400
Max. Take-off Weight	89 000	89 000	93 500	93 500	92 500	92 500	91 000	90 500	90 000
Max. Landing Weight	77 300	79 200	77 300	79 200	77 300	79 200	79 200	79 200	79 200
Max. Zero Fuel Weight	73 300	75 600	73 300	75 600	73 300	75 600	75 600	75 600	75 600

VARIANT WEIGHT (Kg)	70* (MOD 161735)
Max. Ramp Weight	80 400
Max. Take-off Weight	80 000
Max. Landing Weight	71 500
Max. Zero Fuel Weight	67 000



SECTION 2: A321 SERIES

Notes:

- * WV option certified concurrently with the basic WV at the time of the model's approval

Minimum Weight:

A321-271N/-272N 46 300 Kg

A321-251N/-252N/-253N 46 600 Kg



SECTION 2: A321 SERIES**A321-271NX / -272NX / -251NX / -252NX / -253NX**

VARIANT WEIGHT (Kg)	50 BASIC (MOD 161448)	51* (MOD 161555)	52* (MOD 161556)	53* (MOD 161557)	56 (MOD 158238)	57 (MOD 158239)	63 (MOD 158245)	65 (MOD 158247)
Max. Ramp Weight	89 400	89 400	93 900	93 900	92 900	92 900	91 400	90 900
Max. Take-off Weight	89 000	89 000	93 500	93 500	92 500	92 500	91 000	90 500
Max. Landing Weight	77 300	79 200	77 300	79 200	77 300	79 200	79 200	79 200
Max. Zero Fuel Weight	73 300	75 600	73 300	75 600	73 300	75 600	75 600	75 600

VARIANT WEIGHT (Kg)	67 (MOD 158249)	70* (MOD 161735)	71* (MOD 160287)	72* (MOD 160288)	80* (MOD 161729)
Max. Ramp Weight	90 400	80 400	97 400	97 400	95 400
Max. Take-off Weight	90 000	80 000	97 000	97 000	95 000
Max. Landing Weight	79 200	71 500	77 300	79 200	79 200
Max. Zero Fuel Weight	75 600	67 000	73 300	75 600	75 600

Notes:

* WV option certified concurrently with the basic WV at the time of the model's approval

Minimum Weight:

A321-271NX/-272NX 46 300 Kg

A321-251NX/-252NX/-253NX 46 600 Kg

14. Centre of Gravity Range

See the appropriate EASA approved Airplane Flight Manual.

15. Datum

Station 0.0, located 2.540 meters forward of airplane nose.

16. Mean Aerodynamic Chord (MAC)

4.1935 meters.

17. Levelling Means

The A/C can be jacked on three primary jacking points.

See the appropriate EASA approved Weight and Balance Manual.

18. Minimum Flight Crew

2 pilots.



SECTION 2: A321 SERIES

19. Minimum Cabin Crew

See paragraph 20.

20. Maximum Seating Capacity

The table below provides the certified Maximum Passenger Seating Capacities (MPSC), the corresponding cabin configuration (exit arrangement and modifications) and the associated minimum numbers of cabin crew members used to demonstrate compliance with the certification requirements:

MPS C	Cabin configuration	Modificatio n	Minimu m CC
230	C*-C-C-C*	157272 ⁽¹⁾ or 159536 ⁽¹⁾	5
220	C-C-C-C	---	5
200	C-C-C-C	---	4
200	C-I-I-C	---	4
200	C*-(III-III)*-O-C*	160908 ^{(1) (2)}	4
244	C*-(III-III)*-C-C*	160766 ^{(1) (3)}	5
180	C-(III-III)*-O-C	160908 ⁽²⁾ and 162227	4
235	C-(III-III)*-C-C	160766 ⁽³⁾ and 162227	5
224	C*-(0-III)*-C-C* Or C*-(III-0)*-C-C*	160906 ⁽²⁾⁽³⁾	5
200	C-(0-III)*-C-C Or C-(III-0)*-C-C	160906 ⁽²⁾⁽³⁾ and 162227	4
204	C-(0-III)*-C-C Or C-(III-0)*-C-C	160906 ⁽²⁾⁽³⁾ and 162227	5
169	C*-(0-III)*-O-C* Or C*-(III-0)*-O-C*	160907 ⁽²⁾⁽³⁾	4



SECTION 2: A321 SERIES

149	C-(0-III) ⁺ -0-C Or C-(III-0) ⁺ -0-C	160907 ⁽²⁾⁽³⁾ and 162227	3
-----	--	--	---

- (1) C* is the overperforming Type C as defined by ESF D-02
 (2) 0 is a plugged door
 (3) C* is the overperforming Type C as defined by ESF D-09 and (III-III)⁺ or III⁺ are the overperforming Type III (double or single) as defined by ESF D-13

Note:

- The original maximum passenger seating capacity is 220.
- The modifications 157272 or 159536 enable the maximum seating capacity to be increased from 220 up to 230. This modification defines a virtual envelope of the Layout of Passenger Accommodations (LOPA) and does not constitute an authorization for the installation of seats in excess of 220. A separate approval is needed for the installation of the individual customized cabin layout and the necessary cabin adaptations up to 230 seats.
- The modification 160908 enables a maximum seating capacity of 200. This modification defines a virtual envelope of the Layout of Passenger Accommodations (LOPA) and does not constitute an authorization for the installation of seats up to 200. A separate approval is needed for the installation of the individual customized cabin layout and the necessary cabin adaptations up to 200 seats.
- The modification 160766 enable the maximum seating capacity to be increased from 220 up to 244. This modification defines a virtual envelope of the Layout of Passenger Accommodations (LOPA) and does not constitute an authorization for the installation of seats in excess of 220. A separate approval is needed for the installation of the individual customized cabin layout and the necessary cabin adaptations up to 244 seats.
- The modification 160906 enables a maximum seating capacity of 224. This modification defines a virtual envelope of the Layout of Passenger Accommodations (LOPA) and does not constitute an authorization for the installation of seats up to 224. A separate approval is needed for the installation of the individual customized cabin layout and the necessary cabin adaptations up to 224 seats.
- The modifications 160907 enable the maximum seating capacity of 169. This modification defines a virtual envelope of the Layout of Passenger Accommodations (LOPA) and does not constitute an authorization for the installation of seats in excess of 169. A separate approval is needed for the installation of the individual customized cabin layout and the necessary cabin adaptations up to 169 seats.
- The modification 162227 installs a narrow slide.
- With MOD 153648 "EQUIPMENT/FURNISHINGS - GENERAL - DELIVER AIRCRAFT WITH INCOMPLETE CABIN" embodied, the cabin is limited to zero occupancy and no cargo (i.e. no



SECTION 2: A321 SERIES

occupancy and no cargo in cabin) during all phases of flight, unless a separate approved Modification is embodied to remove the limitation.

21. Baggage/ Cargo Compartment

For A321-111/-112/-131/-211/-212/-213/-231/-232/-271N/-272N/-251N/-252N/-253N

CARGO COMPARTMENT	MAXIMUM LOAD (kg)
Forward	5 670
Aft	5 670
Rear (bulk)	1 497

For A321-271NX/-272NX/-251NX/-252NX/-253NX

CARGO COMPARTMENT	MAXIMUM LOAD (kg)
Forward	5 670
Aft	5 670
Rear (bulk)	800

For the positions and the loading conditions authorized in each position (references of containers, pallets and associated weights) see Weight and Balance Manual, ref. 00E080A0001/C1S Chapter 1.10.

22. Wheels and Tyres

See SB A320-32-1007 for A321-111/-112/-131/-211/-212/-213/-231/-232 and SB A320 32 1439 for A321-271N/-272N/-251N/-252N/-253N/-271NX/-272NX/-251NX/-252NX/-253NX.

23. ETOPS

The Type Design, system reliability and performance of A321 models were found capable for Extended Range Operations when configured, maintained and operated in accordance with the current revision of the ETOPS Configuration, Maintenance and Procedures (CMP) document, SA/EASA: AMC 20-6/CMP.

This finding does not constitute an approval to conduct Extended Range Operations (operational approval must be obtained from the responsible Authority).

The following table provides details on the ETOPS approvals.

Aircraft model	Engine Type	120 min Approval Date	180 min Approval Date
A321-111	CFM56-5B1	29 May 1996	11 March 2004
A321-112	CFM56-5B2	29 May 1996	11 March 2004
A321-131	V2530-A5	29 May 1996	11 March 2004
A321-211	CFM56-5B3	28 July 1997	11 March 2004
A321-212	CFM56-5B1	N/A	28 April 2006
A321-213	CFM56-5B2	N/A	28 April 2006



SECTION 2: A321 SERIES

Aircraft model	Engine Type	120 min Approval Date	180 min Approval Date
A321-231	V2533-A5	28 July 1997	11 March 2004
A321-232	V2530-A5	N/A	28 April 2006
A321-271N	PW1133G-JM	27 June 2017	27 June 2017
A321-272N	PW1130G-JM	27 June 2017	27 June 2017
A321-251N	LEAP-1A32	10 July 2017	10 July 2017
A321-253N	LEAP-1A33	10 July 2017	10 July 2017
A321-252N	LEAP-1A30	17 January 2018	17 January 2018
A321-271NX	PW1133G-JM	5 June 2018	5 June 2018
A321-272NX	PW1130G-JM	5 June 2018	5 June 2018
A321-251NX	LEAP-1A32	5 June 2018	5 June 2018
A321-253NX	LEAP-1A33	5 June 2018	5 June 2018
A321-252NX	LEAP-1A30	5 June 2018	5 June 2018

Note:

The Configuration, Maintenance and Procedure Standards for extended range twin-engine airplane operations are contained in ETOPS CMP document reference SA/EASA: AMC 20-6/CMP at latest applicable revision. Certificated models are A321-111/-112/-131/-211/-212/-213/-231/-232/251N/-252N/-253N/-271N/-272N/251NX/-252NX/-253NX/-271NX/-272NX with all applicable engines.

Embodiment of modification:

36666 provides ETOPS 120 mn capability for EASA

32009 provides ETOPS 180 mn capability for EASA

IV. Operating and Service Instructions**1. Airplane Flight Manual (AFM)**

EASA Approved Airplane Flight Manual for A321.

2. Instructions for Continued Airworthiness and Airworthiness Limitations

The complete set of Instructions for Continued Airworthiness is identified in paragraph 2 of the Aircraft Maintenance Manual introduction.

Airworthiness Limitations

- Limitations applicable to Safe Life Airworthiness Limitation Items are provided in the A318/A319/A320/A321 approved Airworthiness Limitations Section (ALS) sub-parts 1-2 and 1-3.
- Limitations applicable to Damage Tolerant Airworthiness Limitation Items are provided in the A318/A319/A320/A321 approved Airworthiness Limitations Items document (ALS Part 2).
- Certification Maintenance Requirements are provided in the A318/A319/A320/A321 approved Airworthiness Limitations Section (ALS) Part 3.



SECTION 2: A321 SERIES

- System Equipment Maintenance Requirements are provided in the A318/A319/A320/A321 approved Airworthiness Limitations Section (ALS) Part 4.
- Fuel Airworthiness Limitations are provided in the A318/A319/A320/A321 approved Fuel Airworthiness Limitations document (ALS Part 5).
- Maintenance Review Board Report

Note:

- For A321-211, -212, -213, -231, -232 models without Sharklets, the embodiment of modification 154881 leads to change the maintenance program and its associated Maintenance Programme Publication Trigger (MPPT) from 48,000FC/60,000FH to 37,000FC/74,000FH (whichever occurs first).
- For A321-111,-112,-131,-211,-212,-213,-231,-232 models without Sharklets, the embodiment of modification 156130 leads to change the maintenance program and its associated Maintenance Programme Publication Trigger (MPPT) from 48,000FC/60,000FH to 60,000FC/120,000FH (whichever occurs first).

Other limitations

See EASA approved Flight Manual.

3. Weight and Balance Manual (WBM)

Airbus Compliance Document 00E80A0001/C1S.

V. Operational Suitability Data (OSD)

The Operational Suitability Data elements listed below are approved by the European Union Aviation Safety Agency under the EASA Type Certificate EASA.A.064 as per Commission Regulation (EU) 748/2012 as amended by Commission Regulation (EU) No 69/2014.

1. Master Minimum Equipment List

- a. The Master Minimum Equipment List has been approved as per the defined Operational Suitability Data Certification Basis (JAR-MMEL/MEL – Subpart B – MMEL at Amendment 1) and as documented in A320 MMEL reference “MMEL STL11000” at the latest applicable revision.
- b. Required for entry into service by EU operator.

2. Flight Crew Data

- a. The Flight Crew data has been approved as per the defined Operational Suitability Data Certification Basis (CS-FCD, initial issue) and as documented in reference “A320 Operational Suitability Data Flight Crew - SA01RP1536744” at the latest applicable revision.



SECTION 2: A321 SERIES

- b Required for entry into service by EU operator.
- c. The aircraft models: A318, A319, A321 are determined to be variants to the A320 aircraft model.

3. Cabin Crew Data

- a. The Cabin Crew data has been approved as followed and as documented in reference “A320 Operational Suitability Data Cabin Crew - SA01RP1534113” at the latest applicable revision.
 - 1. Until 20 Jan 2022 (date of MOD 165947 iss 1 Adapt lavatory SpaceFlex V2 for Airspace Cabin):
 - A318, A319, A320: Certification Basis/SC CCD-01
 - A321 except A321NX: Certification Basis/SC CCD-01
 - A321NX (A321-271NX,-272NX,-251NX,-252NX,-253NX): SC CCD-01 + CS-CCD.400(a) at initial issue
 - 2. After 20 Jan 2022 (date of MOD 165947 iss 1 Adapt lavatory SpaceFlex V2 for Airspace Cabin): A318, A319, A320, A321: Certification Basis/SC CCD-01 + CS-CCD.400 at initial issue
- b. Required for entry into service by EU operator.
- c. The aircraft models: A318, A319, A321 are determined to be variants to the A320 aircraft model.

VI. Part-26 compliance information

For all models, compliance with point 26.300(a) of Part-26 is demonstrated by complying with points

- 26.301 Compliance Plan for (R)TC holders
- 26.302 Fatigue and damage tolerance evaluation
- 26.303 Limit of Validity
- 26.304 Corrosion prevention and control programme
- 26.306 Fatigue critical baseline structure
- 26.307 Damage tolerance data for existing changes to fatigue-critical structure
- 26.308 Damage tolerance data for existing repairs to fatigue-critical structure
- 26.309 Repair Evaluation Guidelines

VII. Notes

- 1. For models A321-111 and A321-112, modification 25199 shall be installed to enable Cat IIIB precision approach.
For models A321-131, modification 25200 shall be installed to enable Cat IIIB precision approach.

A321-211/-212/-213/-231/-232 are basically qualified for Cat IIIB precision approach.

For A321-251N/-252N/-253N/-271N/-272N/251NX/-252NX/-253NX/-271NX/-272NX modification 161765 shall be installed to enable Cat IIIB precision approach.



SECTION 2: A321 SERIES

For A321-111/-112/-131/-211/-212/-213/-231/-232/-271N/-272N/-251N/-252N/-253N/-271NX/-272NX/-251NX/-252NX/-253NX DOOR 2 and/or DOOR 3 may be derated to Type III.



SECTION 3: A319 SERIES**SECTION 3: A319 SERIES****I. General**

1. Type/ Model/ Variant

A319-111
 A319-112
 A319-113
 A319-114
 A319-115
 A319-131
 A319-132
 A319-133
 A319-151N
 A319-153N
 A319-171N
 A319-173N

Significant Product Level Changes i.a.w. 21.A.101:

160500 Sharklet applicable on	A319-111/-112/-115/-131/-132/-133 including CJ
157777 Max Pax applicable on	A319-111 /-112 / -113 / -114 / -115/ -131/ - 132 /-133
160080 Sharklet retrofit applicable on	A319-111/-112/-115/-131/-132/-133 including CJ
159535 Max Pax applicable on	A319-111 /-112 / -113 / -114 / -115/ -131/ - 132 /-133
161004 applicable on	A319-151N
161001 applicable on	A319-171N
159533 iss1 Max Pax applicable on	A319-111/ -112/ -115/ -131/ -132/ -133
159533 iss2 Max Pax applicable on	A319-151N/-153N/-171N
169981 applicable on	A319-173N
ACJ319 NEO*	A319-153N
A319 CEO*	A319-111/-112/-113/-114/-115/-131/-132/-133
A319 NEO*	A319-151N/-153N/-171N/173N

*Commercial designation only

2. Performance Class

A



SECTION 3: A319 SERIES**3. Certifying Authority**

European Union Aviation Safety Agency (EASA)
Postfach 101253
D-50452 Köln
Deutschland

4. Manufacturer

AIRBUS
2 rond-point Emile Dewoitine
31700 BLAGNAC – France

5. State of Design Authority Certification Application Date

A319-111	June 17, 1992
A319-112	June 17, 1992
A319-113	June 17, 1992
A319-114	June 17, 1992
A319-115	September 14, 1998
A319-131	June 17, 1992
A319-132	June 17, 1992
A319-133	September 14, 1998

6. EASA Type Certification Application Date

MOD 160500	08 April 2010
MOD 157777	13 March 2015
MOD 160080	24 April 2012
MOD 159535	1 July 2016
MOD 159533 iss 1	19 January 2017
MOD 161004	18 December 2013
MOD 161001	30 November 2014
MOD 165511	4 December 2018
ACJ319 NEO	June 06, 2015
MOD 159533 iss 2	19 January 2017
MOD 169981	20 October 2021

7. State of Design Authority Type Certificate Date

A319-111	April 10, 1996
A319-112	April 10, 1996
A319-113	May 31, 1996
A319-114	May 31, 1996
A319-115	July 30, 1999
A319-131	December 18, 1996



SECTION 3: A319 SERIES

A319-132	December 18, 1996
A319-133	July 30, 1999

Note: For A319 produced before the 21st of December 2005, DGAC-F TC 180 remains a valid reference.

8. EASA Type Certification Date

EASA TCDS issue 1 issued December 21, 2005

MOD 160500 iss.4 May 28, 2013	A319-111,-112,-115 excluding CJ
MOD 160500 iss 5 September 6, 2013	A319-112 (CJ), A319-115 (CJ), A319-131 (PAX), A319-132 (PAX and CJ), A319-133 (PAX and CJ)
MOD 157777 iss 1 July 1, 2015	A319-111 /-112 / -113 / -114 / -115/ -131/ -132 /-133
MOD 160080 iss 2 December 17, 2015	A319-111/-112/-115/-131/-132/-133 including CJ
MOD 159535 iss 1 September 6, 2017	A319-111 /-112 / -113 / -114 / -115/ -131/ -132 /-133
MOD 161004 iss 1 December 14, 2018	A319-151N
MOD 161001 iss 1 November 29, 2019	A319-171N
MOD 159533 iss 1 February 18, 2019	A319-111 / -112 / -115 / -131 / -132 / -133
MOD 165511 iss 1 May 20, 2019	A319-153N
ACJ319 NEO Iss 1 July 9, 2019	A319-153N(CJ)
MOD 159533 iss 2 January 11, 2022	A319 -151N/-153N/-171N
MOD 169981 iss 1 February 28, 2024	A319-173N

II. Certification Basis**1. Reference Date for determining the applicable requirements**

AIRBUS INDUSTRIE has applied for A319 certification on June 17, 1992 by letter AI/EA 410.0122/92.

2. State of Design Airworthiness Authority Type Certification Data Sheet No.

Original French TCDS DGAC no. 180 was replaced by the EASA TCDS A.064.

3. State of Design Airworthiness Authority Certification Basis

See below.

4. EASA Airworthiness Requirements

SECTION 3: A319 SERIES

Hereafter are listed the certification bases for the different A319 models. The amendments made to a particular basis at the occasion of further A319 models certification are identified per model.

4.1 JAR 25 Change 11

- except Subpart BB,
- except all National Variants,
- except, due to the application of the procedure for establishing the Joint Type Certification Basis for derivative large aeroplanes, the following JAR 25 paragraphs which are upgraded at Change 13 and eventually amended by Orange Paper 90/1 or Orange Paper 91/1:

25 X 20	25.253
25.107(d)	25.365 amended by OP 91/1
25.121	25.807(c) amended by OP 90/1
25.125	25.812(e)
25.143(f)	25.853(a)(b) since MSN 118
25.207	25.857(d)(6)

except, due to the Elect to Comply with SC F-11 and SC S-79, the following deleted paragraphs:

25x131
25x132
25x133
25x135
25x1588

- the following JAR 25 paragraphs upgraded at Change 13 and amended by SC F-11 and SC S-79:

25.101	25.105
25.109	25.113
25.115	25.735
25x1591	

4.2 JAR AWO at Change 1 for autoland and operations in low visibility.**4.3 For the Extended Twin Engine Airplane Operations the applicable technical conditions are contained in AMC 20-6 (as initially published in AMJ 120-42/IL 20) and:**

- G-4006 ETOPS
G-4007 ETOPS - One engine inoperative cruise speed.

4.4 Certification basis has been revised for MOD 160500 "Sharklet" and MOD 160080 "Sharklet retrofit".

The certification basis is that of the A319-111/-112/-115/-131/-132/-133 amended by the following:



SECTION 3: A319 SERIESCS 25 Amdt 8 for

§ 25.23	§ 25.481(a)(c) amended by SC A-2 for § 25.481(a)
§ 25.25	§ 25.483
§ 25.117	§ 25.485
§ 25.147	§ 25.489
§ 25.161	§ 25.491
§ 25.177 amended by SC-F16	§ 25.571(a)(b)(e)
§ 25.235	§ 25.581
§ 25.251	§ 25.601
§ 25.301	§ 25.603
§ 25.302	§ 25.605
§ 25.303	§ 25.607
§ 25.305(a)(b)(c)(e)(f)	§ 25.609
§ 25.307(a)(d)	§ 25.613
§ 25.321(a)(b)(c)(d)	§ 25.619
§ 25.331(a)(b)(c)	§ 25.623
§ 25.333(a)(b)	§ 25.625
§ 25.335(a)(c)(d)(e)(f) amended by SC A-5003 for (b) and SC A-2 for (e)	§ 25.629
§ 25.337	§ 25.631
§ 25.341(a)(b)	§ 25.651
§ 25.343(a)(b)	§ 25.683
§ 25.345(a)(b)(c)(d)	§ 25.899
§ 25.349(a)(b) amended by SC A-2.2.2 for 25.349(a)	§ 25.903(d)(1)
§ 25.351	§ 25.1385
§ 25.365(a)(b)(d)	§ 25.1387
§ 25.367	§ 25.1389
§ 25.371	§ 25.1391
§ 25.373	§ 25.1393
§ 25.391	§ 25.1395
§ 25.393(b)	§ 25.1397
§ 25.427	§ 25.1401
§ 25.445	§ 25.1505
§ 25.457	§ 25.1511
§ 25.459	§ 25.1515
§ 25.471(a)(b)	§ 25.1527
§ 25.473	§ 25.1587
§ 25.479(a)(c)(d) amended by SC A-2 for § 25.479(a)	§ 25.1591

CS 25 Amdt 2 for

§ 25.253

JAR 25 Chg 15 for

§ 25.1517



SECTION 3: A319 SERIES**JAR 25 Chg 14 for**

§ 25.21 amended by A318 SC F-5001 (for b)	§ 25.149 + OP96/1
§ 25.101 amended by SC F-11/S-79	§ 25.171 replaced by SC-F5004
§ 25.103 replaced by A318 SC F-5001	§ 25.173 replaced by SC-F5004
§ 25.105 amended by SC F-11/S-79	§ 25.175 replaced by SC-F5004
§ 25.107 amended by A318 SC F-5001	§ 25.181
§ 25.109 amended by SC F-11/S-79	§ 25.201 + OP96/1, replaced by SC F-5001
§ 25.111	§ 25.203 + OP96/1, replaced by SC F-5001
§ 25.113 + OP96/1 amended by SC F-11/S-79	§ 25.207 amended by SC F-5001
§ 25.115 amended by SC F-11/S-79	§ 25.231
§ 25.119 + OP96/1 amended by A318 SC F-5001 (for b)	§ 25.233
§ 25.121 + OP96/1, amended by A318 SC F-5001 (for c & d)	§ 25.237
§ 25.123	§ 25X261
§ 25.125 + OP96/1, amended by A318 SC F-5001	§ 25.1533
§ 25.143 + OP96/1, amended by SC F-3, F-7 & F-8	§ 25.1581
§ 25.145 + OP96/1	§ 25.1585(a)

JAR 25 Chg 11 for

§ 25.671
 § 25.672
 § 25.1001
 § 25.1301
 § 25.1309
 § 25.1419

ETOPS

AMC 20-6 Rev 1 paragraphs related to operation in icing conditions 8.b.(11) for ice shapes on the Sharklet device.

AMC 20-6 Rev 1 paragraphs related to performance data in the AFM supplement for ETOPS 8.f.(1) (iii).

AMJ 120-42 for ETOPS for non-affected areas.

Note: This corresponds to the certification basis used for the initial ETOPS demonstration (refer to A320 EtC G-1006).

4.5 Certification basis has been revised for MOD 157777 “Max Pax” for aircraft equipped with wing tip fence.

The certification basis is that of the A319-111, -112, -113, -114, -115, -131, -132, -133 amended by the following:

CS 25 Amdt 15 for

§25.23	§25.479(a)(c)(d) amended by SC A-2 for § 25.479(a)
§25.305(a)(b)	§25.481(a)(c) amended by SC A-2 for § 25.481(a)



SECTION 3: A319 SERIES

§25.321	§25.489
§25.331(a)(b)(c)(1) amended by IM A-2.2.2	§25.801(d)
§25.341(a)	§25.803(c)
§25.351	§25.807(g) amended by ESF E-4001 and demonstrated through ESF D-03
§25.473	§25.1529

JAR 25 change 13

§25.331(c)(2)	§25.812(e)(1)(2)
§25.341(b)	§25.812(k)(l)
§25.365(a)	§25.853(a)1 amended by SC D-0306-000

JAR 25 change 12

§25.787(a)(b) §25.853(c)(d)(e)

JAR 25 change 11

§25.307(a)	§25.1301
§25.561	§25.1351(a)
§25.571(a)(b)	§25.1353(a)(b)
§25.785	§25.1359(a)(d)
§25.789(a)	§25.1413
§25.791	§25.1415(b)(c)(d)
§25.853(a)(b)	§25.1431(c)

4.6 Certification basis revised for MOD 159535 “Max Pax” for aircraft equipped with wing tip fence.

The certification basis is that of the A319-111, -112, -113, -114, -115, -131, -132, -133 amended by the following:

CS 25 Amdt 18 for

§25.23	§25.489
§25.305(a)(b)	§25.801(d)
§25.321	§25.803(c)
§25.331(a)(b)(c)(1) amended by IM A-2.2.2	§25.807(g) amended by ESF E-4001 and demonstrated through ESF D-03
§25.341(a)	§25.1519
§25.351	§25.1529
§25.473	§25.1541(a)(b)
§25.479(a)(c)(d) amended by SC A-2 for § 25.479(a)	§25.1557(a)
§25.481(a)(c) amended by SC A-2 for § 25.481(a)	

JAR 25 change 13

§25.331(c)(2)	§25.812(e)
---------------	------------



SECTION 3: A319 SERIES

§25.341(b)	§25.812(k)(l)
§25.365(a)	§25.853(a)1 amended by SC D-0306-000

JAR 25 change 12

§25.853(c)

JAR 25 change 11

§25.307(a)	§25.1301
§25.561	§25.1351(a)
§25.571(a)(b)	§25.1353(a)(b)
§25.785	§25.1357(a)
§25.787(a)(b)	§25.1359(a)(d)
§25.789(a)	§25.1413
§25.791	§25.1415(b)(c)(d)
§25.853(a)(b)	§25.1431(c)
	§25.1447(c)1

4.7 Certification basis for A319-151N/-153N/-171N/-173N

The certification basis for the A319-151N/-153N/-171N/-173N has been revised.

The certification basis is that of the “Sharklet” amended by the following:

CS 25 Amdt 15 for

§25.23 (a) (b)	§25.951 (a) (b) amended by SC E-37 (Water/Ice in Fuel System), for pylon area only.
§25.25 (a) (b)	§25.951(c) amended by SC E-37 (Water/Ice in Fuel System), for pylon area only.
§25.27	§25.952 (a) (b) (for pylon area)
§25.101	§25.954
§25.109	§25.955 (a)
§25.113	§25.961 (a) (b)
§25.115	§25.963 (a) (e)(2) (subparagraph (e)(2) applicable only for A319-171N and -173N)
§25.117	§25.969
§25.143(k)	§25.971 (a) (b) (c)
§25.145 (a)	§25.981 for pylon area only
§25.147	§25.993 (a) (b) (c) (d) (e) for Engines and Pylon area only.
§25.149	§25.994 for fuel system component in the pylon and powerplant system area
§25.161	§25.995 for engine and pylon areas only
§25.171 replaced by SC B-04 (Static Directional, Lateral and Longitudinal Stability and Low Energy awareness)	§25.997 (a) (b) (c) (d)



SECTION 3: A319 SERIES

§25.173 replaced by SC B-04 (Static Directional, Lateral and Longitudinal Stability and Low Energy awareness)	§25.999 (a) (b)
§25.175 replaced by SC B-04 (Static Directional, Lateral and Longitudinal Stability and Low Energy awareness)	§25.1001
§25.177 with subparagraphs (b) and (c) replaced by SC B-04 (Static Directional, Lateral and Longitudinal Stability and Low Energy awareness)	§25.1011 (a) (b)
§25.181	§25.1013 (a) (b) (c) (d) (e) (f)
§25.201 replaced by SC B-01 (Stalling and scheduled operating speeds)	§25.1015 (a) (b)
§25.203 replaced by SC B-01 (Stalling and scheduled operating speeds),	§25.1017 (a) (b)
§25.231	§25.1019 (a)
§25.233	§25.1021 (a) (b)
§25.235	§25.1023 (a) (b)
§25.251	§25.1025 (a) (c)
§25.301 (a) (b) (c)	§25.1041
§25.302 (for new or modified parts)	§25.1043(a)(b)(c)
§25.303 (for new or modified parts)	§25.1045 (a) (b) (c)
§25.305 (a) (b) (c) (e) (f) (for new or modified parts)	§25.1091 (a) (b) (c) (d) (e)
§25.307 (a) (d) (for new or modified parts)	§25.1093 (b)
§25.321 (a) (b) (c) (d)	§25.1103 (b) (c) (d)
§25.331 (a) (b) (c)	§25.1121 (a) (b) (c) (d) (f) (g)
§25.333 (a) (b)	§25.1123 (a) (b) (c)
§25.335 (a) (b) (c) (d) (e) (f) with subparagraph (b) replaced by Legacy SC B-14 (Design Dive Speed Vd) and subparagraph (e) amended by Legacy SC A-2 (Stalling speeds for structural design)	§25.1141 (a) (b) (c) (d) (e) (f)
§25.337 (a) (b) (c) (d)	§25.1143 (a) (b) (c) (d) (e)
§25.341(a)(b)(c)	§25.1145 (a) (b) (c)
§25.343 (a) (b) (for new or modified parts)	§25.1155 (a) (b) (c) (d) (e)
§25.345 (a) (b) (c) (d)	§25.1163 (a) (b) (c)
§25.349 §25.349(a) amended by SC A-2.2.2.2 (b)	§25.1165 (a) (b) (c) (e) (f) (h)
§25.351	§25.1167 (a) (b) (c)
§25.361 (a) (b)	§25.1181 (a) (b) amended by ESF E-44 (Fan Zone non-fire zone)
§25.362 (a) (b) (for new or modified parts)	§25.1182 (a) (b)
§25.363 (a) (b)	§25.1183 (a) (b) (c)
§25.365 (a) (b) (c) (d) (e)(1) (for new or modified parts)	§25.1185 (a) (b) (c)



SECTION 3: A319 SERIES

§25.367 (a) (b)	§25.1187 (a) (b) (c) (d) (e)
§25.371	§25.1189 (a) (b) (d) (e) (f)
§25.373 (a) (b)	§25.1191 (a) (b)
§25.391 (a) (b) (c) (d) (e)	§25.1193 (a) (b) (c) (d) (e)(1)(2) amended by SC E-45 (Engine Cowl Retention) §25.1193(e)(3) amended by SC E-45 (Engine Cowl Retention)
§25.427 (a) (b) (c) (d)	§25.1195 (a) (b) (c)
	§25.1197(a)(b)
§25.445 (a) (b)	§25.1199 (a) (b) (c) (d) (e)
§25.457	§25.1201 (a) (b)
§25.459	§25.1203 (a) (b) (c) (d) (e) (f) (g)
§25.471 (a) (b)	§25.1207 (a) (b) (c) (d)
§25.473 (a) (b) (c) (d) (e)	§25.1305(a)(c)(d)
§25.479 (a) (c) (d) amended by Legacy SC A-2 for § 25.479(a)	§25.1309 (for newly designed systems) amended by: Legacy SC S-76 – Effects of external radiations upon aircraft systems, Legacy SC S-76-1 – Protection from the effects of HIRF
§25.481 (a) (c) amended by Legacy SC A-2 for § 25.481(a)	§25.1316 (a) (b) (c)
§25.483 (a) (b)	§25.1337 (a) (c) (d)
§25.485 (a) (b)	§25.1353 (a) (b) (for engine and pylon areas)
§25.489	§25.1355 (c)
§25.491	§25.1357 (a) (for newly designed systems)
§25.493 (b) (c) (d) (e)	§25.1401 (b)
§25.495	§25.1403
§25.499 (a) (b) (c) (d) (e)	§25.1419 (a) (b) (c) (d) (e) (f) (g) (h) for engine air intake protection
§25.503 (a) (b)	§25.1431 amended by Legacy SC S-76 - Effects of external radiations upon aircraft systems Legacy SC S-76-1 – Protection from the effect of HIRF For newly designed equipment only
§25.507 (a) (b) (c)	§25.1438 (for newly designed equipment)
§25.509	§25.1459 (a) (b) (c) (d) amended by Legacy SC S-72 (HC-S72 – Flight recorders)
§25.511	§25.1461 (a) (b) (c) (d) For newly designed equipment
§25.519 (a) (b) (c)	§25.1501(a) (b)
§25.571 (a) (b) (c) (d) (e) (for new or modified parts)	§25.1503



SECTION 3: A319 SERIES

§25.581 amended by Legacy SC S-75 – Lightning protection indirect effects for pylon and nacelle areas	§25.1507
§25.601 (for new or modified parts)	§25.1511
§25.603 (a) (b) (c) (for new or modified parts)	§25.1513
§25.605 (a) (b) (for new or modified parts)	§25.1515
§25.607 (a) (b) (for new or modified parts)	§25.1517
§25.609 (a) (b) (for new or modified parts)	§25.1519
§25.611 (a)	§25.1521 (a) (c) (d)
§25.613 (a) (b) (c) (d) (e) (f) (for new or modified parts)	§25.1525
§25.619 (a) (b) (c) (for new or modified parts)	§25.1527
§25.623 (a) (b) (for new or modified parts)	§25.1531
§25.625 (a) (b) (c) (d) (for new or modified parts)	§25.1533
§25.629 (a) (b) (c) (d) (e)	§25.1535 (a) (b) (c)
§25.631 (for new or modified parts)	§25.1549 (a) (b) (c) (d) amended by ESF E-51 (Oil temperature indication)
§25.651 (for new or modified parts)	§25.1551
§25.671 (a) (b) (c) (d) amended by legacy SC F-9 - Dual Control System	§25.1553
§25.731 (a) (b) (c)	§25.1557 (b)
§25.733 (b) (c) (d)	§25.1581
§25.777(i) Sub-paragraph (b) amended by SC B-03 (Motion and Effect of Cockpit Control)	§25.1583 (a) (b) (c) (d) (e) (f) (h) (i) (k)
§25.779	§25.1585
§25.831 (a) (e)	§25.1587
§25.841 (a)	§25.1591
§25.851(b)(c)	§25.1593
§25.855(c)	§25.1701 (a) (b) (c) for engines and pylon areas
	§25.1703 (a) (b) (d) (e) for engines and pylon areas
§25.863 (a) (b) (c) (d)	§25.1705 (a) (b) for engines and pylon areas
§25.865	§25.1707 (a) (b) (c) (d) (e) (f) (g) (h) (i) (j) (k) (l) for engines and pylon areas
§25.867 (a) (b)	§25.1709 (a) (b) for engines and pylon areas
§25.869 (a) (b) (c)	§25.1711 (a) (b) (c) (d) (e) for engines and pylon areas
§25.899 amended by Legacy SC S-75 – Lightning protection indirect effects, for Pylon and Nacelle areas only	§25.1713 (a) (b) (c) for engines and pylon areas
§25.901 (a) (b) (c) amended by SC E-45 (Engine Cowl Retention),	§25.1715 (a) (b) for engines and pylon areas
§25.903 (a) (b) (c) (d) (e)	§25.1717 for engines and pylon areas
§25.904	§25.1719 for engines and pylon areas
§25.933 (a)	§25.1723 for engines and pylon areas



SECTION 3: A319 SERIES

§25.934 amended by ESF E-43 (Thrust Reverser Testing).	§25.1725 (a) (b) for engines and pylon areas
§25.939 (a) (c)	§25.1727 for engines and pylon areas §25.1731 (a) (b)
§25.943	

CS 25 Amdt 13 for

<p>§25.963(e)(1)</p> <p><i>Note: "The A319-171N was granted a reversion to CS25.963(e)(1) at Amdt 13 based on a justification that takes credit from specific design features that are present in the aircraft A319-171N Type Design (refer to EASA Reversion E-65 "Fuel Tanks Reversion from CS25.963(e)(1) at Amdt 15 to CS25.963(e)(1) at Amdt 13").</i></p> <p><i>The validity of this justification must be reassessed in case of any subsequent type design change, modification, or repair to ensure the level of safety of the A319-171N is maintained."</i></p> <p><i>This reversion is also applicable for the A319-173N</i></p>	§25.963(e)(2) (applicable only for A319-151N)
--	---

CS25 Amdt 8 for:

§25.683 (b)	
-------------	--

CS 25 Amdt 2 for:

§25.21 with sub-paragraph (b) added by SC B-01 (Stalling and Scheduled Operating Speeds)	§25.123
§25.103 replaced by SC B-01 (Stalling and Scheduled Operating Speeds)	§25.125
§25.105	§25.143 Sub-Paragraphs (j), (k), (l) added by SC B-03 (Motion and Effect of Cockpit control), Sub-paragraph (h) added by SC B-07 (Flight envelope protection), Sub paragraph (i) added by SC B-08 (Normal Load factor limiting System).
§25.107	§25.207 replaced by SC B-01 (Stalling and scheduled operating speeds).
§25.111	§25.237
§25.119	§25.253
§25.121	§25.1419

CS25 Amdt 1:

SECTION 3: A319 SERIES

§25.981 (a) (3) amended by generic SC E-48 – Fuel Tank Safety for all areas except engine and pylon areas	
---	--

JAR 25 Chg 14 for:

§25.145 (b) (c)	§25.1423 (a) (b) (c) (d) (e) (f) (g)
§25.365 (e)(2), (e)(3)	§25.1583 (j)

JAR 25 Chg 13 for

§25.365 (f) (g)

§25.735 (a) (f) (g) (h) amended by

Legacy SC F-11 – Accelerate-stop distances and related performances, worn brakes

Legacy SC S-79 - Brake requirements, qualification and testing – A321

§25.853(a)(1)

JAR 25 Chg 12 for

§25.853(c)

JAR 25 Chg 11 for:

§25.561 (a) (b) (c)	§25.1309 amended by Generic SC D-0332-001 (Towbarless Towing) For systems adaptations.
§25.563	§25X1315
§25.672 (a) (b) (c)	§25.994 for all areas except engine and pylon areas
§25.677 (b)	§25.1301
§25.703 (a) (b) (c)	§25.1321 (d)
§25.721 (a) (b) (c)	§25.1322 (a) (b) (c) (d) amended by generic SC D-0332-001 (Towbarless Towing)
§25.729 (b) (c) (d) (e) (f)	§25.1323 (a) (b) (c)
§25.735 (b) (c)	§25.1325 (b) (d) (e)
§25.771 (e)	§25.1329 (f) amended by: Legacy SC S-30 (Automatic Flight/Flight Management Functions),
	§25.1337 (b)
§25.783 (a) (b) (c) (e) (f) (g)	§25.1351 (a) (b) (d) where (d) is replaced by Legacy SC-S52 (Operation without normal Electrical power)
§25.791	§25.1353 (a) (b) (for all areas except pylon and engine)
§25.801	§25.1359
§25.807 (a) (b) (c) (d)	§25.1363 (a) (b)
§25.809 (a) (b) (c) (d) (e) (f)	§25.1419 (a) (b) (c) (d)
§25.843 (a)	§25.1431 (for system adaptations)
§25.853 (a)	§25.1435 (a) (b) (c) (d)



SECTION 3: A319 SERIES

§25X899 amended by Legacy SC S-75 – Lightning protection indirect effects	§25.1457 (a) (b) (c) (d) (e) (f) (g)
§25.959	§25.1529 amended by SC H-01
§25.963 (d) (e)	§25A901 (c)
§25.967 (d)	§25A939 (a)
§25.975 (a)	§25A1521
§25.981 for all paragraph except (a) (3) in all areas except engine and pylon areas	§25A1527

4.8 Certification basis has been revised for MOD 159533 iss1 “Max Pax” for aircraft equipped with modification 160500 (Sharklets).

The certification basis is that of the A319-111, -112, -115, -131, -132, -133 equipped with modification 160500 amended by the following:

CS 25 Amdt 18 for

§25.23	§25.489
	§25.801(d)
§25.321	§25.803(c)
§25.331	§25.807(g) amended by ESF E-4001 and demonstrated through ESF D-03
§25.341(a)(b)	§25.1519
§25.351	§25.1529
§25.473	§25.1541(a)(b)
§25.479(a)(c)(d) amended by SC A-2 for § 25.479(a)	§25.1557(a)
§25.481(a)(c) amended by SC A-2 for § 25.481(a)	

JAR 25 change 13

§25.305(a)(b)	§25.812(k)(l)
§25.365(a)	§25.853(a)1 amended by SC D-0306-000
§25.812(e)	

JAR 25 change 12

§25.853(c)

JAR 25 change 11

§25.307(a)	§25.1301
§25.561	§25.1351(a)
§25.571(a)(b)	§25.1353(a)(b)
§25.785	§25.1357(a)
§25.787(a)(b)	§25.1359(a)(d)
§25.789(a)	§25.1413
§25.791	§25.1415(b)(c)(d)
§25.853(a)(b)	§25.1431(c)



SECTION 3: A319 SERIES

	§25.1447(c)1
--	--------------

4.9 Certification basis revised for ACJ319 NEO.

The certification basis is that of the A319-153N amended by the following:
CS25 Amdt 16 for the following chapters

25.23	25.957
25.25	25.959
25.27	25.963 (a)(b)(c)(e)(1)(d)(1)(d)(3)(f)(d)(4)(e)(1)(e)(2)
25.29	25.965 (a) (b) (c) (d)
25.101 (c)(d)(e)(f)(h)	25.967 (a) (b) (e)
25.109 (a)(b)	25.969
25.113 (a)(b)	25.971 (a) (b) (c)
25.115 (a)(b)	25.975 (a)
25.117	25.977 (a) (c) (d)
25.147 (c)(d)	25.979 (b) (c) (d) (e)
25.175 replaced by SC B-04	25.981 (a)(d)
25.201 replaced by SC B-01	25.993 (a) (b) (c) (d) (e) (f)
25.203 replaced by SC B-01	25.994
25.235	25.995 (b)
25.301 (a)(b)(c)	25.999 (a) (b)
25.302	25.1001 (a)(b)
25.303	25.1141 (a)(b)(c)(d)(f)
25.305 (a)(b)(c)(e)(f)	25.1189 (h)
25.307 (a)	25.1301 (a)(b)
25.321 (a)(b)(c)(d)	25.1302 (a) (b) (c)
25.331 (a)(b)(c)	25.1305 (a)(2)
25.333 (a)(b)	25.1309 (a) (b) (c) (d)
25.335 (a)(b)(c)(d)(e)(f), (b) amended by SC B14 and (e) amended by SC A-2	25.1310
25.337 (a)(b)(c)	25.1315
25.341 (a)(b)(c)	25.1316 (a) (b) (c)
25.343 (a) (b)(1)(b)(2)(b)(3)	25.1337 (b)
25.351 (a)(b)(c)(d)	25.1353 (a) (b)
25.361 (a)	25.1381 (a)(2)(ii)(b)
25.362 (a)(b)	25.1431 (a) (c) (d)
25.363 (a)(b)	25.1511
25.365 (a)(b)(d)(e)(f)	25.1517
25.367 (a)(b)	25.1519
25.371	25.1527
25.373 (a)(b)	25.1533
25.391 (a)(b)(d)(e)	25.1535 (a) and AMC 20-6 rev2
25.427 (a)(b)(d)	25.1543 (b)
25.445 (a)	25.1553
25.457	25.1555 (a) (c)
25.459	25.1581
25.471 (a)(b)	25.1583 (c)(f)(h)
25.473 (a)(b)(c)(d)(e)	25.1585 (a)(b)(c)(e)(f)



SECTION 3: A319 SERIES

25.479 (a)(c)(d) amended by SC A-2	25.1587
25.481 (a)(c), (a) emended by SC A-2	25.1591
25.483 (a)(b)	25.1703 (a1)(a2)a(3)(a4) (b) (d)
25.485 (a)(b)	25.1705 (a) (b)(4)(b)(9)(b)(16)
25.489	25.1707 (a)(b)(c)(e)(l)
25.491	25.1709 (a) (b)
25.493 (b)(c)(d)(e)	25.1711 (a) (b) (c) (d) (e)
25.495	25.1713
25.499 (a)(b)(c)(d)(e)	25.1715 (a) (b)
25.503 (a)(b)	25.1719
25.507 (a)(b)	25.1721 (b)
25.509 (a)(c)(d)	25.1723
25.511 (a)(b)(c)(d)(e)(f)	25.1725(b)
25.519 (a)(b)(c)	
25.561 (a)(b)(c)(d)	
25.571 (a)(b)(c)(e)	
25.581 (a) (b) (c)	
25.611	
25.619	
25.625	
25.629 (a)(b)(c)(d)(e)	
25.631	
25.721 (b)	
25.723 (b)	
25.733 (b)(c)	
25.777 (a)	
25.843 (a)	
25.851 (b)(2)	
25.855 (a) (c) (e) (f) (g)(h)(1)(h)(2)(h)(3)	
25.857	
25.858	
25.863 (a) (b) (c) (d)	
25.869	
25.899 (a) (b)	
25.901 (c)	
25.903 (c) (d)(1)	
25.943	
25.951 (c)	
25.952 (a)	
25.954 (a) (b) (c)	

CS 25 Amdt 11 for the following chapters

25.101 (c)(d)(e)(f)(g)(h)	25.671 (c)
25.109 (a)(b)	25.855 (c)(e)(1)
25.113 (a)(b)	25.901 (b)(c)
25.115 (a)(b)	25.1001 (a)(b)
25.117	25.1301 (a)(1)(a)(2)(a)(3)
25.143 (i) introduced by SC B-08	25.1309 (a)(b)
25.251	25.1519
25.305 (a) (b)	25.1533 (a)



SECTION 3: A319 SERIES

25.307 (a)	25.1527
25.335 (b)	25.1581 (a)(b)
25.365 (e)	25.1587 (b)
25.561 (b)(3)	25.1591 (b)
25.601	

CS 25 Amdt 2 for the following chapters

25.21 (a)(c)(d)	25.121 (a)(b)(c)
25.103 replaced by SC B-01	25.123
25.105 (a)	25.125 (a)(b)
25.107 (a)(b)(c)(d)(e)(f)(g)	25.143 (a)(b)(3)(g)
25.111 (a)(b)(c)(d)	25.253 (a)
25.119	25.1419, (b)

JAR 25 Change 13 for the following chapters

25.365 (e)(2)(3)(f)(g)

JAR 25 Change 11 for the following chapters

25.571 (a)(3) (c)	25.1309 (a)(b)(c)(d)(g)
25.672	25.1351 (a)
25.689 (f)	25.1353 (b)
25.775 (a)(b)(c)(d)	25.1529 amended by SC H-01
25.1103 (d)	25.1541
25.1301 (a) (b) (c) (d)	25.1557 (a)

With the removal of the aft cargo compartment through embodiment of the modification 165550 on ACJ319 NEO,

- FAR 25.856(b) (EtC E-28 plus ESF E-32) was not demonstrated in the aft cargo compartment. Instead, the passenger capacity is limited to 19 passengers.
- "Class C" cargo compartment airworthiness requirements CS25.855(a)(b)(c)(e)(f)(g)(h)(i) and CS25.857(c) are not applicable anymore for the changed AFT lower deck compartment.

4.10 Certification basis has been revised for MOD 159533 iss2 "Max Pax".

The certification basis is that of the A319-151N/-153N/-171N amended by the following:

For A319-151N/-153N

CS 25 Amdt 18 for the following chapters

25.23	25.489
25.305(a)(b)	25.571(a)(b)
25.307(a)	25.801(d)
25.321	25.803(c)
25.331	25.807(g) as amended by ESF E-4001 and demonstrated through ESF D-03
25.341(a)(b)	25.901(c)
25.351	25.1519
25.365(a)	25.1529
25.473	25.1541(a)(b)



SECTION 3: A319 SERIES

25.479(a)(c)(d) as amended by SC A-2	25.1557(a)
25.481(a)(c) as amended by SC A-2	

For A319-171N

CS 25 Amdt 18 for the following chapters

25.23	25.489
25.305(a)(b)	25.571(a)(b)
25.307(a)	25.801(d)
25.321	25.803(c)
25.331	25.807(g) As amended by ESF E-4001 and demonstrated through ESF D-03
25.341(a)(b)	25.901(c)
25.351	25.1519
25.365(a)	25.1529
25.473	25.1541(a)(b)
25.479(a)(c)(d) as amended by SC A-2	25.1557(a)
25.481(a)(c) as amended by SC A-2	

4.11 Post TC changes

4.11.1 In accordance with NPA 25-C205, the following JAR 25 paragraphs are upgraded at Change 13 and amended by Orange Paper 91/1:

25.305	25.349 (b)
25.321	25.351
25.331	25.365 (e)
25.333	25.371
25.335 (d)	25.373
25.341	25.391
25.343 (b) (1) (ii)	25.427
25.345 (a) and (c)	25.571 (b) (2)

4.11.2 If modification 153945 is embodied, the paragraph 25.813(c)(2)(ii) is upgraded at CS25 amendment 11.

4.11.3 When reinforced cockpit door is installed (see EtC E-12), 14 CFR Part 25.772(a) and (c) and 25.795 are at amendment 106.

4.11.4 When halon free hand-held fire extinguishers are installed, CS25.851(a),(c) is at Amdt 17 (see EtC D-GEN-AIRBUS-01).

4.11.5 For cabin and/or passengers improved seats (see EtC E-31), CS 25.562 is at amendment initial issue.

4.11.6 Airbus complies with CS-ACNS:

- Subpart B, Section 2 – for optional modifications (Post TC) installing FANS aiming at answering to SES mandate as defined in (EU) N° 29/2009 and amended by (EU) N° 310/2015 of 26 February 2015.



SECTION 3: A319 SERIES

Note: For compliance to CS-ACNS Subpart B, Section 2, a deviation to CS-ACNS.B.DLS.B1.075 is accepted by DEV ACNS-B-GEN-01 to not include DM89 MONITORING [unit name] [frequency] in the downlink message set installed.

- Subpart D – for optional modifications installing transponders aiming at answering to SES mandate as defined in (EU) No 1207/2011 and amended by (EU) No 1028/2014 of 26 September 2014.

4.11.7 When Mod 160139 “Passenger information signs and placards” is installed CS 25-791 is at Amdt 20.

4.11.8 When mod 167557 “Define Modified Airspace Lavatory A Option for 25.795 Compliance” is installed, CS 25.795(a)(1), 25.795(a)(2) and §25.795(c)(3)(ii) are at Amdt 22 (ESF D-31).

4.11.9 When equipped with modification 161765 on A319-151N/-153N/171N, paragraphs JAR AWO 140 and 183 at change 2.

4.11.10 For A319 corporate Jet, JAR 25.561(c) is at change 14 (EtC A-4008)

4.11.11 For A/C configuration with ELT-DT equipment MOD 166219: CS ACNS is at Issue 3 Subpart E Section 3.

4.11.12 From 14 December 2023, CS-FCD is at issue 2 for CS FCD.300, CS FCD.310, CS FCD.400, CS FCD.410, CS FCD.415.

5. Special Conditions

5.1 The following A320 Special conditions, Experience Related Conditions and Harmonization Conditions which are kept for the A319:

Reminder: Within the scope of the establishment of the A320 Joint Certification Basis, three types of special conditions were developed:

- Special conditions: rose to cover novel or unusual features not addressed by the JAR.
- Experience related conditions: rose to record an agreed text for the A320 Joint Certification Basis when evolution of JAR was in progress under the NPA procedure.
- Harmonization conditions: to record, for the purpose of the A320 Joint Certification Basis, a common understanding with respect to National variant. This should not be confused with the FAA/JAA harmonised regulations.

Compulsory

(DGAC-F) SC G-17	Operational proving flights
------------------	-----------------------------



SECTION 3: A319 SERIES

(CAA-UK) SC G-17	Operational flight before certification
SC F-3	Cockpit control - motion and effect of cockpit control
SC F-4	Static longitudinal stability
SC F-6	Static directional and lateral stability
SC F-7	Flight envelope protection
SC F-8	Normal load factor limiting
SC F-9	Dual control system
SC A-2.2.2	Design manoeuvre requirement
SC A-2.2.3	Design dive speed
HC A-4.5	Braked roll conditions
HC A-4.6	Speed control device
SC S-11	Limit pilot forces and torques
HC S-23	Standby gyroscopic horizon
HC S-24	VMO/MMO Warning (setting)
EC S-30	Autoflight system
SC S-33	Autothrust system
SC S-52	Operation without normal electrical power
EC S-54	Circuit protective devices
HC S-72	Flight recorder
SC S-74	Abnormal attitudes
SC S-75	Lightning protection indirect effects
SC S-76	Effect of external radiations up on aircraft systems
SC S-77	Integrity of control signal

5.2 The following Special Conditions developed for the A319:

SC A-2	Stalling Speeds for Structural Design
SC F-1	Stalling and Scheduled Operating Speeds
SC F-11	Accelerate-Stop distances and related performances, worn brakes
SC S-79	Brakes requirements, qualification and testing

5.3 For A319, Airbus Industrie has elected to comply with the following A321 Special Conditions:

SC A-1	Interaction of Systems and Structure
SC P-1	FADEC
SC E-1	Resistance to Fire Terminology

5.4 For any new application (new or modified aeroplane system and associated components) after July 10, 1998, SC S-76 (Effect of external radiations upon aircraft systems) are superseded by SC S-76-1.



SECTION 3: A319 SERIES

5.5 For A319 weight variant 002 and for any further variant certification after Aug. 10, 1998, the HC-A.4.5 (Braked roll conditions) is superseded by JAR 25.493(d) at Change 14 (EtC A-7).

5.6 For A319-115 and -133 models, the following JAR 25 paragraphs and Special Conditions are upgraded at Change 14 and Orange Paper 96/1:

- 25.119(a)
- 25.121(d)/SC F-1 Appendix 3
- 25.145(b)(c)
- 25.149(f)(g)(h)(i) and associated ACJ

This is introduced as Special Condition applicable to the "Third Rating", with a wording as close as possible to those paragraphs of the NPA 25B-261 involving the Go-around rating (SC F-8).

5.7 The following special conditions have been developed post Type Certification:

SC H-01	Enhanced Airworthiness Programme for Aeroplane Systems - ICA on EWIS (applicable from May 2010)
SC D-0306	Heat release and smoke density requirements to seat material (applicable from June 2010)
SC P-27	Flammability Reduction System If fitted, the centre fuel tank of aircraft which have made their first flight after 1st of January 2012 must be equipped in production with a fuel tank Flammability Reduction System (modification 38062). This system shall remain installed and operative and can only be dispatched inoperative in accordance with the provisions of the MMEL revision associated with modification 38062. If modification 38062 (Fuel Tank Inerting System (FTIS)) is embodied on A318, A319, A320, or A321 airplanes, the airplane is compliant with paragraph FR Section 25.981(a) & (b) at amendment 25-102, Part 25 appendix M & N at amendment 25-125, and Section 26.33 at amendment 26-3.
SC E-48	Fuel Tank Safety (applicable from October 2013)
SC F-0311-001	Flight Recorders including Data Link Recording (applicable as per operational regulations)
F-GEN-01	Installation of non-rechargeable lithium battery (applicable from March 2019)

5.8 Special Conditions for aircraft equipped with MOD 160500 & 160080

SC F-16	Static directional and lateral stability
A318 SC F-5001	Stalling and scheduled operating speeds
A318 SC F-5004	Static Longitudinal Stability and Low energy awareness
A318 SC A-5003*	Design Dive Speed Vd



SECTION 3: A319 SERIES

*From 07th December 2018 SC B-14 is replacing SC A-5003

Note: All other original Special Conditions applicable to each model remain effective.

5.9 Special Conditions for A319-151N/-153N/-171N/-173N

B-01	Stalling and Scheduled Operating Speeds
B-03	Motion and effect of cockpit control
B-04	Static Directional, Lateral and Longitudinal Stability and Low energy awareness
B-07	Flight Envelope Protection
B-08	Normal Load Factor limiting System
E-37	Water/Ice in Fuel System
E-45	Engine Cowl Retention
F-13	Fuel System Low Level Indication - Fuel Exhaustion
E-55*	Fan Blade Loss

*Only applicable to CFM models

5.9.1 The following special conditions developed for previous models are also applicable to the A319-151N/-153N/-171N/-173N affected areas:

A2.2.2	Design Manoeuvre requirement
SC A1	Interaction of systems and structure
SC A2	Stalling Speeds for structural design
B-14	Design dive speed Vd
D-0332-001	Towbarless Towing
E-48	Fuel Tank Safety
SC F-11	Accelerate-stop distances and relates performances, worn brakes
SC F-9	Dual Control System
H-01	Enhanced Airworthiness Programme for Aeroplane Systems - ICA on EWIS
P-27	Flammability Reduction System (consisting of Cooled Serviced Air System and Inert Gas Generation System)
S-11	Limit Pilot forces and torques
S-30	Automatic Flight/Flight Management Functions
S-33	Autothrust system
S-72 (HC S-72)	Flight recorders
SC S-76-1	Protection from the effect of HIRF
SC S-75	Lightning protection indirect effects
SC S-79	Brake requirements, qualification and testing (A321)

5.10 Additional Special Conditions part of the Certification Basis (added post TC):
The following Special Conditions are additionally applicable when an A/C configuration include the subject design change(s):



SECTION 3: A319 SERIES

D-08	Installation of Personal Electronic Device charging stowage for cabin crew use
D-15	Pilot Control Mode TaxiBot Operations
D-19	Incorporation of Inertia Locking Device in Dynamic Seats
D-24	Installation of Airbags in the backrest of seats
D-25	Installation of structure mounted airbag
D-27	Installation of Three Point Restraint & Pretensioner System
D-28	Installation of oblique seats
D-0322-001	Installation of suite type seating
D-0332-001	Towbarless Towing
E-10	High altitude airport operations (up to 14,100 ft)"
E-13	Installation of inflatable restraints
E-21	Flight Instrument External Probes – Qualification in Icing Conditions New UTAS Pitot Probes
E-34	Seat with inflatable restraints
F-119	Security Protection of Aircraft Systems and Networks
D-33	Cabin attendant seat mounted on movable part of an interior monument
F-MULTI-04	Rechargeable Lithium Battery Installations
F-37	ATN over SATCOM

6. Exemptions/Deviations**Optional**

ACNS-B-GEN-01 Deviation to CS-ACNS Initial Issue Subpart B, Section 2 (See Note in §II-4.11.6)

7. Equivalent Safety Findings**Compulsory****7.1 Equivalent Safety findings to the following requirements are granted:**

JAR 25-783(f)	ESF SM-4004	"Passenger doors"; The same Equivalent Safety finding was previously granted for A320 and A321).
JAR 25-807(c)(1)	ESF E-4001	"Exit configuration" issued on the basis of the JAA policy dated December 1995).
JAR 25-813(c)(1)	ESF E-4105	"Type III over wing emergency exit access", issued on the basis of A320 E-2105 issue 3).
JAR 25-933(a)(1)	ESF P-4008	"Thrust Reverser Auto restow", issued on the basis of A320 ESF P-1002).
JAR AWO 313	ESF SE-4005	"Minimum approach break-off height".



SECTION 3: A319 SERIES

7.2 The following Equivalent Safety Findings have been developed post Type Certification:

FAR 25.856(b)	E-32 E-28	Fuselage burnthrough protection in bilge area, see note below If modifications 150700, and 37270 (with CLS option only), 37048 and 36985 are embodied in production on A318, A319, A320, or A321 airplanes, the airplane is compliant with Fuselage Flame Penetration "Burnthrough" requirements addressed by paragraph 14 CFR Part 25.856(b) Amdt 25-111 (applicable as per operational regulations)
14CFR Part 25.856(a)	ESF E-18	Improved flammability standards for insulation materials (applicable as per operational regulations)

Note: The original ESFs applicable to each model remain effective.

7.3 Equivalent Safety Findings for aircraft equipped with MOD 160500 & 160080

25.1419(c)	ESF F-19	Flight in natural icing condition
------------	----------	-----------------------------------

7.4 Equivalent Safety Findings for aircraft equipped with MOD 157777, 159533 or 159535

CS25.807(g)	D-03	Over-performing Type I exit
-------------	------	-----------------------------

7.5 The following Equivalent Safety Findings have been developed for the A319-151N/-153N/-171N/-173N:

CS25.934, CS-E 890	E-43	Thrust Reverser Testing
CS25.1549(a)	E-51	Oil temperature indication
CS25.1181, CS25.1182	E-52	Nacelle area adjacent to fire
CS25.997(d)	E-49*	Fuel Filter Location
CS25.1181(a)	E-44**	Fan Zone as non fire zone

*Applicable to CFM models only

**Applicable to IAE models only

7.6 Additional ESF part of the Certification Basis (added post TC):

The following ESF are additionally applicable when an A/C configuration include the subject design change(s):

CS 25.251(b)	B-17	Vibration/buffeting compliance criteria for large external antenna installation applicable from February 2021.
JAR 25.785(c)	D-0329-001	Forward facing seats with more than 18° to aircraft centreline.
CS 25.795(a)(1)	D-31	Application of reduced Intrusion Loads in certain areas of the flight deck boundaries



SECTION 3: A319 SERIES

JAR 25.811(f)	E-16	Emergency exit marking reflectance
JAR 25.812(b)(1)(ii)	E-14	Photo-luminescent EXIT sign for MCD (Moveable Class Divider)
JAR 25.812(b)(1)(i)(ii)	SE-42	Symbolic EXIT signs as an alternative to red EXIT signs for passenger aircraft
JAR 25.1441(c)	F-21	Crew Determination of Quantity of Oxygen in Passenger Oxygen System
JAR 25.1443(c)	F-20	Minimum Mass Flow of Supplemental Oxygen (optional)
CS FCD.425(g)	FCD-MULTI-01	CS-FCD T3 Evaluation Process
CS 25.811(e)(4)	SE-63	Green Arrow and "Open" placard for Emergency Exit Marking
JAR 25.1441(c)	F-122	Crew Determination of Quantity of Oxygen in Passenger Oxygen System

8. Environmental Protection

ICAO Annex 16:

Vol. I, Part II	Noise Requirements
Vol. II, Part II	Fuel Venting
Vol. II, Part III Chapter 2	Emissions

Note: Further details are defined within TCDSN EASA.A.064

III. Technical Characteristics and Operational Limitations**1. Type Design Definition**

- 1.1 Certificated model: A319-111
Definition of reference airplane by doc: AI/EA-S 413.0700/96 (00J000A0011/C21).
- 1.2 Certificated model: A319-112
Definition of reference airplane by doc: AI/EA-S 413.0505/96 (00J000A0003/C21).
- 1.3 Certificated model: A319-113
Definition of reference airplane by doc: AI/EA-S 413.1377/96 (00J000A0113/C21).
- 1.4 Certificated model: A319-114
Definition of reference airplane by doc: AI/EA-S 413.1400/96 (00J000A0114/C21).
- 1.5 Certificated model: A319-115
Definition of reference airplane by doc: AI/EA-S 413.1204/99 (00J000A0115/C21).
- 1.6 Certificated model: A319-131
Definition of reference airplane by doc: AI/EA-S 413.3250/96 (00J000A0131/C21).
- 1.7 Certificated model: A319-132
Definition of reference airplane by doc: AI/EA-S 413.3300/96 (00J000A0132/C21).
- 1.8 Certificated model: A319-133
Definition of reference airplane by doc: AI/EA-S 413.1205/99 (00J000A0133/C21).
- 1.9 Certificated model: A319-151N



SECTION 3: A319 SERIES

- 2.0 Definition of reference airplane by doc: 00J000A5025/C20
Certificated model: A319-153N
Definition of reference airplane by doc: 00J000A5240/C00
- 2.1 Certificated model: A319-171N
Definition of reference airplane by doc: 00J000A5022/C20
- 2.2 Certificated model: A319-173N
Definition of reference airplane by doc: 00J000A5288/C00

NOTES**Model conversions:**

- If modification 30149 is embodied on A319-113 model powered with CFM56-5A4 engines, it is converted into A319-114 model, powered with CFM56-5A5 engines.
- If modification 34281 is embodied on A319-111 model powered with CFM56-5B5/P engines, it is converted into A319-112 model, powered with CFM56-5B6/P engines.
- If modification 34815 is embodied on A319-132 model powered with V2524-A5 engines, it is converted into A319-133 model, powered with V2527M-A5 engines.
- If modification 156502 is embodied on A319-111 model powered with CFM56-5B5/3 engines, it is converted into A319-112 model, powered with CFM56-5B6/3 engines.
- If modification 155359 is embodied on A319-131 model powered with V2522-A5 engines, it is converted into A319-132 model, powered with V2524-A5 engines.
- If modification 39029 is embodied on A319-112 model powered with CFM56-5B6/3 engines, it is converted into A319-115 model, powered with CFM56-5B7/3 engines
- If modification 39122 is embodied on A319-115 model powered with CFM56-5B7/3 engines, it is converted into A319-112 model, powered with CFM56-5B6/3 engines
- If modification 152186 is embodied on A319-115 model powered with CFM56-5B7/P or /3 engines, it is converted into A319-111 model, powered with CFM56-5B5/P or /3 engines
- If modification 153779 is embodied on A319-111 model powered with CFM56-5B5/3 or /P engines, it is converted into A319-115 model, powered with CFM56-5B7/3 or /P engines
- If modification 39236 is embodied on A319-112 model powered with CFM56-5B6/3 or /P engines, it is converted into A319-111 model, powered with CFM56-5B5/3 or /P engines

2. Description

Twin turbo-fan, short to medium range, single aisle, transport category airplane.

3. Equipment**A319-111**

Equipment approved for installation is listed in the Certification Standard Equipment List ref. 00J000A0012/COS at latest approved issue.

A319-112

Equipment approved for installation is listed in the Certification Standard Equipment List ref. 00J000A0004/COS at latest approved issue.

A319-113

SECTION 3: A319 SERIES

Equipment approved for installation is listed in the Certification Standard Equipment List ref. 00J000A0113/COS at latest approved issue.

A319-114

Equipment approved for installation is listed in the Certification Standard Equipment List ref. 00J000A0114/COS at latest approved issue.

A319-115

Equipment approved for installation is listed in the Certification Standard Equipment List ref. 00J000A0115/COS at latest approved issue.

A319-131

Equipment approved for installation is listed in the Certification Standard Equipment List ref. 00J000A0131/COS at latest approved issue.

A319-132

Equipment approved for installation is listed in the Certification Standard Equipment List ref. 00J000A0132/COS at latest approved issue.

A319-133

Equipment approved for installation is listed in the Certification Standard Equipment List ref. 00J000A0133/COS at latest approved issue.

Certification Standard Equipment List is not applicable to the A319-151N/-153N/-171N/-173N.

Note

The type design definitions and certification standard equipment lists are complemented by doc. 00D000A0546/COS "A319-100/A321-200 FMGC Type Std Evolution" and doc. 00J000A0067/COS "A319-111/112 ATC Transponder Type Std Evolution".

Cabin furnishings, equipment and arrangement shall be in conformance to the following specifications:

Cabin seats	2521M1F10000 at latest approved issue plus technical note J2521RP1719259
Galleys	2530M1F000900 at latest approved issue

4. Dimensions

Principal dimensions of A319 Aircraft:

Length:	33.84 m
Width:	34.10 m
(if MOD 160500 is installed)	35.80 m
Height:	11.76 m
Width at horizontal stabilizer:	12.45 m
Outside fuselage diameter:	3.95 m
Distance between engine axes:	11.51 m
Distance between main landing gear:	7.59 m
Distance between nose and main landing gear:	11.04 m

5. Engines

The list below lists the basic engines fitted on the aircraft models. The notes describe usual names and



SECTION 3: A319 SERIES

certified names as well as new engines variants.

A319-111

Two CFMI CFM 56-5B5 jet engines (MOD 24932)

A319-112

Two CFMI CFM 56-5B6 jet engines (MOD 25287), or
CFM 56-5B6/2 jet engines (MOD 25530)

A319-113

Two CFMI CFM 56-5A4 jet engines (MOD 25238), or
CFM 56-5A4/F jet engines (MOD 23755)

A319-114

Two CFMI CFM 56-5A5 jet engines (MOD 25286), or
CFM 56-5A5/F jet engines (MOD 23755)

A319-115

Two CFMI CFM 56-5B7 jet engines (MOD 27567)

A319-131

Two IAE V2522-A5 jet engines (MOD 26152)

A319-132

Two IAE V2524-A5 jet engines (MOD 26298)

A319-133

Two IAE V2527M-A5 jet engines (MOD 27568)

A319-151N

Two CFMI LEAP-1A24 jet engines (MOD 161004)

A319-153N

Two CFMI LEAP-1A26 jet engines (MOD 165511), or
LEAP-1A26E1 jet engines (MOD 166794)

ACJ319 NEO

Two CFMI LEAP-1A26CJ jet engines (MOD 165333)

A319-171N

Two IAE PW1124G-JM Geared Turbo Fan jet engines (MOD 161001)

A19-173N

Two IAE PW1127G1-JM Geared Turbo Fan jet engines (MOD 169981)



SECTION 3: A319 SERIES**Notes:**

1. From March 31st, 2008, there is no longer any CFM56-5B5 non /P in field or in production.
2. From March 31st, 2008, there is no longer any CFM56-5B6 non /P in field or in production.
3. From March 31st, 2008, there is no longer any CFM56-5B6/2 non /P in field or in production.
4. From March 31st, 2008, there is no longer any CFM56-5B7 non /P in field or in production.
5. If modification 25800 is embodied on models with CFM-5B engines, the engine performance is improved. The engine denomination changes to /P. The modification is currently applicable for:

A319-111: CFM 56-5B5 (SAC) which changes to CFM 56-5B5/P

A319-112: CFM 56-5B6 (SAC) which changes to CFM 56-5B6/P

A319-112: CFM 56-5B6/2 (DAC) which changes to CFM 56-5B6/2P

A319-115: CFM 56-5B7 (SAC) which changes to CFM 56-5B7/P

CFM 56-5B/"non-P" engine can be intermixed with CFM 56-5B/P engine on the same aircraft.

6. A319-112 CFM 56-5B6 engine can be intermixed with CFM 56-5B6/2 engine (MOD 25532) on the same aircraft (AFM supplement).
7. If modification 26610 is embodied on models with CFM-5B/2 (DAC) engines, the engine performance and gaseous emission levels are improved.

A319-112: CFM 56-5B6/2 (DAC) which changes to CFM 56-5B6/2P (DAC II C)

CFM 56-5B/2 "non P" (DAC) engine can be intermixed with CFM 56-5B/2P (DAC II C) engine on the same aircraft (AFM supplement).

CFM 56-5B/P or / "non P" (SAC) engine can be intermixed with CFM 56-5B/2P (DAC II C) engine on the same aircraft (AFM supplement).

Modification 26610 is not compatible with modification 160080 (sharklet retrofit).

8. Introduction of CFM56-5Bx/3 "Tech Insertion" engine is done through embodiment of modification 37147 in production or 38770 in field.

This modification is only applicable on CFM56-5Bx /P SAC engines.

If modification 37147 is embodied on models with CFM-5B engines, the engine denomination changes to /3.

The modification is currently applicable for:

A319-111: CFM 56-5B5 (SAC) which changes to CFM 56-5B5/3



SECTION 3: A319 SERIES

A319-112: CFM 56-5B6 (SAC) which changes to CFM 56-5B6/3
A319-115: CFM 56-5B7 (SAC) which changes to CFM 56-5B7/3

Modification 37147 has been demonstrated as having no impact on previously certified noise levels.

The engine characteristics remain unchanged.

CFM56-5Bx/3 engine can be intermixed with CFM56-5Bx/P engine under considerations as prescribes in modification 38573.

9. CFM56-5B engines are not compatible with modification 160080 (Sharklet retrofit) unless modification 37147 or modification 38770 are installed.

10. If modification 165333 is installed on the A319-153N equipped with CFM LEAP-1A26 engines, then the engine model is changed to LEAP-1A26CJ".

6. Auxiliary Power Unit

APU GARRETT

The APU GARRETT AIRESEARCH GTCP 36-300 (A) installation is defined by mod 20020.

(Specification 31-5306B)

Approved oils: see GARRETT REPORT GT.7800

APU Pratt & Whitney Rzeszow S.A. (Option)

The APU Pratt & Whitney Rzeszow S.A. installation is defined by MOD 22562 or MOD 35864.

Pratt & Whitney Rzeszow S.A. APS 3200 (Specification ESR 0802, Rev. A).

Approved oils: in conformance to MIL-L-7808, MIL-L-23699 or DERD 2487.

APU AlliedSignal (Option)

The APU Honeywell International installation is defined by MOD 25888 or 37987.

Honeywell International 131-9[A] (Specification 4900 M1E 03 19 01).

Approved oils: according to model Specification 31-12048A-3A.

7. Propellers

N/A.

8. Fluids (Fuel, Oil, Additives, Hydraulics)

Fuel

ENGINES	KEROSENE DESIGNATION
---------	----------------------



SECTION 3: A319 SERIES

CFM56: Installation document CFM 2026 or CFM 2129)	JET A, JET A-1, JP5, JP8, N°3 Jet Fuel, JET B**, JP 4**, TS-1, RT(GOST), F44, F34, AVTUR, AVTUR/FSII, AVTAG/FSII, AVCAT/FSII
IAE V2500: IAE Standard Practices and processes Manual IAE 0043	JET A, JET A-1, JP5, JP8, N°3 Jet Fuel, JET B**, JP 4**, TS-1*, RT(GOST), F44, F34, AVTUR, AVTUR/FSII, AVTAG/FSII, AVCAT/FSII
IAE PW1100G-JM: (Service Bulletin PW1000G -100-73 00-0002-00A930AD)	JET A, JET A-1, JP5, JP8, N°3 Jet fuel, TS-1(GOST), RT(GOST), AVTUR, AVTUR/FSII, AVCAT/FSII
CFMI LEAP-1A: Service Bulletin LEAP-1A S/B 73-0001	JET A, JET A-1, JP5, JP8, N°3 Jet fuel, TS-1(GOST), RT(GOST), AVTUR, AVTUR/FSII, AVCAT/FSII

The above-mentioned fuels are also suitable for the APU.

Refer to Consumable Material List (CML) for details on approved fuel specifications

* For IAE engines, TS-1 is cleared for transient use (less than 50% of operations)

** JET B and JP 4 fuels are not authorized for use in aircraft fitted with jet pumps (modification 154327)



SECTION 3: A319 SERIES**OIL**

For oil specification:

Engine	CFM56-5B5 CFM56-5B6 CFM56-5B6/2 CFM56-5B7 CFM56-5A4 CFM56-5A4/F CFM56-5A5 CFM56-5A5/F	IAE V2522-A5 IAE V2524-A5 IAE V2527M-A5	CFMI-LEAP-1A24 CFMI-LEAP-1A26	PW1124G1-JM PW1127G1-JM
Approved Oils	SB CFMI 79-001-OX	See doc IAE 0043 Sect 4.9 (MIL-L-23699)	Service Bulletin LEAP-1A S/B 73-0001	Service Bulletin PW1000G – 1000 – 79 – 00 – 0002 - 00A - 930A – D

Additives

Refer to Airbus Consumable Material List (CML).

Hydraulics

Hydraulic fluids: Type IV or Type V - Specification NSA 30.7110.

9. Fluid Capacities

Fuel quantity (0.8 kg/litre)**A319-111/-112/-113/-114/-115/-131/-132/-133 aircraft (without MOD 160001)**

Tank	3 TANK AIRPLANE		4 or 5 TANK AIRPLANE*		4 or 5 TANK AIRPLANE**	
	Usable fuel litres (kg)	Unusable fuel litres (kg)	Usable fuel litres (kg)	Unusable fuel litres (kg)	Usable fuel litres (kg)	Unusable fuel litres (kg)
Wing	15 609 (12 487)	58.9 (47.1)	15 609 (12 487)	58.9 (47.1)	15 609 (12 487)	58.9 (47.1)
Centre	8 250 (6 600)	23.2 (18.6)	8 250 (6 600)	23.2 (18.6)	8 250 (6 600)	23.2 (18.6)
ACT			3 121 / 6 242 (2 497 / 4 994)	17 / 34 (13.6 / 27.2)	2 992 / 5 984 (2 393 / 4 786)	17 / 34 (13.6 / 27.2)
TOTAL	23 859 (19 087)	82.1 (65.7)	26 980 / 30 101 (21 584 / 24 081)	99.1 / 116.1 (79.3 / 92.9)	26 851 / 29 843 (21 480 / 23 873)	99.1 / 116.1 (79.3 / 92.9)

* see note 1 below

** see note 2 below

Tank	6 or 7 TANK AIRPLANE*		8 or 9 TANK AIRPLANE*	
	Usable fuel litres (kg)	Unusable fuel Litres (kg)	Usable fuel litres (kg)	Unusable fuel litres (kg)



SECTION 3: A319 SERIES

Wing	15 609 (12 487)	58.9 (47.1)	15 609 (12 487)	58.9 (47.1)
Centre	8 250 (6 600)	23.2 (18.6)	8 250 (6 600)	23.2 (18.6)
ACT	8 428 / 10 614 (6 743 / 8 492)	56 / 78 (44.8 / 62.4)	12 660 / 16 781 13 (10 929 / 13 426)	90 / 107 (72 / 85.6)
TOTAL	32 287 / 34 473 (25 830 / 27 579)	138.1 / 160.1 (110.5 / 128.1)	37 519 / 40 640 (30 016 / 32 513)	172.1 / 189.1 (137.7 / 151.3)

* see note 1 below

A319-111/-112/-113/-114/-115/-131/-132/-133 aircraft (without MOD 160001 and with MOD 37331)

Tank	3 TANK AIRPLANE		4 or 5 TANK AIRPLANE*		4 or 5 TANK AIRPLANE**	
	Usable fuel litres (kg)	Unusable fuel litres (kg)	Usable fuel litres (kg)	Unusable fuel litres (kg)	Usable fuel litres (kg)	Unusable fuel litres (kg)
Wing	15 959 (12 767)	58.9 (47.1)	15 959 (12 767)	58.9 (47.1)	15 959 (12 767)	58.9 (47.1)
Centre	8 250 (6 600)	23.2 (18.6)	8 250 (6 600)	23.2 (18.6)	8 250 (6 600)	23.2 (18.6)
ACT			3 121 / 6 242 (2 497 / 4 994)	17 / 34 (13.6 / 27.2)	2 992 / 5 984 (2 393 / 4 786)	17 / 34 (13.6 / 27.2)
TOTAL	24 209 (19 367)	82.1 (65.7)	27 330 / 30 451 (21 864 / 24 361)	99.1 / 116.1 (79.3 / 92.9)	27 201 / 30 193 (21 760 / 24 154)	99.1 / 116.1 (79.3 / 92.9)

* see note 1 below

** see note 2 below

Tank	6 or 7 TANK AIRPLANE*		8 or 9 TANK AIRPLANE*	
	Usable fuel litres (kg)	Unusable fuel Litres (kg)	Usable fuel litres (kg)	Unusable fuel litres (kg)
Wing	15 959 (12 767)	58.9 (47.1)	15 959 (12 767)	58.9 (47.1)
Centre	8 250 (6 600)	23.2 (18.6)	8 250 (6 600)	23.2 (18.6)
ACT	8 428 / 10 614 (6 743 / 8 492)	56 / 78 (44.8 / 62.4)	13 660 / 16 781 (10 929 / 13 426)	90 / 107 (72 / 85.6)
TOTAL	32 637 / 34 823 (26 110 / 27 859)	138.1 / 160.1 (110.5 / 128.1)	37 869 / 40 990 (30 296 / 32 793)	172.1 / 189.1 (137.7 / 151.3)

* see note 1 below



SECTION 3: A319 SERIES**A319-111/-112/-113/-114/-115/-131/-132/-133 aircraft (with MOD 37331 and MOD 160001)**

TANK	3 TANK AIRPLANE		4 TANK AIRPLANE		4 or 5 TANK AIRPLANE *	
	Usable fuel litres (kg)	Unusable fuel litres (kg)	Usable fuel litres (kg)	Unusable fuel litres (kg)	Usable fuel litres (kg)	Unusable fuel litres (kg)
WING	15 919 (12 735)	58.9 (47.1)	15 919 (12 735)	58.9 (47.1)	15 919 (12 735)	58.9 (47.1)
CENTRE	8 248 (6 598)	23.2 (18.6)	8 248 (6 598)	23.2 (18.6)	8 248 (6 598)	23.2 (18.6)
ACT (*)			2992 (2 393)	17 (13.6)	2 992 / 5 984 (2 393 / 4 786)	17 / 34 (13.6 / 27.2)
TOTAL	24 167 (19 334)	82.1 (65.7)	27 159 (21 727)	99.1 (79.3)	27 159 / 30 151 (21 727 / 24 121)	99.1 / 116.1 (79.3 / 92.9)

(*) On the A319 aircraft, the certification of installing one or two Additional Centre Tanks (ACT) in bulk version is defined by modification 33973.

An alternative is the installation of one ACT only (with the provisions for only one ACT), as defined by modification 37226.

Tank	6 or 7 TANK AIRPLANE*		8 or 9 TANK AIRPLANE*	
	Usable fuel litres (kg)	Unusable fuel Litres (kg)	Usable fuel litres (kg)	Unusable fuel litres (kg)
Wing	15 919 (12 735)	58.9 (47.1)	15 919 (12 735)	58.9 (47.1)
Centre	15 919 (12 735)	58.9 (47.1)	15 919 (12 735)	58.9 (47.1)
ACT	8 428 / 10 614 (6 743 / 8 492)	56 / 78 (44.8 / 62.4)	660 / 16 781 (10 929 / 13 426)	90 / 107 (72 / 85.6)
TOTAL	32 595 / 34 781 (26 076 / 27 825)	138.1 / 160.1 (110.5 / 128.1)	37 827 / 40 948 (30 262 / 32 759)	172.1 / 189.1 (137.7 / 151.3)

* see note 1 below



SECTION 3: A319 SERIES**A319-111/-112/-113/-114/-115/-131/-132/-133 aircraft (without MOD 37331 and with MOD 160001)**

TANK	3 TANK AIRPLANE		4 TANK AIRPLANE		4 or 5 TANK AIRPLANE *	
	Usable fuel litres (kg)	Unusable fuel litres (kg)	Usable fuel litres (kg)	Unusable fuel litres (kg)	Usable fuel litres (kg)	Unusable fuel litres (kg)
WING	15 569 (12 455)	58.9 (47.1)	15 569 (12 455)	58.9 (47.1)	15 569 (12 455)	58.9 (47.1)
CENTRE	8 248 (6 598)	23.2 (18.6)	8 248 (6 598)	23.2 (18.6)	8 248 (6 598)	23.2 (18.6)
ACT (*)			2992 (2 393)	17 (13.6)	2 992 / 5 984 (2 393 / 4 786)	17 / 34 (13.6 / 27.2)
TOTAL	23 817 (19 054)	82.1 (65.7)	26 809 (21 447)	99.1 (79.3)	26 809 / 29 801 (21 447 / 23 841)	99.1 / 116.1 (79.3 / 92.9)

(*) On the A319 aircraft, the certification of installing one or two Additional Centre Tanks (ACT) in bulk version is defined by modification 33973.

An alternative is the installation of one ACT only (with the provisions for only one ACT), as defined by modification 37226.

Tank	6 or 7 TANK AIRPLANE*		8 or 9 TANK AIRPLANE*	
	Usable fuel litres (kg)	Unusable fuel Litres (kg)	Usable fuel litres (kg)	Unusable fuel litres (kg)
Wing	15 569 (12 455)	58.9 (47.1)	15 569 (12 455)	58.9 (47.1)
Centre	8 248 (6 598)	23.2 (18.6)	8 248 (6 598)	23.2 (18.6)
ACT	8 428 / 10 614 (6 743 / 8 492)	56 / 78 (44.8 / 62.4)	13 660 / 16 781 (10 929 / 13 426)	90 / 107 (72 / 85.6)
TOTAL	32 245 / 34 431 (25 796 / 27 545)	138.1 / 160.1 (110.5 / 128.1)	37 477 / 40 598 (29 982 / 32 479)	172.1 / 189.1 (137.7 / 151.3)

* see note 1 below



SECTION 3: A319 SERIES**A319-151N/-153N/-171N/-173N**

TANK	3 TANK AIRPLANE	
	Usable fuel litres (kg)	Unusable fuel litres (kg)
WING	15476.7 (12427.8)	58.9 (47.3)
CENTRE	8248.0 (6623.1)	23.2 (18.6)
TOTAL	23724.7 (19050.9)	82.1 (65.9)

A319-153N equipped with modification 163214 (ACJ319 NEO)

TANK	3 TANK AIRPLANE		4 TANK AIRPLANE		5 TANK AIRPLANE	
	Usable fuel litres (kg)	Unusable fuel litres (kg)	Usable fuel litres (kg)	Unusable fuel litres (kg)	Usable fuel litres (kg)	Unusable fuel litres (kg)
WING	15476.7 (12427.8)	58.9 (47.3)	15476.7 (12427.8)	58.9 (47.3)	15476.7 (12427.8)	58.9 (47.3)
CENTRE	8248.0 (6623.1)	23.2 (18.6)	8248.0 (6623.1)	23.2 (18.6)	8248.0 (6623.1)	23.2 (18.6)
FWD						
AFT 1			3121 (2506.2)	17 (13.6)	3121 (2506.2)	17 (13.6)
AFT 2					2186 (1755.4)	22 (17.7)
AFT 3						
AFT 4						
TOTAL	23724.7 (19050.9)	82.1 (65.9)	26845.7 (21557.1)	99.1 (79.6)	29031.7 (23312.5)	121.1 (97.2)



SECTION 3: A319 SERIES

TANK	6 TANK AIRPLANE Fuel Sequence A		6 TANK AIRPLANE Fuel Sequence B		6 TANK AIRPLANE Fuel Sequence C	
	Usable fuel litres (kg)	Unusable fuel litres (kg)	Usable fuel litres (kg)	Unusable fuel litres (kg)	Usable fuel litres (kg)	Unusable fuel litres (kg)
WING	15476.7 (12427.8)	58.9 (47.3)	15476.7 (12427.8)	58.9 (47.3)	15476.7 (12427.8)	58.9 (47.3)
CENTRE	8248.0 (6623.1)	23.2 (18.6)	8248.0 (6623.1)	23.2 (18.6)	8248.0 (6623.1)	23.2 (18.6)
FWD			3121 (2506.2)	17 (13.6)		
AFT 1	3121 (2506.2)	17 (13.6)	3121 (2506.2)	17 (13.6)	3121 (2506.2)	17 (13.6)
AFT 2	2186 (1755.4)	22 (17.7)	2186 (1755.4)	22 (17.7)	2186 (1755.4)	22 (17.7)
AFT 3	2186 (1755.4)	22 (17.7)				
AFT 4					3046 (2445.9)	12 (9.6)
TOTAL	31217.7 (25067.8)	143.1 (114.9)	32152.7 (25818.6)	138.1 (110.9)	32077.7 (25758.4)	133.1 (106.9)



SECTION 3: A319 SERIES

TANK	7 TANK AIRPLANE Fuel Sequence A		7 TANK AIRPLANE Fuel Sequence C		8 TANK AIRPLANE	
	Usable fuel litres (kg)	Unusable fuel litres (kg)	Usable fuel litres (kg)	Unusable fuel litres (kg)	Usable fuel litres (kg)	Unusable fuel litres (kg)
WING	15476.7 (12427.8)	58.9 (47.3)	15476.7 (12427.8)	58.9 (47.3)	15476.7 (12427.8)	58.9 (47.3)
CENTRE	8248.0 (6623.1)	23.2 (18.6)	8248.0 (6623.1)	23.2 (18.6)	8248.0 (6623.1)	23.2 (18.6)
FWD	3121 (2506.2)	17 (13.6)	3121 (2506.2)	17 (13.6)	3121 (2506.2)	17 (13.6)
AFT 1	3121 (2506.2)	17 (13.6)	3121 (2506.2)	17 (13.6)	3121 (2506.2)	17 (13.6)
AFT 2	2186 (1755.4)	22 (17.7)	2186 (1755.4)	22 (17.7)	2186 (1755.4)	22 (17.7)
AFT 3	2186 (1755.4)	22 (17.7)			2186 (1755.4)	22 (17.7)
AFT 4			3046 (2445.9)	12 (9.6)	3046 (2445.9)	12 (9.6)
TOTAL	34338.7 (27574)	160.1 (128.6)	35198.7 (28264.6)	150.1 (120.5)	35198.7 (28264.6)	172.1 (138.2)

Notes:

- 1- On A319ceo for Corporate Jet use, the certification of installing up to six Additional Centre Tanks (ACT) in bulk version is defined by modification 28238. The approval together with structural and system provisions is subject of Major Change J1-CJT

A319ceo for Corporate Jet use are defined through the following set of modifications:

- modification 28238: Installation of up to 6 ACTs
- modification 28162: Extension of the flight envelope up to 41000ft
- modification 28342: Extension of the forward C.G.

- 2- The certification of installing one or two Additional Centre Tanks (ACT) in bulk version is defined by modification 33973. The approval together with structural and system provisions is subject of Major Change J-33973.

- 3- On the series A319 equipped with IAE engines, introduction of standard of wingbox with dry bay (modification 37332) will decrease the fuel capacity by 350 litres.



SECTION 3: A319 SERIES

4. A319-153N for Corporate Jet use (commercially identified as ACJ319 NEO) is defined through the following set of modifications:

- Modification 163214: INSTALL UP TO 5 ACTS ON A319 ACJ NEO
- Modification 163216: EXTEND FLIGHT ENVELOPE UP TO 41000 FT
- Modification 162337: EXTEND GROUND AND FLIGHT FORWARD CG LIMITATIONS
- Modification 23398: Install stairs at fwd pax door.
- Modification 162193: Lower Cabin Altitude activation
- Modification 162338: Certify Envelope for design weight of ACJ319 NEO

10. Airspeed Limits (Indicated Airspeed – IAS – unless otherwise stated)

Maximum Operating Mach (MMO):	0.82
Maximum Operating Speed (VMO):	350 kt
Manoeuvring Speed (VA):	see Limitations Section of the EASA approved Flight Manual



SECTION 3: A319 SERIES

Extended Flaps/Slats Speed (VFE):

see table below

Configuration	Slats/Flaps (°)	VFE (kt)	
1	18/0 18/10*	230 215	Intermediate approach Take-off
2	22/15	200	Take-off and approach
3	22/20	185	Take-off, approach, landing
Full	27/40	177	Landing

* Auto flap retraction at 210 kt in Take-off configuration

Landing gear:

VLE - Extended:

280 kt/Mach 0.67

VLO - Extension:

250 kt

Retraction:

220 kt

Tyres limit speed (ground speed):

195.5 kt (225 mph)

11. Flight Envelope

Maximum operating altitude:

39 100 ft (pressure altitude)

41 100 ft (pressure altitude)

if modification 28162 is embodied
(A319-112/-115/-132/-133 only)

39 800 ft (pressure altitude)

if modification 30748 is embodied

41 000 ft (pressure altitude)

if modification 163216 is embodied (A319-
153N (ACJ319 NEO) only)

SECTION 3: A319 SERIES**12. Operating Limitations**

See the appropriate EASA approved Airplane Flight Manual

Powerplant (2.2482 lb/daN)**CFMI Engines**

Engine	CFMI				
	CFM56-5B5	CFM56-5B6 CFM56-5B6/2	CFM56-5B7	CFM56-5A4 CFM56-5A4/F	CFM56-5A5 CFM56-5A5/F
Data sheets	E37NE (FAA) E38NE (FAA) EASA.E.003	E37NE (FAA) E38NE (FAA) EASA.E.003	E37NE (FAA) E38NE (FAA) EASA.E.003	E28NE (FAA) M-15 (DGAC) M-IM19 (DGAC)	E28NE (FAA) M-15 (DGAC) M-IM19 (DGAC)
Static thrust at sea level					
Take-off (5 min)* (Flat rated 30° C)	9 786 daN (22 000 lbs)	10 453 daN (23 500 lbs)	12 010 daN (27 000 lb)	9 786 daN (22 000 lbs)	10 453 daN (23 500 lbs)
Maximum continuous (Flat rated 25° C)	9 008 daN (20 250 lbs)	9 008 daN (20 250 lbs)	10 840 daN (24 370 lb)	9 195 daN (20 670 lbs)	9 195 daN (20 670 lbs)

* 10 minutes at take-off thrust allowed only in case of engine failure (at take-off or during go-around) in accordance with DGAC "Fiche de Caractéristiques Moteur".

Engine	CFM LEAP-1A24	CFM LEAP-1A26
	E00089EN (FAA) EASA.E.110	E00089EN (FAA) EASA.E.110
Static thrust at sea level		
Take-off (5 min)* (Flat rated 30° C)	10 680daN (24 010 lbs)	12 064 daN (27 120 lbs)
Maximum continuous (Flat rated 25° C)	10 676daN (24 000 lbs)	11 868 daN (26 680 lbs)

Other engine limitations: see the relevant Engine Type Certificate Data Sheet.



SECTION 3: A319 SERIES**IAE Engines**

Engine	V2522-A5	V2524-A5	V2527M-A5
Data sheets	E40NE (FAA) EASA.E.069	E40NE (FAA) EASA.E.069	E40NE (FAA) EASA.E.069
Static thrust at sea level			
Take-off (5 min)* (Flat rated 30° C)	10 249 daN (23 040 lb)	10 889 daN (24 480 lb)	11 031 daN (24 800 lb)
Maximum continuous (Flat rated 25° C)	8 540 daN (19 200 lb)	8 540 daN (19 200 lb)	9 893 daN (22 240 lb)

* 10 minutes at take-off thrust allowed only in case of engine failure (at take-off or during go-around) in accordance with DGAC "Fiche de Caractéristiques Moteur".

Engine	PW1124G1-JM	PW1127G1-JM
Data sheets	E87EN (FAA) EASA.IM.E.093	E87EN (FAA) EASA.IM.E.093
Static thrust at sea level		
Take-off (5 min)* (Flat rated 30° C)	10 782 daN (24 240 lbs)	12 043 daN (27 075 lbs)
Maximum continuous (Flat rated 25° C)	10 691 daN (24 035 lbs)	11 718 daN (26 345 lbs)

Other engine limitations: see the relevant Engine Type Certificate Data Sheet.

Note:

A319-113/-114 (CFM 56-5A4/F or -5A5/F engines):

- The maximum permissible gas temperature at take-off and max. continuous is extended to 915° C and 880° C respectively. However, the ECAM indication remains at 890° C and 855° C.
- CFM 56-5A4 engines can be intermixed with CFM 56-5A4/F engine (MOD 23755) on the same aircraft.
- CFM 56-5A5 engines can be intermixed with CFM 56-5A5/F engine (MOD 23755) on the same aircraft.

12.1 Approved Operations

Transport Commercial operations.

12.2 Other Limitations

For a complete list of applicable limitations, see the appropriate EASA approved Airplane Flight Manual.



SECTION 3: A319 SERIES



SECTION 3: A319 SERIES

13. Maximum Certified Masses

A319-111/A319-112/A319-113/A319-114/A319-115/A319-131/A319-132/A319-133

VARIANT	000 BASIC	001 MOD 25328	002 MOD 27112	003 MOD 26457	004 MOD 28053	005 MOD 28136	006 MOD 33418
WEIGHT (Kg)							
Max. Ramp Weight	64 400	70 400	75 900	68 400	68 400	70 400	73 900
Max. Take-off Weight	64 000	70 000	75 500	68 000	68 000	70 000	73 500
Max. Landing Weight	61 000	61 000	62 500	61 000	62 500	62 500	62 500
Max. Zero Fuel Weight	57 000	57 000	58 500	57 000	58 500	58 500	58 500
Minimum Weight	35 400	35 400	35 400	35 400	35 400	35 400	35 400

VARIANT	007 MOD 35197	008 MOD 36291	009 MOD 36292	010 (*) MOD 39021	011 MOD 36933	012 MOD 36934	013 (**) MOD 153453
WEIGHT (Kg)							
Max. Ramp Weight	75 900	64 400	66 400	76 900	66 400	62 400	75 900
Max. Take-off Weight	75 500	64 000	66 000	76 500	66 000	62 000	75 500
Max. Landing Weight	61 000	62 500	62 500	62 500	61 000	61 000	62 500
Max. Zero Fuel Weight	57 000	58 500	58 500	58 500	57 000	57 000	52 000
Minimum Weight	35 400	35 400	35 400	35 400	35 400	35 400	35 400

* WV010 is only certified for A319 in Corporate Jet configuration (modifications 28238, 28162 and 28342).

** WV013 is only certified for A319-133, MSN 4042

Note:

1. MOD 160500 and 160080 are approved for WV 00 to WV 12, only
2. For A319-111/-112/-113/-114/-131/-132 models the WV 01 was certified concurrently with the basic WV at the time of the model's approval
3. For the A319-115/-133 models the WV 01 to WV 05 were certified concurrently with the basic WV at the time of the model's approval



SECTION 3: A319 SERIES**A319-151N/-153N/-171N/-173N**

VARIANT	050 MOD 161385	051* MOD 161386	052* MOD 161387	053* MOD 161388	054* MOD 161389	055* MOD 161390
Max. Ramp Weight	64 400	64 400	70 400	70 400	75 900	75 900
Max. Take-off Weight	64 000	64 000	70 000	70 000	75 500	75 500
Max. Landing Weight	62 800	63 900	62 800	63 900	62 800	63 900
Max. Zero Fuel Weight	58 800	60 300	58 800	60 300	58 800	60 300
Minimum Weight	39 600	39 600	39 600	39 600	39 600	39 600

Notes: * WV option certified concurrently with the basic WV at the time of the model's approval

In addition, the following weight variant are also certified for the A319-153N equipped with modifications 163214, 163216, 162337, 23398 and 162193 (ACJ319 NEO specific weight variants)

VARIANT	110* (MOD 160801)	111* (MOD 160802)	112* (MOD 160803)	113* (Mod 160804)	114* (Mod 160805)	115* (Mod 160806)	116* (Mod 160807)
Max. ramp weight	77 700	77 700	77 700	76 900	76 900	76 900	75 900
Max. Take-off Weight	77 300	77 300	77 300	76 500	76 500	76 500	75 500
Max. Landing Weight	63 900	62 800	63 900	63 900	62 800	63 900	63 900
Max. Zero Fuel Weight	60 300	58 800	53 800	60 300	58 800	53 800	53 800

VARIANT	120* (MOD 164385)
Max. ramp weight	78 600
Max. Take-off Weight	78 200
Max. Landing Weight	63 900
Max. Zero Fuel Weight	53 000

Notes: A319-153N weight variants 050, 051, 052 and 053 are excluded from ACJ319 NEO weight variants

* WV option certified concurrently at the time of ACJ319 NEO approval

14. Centre of Gravity Range

See EASA approved Airplane Flight Manual.

15. Datum

Station 0.0, located 2.540 meters forward of airplane nose.

16. Mean Aerodynamic Chord (MAC)

SECTION 3: A319 SERIES

4.1935 meters.

17. Levelling Means

The A/C can be jacked on three primary jacking points.
See the appropriate EASA approved Weight and Balance Manual.

18. Minimum Flight Crew

2 pilots.

19. Minimum Cabin Crew

See paragraph 20.

20. Maximum Seating Capacity

The table below provides the certified Maximum Passenger Seating Capacities (MPSC), the corresponding cabin configuration (exit arrangement and modifications) and the associated minimum numbers of cabin crew members used to demonstrate compliance with the certification requirements:



SECTION 3: A319 SERIES

MPSC	Cabin configuration	Modification	Minimum CC
160	C-III-III-C	32208	4
160	C*-III-C*	159535 or 159533	4
150	C-III-III-C	32208 and 150365	3
150	C*-III-C*	157777	3
145	C-III-C	---	3

Note: C* is the over-performing exit according to modification 157777, 159533 or 159535

The original maximum passenger seating capacity is 145.

The Modification 157777 enables the maximum seating capacity to be increased from 145 up to 150. This modification defines a virtual envelope of the Layout of Passenger Accommodations (LOPA) and does not constitute an authorization for the installation of seats in excess of 145. A separate approval is needed for the installation of the individual customized cabin layout and the necessary cabin adaptations up to 150 seats.

The Modifications 159535 or 159533 enable the maximum seating capacity to be increased from 145 up to 160. This modification defines a virtual envelope of the Layout of Passenger Accommodations (LOPA) and does not constitute an authorization for the installation of seats in excess of 145. A separate approval is needed for the installation of the individual customized cabin layout and the necessary cabin adaptations up to 160 seats.

Notes:

A second pair of overwing emergency exit (Type III) can be installed by embodiment of modification 32208.

1. The LH & RH rear passenger doors can be de-activated by embodiment of modification 37807. In this case, the maximum number of passengers is 80.
2. The Type III emergency exit hatch can be de-activated by embodiment of modification 152777. In this case, the maximum number of occupants in the passenger cabin is limited to zero during taxi, take-off, flight and landing, unless terms and conditions to



SECTION 3: A319 SERIES

occupy specific cabin areas have been approved by operator's competent airworthiness authority

3. With MOD 165550, EtC E-28 and ESF E-32 are not applicable and therefore Maximum capacity is limited to 19 Passengers.
4. The modification 167900 deactivates the forward over-wing emergency exits. The maximum number of occupants in the cabin is then limited to 0 (zero).

21. Baggage/ Cargo Compartment

CARGO COMPARTMENT	MAXIMUM LOAD (kg)
Forward	2 268
Aft	3 021
Rear (bulk)	1 497

For the positions and the loading conditions authorized in each position (references of containers, pallets and associated weights) see Weight and Balance Manual, ref. 00 J 080 A 0001/C1S Chapter 1.10.

With MOD 153648 "EQUIPMENT/FURNISHINGS - GENERAL - DELIVER AIRCRAFT WITH INCOMPLETE CABIN" embodied, the cabin is limited to zero occupancy and no cargo (i.e. no occupancy and no cargo in cabin) during all phases of flight, unless a separate approved Modification is embodied to remove the limitation.

22. Wheels and Tyres

See SB A320-32-1007 for A319-111/-112/-113/-114/-115/-121/-132/-122
SB A320-32-1439 for A319-151N/-153N/-171N/-173N

23. ETOPS

The Type Design, system reliability and performance of A319 models were found capable for Extended Range Operations when configured, maintained and operated in accordance with the current revision of the ETOPS Configuration, Maintenance and Procedures (CMP) document, SA/EASA: AMC 20-6/CMP.

This finding does not constitute an approval to conduct Extended Range Operations (operational approval must be obtained from the responsible Authority).



SECTION 3: A319 SERIES

The following table provides details on the ETOPS approvals.

Aircraft model	Engine Type	120 min Approval Date	180 min Approval Date
A319-111	CFM56-5B5	14 February 1997	11 March 2004
A319-112	CFM56-5B6	14 February 1997	11 March 2004
A319-113	CFM56-5A4	14 February 1997	11 March 2004
A319-114	CFM56-5A5	14 February 1997	11 March 2004
A319-115	CFM56-5B7	25 November 1999	11 March 2004
A319-131	V2522-A5	14 February 1997	11 March 2004
A319-132	V2524-A5	14 February 1997	11 March 2004
A319-133	V2527M-A5	25 November 1999	11 March 2004
A319-151N	CFM LEAP-1A24	19 August 2019	19 August 2019
A319-153N	CFM LEAP-1A26	19 August 2019	19 August 2019 (including ACJ319 NEO)
A319-153N	CFM LEAP-1A26E1	07 May 2020	07 May 2020 (including the ACJ319 NEO)
A319-171N	PW1124G-JM	07 May 2020	07 May 2020

Note:

The Configuration, Maintenance and Procedure Standards for extended range twin-engine airplane operations are contained in ETOPS CMP document reference SA/EASA: AMC 20-6/CMP at latest applicable revision. Certificated models are A319-111/-112/-113/-114/-115/-131/-132/-133/-151N/-153N/-171N/-173N, with all applicable engines.

Embodiment of modification:

36666 provides ETOPS 120 mn capability for EASA

32009 provides ETOPS 180 mn capability for EASA

IV. Operating and Service Instructions**1. Airplane Flight Manual (AFM)**

EASA Approved Airplane Flight Manual for A319.

2. Instructions for Continued Airworthiness and Airworthiness Limitations

The complete set of Instructions for Continued Airworthiness is identified in paragraph 2 of the Aircraft Maintenance Manual introduction.

Airworthiness limitations

- * Limitations applicable to Safe Life Airworthiness Limitation Items are provided in the A318/A319/A320/A321 approved Airworthiness Limitations Section (ALS) sub-parts 1-2 and 1-3.



SECTION 3: A319 SERIES

- * Limitations applicable to Damage Tolerant Airworthiness Limitation Items are provided in the A318/A319/A320/A321 approved Airworthiness Limitations Items document (ALS Part 2).
- * Certification Maintenance Requirements are provided in the A318/A319/A320/A321 approved Airworthiness Limitations Section (ALS) Part 3.
- * System Equipment Maintenance Requirements are provided in the A318/A319/A320/A321 approved Airworthiness Limitations Section (ALS) Part 4.
- * Fuel Airworthiness Limitations are provided in the A318/A319/A320/A321 approved Fuel Airworthiness Limitations document (ALS Part 5).
- * Maintenance Review Board Report

Note: For A319-111, 112, -113, -114, -115, -131, -132, -133 models without sharklets, the embodiment of modification 155789 leads to change the maintenance program and its associated Maintenance Programme Publication Trigger (MPPT) from 48,000FC/60,000FH to 60,000FC/120,000FH (whichever occurs first).

Other limitations

See EASA approved Flight Manual.

3. Weight and Balance Manual (WBM)

Airbus Compliance Document 00J080A0001/C1S for A319-111/-112/-113/-114/-115/-131/-132/-133,
00J080A0002/C1S for A319-151N/-153N/-171N
00J080A0004/C0S for A319-173N

V. Operational Suitability Data (OSD)

1. Master Minimum Equipment List
 - a. The Master Minimum Equipment List has been approved as per the defined Operational Suitability Data Certification Basis (JAR-MMEL/MEL – Subpart B – MMEL at Amendment 1) and as documented in A320 MMEL reference “MMEL STL11000” at the latest applicable revision.
 - b. Required for entry into service by EU operator.
2. Flight Crew Data
 - a. The Flight Crew data has been approved as per the defined Operational Suitability Data Certification Basis (CS-FCD, initial issue) and as documented in reference “A320 Operational Suitability Data Flight Crew - SA01RP1536744” at the latest applicable revision.
 - b. Required for entry into service by EU operator.
 - c. The aircraft models: A318, A319, A321 are determined to be variants to the A320 aircraft model.



SECTION 3: A319 SERIES**3. Cabin Crew Data**

- a. The Cabin Crew data has been approved as followed and as documented in reference "A320 Operational Suitability Data Cabin Crew - SA01RP1534113" at the latest applicable revision.
 1. Until 20 Jan 2022 (date of MOD 165947 iss 1 Adapt lavatory SpaceFlex V2 for Airspace Cabin):
 - A318, A319, A320: Certification Basis/SC CCD-01
 - A321 except A321NX: Certification Basis/SC CCD-01
 - A321NX (A321-271NX,-272NX,-251NX,-252NX,-253NX): SC CCD-01 + CS-CCD.400(a) at initial issue
 2. After 20 Jan 2022 (date of MOD 165947 iss 1 Adapt lavatory SpaceFlex V2 for Airspace Cabin): A318, A319, A320, A321: Certification Basis/SC CCD-01 + CS-CCD.400 at initial issue
- b. Required for entry into service by EU operator.
- c. The aircraft models: A318, A319, A321 are determined to be variants to the A320 aircraft model.

VI. Part-26 compliance information

For all models, compliance with point 26.300(a) of Part-26 is demonstrated by complying with points

- 26.301 Compliance Plan for (R)TC holders
- 26.302 Fatigue and damage tolerance evaluation
- 26.303 Limit of Validity
- 26.304 Corrosion prevention and control programme
- 26.306 Fatigue critical baseline structure
- 26.307 Damage tolerance data for existing changes to fatigue-critical structure
- 26.308 Damage tolerance data for existing repairs to fatigue-critical structure
- 26.309 Repair Evaluation Guidelines

VII. Notes

1. For models A319-111, A319-112, A319-113 and A319-114, modification 26799 (FM without ACARS) or 26968 (FM ACARS) shall be installed to enable Cat IIIB precision approach. For models A319-131 and A319-132, modification 26716 (FM without ACARS) or 26717 (FM ACARS) shall be installed to enable Cat IIIB precision approach.
2. A319-115,-131,-132, -133 are basically qualified for Cat IIIB precision approach.
3. For A319-151N/-153N/171N, modification 161765 shall be installed to enable Cat IIIB precision approach. MOD 161765 is already part of the Type Design Definition (TDD) of the A319-173N.



SECTION 4: A318 SERIES**SECTION 4: A318 SERIES****I. General**

1. Type/ Model/ Variant

A318-111
A318-112
A318-121
A318-122

2. Performance Class

A

3. Certifying Authority

European Union Aviation Safety Agency (EASA)
Postfach 101253
D-50452 Köln
Deutschland

4. Manufacturer

AIRBUS S.A.S.
2 rond-point Emile Dewoitine
31700 BLAGNAC – France

5. State of Design Authority Certification Application Date

Airbus Industrie has applied for A318 certification on December 11, 1998, by letter AI/EA S 413.2952/1998.

6. EASA Type Certification Application Date

N/A

7. State of Design Authority Type Certificate Date

A318-111	May 23, 2003
A318-112	May 23, 2003

8. EASA Type Certification Date



SECTION 4: A318 SERIES

EASA TCDS issue 1 issued December 21, 2005

A318-121	December 21, 2005
A318-122	December 21, 2005

Note: For A318-111/-112 models produced before the 21st of December 2005, DGAC-F TC 180 remains a valid reference

II. Certification Basis

1. Reference Date for determining the applicable requirements

Airbus Industrie has applied for A318 certification on December 11, 1998, by letter AI/EA S 413.2952/1998.

2. State of Design Airworthiness Authority Type Certification Data Sheet No.

Original French TCDS DGAC no. 180 was replaced by the EASA TCDS A.064.

3. State of Design Airworthiness Authority Certification Basis

See below

4. EASA Airworthiness Requirements

Hereafter are listed the certification bases for the different A318 models. The amendments made to a particular basis at the occasion of further A318 models certification are identified per model.

The applicable Joint Certification Basis is:

- 4.1 JAR 25 Change 11

- except Subpart BB which remains at Change 10,
- except all National Variants,

JAR 25 X 20 Change 14	JAR 25.335 Change 15
JAR 25.21 Change 14	JAR 25.341 Change 15
JAR 25.23 Change 14	JAR 25.343 Change 15
JAR 25.25 Change 14	JAR 25.345 Change 15
JAR 25.27 Change 14	JAR 25.349 Change 15
JAR 25.29 Change 14	JAR 25.351 Change 15
JAR 25.31 Change 14	JAR 25.361 Change 15 ONLY for A318-121/-122
JAR 25.101 Change 14	JAR 25.363 Change 15 ONLY for A318-121/-122
JAR 25.103 Change 14	JAR 25.365 Change 13
JAR 25.105 Change 14	JAR 25.367 Change 15 ONLY for A318-121/-122



SECTION 4: A318 SERIES

JAR 25.107 Change 14	JAR 25.371 Change 15
JAR 25.109 Change 14	JAR 25.373 Change 15
JAR 25.111 Change 14	JAR 25.391 Change 15
JAR 25.113 Change 14 amended by OP 96/1	JAR 25.415 Change 15
JAR 25.115 Change 14	JAR 25.427 Change 15
JAR 25.117 Change 14	JAR 25.445 Change 15
JAR 25.119 Change 14 amended by OP 96/1	JAR 25.473 Change 15
JAR 25.121 Change 14 amended by OP 96/1	JAR 25.479 Change 15
JAR 25.123 Change 14	JAR 25.481 Change 15
JAR 25.125 Change 14 amended by OP 96/1	JAR 25.483 Change 15
JAR 25.143 Change 14 amended by OP 96/1	JAR 25.485 Change 15
JAR 25.145 Change 14 amended by OP 96/1	JAR 25.491 Change 15
JAR 25.147 Change 14	JAR 25.493(d) Change 14 amended by OP 96/1
JAR 25.149 Change 14 amended by OP 96/1	JAR 25.499 Change 15
JAR 25.161 Change 14	JAR 25.511 Change 15
JAR 25.171 Change 14	JAR 25.X519 Change 13
JAR 25.173 Change 14	JAR 25.561(c) Change 15
JAR 25.175 Change 14	JAR 25.562 Change 14 (see SC E-5001)
JAR 25.177 Change 14 amended by OP 96/1	JAR 25.571 Change 15
JAR 25.181 Change 14	JAR 25.801 Change 14
JAR 25.201 Change 14 amended by OP 96/1	JAR 25.803 Change 14
JAR 25.203 Change 14 amended by OP 96/1	JAR 25.807 Change 14
JAR 25.207 Change 14	JAR 25.809 Change 14
JAR 25.231 Change 14	JAR 25.810 Change 14
JAR 25.233 Change 14	JAR 25.811 Change 14
JAR 25.235 Change 14	JAR 25.812 Change 14
JAR 25.237 Change 14	JAR 25.813 Change 14
JAR 25.251 Change 14	JAR 25.853 Change 14
JAR 25.253 Change 14 amended by OP 96/1	JAR 25.855 Change 14
JAR 25.255 Change 14	JAR 25.857 Change 14
JAR 25X261 Change 14	JAR 25.858 Change 14
JAR 25.305 Change 15	JAR 25.901 Change 15 ONLY for A318-121/-122
JAR 25.321 Change 15	JAR 25.903 Change 15 ONLY for A318-121/-122
JAR 25.331 Change 15	JAR 25.933 Change 15 ONLY for A318-121/-122
JAR 25.333 Change 15	JAR 25.934 Change 15 ONLY for A318-121/-122

JAR 25.939 Change 15 ONLY for A318-121/-122	JAR 25.1143 Change15 ONLY for A318-121/-122
JAR 25.941 Change 15 ONLY for A318-121/-122	JAR 25.1163 Change15 ONLY for A318-121/-122
JAR 25.943 Change 15 ONLY for A318-121/-122	JAR 25.1165 Change15 ONLY for A318-121/-122
JAR 25.945 Change 15 ONLY for A318-121/-122	JAR 25.1167 Change15 ONLY for A318-121/-122
JAR 25.1041 Change15 ONLY for A318-121/-122	JAR 25.1181 Change15 ONLY for A318-121/-122
JAR 25.1043 Change15 ONLY for A318-121/-122	JAR 25.1182 Change15 ONLY for A318-121/-122
JAR 25.1045 Change15 ONLY for A318-121/-122	JAR 25.1183 Change15 ONLY for A318-121/-122
JAR 25.1091 Change15 ONLY for A318-121/-122	JAR 25.1185 Change15 ONLY for A318-121/-122
JAR 25.1093 Change15 ONLY for A318-121/-122	JAR 25.1187 Change15 ONLY for A318-121/-122



SECTION 4: A318 SERIES

JAR 25.1103 Change15 ONLY for A318-121/-122	JAR 25.1189 Change15 ONLY for A318-121/-122
JAR 25.1105 Change15 ONLY for A318-121/-122	JAR 25.1191 Change15 ONLY for A318-121/-122
JAR 25.1107 Change15 ONLY for A318-121/-122	JAR 25.1193 Change15 ONLY for A318-121/-122
JAR 25.1121 Change15 ONLY for A318-121/-122	JAR 25.1501 Change 14
JAR 25.1123 Change15 ONLY for A318-121/-122	JAR 25.1517 Change 15
JAR 25.1125 Change15 ONLY for A318-121/-122	JAR 25.1583 Change 14
JAR 25.1127 Change15 ONLY for A318-121/-122	JAR 25.1587 Change 14
JAR 25.1141 Change15 ONLY for A318-121/-122	JAR 25.X1591Change 14 (replacing JAR 25X131, 25X132, 25X133, 25X135, 25X1588 at Change 11)

4.2 JAR AWO at Change 1 for autoland and operations in low visibility.

4.3 For the Extended Twin Engine Airplane Operations the applicable technical conditions are contained in AMC 20-6 (as initially published in AMJ 120-42/IL 20) and:

G-22 ETOPS approval.

4.4 Post TC changes

4.4.1 When reinforced cockpit door is installed (see EtC E-12), 14 CFR Part 25.772(a) and (c) and 25.795 are at amendment 106.

4.4.2 When halon free hand-held fire extinguishers are installed, CS25.851(a),(c) is at Amdt 17 (see EtC D-GEN-AIRBUS-01).

4.4.3 For cabin and/or passengers improved seats (see EtC E-31), CS 25.562 is at amendment initial issue.

4.4.4 Airbus complies with CS-ACNS:

- Subpart B, Section 2 – for optional modifications (Post TC) installing FANS aiming at answering to SES mandate as defined in (EU) N° 29/2009 and amended by (EU) N° 310/2015 of 26 February 2015.

Note: For compliance to CS-ACNS Subpart B, Section 2, a deviation to CS-ACNS.B.DLS.B1.075 is accepted by DEV ACNS-B-GEN-01 to not include DM89 MONITORING [unit name] [frequency] in the downlink message set installed.

- Subpart D – for optional modifications installing transponders aiming at answering to SES mandate as defined in (EU) No 1207/2011 and amended by (EU) No 1028/2014 of 26 September 2014.

4.4.5 When Mod 160139 “Passenger information signs and placards” is installed CS25-791 is at Amdt 20

4.4.6 When mod 167557 “Define Modified Airspace Lavatory A Option for 25.795 Compliance” is installed, CS 25.795(a)(1), 25.795(a)(2) and §25.795(c)(3)(ii) are at Amdt 22 (ESF D-31).

4.4.7 From 14 December 2023, CS-FCD is at issue 2 for CS FCD.300, CS FCD.310, CS FCD.400, CS FCD.410, CS FCD.415.



SECTION 4: A318 SERIES**5. Special Conditions**

5.1 The following A320 Special Conditions, Experience Related Conditions and Harmonization Conditions which are kept for the A318:

Reminder: Within the scope of the establishment of the A320 Joint Certification Basis, three types of special conditions were developed:

- Special conditions: rose to cover novel or unusual features not addressed by the JAR.
- Experience related conditions: rose to record an agreed text for the A320 Joint Certification Basis when evolution of JAR was in progress under the NPA procedure.
- Harmonization conditions: to record, for the purpose of the A320 Joint Certification Basis, a common understanding with respect to National variant. This should not be confused with the FAA/JAA harmonised regulations.

Compulsory

(DGAC-F) SC G-17	Operational proving flights
(CAA-UK) SC G-17	Operational flight before certification
SC F-3	Cockpit control - motion and effect of cockpit control
SC F-6	Static directional and lateral stability
SC F-7	Flight envelope protection
SC F-8	Normal load factor limiting
SC F-9	Dual control system
SC A-2.2.2	Design manoeuvre requirements
SC S-11	Limit pilot forces and torques
SC S-33	Auto-thrust system
SC S-52	Operation without normal electrical power
SC S-74	Abnormal attitudes
SC S-75	Lightning protection indirect effects
SC S-77	Integrity of control signal
HC A-4.6	Speed control device
HC S-23	Standby gyroscopic horizon
HC S-24	VMO/MMO warning (setting)
HC S-72	Flight recorder
EC G-11	Turbine Engine - Maximum Take-Off Power and/or Thrust Duration - General definition
EC S-30	Autoflight system
EC S-54	Circuit protective devices

5.2 The following A319 Special Conditions, are kept for the A318:



SECTION 4: A318 SERIES

SC A-2	Stalling speeds for structural design
SC F-11	Accelerate-stop distances and relates performances, worn brakes
SC A-1	Interaction of systems and structure
SC P-1	FADEC for CFM56 and AMJ20X-1 change 14 for PW6000
SC S-79	Brakes requirements, qualification and testing

5.3 The following A319/A320/A321 Special Conditions are kept for the A318:

SC S-76-1	Effect of external radiations upon aircraft systems (modified by SC SE-14)
-----------	--

5.4 The following Special Conditions are developed for the A318:

SC F-5001	Stalling and scheduled operation speed
SC F-5004	Static longitudinal stability and low energy awareness
SC A-5001	Engine Failure Loads (PW engine only)
SC A-5003*	Design Dive Speed
SC P-5004	Engine Sustained Imbalance (PW engine only)
SC SE-5002	AFM – RVR limits

From 07th December 2018 SC B-14 is replacing SC A-5003



SECTION 4: A318 SERIES

5.5 The following special conditions have been developed post Type Certification:

SC D-0306	Heat release and smoke density requirements to seat material (applicable from June 2010)
SC E-48	Fuel Tank Safety (applicable from October 2013)
SC F-0311-001	Flight Recorders including Data Link Recording (applicable as per operational regulations)
F-GEN-01	Installation of non-rechargeable lithium battery (applicable from March 2019)
SC H-01	Enhanced Airworthiness Programme for Aeroplane Systems - ICA on EWIS (applicable from May 2010)
SC P-27	Flammability Reduction System (see Note 4.3.8) If fitted, the centre fuel tank of aircraft which have made their first flight after 1st of January 2012 must be equipped in production with a fuel tank Flammability Reduction System (modification 38062). This system shall remain installed and operative and can only be dispatched inoperative in accordance with the provisions of the MMEL revision associated with modification 38062. If modification 38062 (Fuel Tank Inerting System (FTIS)) is embodied on A318, A319, A320, or A321 airplanes, the airplane is compliant with paragraph FR Section 25.981(a) & (b) at amendment 25-102, Part 25 appendix M & N at amendment 25-125, and Section 26.33 at amendment 26-3.

5.6 Additional Special Conditions part of the Certification Basis (added post TC):

The following Special Conditions are additionally applicable when an A/C configuration include the subject design change(s):

D-15	Pilot Control Mode TaxiBot Operations
D-19	Incorporation of Inertia Locking Device in Dynamic Seats
D-24	Installation of Airbags in the backrest of seats
D-25	Installation of structure mounted airbag
D-27	Installation of Three Point Restraint & Pretensioner System
D-0322-001	Installation of suite type seating
D-0332-001	Towbarless Towing
E-13	Installation of inflatable restraints
E-21	Flight Instrument External Probes – Qualification in Icing Conditions New UTAS Pitot Probes
E-34	Seat with inflatable restraints
F-5011	Steep approach
F-119	Security Protection of Aircraft Systems and Networks



SECTION 4: A318 SERIES

F-MULTI-04	Rechargeable Lithium Battery Installations
F-37	ATN over SATCOM

6. Exemptions/Deviations**Optional**

ACNS-B-GEN-01 Deviation to CS-ACNS Initial Issue Subpart B, Section 2 (See Note in §II-4.4.4)

7. Equivalent Safety Findings**Compulsory****7.1 Equivalent Safety findings to the following requirements are granted:**

JAR 25.783(f)	SM-4004	"Passenger Doors N. 1 and 4" (see A319 "passenger doors")
JAR 25.807(d)	E-5004	"Exit configuration" similar to A319 ESF E-4001)
JAR 25.813(c)(1)	E-5005	"Type III overwing emergency exit access"
JAR 25.831(a)	E-5006	"Packs Off Operation"
JAR 25.933(a)(1)	P-4008 (A319)	"Thrust Reverser Auto restow"
JAR AWO 313	SE-4005 (A319)	"Minimum Approach Break-Off Height"
JAR AWO 236	SE-5005	"Cat III Operation – Excess Deviation Alert"
NPA AWO 10	SE-5002	"AFM – RVR limits"

7.2 The following Equivalent Safety Findings have been developed post Type Certification:

FAR 25.856(b)	E-32 E-28	Fuselage burnthrough protection in bilge area, see note below If modifications 150700, and 37270 (with CLS option only), 37048 and 36985 are embodied in production on A318, A319, A320, or A321 airplanes, the airplane is compliant with Fuselage Flame Penetration "Burnthrough" requirements addressed by paragraph 14 CFR Part 25.856(b) Amdt 25-111 (applicable as per operational regulations)
14CFR Part 25.856(a)	E-18	Improved flammability standards for insulation materials (applicable as per operational regulations)

7.3 Additional ESF part of the Certification Basis (added post TC):

The following ESFs are additionally applicable when an A/C configuration include the subject design change(s):

CS 25.251(b)	B-17	Vibration/buffeting compliance criteria for large external antenna installation applicable from February 2021.
JAR 25.785(c)	D-0329-001	Forward facing seats with more than 18° to aircraft centreline.
CS 25.795(a)(1)	D-31	Application of reduced Intrusion Loads in certain areas of the flight deck boundaries
JAR 25.811(f)	E-16	Emergency exit marking reflectance
CS 25.811(e)(4)	SE-63	Green Arrow and "Open" placard for Emergency Exit Marking



SECTION 4: A318 SERIES

JAR 25.812(b)(1)(ii)	E-14	Photo-luminescent EXIT sign for MCD (Moveable Class Divider)
JAR 25.812(b)(1)(i)(ii)	SE-42	Symbolic EXIT signs as an alternative to red EXIT signs for passenger aircraft
JAR 25.1441(c)	F-21	Crew Determination of Quantity of Oxygen in Passenger Oxygen System
JAR 25.1443(c)	F-20	Minimum Mass Flow of Supplemental Oxygen (optional)
CS FCD.425(g)	FCD-MULTI-01	CS-FCD T3 Evaluation Process

8. Environmental Protection

ICAO Annex 16:

Vol. I, Part II	Noise Requirements
Vol. II, Part II	Fuel Venting
Vol. II, Part III Chapter 2	Emissions

Notes: Further details are defined within TCDSN EASA.A.064

III. Technical Characteristics and Operational Limitations**1. Type Design Definition**

- 1.1 Certificated model: A318-111
Definition of reference airplane by doc.: D03006056 (00P000A0111/C21).
- 1.2 Certificated model: A318-112
Definition of reference airplane by doc.: D03006716 (00P000A0112/C21).
- 1.3 Certificated model: A318-121
Definition of reference airplane by doc.: D05028326 (00P000A0121/C21).
- 1.4 Certificated model: A 318-122
Definition of reference airplane by doc.: D05028327 (00P000A0122/C21).

NOTES

Model conversions:

- If modification 152796 is embodied on A318-121 model powered with PW6122A engines, it is converted into A318-122 model, powered with PW6124A engines.
- If modification 153997 is embodied on A318-111 model powered with CFM56-5B8/P or /3 engines, it is converted into A318-112 model, powered with CFM56-5B9/P or /3 engines.
- If modification 153998 is embodied on A318-112 model powered with CFM56-5B9/P or /3 engines, it is converted into A318-111 model, powered with CFM56-5B8/P or /3 engines.

2. Description

SECTION 4: A318 SERIES

Twin turbo-fan, short to medium range, single aisle, transport category airplane.

3. Equipment

Not applicable.

Cabin furnishings, equipment and arrangement shall be in conformance to the following Specifications:

Cabin seats	2521M1F10000 at latest approved issue
Galleys	2530M1F000900 at latest approved issue

4. Dimensions

Principal dimensions of A318 Aircraft:

Length:	31.45 m
Width:	34.10 m
Height:	12.79 m
Width at horizontal stabilizer:	12.45 m
Outside fuselage diameter:	3.95 m
Distance between engine axes:	11.51 m
Distance between main landing gear:	7.59 m
Distance between nose and main landing gear:	11.04 m

5. Engines

The list below lists the basic engines fitted on the aircraft models. The notes describe usual names and certified names as well as engines variants.

A318-111

Two CFMI CFM 56-5B8/P jet engines (MOD 32028)

A318-112

Two CFMI CFM 56-5B9/P jet engines (MOD 32029)

A318-121

Two PW 6122A jet engines (MOD 30034)

A318-122

Two PW 6124A jet engines (MOD 31882)

Notes:

- 1 Introduction of CFM56-5Bx/3 "Tech Insertion" engine is done through embodiment of modification 37147 in production or 38770 in field.

This modification is only applicable on CFM56-5Bx /P SAC engines. If modification 37147 is embodied on models with CFM-5B engines, the engine's denomination changes to /3.



SECTION 4: A318 SERIES

The modification is currently applicable for:

A318-111: CFM 56-5B8 (SAC) which changes to CFM 56-5B8/3

A318-112: CFM 56-5B9 (SAC) which changes to CFM 56-5B9/3

The engine characteristics remain unchanged.

Modification 37147 has been demonstrated as having no impact on previously certified noise levels.

CFM56-5Bx/3 engine can be intermixed with CFM56-5Bx/P engine under considerations as prescribes in modification 38573.

6. Auxiliary Power Unit**1. Basic****- A318-111/-112**

HONEYWELL AIRESEARCH GTCP 36-300 (A) (Specification 31-5306 B)
Approved oil: See Garrett report GT 7800.

- A318-121/-122

Pratt & Whitney Rzeszow S.A. APS 3200 (Specification ESR 0802, Rev. A).
APU Pratt & Whitney Rzeszow S.A. installation defined by MOD 35864.
Approved oils: in conformance to MIL-L-7808, MIL-L-23699 or DERD 2487.

2. Option**- A318-111/-112**

Pratt & Whitney Rzeszow S.A. APS 3200 (Specification ESR 0802, Rev. A).
APU Pratt & Whitney Rzeszow S.A. installation defined by MOD 22562 or 35864.
Approved oils: in conformance to MIL-L-7808, MIL-L-23699 or DERD 2487.

Or

Honeywell International I 131-9[A] (Specification 4900 M1E 03 19 01)
The APU Honeywell International installation is defined by MOD 25888.
Approved oils: according to model Specification 31-12048A-3A.

- A318-121/-122

Honeywell International I 131-9[A] (Specification 4900 M1E 03 19 01)
The APU Honeywell International installation is defined by MOD 25888.
Approved oils: according to model Specification 31-12048A-3A.



SECTION 4: A318 SERIES

Note: For A318 models, the APU Pratt & Whitney Rzeszow S.A. APS 3200 (MOD 35864) is the production standard from MSN 2686

7. Propellers

N/A

8. Fluids (Fuel, Oil, Additives, Hydraulics)**Fuel**

ENGINES	KEROSENE DESIGNATION
CFM56: Installation document CFM 2129)	JET A, JET A-1, JP5, JP8, N°3 Jet Fuel, JET B*, JP 4*, F44, F34, AVTUR, AVTUR/FSII, AVTAG/FSII*, AVCAT/FSII
PW6000: Installation document PWA-7707	JET A, JET A-1, JP5, JP8, N°3 Jet Fuel, JET B*, JP 4*, F44, F34, AVTUR, AVTUR/FSII, AVTAG/FSII*, AVCAT/FSII

The above-mentioned fuels are also suitable for the APU.

Refer to Consumable Material List (CML) for details on approved fuel specifications

* Wide cut is only certified for CFM engines

OIL

For oil specification:

Engine	CFM56-5B8/P CFM56-5B9/P	PW6122A PW6124A
Approved Oils	SB CFMI 79-001-OX	SB PW 238

Additives:

Refer to Airbus Consumable Material List (CML)

Hydraulics:

Hydraulic fluids: Type IV or Type V - Specification NSA 30.7110.

9. Fluid Capacities**Fuel quantity (0.8 kg/litre)****A318-100 series (without MOD 160001)**

Tank	3 TANK AIRPLANE	
	Usable fuel litres (kg)	Unusable fuel Litres (kg)
Wing	15 609 (12 487)	58.9 (47.1)



SECTION 4: A318 SERIES

Centre	8 250 (6 600)	23.2 (18.6)
TOTAL	23 859 (19 087)	82.1 (65.7)

A318-100 series (with MOD 37331 and without MOD 160001)

Tank	3 TANK AIRPLANE	
	Usable fuel litres (kg)	Unusable fuel Litres (kg)
Wing	15 959 (12 767)	58.9 (47.1)
Centre	8 250 (6 600)	23.2 (18.6)
TOTAL	24 209 (19 367)	82.1 (65.7)

A318-100 series (without MOD 37331 and with MOD 160001)

Tank	3 TANK AIRPLANE	
	Usable fuel litres (kg)	Unusable fuel Litres (kg)
Wing	15 568 (12 454)	58.9 (47.1)
Centre	8 248 (6 598)	23.2 (18.6)
TOTAL	23 816 (19 052)	82.1 (65.7)

A318-100 series (with MOD 37331 and with MOD 160001)

Tank	3 TANK AIRPLANE	
	Usable fuel litres (kg)	Unusable fuel Litres (kg)
Wing	15 918 (12 734)	58.9 (47.1)
Centre	8 248 (6 598)	23.2 (18.6)
TOTAL	24 166 (19 332)	82.1 (65.7)

10. Airspeed Limits (Indicated Airspeed – IAS – unless otherwise stated)

Maximum Operating Mach (MMO): 0.82
Maximum Operating Speed (VMO): 350 kt



SECTION 4: A318 SERIES

Manoeuvring Speed (VA): see Limitations Section of the EASA approved Flight Manual

Extended Flaps/Slats Speed (VFE): see table below

Configuration	Slats/Flaps (°)	VFE (kt)	
1	18/0 18/10*	230 215	Intermediate approach Take-off
2	22/15	200	Take-off and approach
3	22/20	185	Take-off, approach, landing
Full	27/40	177	Landing

* Auto flap retraction at 210 kt in Take-off configuration

Landing gear:

VLE - Extended: 280 kt/Mach 0.67

VLO - Extension: 250 kt

- Retraction: 220 kt

Tyres Limit Speed (Ground speed): 195.5 kt (225 mph)

11. Flight Envelope

Maximum operating altitude

39 800 ft (pressure altitude)

41 100 ft (pressure altitude)

if modification 39195 is embodied
(Models A318-111/-112 only)

12. Operating Limitations

See the appropriate EASA approved Airplane Flight Manual

Powerplant (2.2482 lb/daN)**CFMI Engines**

Engine	CFMI CFM565B8/P	CFM56-5B9/P
Data sheets	E37NE, E38NE (FAA) EASA.E.003	E37NE, E38NE (FAA) EASA.E.003
Static thrust at sea level		
Take-off (5 min)* (Flat rated 30° C)	9 608 daN (21 600 lbs)	10 364 daN (23 300 lbs)
Maximum continuous	8478 daN	9 008 daN



SECTION 4: A318 SERIES

(Flat rated 25° C)	(19060 lbs)	(20 250 lbs)
--------------------	-------------	--------------

* 10 minutes at take-off thrust allowed only in case of engine failure (at take-off or during go-around) in accordance with DGAC "Fiche de Caractéristiques Moteur".

PW Engines

Engine	PW6000	
	PW6122A	PW6124A
Data sheets	IM.E.020 (EASA) E00064EN (FAA)	
Sea level static thrust ratings		
Take-off (5 min)* (Flat rated 30° C)	9 830 daN (22 100 lbs)	10 587 daN (23 800 lbs)
Maximum continuous (Flat rated 25° C)	9030 daN (20 300 lbs)	9297 daN (20 900 lbs)

* 5 min TO time limit can be extended to 10 min for one engine inoperative

Other engine limitations: see the relevant Engine Type Certificate Data Sheet.

12.1 Approved Operations

Transport commercial operations.

12.2 Other Limitations

For a complete list of applicable limitations see the appropriate EASA approved Airplane Flight Manual

13. Maximum Certified Masses

VARIANT	000 BASIC	001* MOD 31672	002* MOD 31673	003* MOD 31674	004* MOD 31675	005* MOD 31676
WEIGHT (Kg)						
Max. Ramp Weight	59 400	61 900	63 400	64 900	66 400	68 400
Max. Take-off Weight	59 000	61 500	63 000	64 500	66 000	68 000
Max. Landing Weight	56 000	56 000	57 500	57 500	57 500	57 500
Max. Zero Fuel Weight	53 000	53 000	54 500	54 500	54 500	54 500
Minimum Weight	34 500	34 500	34 500	34 500	34 500	34 500

VARIANT	006* MOD 33235	007* MOD 33126	008* MOD 33128
WEIGHT (Kg)			
Max. Ramp Weight	56 400	61 400	64 400



SECTION 4: A318 SERIES

Max. Take-off Weight	56 000	61 000	64 000
Max. Landing Weight	56 000	56 000	56 000
Max. Zero Fuel Weight	53 000	53 000	53 000
Minimum Weight	34 500	34 500	34 500

Notes:

- * WV option certified concurrently with the basic WV at the time of the model's approval

14. Centre of Gravity Range

See the appropriate EASA approved Airplane Flight Manual.

15. Datum

Station 0.0, located 2.540 meters forward of airplane nose.

16. Mean Aerodynamic Chord (MAC)

4.1935 meters.

17. Levelling Means

The A/C can be jacked on three primary jacking points.

See the appropriate EASA approved Weight and Balance Manual.

18. Minimum Flight Crew

2 pilots.

19. Minimum Cabin Crew

See paragraph 20.

20. Maximum Seating Capacity

The table below provides the certified Maximum Passenger Seating Capacities (MPSC), the corresponding cabin configuration (exit arrangement and modifications) and the associated minimum numbers of cabin crew members used to demonstrate compliance with the certification requirements:

MPSC	Cabin configuration	Modification	Minimum CC
136	C-III-C	---	3



SECTION 4: A318 SERIES**Notes:**

1. The LH & RH rear passenger doors can be de-activated by embodiment of modification 37807. In this case, the maximum number of passengers is 80.
2. The Type III emergency exit can be de-activated by embodiment of modification 39673. In this case, the maximum number of passengers is 110 when operating overland and 32 when operating overwater.
3. With MOD 153648 "EQUIPMENT/FURNISHINGS - GENERAL - DELIVER AIRCRAFT WITH INCOMPLETE CABIN" embodied, the cabin is limited to zero occupancy and no cargo (i.e. no occupancy and no cargo in cabin) during all phases of flight, unless a separate approved Modification is embodied to remove the limitation.

21. Baggage/ Cargo Compartment

CARGO COMPARTMENT	MAXIMUM LOAD (kg)
Forward	1614
Aft	2131
Rear (bulk)	1372

For the positions and the loading conditions authorized in each position (references of containers, pallets and associated weights) see Weight and Balance Manual, ref. 00 P 080 A 0001/C1S Chapter 1.10.

22. Wheels and Tyres

See SB A320-32-1007.

23. ETOPS

The Type Design, system reliability and performance of A318 models were found capable for Extended Range Operations when configured, maintained and operated in accordance with the current revision of the ETOPS Configuration, Maintenance and Procedures (CMP) document, SA/EASA: AMC 20-6/CMP.

This finding does not constitute an approval to conduct Extended Range Operations (operational approval must be obtained from the responsible Authority).

The following table provides details on the ETOPS approvals.

Aircraft model	Engine Type	120 min Approval Date	180 min Approval Date
A318-111	CFM56-5B8	N/A	06 November 2006
A318-112	CFM56-5B9	N/A	06 November 2006
A318-121	PW6122A	N/A	16 November 2010
A318-122	PW6124A	N/A	16 November 2010



SECTION 4: A318 SERIES**Note:**

The Configuration, Maintenance and Procedure Standards for extended range twin-engine airplane operations are contained in ETOPS CMP document reference SA/EASA: AMC 20-6/CMP at latest applicable revision. Certificated models are A318-111/-112/-121/-122, with all applicable engines.

Embodiment of modification:

- 36666 provides ETOPS 120 min capability for EASA,
- 32009 provides ETOPS 180 min capability for EASA

IV. Operating and Service Instructions**1. Airplane Flight Manual (AFM)**

EASA Approved Airplane Flight Manual for A318.

2. Instructions for Continued Airworthiness and Airworthiness Limitations

The complete set of Instructions for Continued Airworthiness is identified in paragraph 2 of the Aircraft Maintenance Manual introduction.

Airworthiness Limitations

- Limitations applicable to Safe Life Airworthiness Limitation Items are provided in the A318/A319/A320/A321 approved Airworthiness Limitations Section (ALS) sub-parts 1-2 and 1-3.
- Limitations applicable to Damage Tolerant Airworthiness Limitation Items are provided in the A318/A319/A320/A321 approved Airworthiness Limitations Items document (ALS Part 2).
- Certification Maintenance Requirements are provided in the A318/A319/A320/A321 approved Airworthiness Limitations Section (ALS) Part 3.
- System Equipment Maintenance Requirements are provided in the A318/A319/A320/A321 approved Airworthiness Limitations Section (ALS) Part 4.
- Fuel Airworthiness Limitations are provided in the A318/A319/A320/A321 approved Fuel Airworthiness Limitations document (ALS Part 5).
- Maintenance Review Board Report

Other limitations

See EASA approved Flight Manual.

3. Weight and Balance Manual (WBM)

SECTION 4: A318 SERIES

Airbus Compliance Document 00P80A0001/C1S.

V. Operational Suitability Data (OSD)

The Operational Suitability Data elements listed below are approved by the European Union Aviation Safety Agency under the EASA Type Certificate EASA.A.064 as per Commission Regulation (EU) 748/2012 as amended by Commission Regulation (EU) No 69/2014.

1. Master Minimum Equipment List
 - a. The Master Minimum Equipment List has been approved as per the defined Operational Suitability Data Certification Basis (JAR-MMEL/MEL – Subpart B – MMEL at Amendment 1) and as documented in A320 MMEL reference “MMEL STL11000” at the latest applicable revision.
 - b. Required for entry into service by EU operator.
2. Flight Crew Data
 - a. The Flight Crew data has been approved as per the defined Operational Suitability Data Certification Basis (CS-FCD, initial issue) and as documented in reference “A320 Operational Suitability Data Flight Crew - SA01RP1536744” at the latest applicable revision.
 - b. Required for entry into service by EU operator.
 - c. The aircraft models: A318, A319, A321 are determined to be variants to the A320 aircraft model.
3. Cabin Crew Data
 - a. The Cabin Crew data has been approved as followed and as documented in reference “A320 Operational Suitability Data Cabin Crew - SA01RP1534113” at the latest applicable revision.
 1. Until 20 Jan 2022 (date of MOD 165947 iss 1 Adapt lavatory SpaceFlex V2 for Airspace Cabin):
 - A318, A319, A320: Certification Basis/SC CCD-01
 - A321 except A321NX: Certification Basis/SC CCD-01
 - A321NX (A321-271NX,-272NX,-251NX,-252NX,-253NX): SC CCD-01 + CS-CCD.400(a) at initial issue
 2. After 20 Jan 2022 (date of MOD 165947 iss 1 Adapt lavatory SpaceFlex V2 for Airspace Cabin): A318, A319, A320, A321: Certification Basis/SC CCD-01 + CS-CCD.400 at initial issue
 - b. Required for entry into service by EU operator.
 - c. The aircraft models: A318, A319, A321 are determined to be variants to the A320 aircraft model.

VI. Part-26 compliance information

For all models, compliance with point 26.300(a) of Part-26 is demonstrated by complying with points

- 26.301 Compliance Plan for (R)TC holders



SECTION 4: A318 SERIES

- 26.302 Fatigue and damage tolerance evaluation
- 26.303 Limit of Validity
- 26.304 Corrosion prevention and control programme
- 26.306 Fatigue critical baseline structure
- 26.307 Damage tolerance data for existing changes to fatigue-critical structure
- 26.308 Damage tolerance data for existing repairs to fatigue-critical structure
- 26.309 Repair Evaluation Guidelines

VII. Notes

All models are basically qualified for Cat IIIB precision approach.



SECTION 5: ADMINISTRATIVE – continued**SECTION: ADMINISTRATIVE****I. Acronyms and Abbreviations**

- reserved -

II. Type Certificate Holder Record

AIRBUS S.A.S
2 Rond-point Emile Dewoitine
31700 BLAGNAC
FRANCE

III. Change Record

Issue	Date	Changes	TC issue
1	21.12.2005	Initial EASA Issue / Approval of A318-121,-122	21.12.2005
2	22.06.2006	-	No change
3	20.05.2008	-	No change
4	18.07.2008	-	No change
5	06.05.2009	-	No change



SECTION 5: ADMINISTRATIVE – continued

Issue	Date	Changes	TC issue
6	25.05.2011	<ul style="list-style-type: none"> ETOPS approval information added Weight Variants added. 015, 017, 018 (A320), 004, 006 (A321) Introduction of Post-TC SC (H-01, E-34, D-0306, P-27) Introduction of Post-TC ESF (E-28), ETOPS reference doc updated Limitation on JP4 deleted, ACT fuel quantity corrected Note reworded on Cat IIIB precision approach, Notes 2.4.2 to 2.4.5, 3.3.7 deleted ETOPS reference doc updated and models added (A320-215/-216) Noise compliance clarified to take into account D/E/J noise project MOD 150365 (capacity of 150 pax + 3 cabin attendants) added to note MOD 38770 for “tech insertion kit” for in-service aircraft added to note models A320-211/-212 added to note Note added to take into account the burnthrough (EtC E-28 and E-32) Note added to take into account the flammability reduction system (SC P-27) Note added to introduce the wingbox without dry bay (MOD 38616) MOD 39673 De-activation of Type III exit MOD 39195 Operations up to 41 000 ft 	No change
7	13.06.2011	<ul style="list-style-type: none"> MOD 150016 – deactivation of forward Type III exit for A320 added to note Note modified to take into account the production cut-in for installation of flammability reduction system on new aeroplanes 	No change



SECTION 5: ADMINISTRATIVE – continued

Issue	Date	Changes	TC issue
8	06.06.2012	<ul style="list-style-type: none"> • Correction of Post-TC ESF (E-32 instead of E-28) • Title of SC E-34 modified to reflect the real title • Correction in the table of fuel specification due to obsolescence • MOD 150364 – cabin operational flexibility added • Introduction of D/E/J noise project step 2 for A320-214 • Reference to CFM document 2129 “Installation manual” for CFM-5B added • Reference to CFM document 2129 “Installation manual” for CFM-5B added and reference to CFM document 2026 “installation manual” for CFM-5A deleted • MOD 153453 - WV013 A319-133, MSN 4042 • MOD 152777 - DOORS - EMERGENCY EXIT- DEACTIVATE TYPE III OVERWING EXITS • Note reworded on Cat IIIB precision approach (error on MOD numbers) 	No change
9	30.11.2012	<ul style="list-style-type: none"> • Editorial changes to accommodate new TCDS template. • A320 Fuel Quantity figures revised due to MOD 160001. • Approval of MOD 160500 “Sharklets” for A320-214, -215, -216. • Detailed references to modifications concerning noise removed. Reference to TCDSN added. 	No change
10	21.12.2012	<ul style="list-style-type: none"> • Approval of MOD 160500 “Sharklets” for A320-232, -233 • A319 Fuel Quantity figures revised due to MOD 160001 	No change
11	31.05.2013	<ul style="list-style-type: none"> • A318 Fuel Quantity figures revised due to MOD 160001 • Removal of MOD 36984 • Approval of MOD 160500 “Sharklets” for A319-111,112, 115 excluding CJ • Clarification of fuel additives 	No change



SECTION 5: ADMINISTRATIVE – continued

Issue	Date	Changes	TC issue
12	12.09.2013	<ul style="list-style-type: none"> • Correction of TC date for A320-233 • Correction of reference number of SC-S79-1 for A318; • Inclusion of Post TC SC F5011 - Steep Approach for A318; • Inclusion of Elect-to-Comply E12 for all models; • Inclusion of SC E1005 for A320 models; • Inclusion of SC E13 for all models; • Inclusion of ESF E14 for all models; • Inclusion of ESF E16 for all models; • Inclusion of ESF E18 for all models; • Inclusion of ESF SE42 for all models; • Inclusion of ESF S53 for A320 models; • Moving SC E10 to Post-TC SC section; • Inclusion of A321 mod 160023 • Inclusion of A321 WV 10 for A321-211 and A321-231 • Extension of the applicability of mod 160500 	12.09.2013
13	31.01.2014	<ul style="list-style-type: none"> • Surrender/Removal of the A320-111 • Introduction of WV restriction for mod 160023 • A319 engine model note correction • Addition of hydraulic fluid type V for all models • A320 LOV note amended due to mod 39020 • Correction of VFE flap setting for A320 equipped with IAE engines • Inclusion of SC F-0311 for all models • Inclusion of SC E-48 for all models • Inclusion of ESF D-0329-1 for all models • Inclusion of SC D-0322-001 for all models 	31.01.2014
14	14.07.2014	<ul style="list-style-type: none"> • Inclusion of ESF F20 for all models • Inclusions of ESF F21 for all models • Extension of mod 160023 approval • Fuel table clarifications 	No change
15	19.12.2014	<ul style="list-style-type: none"> • Inclusion of A320 WV 19 • Clarification of A320 LOV • Introduction of A319 LOV 	No change
16	06.02.2015	<ul style="list-style-type: none"> • Update of A320 WV 019 applicability • Introduction of mod 156723 • Inclusion of ESF D-01 • Inclusion of SC D-0332-001 • Inclusion of SC E-57 • Note on dry bay mod 37332 for IAE equipped aircraft • Inclusion of minimum cabin crew • Model conversion notes updated 	No change



SECTION 5: ADMINISTRATIVE – continued

Issue	Date	Changes	TC issue
17	08.07.2015	<ul style="list-style-type: none"> • Introduction of mod 157272 • Introduction of mod 157777 • Inclusion of ESF D-02 • Inclusion of ESF D-03 	No change
18	24.11.2015	<ul style="list-style-type: none"> • Introduction of A320-271N • Introduction of modification 160080 • Correction of SC F-0311-001 reference • Inclusion of EASA engine TCDS references • Inclusion of SC B-12 • Seat and Galley frame references updated • Fuel tables updated • Introduction of OSD data 	24.11.2015
19	18.12.2015	<ul style="list-style-type: none"> • Introduction of modification 160080 issue 2 • APIC APU name change to Pratt & Whitney Rzeszow S.A. • Introduction of OSD certification basis 	No change
20	17.03.2016	<ul style="list-style-type: none"> • Allied Signal APU name change to Honeywell International • Introduction of mod 156723 iss 4 • Introduction of Mobile, USA as a production site for A321 • Clarification of MAX PAX certification basis 	No change
21	31.05.2016	<ul style="list-style-type: none"> • Correction of A320-271N nomenclature • Clarification of Airbus SAS as TC holder • Introduction of A320-251N • Update of Mobile production site for A319 & A320 • Clarification of cabin crew requirements 	31.05.2016
22	28.06.2016	<ul style="list-style-type: none"> • Introduction of mod 156723 iss 5 • Introduction of mod 158708 iss 1 	No change
23	14.10.2016	<ul style="list-style-type: none"> • Introduction of weight variant 69, 71, 78 & 82 for A320 NEO • Update of fuel tables • Inclusion of SE-63 & D-08 • Update of A321 WV 8 applicability 	No change
24	15.12.2016	<ul style="list-style-type: none"> • Introduction of A321-271N • Introduction of mod 161765 • Introduction of D-GEN-AIRBUS-01 	15.12.2016
25	06.02.2017	<ul style="list-style-type: none"> • New TCDS EASA template • Update of A321 and A319 POA agreement • Introduction of MOD 161765 for A320-271N 	No change
26	01.03.2017	<ul style="list-style-type: none"> • Introduction of A321-251N • Introduction of MOD 158819 iss 1 	01.03.2017
27	06.03.2017	<ul style="list-style-type: none"> • Introduction of A321-253N • Introduction of MOD 157272 iss 2 	03.03.2017



SECTION 5: ADMINISTRATIVE – continued

Issue	Date	Changes	TC issue
28	31.05.2017	<ul style="list-style-type: none"> • Introduction of ACTs for A321 NEO • Introduction of A321-272N • Introduction of D-15 • Introduction of PW1133GA-JM models • Introduction of mod 157272 iss 3 • Introduction of WV 68 • A319 Fuel table clarification 	23.05.2017
29	13.07.2017	<ul style="list-style-type: none"> • Introduction of LEAP-1A35A engines • Introduction of ETOPS for NEO • Introduction of clarifications regarding the WV approvals 	No change
30	19.09.2017	<ul style="list-style-type: none"> • New Airbus Address • New SB for SA NEO tires • Introduction MOD 161765 for A321-251N/-253N • Introduction of MOD 159535 iss 1 • Seat Frame Specification up-issue 	19.09.2017
31	18.12.2017	<ul style="list-style-type: none"> • Introduction of MOD 159536 iss 1 • Introduction of A320-252N • Introduction of A321-252N • Introduction MOD 161765 for A321-271N/-272N/252N • Introduction of ETC E-31 • Introduction of E-21 	18.12.2017
32	22.03.2018	<ul style="list-style-type: none"> • Introduction of A321-251NX/-252NX/-253NX/-271NX/-272NX • Introduction of ETOPS approval for A320-252N and A321-252N • Introduction of F-119 	22.03.2018
33	05.06.2018	<ul style="list-style-type: none"> • Introduction of ETOPS approval for A321-271NX,-272NX,-251NX,-252NX,-253NX • Extension of MOD 160684 to the A321-271NX • Extension of MOD 161765 for A321-271NX,-272NX,-251NX,-252NX,-253NX • Introduction of MOD 164024 	No change
34	05.07.2018	<ul style="list-style-type: none"> • Introduction of MOD 160908 • Introduction of MOD 157914 	No change
35	07.08.2018	<ul style="list-style-type: none"> • Introduction MOD 163213 • Note reworded on Cat IIIB precision approach (A320-231 quoted twice) 	No Change
36	05.11.2018	<ul style="list-style-type: none"> • Introduction of A320-272N • Introduction of MOD 162227 • Introduction of MOD 160906 • Introduction of MOD 160907 • Introduction of MOD 161925 	17 October 2018



SECTION 5: ADMINISTRATIVE – continued

Issue	Date	Changes	TC issue
37	16.01.2019	<ul style="list-style-type: none"> • Introduction of Elect To Comply to CS-ACNS • Introduction of ACNS-B-GEN-01 • Introduction of D-19 • Introduction B-14 • Introduction of A319-151N • Introduction of ACJ320 NEO • Introduction of MOD 158238 	14 December 2018
38	22.02.2019	<ul style="list-style-type: none"> • Introduction of MOD 159533 • Introduction of A320-273N • Introduction of A320-253N • Introduction of MOD 156130 	30 January 2019 5 February 2019
39	20.05.2019	<ul style="list-style-type: none"> • Introduction of A319-153N • Clarification of E-32 (ESF) • Introduction of F-GEN-01 (SC) • Introduction of D-21 (Post TC) • Wording change LOV to MPPT • Fuel specification simplification • Elect To Comply with CS-0791 at Amdt 20 	20 May 2019
40	09.07.2019	<ul style="list-style-type: none"> • Introduction of ACJ319 NEO 	09 July 2019
41	21.08.2019	<ul style="list-style-type: none"> • Introduction of ETOPS approval for A319-151N,-153N, ACJ319N and A320-253N,-272N,-273N • Introduction of WV 065 for A321-2xxN and A321-2xxNX aircraft 	No Change
42	16.09.2019	<ul style="list-style-type: none"> • Introduction of Special Condition D-24 Installation of Airbags in the backrest of seats (SC) for all the A320 family • Introduction of WV 083 for the A320 NEO 	No Change
43	26.11.2019	<ul style="list-style-type: none"> • Correction of typo in the whole document: LEAP1Axx replaced by LEAP-1Axx • Correction of typo: §6 Type Certification Date for A321 – Issue of MOD 157272 corrected from 2 to 3 • Introduction of Special Condition D-25 – Installation of structure mounted airbag for all the A320 family • Introduction of Weight Variant 085 for the A320-251N/-252N/-253N/-271N/-272N/-273N • Introduction of the new rating for the A319-153N: LEAP-1A26E1 jet engines (MOD 166794) • Introduction of MaxPax for A320-252N/-253N/-272N/-273N (mod 156723 iss 7) 	No Change
44	29.11.2019	<ul style="list-style-type: none"> • Introduction of A319-171N 	29 November 2019



SECTION 5: ADMINISTRATIVE – continued

Issue	Date	Changes	TC issue
45	20.12.2019	<ul style="list-style-type: none"> • Introduction of WV 071 for A320-252N/-253N/-273N aircrafts • Introduction of WV 069 for A320-252N/-253N/-273N aircrafts • Introduction of WV 120 for A319-153N • Introduction of SC D-27 	No Change
46	25.06.2020	<ul style="list-style-type: none"> • Introduction of WV 063 for A321-251N/-251NX/-252N/-252NX/-253N/-253NX/-271N/-271NX/-272N/-272NX aircrafts • Introduction of MaxPax for A321-252N/-272N (mod 157272 iss 4) • Introduction of ETOPS 120mn & 180mn approval for A319-171N with engine PW1124G-JM, A319-153N with engine CFM LEAP-1A26E1 and A320-251N with engine CFM LEAP-1A26E1 • A321 series §4.8: “CS 25.307 under CS25 Amdt. 18” is corrected by “CS 25.307(a) under CS25 Amdt. 18” as all other sub-sections of .307 are not applicable to MaxPax • A321 series – Maximum seating capacity : the configuration with 200 MPSC and Cabin configuration C-I-I-C was added • A319 series: the applicability of MOD 152777 to A319-115, A319-132 and A319-133 models was removed • A320 series: add the MOD 162339 as part of the A320 Corporate Jet definition • A319 series: add the MOD 162338 as part of the A320 Corporate Jet definition 	No Change
47	10.02.2021	<ul style="list-style-type: none"> • Typo in paragraph 4.8 corrected to 4.10 of A319 section 3, part II • For A319 Neo ACJ, addition in section 3, part II, paragraph 4.10 of limitation in case of project K5. • For A319, addition of limitations in section 3, part III, paragraph 20 in case of project K5 and MOD 167900. • A319 section 3 part III paragraph 5 addition of bullet 10 to harmonise with A320CJ. • For A320, addition in section 1, part III, paragraph 20 of a limitation linked to MOD 167668 • All sections part II, paragraph 8: addition of ESF B-17 reference. • A320 section 1 part III paragraph 5: ACJ320 NEO sentence on engine to harmonise with ACJ319 • A319/A320/A321 Part II paragraphs 4 reviewed to put 25.853(a)(b) at change 13 since MSN 118 (due to Airbus MOD 21682) 	No change



SECTION 5: ADMINISTRATIVE – continued

Issue	Date	Changes	TC issue
48	04.05.2021	<ul style="list-style-type: none"> • A319/A320/A321 Inclusion of SC D-28, in Part II. • A319/A320/A321 Inclusion of ESF D-31 • A319/A320/A321 Inclusion of EtC related to ESF D-31 with MOD 167557 • A321 ACF: amdt 19 for CS25.603(a) with MOD 166104 (Hero and Effect light) added in EtC. • A319: addition MOD 161765 for Cat II/III Autoland in Part IV notes • A320 part III paragraphs 5 engines: inclusion of the PW engines • All TCDS: Removal of CRI notion. • A318/A319/A320/A321: inclusion of limitation related to incomplete cabin MOD 153648 in Part III paragraph 20 for A318/A319/A320/A321. • A320 paragraph 4.10 corrected from CS25 Amdt 2 §25.21 (b) to §25.21 (c) 	No change
49	03.02.2022	<ul style="list-style-type: none"> • A318/A319/A320/A321 Part II paragraphs 8: introduction of ESF FCD MULTI-01 • WV080 introduced for A321 ACF • Removal of paragraph 9 “Production conditions” to harmonise with other programs • Harmonisation of naming convention: « N » when it is linked to a model and « NEO » when it is related to the family. • Removal of other reference than CML for the list of additives • Correction of typo for A320 NEO and A319 NEO two PW instead of two IAE. • Addition of missing models in certification basis of A320 para 4.1 • CS-ACNS: clarification added in part II paragraphs 7 and 9.x for all models. • 165947: introduction of SC D-33 + update of CCD information in part V of each Series following MOD 165947 iss 1 approval • Addition of Max Pax A319-151N/-153N/-171N with MOD 159533 iss2 “Max Pax” in SECTION 3, part I, paragraph 1 and in part II, paragraph 4.11. • Update of title for EC G-11 to Turbine Engine - Maximum Take-Off Power and/or Thrust Duration – General Definition 	No change



SECTION 5: ADMINISTRATIVE – continued

Issue	Date	Changes	TC issue
50	03.05.2022	<ul style="list-style-type: none"> • Addition of SC D-35 in post TC special conditions of A321 (part II paragraph 5) • Addition WV103 on A320 NEO • P-9 removal as MoC • (re)Correction of typo for A320 NEO A321 NEO and A319 NEO two IAE instead of two PW. 	No change
51	02.06.2023	<ul style="list-style-type: none"> • Correction of mistake by adding of A319-171N in relation with MOD 161765 in Part II paragraph 9 and in Part VI Notes • Removal of “-continued” in the headers mentioned in front of the series. • Correction of AIRBUS S.A.S. in page 57 • Move of EtC into airworthiness requirements (Part II, paragraphs 4) • In all sections, removal of several AMC references. • Correction in Engine paragraph of A321-271N/A321-271NX: two PW replaced by two IAE. • Correction history of revision for rev 46 mentioning 20 instead of 200 MSPC. • Addition of SC F-MULTI-04 - Rechargeable Lithium Battery Installations • Addition of SC SC F-37 – ATN over SATCOM • Addition of WV067 on A321N and A321NX • For A320 and A321, addition in Part II paragraph 4 sentence on bulletproof (compliance to Amdt 22) • List of models corresponding to CEO, NEO in Part I, paragraph 2. • “OPTIONAL” has been replaced by clearer sentence. • Section IV of each model: “The complete set of Instructions for Continued Airworthiness is identified in paragraph 2 of the Aircraft Maintenance Manual introduction.” • Section A320 part III paragraph 5: PW 1127G1JM removed as engine not for A320. • All sections Part VI created for Part 26 compliance information. • Harmonisation with other TCDS: issue reference in the equipment lists replaced by “at latest approved issue”. • Part II paragraph 4 of A319/A320/A321: ACNS upgrade linked to configuration with ELT-DT. 	No change



SECTION 5: ADMINISTRATIVE – continued

Issue	Date	Changes	TC issue
52	28.02.2024	<ul style="list-style-type: none"> SECTION 2, part II, paragraph 4.12 - Typo correction for MOD ref 153213 changed to 163213 (up to 3 additional central tanks) SECTION 3 - Addition of A319-173N SECTION 1, part III, paragraph 5 - Rating corporate jet 29k for A320-271N ACJ with MOD 173371 SECTION 2, part II, paragraph 4.12 - E-Rudder certification basis upgrade for A321. SECTION 1-2-3, part II, paragraph 7 - DPOS ESF F-122 added for A319-A320-A321 SECTION 1-2-3-4, part I, paragraph 4 - Upgrade of CS-FCD at issue 2 for all aircraft. SECTION 3, part II, paragraph 7 - Applicability of ESF SE-63 exit sign which was forgotten for A319. Rearrangement of the cover page as these models were accidentally moved in the A321 column SECTION 3, part III, paragraph 5 - A319ACJ bullet 10 page 135 – correction of typo in MOD reference 	28 February 2024
53	20.03.2024	<ul style="list-style-type: none"> SECTION 1, part III, paragraph 13 Addition of WV057 for A321 NEO and ACF. SECTION 1, part II, paragraph 4.12.7 – clarification of the sentence. 	No

-END-

