

European Aviation Safety Agency

European Technical Standard Order

Subject: Extended Squitter Automatic Dependent Surveillance - Broadcast (ADS-B) and Traffic Information Services (TIS-B) Equipment Operating on the Radio Frequency of 1090 Megahertz (MHz)

1 - Applicability

This ETSO gives the requirements which Extended Squitter Automatic Dependent Surveillance - Broadcast (ADS-B) and Traffic Information Services - Broadcast (TIS-B) Equipment Operating on the Radio Frequency of 1090 Megahertz (MHz) that are manufactured on or after the date of this ETSO must meet in order to be identified with the applicable ETSO marking.

2 - Procedures

2.1 - General

Applicable procedures are detailed in CS-ETSO Subpart A.

2.2 - Specific

None.

3 - Technical Conditions

3.1 - Basic

3.1.1 - Minimum Performance Standard

Standards set forth in the RTCA DO-260B, Minimum Operational Performance Standards for 1090 MHz Extended Squitter Automatic Dependent Surveillance - Broadcast (ADS-B) and Traffic Information Services - Broadcast (TIS-B), dated 02/12/2009, section 2.

This ETSO supports two major classes of 1090 MHz ADS-B and TIS-B equipment:

(a) Class A equipment, consisting of transmit and receive subsystems; and

(b) Class B equipment, containing a transmit subsystem only

(a) Class A equipment includes Classes A0, A1, A1S, A2 and A3. This standard requires 1090 MHz airborne Class A equipment to include the capability of receiving both ADS-B and TISB messages and delivering both ADS-B and TIS-B reports, as well as transmitting ADS-B messages. A Receive-only Class of equipment is allowed.

ETSO-C166b

Date: 05.07.2012

(b) **Class B equipment** includes Classes B0, B1, and B1S. Classes B0, B1, and B1S are the same as A0, A1, and A1S, except they do not have receive subsystems. Note that Classes B2 and B3 are not for aircraft use.

3.1.2 - Environmental Standard

See CS-ETSO Subpart A paragraph 2.1. The required performance under test conditions is defined in RTCA/DO-260B section 2.4

3.1.3 - Computer Software

See CS-ETSO Subpart A paragraph 2.2.

3.1.4 - Electronic Hardware Qualification

See CS-ETSO Subpart A paragraph 2.3.

3.2 - Specific

~~None~~

3.2.1 Failure Condition Classification

See CS-ETSO Subpart A paragraph 2.4.

Failure of the function defined in paragraph 3.1.1 of this ETSO has been determined to be a major failure condition.

NOTE: The major failure condition for transmission of incorrect ADS-B messages is based on use of the data by other aircraft or Air Traffic Control for separation services.

4 - Marking

4.1 - General

Marking as detailed in CS-ETSO Subpart A paragraph 1.2.

4.2 - Specific

Transmitting and receiving components must be permanently and legibly marked.

The following table explains how to mark components.

RTCA/DO-260AB provides the equipment class in Section 2.1.11, and the receiving equipment type in Section 2.2.6.

<i>If component can:</i>	<i>Mark it with:</i>	<i>Sample marking pattern:</i>
Transmit and receive	Equipment class it supports, and Receiving equipment type	Class A0/Type 1
Transmit, but not receive	Equipment class it supports	Class B1, or Class A3-Transmitting Only
Receive, but not transmit	Equipment class it supports, and Receiving equipment type	Class A2/Type 2-Receiving Only

ETSO-C166b

Date: 05.07.2012

5 - Availability of Referenced Document

See CS-ETSO Subpart A paragraph 3.