

European Aviation Safety Agency

Certification Specifications
and
Guidance Material
for
Cabin Crew Data
CS-CCD

Initial Issue

31 January 2014¹

¹ For the date of entry into force of this Amendment, kindly refer to Decision 2014/006/R in the [Official Publication](#) of the Agency

CONTENTS
CS-CCD – Cabin Crew Data

BOOK 1 – CERTIFICATION SPECIFICATIONS

SUBPART A GENERAL

- CS CCD.050 Scope
- CS CCD.100 Applicability
- CS CCD.105 Definitions
- CS CCD.110 OSD box concept – status of provided data

SUBPART B DETERMINATION OF A NEW TYPE AND A VARIANT

- CS CCD.200 Determination process
- CS CCD.205 Determination elements
- CS CCD.210 Determination of a new type
- CS CCD.215 Determination of a variant

SUBPART C TYPE SPECIFIC DATA FOR CABIN CREW

- CS CCD.300 Data required from the applicant
- CS CCD.305 Supplementary data provided at request of the applicant
- CS CCD.310 Type specific data content
- Appendix 1 to CS CCD.310 Type specific data content

SUBPART D CABIN ASPECTS OF SPECIAL EMPHASIS

- CS CCD.400 Cabin aspects of special emphasis

BOOK 2 – GUIDANCE MATERIAL

SUBPART A GENERAL

- GM1 CCD.110 OSD box concept – status of provided data

SUBPART B DETERMINATION OF A NEW TYPE AND A VARIANT

- GM1 CCD.205(b)(2)(vi) Determination elements
- GM1 CCD.205(b)(4) Determination elements
- GM1 to Appendix 1 to CS CCD.200(b)(1) Aircraft difference table
- GM2 to Appendix 1 to CS CCD.200(b)(1) Aircraft difference table
- GM3 to Appendix 1 to CS CCD.200(b)(1) Aircraft difference table

SUBPART C TYPE SPECIFIC DATA FOR CABIN CREW

- GM1 to Appendix 1 to CS CCD.310 Type specific data content

CS-CCD

Book 1

Certification Specifications

Cabin Crew Data

CS-CCD BOOK 1

SUBPART A

GENERAL

CS CCD.050 Scope

These Certification Specifications for Cabin Crew Data (CS-CCD) establish the specifications for the applicant for a type certificate, change approval or supplemental type certificate to develop and provide:

- (a) data for the determination process of a new type or variant for cabin crew; and
- (b) type specific data for cabin crew.

CS CCD.100 Applicability

These Certification Specifications are applicable to:

- (a) aircraft with a passenger seating capacity of more than 19 seats;
- (b) aircraft with a passenger seating capacity of 19 seats or less required to carry cabin crew; and
- (c) any other aircraft with a passenger seating capacity of 19 seats or less if voluntarily elected by the applicant.

CS CCD.105 Definitions

Within the scope of these Certification Specifications, the following definitions apply:

- (a) *Applicant* means an applicant for, or a holder of, a type certificate (TC), change approval or supplemental type certificate (STC), applying for the approval by the Agency of the related operational suitability data (OSD) for cabin crew.
- (b) *Base aircraft* means an aircraft used as a reference to compare differences with another aircraft.
- (c) *Candidate aircraft* means an aircraft subject to the evaluation process.
- (d) *New type* means an aircraft different from the base aircraft requiring completion of aircraft type specific training.
- (e) *Passenger deck* means a deck where passenger seats or cabin doors/exits or both are installed.
- (f) *Passenger seating capacity* means the passenger seating capacity of the aircraft that is subject to initial TC process as specified in the relevant type certification data sheet or the maximum passenger seating configuration of an individually configured aircraft.
- (g) *End user* means an operator or training organisation approved by the competent authority to provide training courses for cabin crew.
- (h) *Type specific data* means all design related data relevant to new type(s) or variant(s).
- (i) *Variant* means an aircraft that has differences to the base aircraft requiring completion of differences training.

CS-CCD BOOK 1

CS CCD.110 OSD box concept – status of provided data

CS-CCD specifies data required from the applicant and data provided at the request of the applicant. Data provided by the applicant is presented as mandatory or non-mandatory (recommendations) for the end user.

- (a) Data required from the applicant and mandatory for the end user (Box 1):
 - CS CCD.200
 - CS CCD.205
 - CS CCD.210
 - Appendix 1 to CS CCD.200(b)(1) including Impact assessment (a)
 - CS CCD.300
 - CS CCD.310
 - Appendix 1 to CS CCD.310
 - CS CCD.400
- (b) Data required from the applicant and non-mandatory (recommendations) for the end user (Box 2):
 - CS CCD.215
 - CS CCD.400
- (c) Data at request of the applicant and mandatory for the end user (Box 3):
 - Appendix 1 to CS CCD.200(b)(1) Impact assessment (b)
 - CS CCD.305(a)
- (d) Data at request of the applicant and non-mandatory (recommendations) for the end user (Box 4):
 - CS CCD.305(b)

CS-CCD BOOK 1

SUBPART B

DETERMINATION OF A NEW TYPE AND A VARIANT

CS CCD.200 Determination process

The candidate aircraft is determined as a new type or a variant of the base aircraft following the determination process conducted by the Agency. For this purpose the applicant:

- (a) identifies differences by comparing the type specific elements specified in CS CCD.205; and
- (b) completes an aircraft difference table using:
 - (1) the form specified in Appendix 1 to CS CCD.200(b)(1); or
 - (2) the applicant's form provided it contains the elements specified in Appendix 1 to CS CCD.200(b)(1) as applicable to the candidate aircraft, and the form is acceptable to the Agency.

CS CCD.205 Determination elements

- (a) At least the following type specific elements, as specified in Appendix 1 to CS CCD.200(b)(1) are assessed to determine whether a candidate aircraft is a new type or a variant of the base aircraft:
 - (1) aircraft configuration;
 - (2) doors and exits;
 - (3) aircraft systems; and
 - (4) normal and emergency operations.
- (b) When identifying differences of the elements specified in (a), the applicant assesses the following:
 - (1) aircraft configuration:
 - (i) number of aisles - single/multi; narrow/wide-bodied; and
 - (ii) number of passenger decks;
 - (2) doors and exits:
 - (i) number, types and location;
 - (ii) direction of movement of the operating handle;
 - (iii) direction of door/exit opening;
 - (iv) door/exit arming/disarming;
 - (v) power assist mechanism;
 - (vi) assisting evacuation means; and
 - (vii) door/exit electrical warning system;
 - (3) aircraft systems:
 - (i) system operation (i.e. system function, method of operation, malfunction, reset, duration); and
 - (ii) location;
 - (4) in normal and emergency operations, any design-related element that would impact either on normal operations or on emergency operations or on both normal and emergency operations.

CS-CCD BOOK 1

CS CCD.210 Determination of a new type

- (a) The candidate aircraft is determined a new type:
 - (1) if so documented in the application and demonstrated to the Agency; or
 - (2) as a result of the determination process required by CS CCD.200.
- (b) The candidate aircraft is determined a new type if the type specific elements of CS CCD.205(b)(1) and (b)(2) are different to the base aircraft.
- (c) The following need not be a factor in determining the candidate aircraft as a new type unless as specified in (d):
 - (1) one additional pair of doors/exits of the same type and operation as any type installed on the base aircraft; or
 - (2) doors/exits that are de-rated; or
 - (3) self-help exit types as defined by CS-25.
- (d) If no differences are identified in the type specific elements of CS CCD.205(b)(1) and (b)(2), but differences are identified in the type specific elements of CS CCD.205(b)(3) or (b)(4) or in both and are combined with one or more of the differences specified in (c), the impact of those differences is assessed and determination of the candidate aircraft as a new type is considered.
- (e) When identifying differences in accordance with CS CCD.205(b)(2)(i), if the number, location and operation of doors/exits is the same but the type of installed door/exit is different to the base aircraft, the candidate aircraft need not be determined as a new type.
- (f) If differences are identified in CS CCD.205(b)(3) only, the candidate aircraft need not be determined as a new type.

CS CCD.215 Determination of a variant

- (a) The candidate aircraft that has not been determined as a new type is determined a variant of the base aircraft.
- (b) Existing differences and their assessed impact are compiled in the aircraft difference table in accordance with CS CCD.200(b)(1), or using the applicant's standard form in accordance with CS CCD.200(b)(2), to support the development of the differences training by end user(s).

CS-CCD BOOK 1

Appendix 1 to CS CCD.200(b)(1) Aircraft difference table

For the purpose of filling in the aircraft difference table, the applicant selects the base and the candidate aircraft.

The aircraft difference table complies with the following format, or equivalent in accordance with CS CCD.200(b)(2).

CS-CCD BOOK 1

Appendix 1 to CS CCD.200(b)(1) Aircraft difference table

Aircraft difference table

Base aircraft						
Candidate aircraft						
Determination elements	Existing difference from base aircraft	Description of identified differences	Impact assessment			
	Yes		(a)		(b)	
			1. Impact on description of the element	2. Impact on operation of the element	1. Potential impact on procedures	2. Combined impact on operation of the element and potentially on procedures
AIRCRAFT CONFIGURATION						
Single aisle						
Multi aisle						
Narrow-bodied						
Wide-bodied						
Single passenger deck						
Multi passenger deck						
DOORS AND EXITS						
Type(s)						
Number						
Location						

CS-CCD BOOK 1

Aircraft difference table

Base aircraft

Candidate aircraft

Determination elements	Existing difference from base aircraft	Description of identified differences	Impact assessment			
			(a)		(b)	
	Yes		1. Impact on description of the element	2. Impact on operation of the element	1. Potential impact on procedures	2. Combined impact on operation of the element and potentially on procedures
Features (e.g. door/exit assist handles)						
Controls (e.g. door/exit locking indicators)						
Electrical operation and malfunction						
Direction of movement of the operating handle						
Direction of door/exit opening						
Door/exit arming/disarming						
Power assist mechanism and malfunction						
Door/exit electrical warning system						
Operation from inside in normal mode						
Operation from inside in emergency mode						
Operation from outside						

CS-CCD BOOK 1

Aircraft difference table

Base aircraft

Candidate aircraft

Determination elements	Existing difference from base aircraft	Description of identified differences	Impact assessment			
			(a)		(b)	
	Yes		1. Impact on description of the element	2. Impact on operation of the element	1. Potential impact on procedures	2. Combined impact on operation of the element and potentially on procedures
Integral stair						
Assisting evacuation means						
Type, number and location of units (e.g. escape slide/slide raft/ramp slide)						
Type and number of additional floatation means (e.g. life raft)						
Single/multi-lane units						
Life lines						
Operation (automatic/manual/electrical) and inflation time						
Slide girt bar engagement (manual/automatic)						
Signalling means of slide readiness (e.g. stop sign/barber pole)						

CS-CCD BOOK 1

Aircraft difference table

Base aircraft

Candidate aircraft

Determination elements	Existing difference from base aircraft	Description of identified differences	Impact assessment			
			(a)		(b)	
	Yes		1. Impact on description of the element	2. Impact on operation of the element	1. Potential impact on procedures	2. Combined impact on operation of the element and potentially on procedures
Capacity and overload						
Detaching and separating from aircraft						
Slide/life raft survival kit (integral/separate)						
Possibility to transfer slide/raft to another door/exit						
Emergency signalling system (e.g. attached ELT; built-in radio locator beacon (RLB)) and activation on land/in water						
AIRCRAFT SYSTEMS						
(a) emergency lighting system:						
Controls						
Interior emergency lighting						
Exterior emergency lighting						

CS-CCD BOOK 1

Aircraft difference table

Base aircraft

Candidate aircraft

Determination elements	Existing difference from base aircraft	Description of identified differences	Impact assessment			
			(a)		(b)	
	Yes		1. Impact on description of the element	2. Impact on operation of the element	1. Potential impact on procedures	2. Combined impact on operation of the element and potentially on procedures
(b) evacuation alarm signal system:						
Availability of activation/indication panel (flight crew/cabin compartment)						
Alert indications						
(c) smoke detection system:						
Function						
Alert indications (aural/visual)						
Availability of smoke barrier						
(d) automatic fire extinguishing system:						
Function of built-in fire extinguishing system						
(e) drop-down oxygen system:						
Type (e.g. gaseous, chemical)						

CS-CCD BOOK 1

Aircraft difference table

Base aircraft

Candidate aircraft

Determination elements	Existing difference from base aircraft	Description of identified differences	Impact assessment			
			(a)		(b)	
	Yes		1. Impact on description of the element	2. Impact on operation of the element	1. Potential impact on procedures	2. Combined impact on operation of the element and potentially on procedures
Activation						
Indications associated with activation of oxygen system (changes of cabin altitude);						
(f) communication system:						
Location of handset unit(s)						
Possibility of interphone calls in normal and emergency circumstances between cabin and flight crew compartment						
Availability of aural/visual indications associated with interphone calls in normal and emergency circumstances						
Signalling panels associated with communication system						
(g) public address system:						

CS-CCD BOOK 1

Aircraft difference table

Base aircraft

Candidate aircraft

Determination elements	Existing difference from base aircraft	Description of identified differences	Impact assessment			
			(a)		(b)	
	Yes		1. Impact on description of the element	2. Impact on operation of the element	1. Potential impact on procedures	2. Combined impact on operation of the element and potentially on procedures
Location of microphone unit when independent from handset unit						
Priority order of public announcement system (flight crew handset/ SCCM handset/any other cabin crew handset/evacuation signal alarm)						
(h) control panels:						
Cabin crew panel(s) - controls related to evacuation, lavatory smoke, emergency lights						
(i) water system:						
Availability of manual water shut-off valve						
(j) other systems as applicable:						
NORMAL AND EMERGENCY OPERATIONS						
Design-related element(s) impacting on either						

CS-CCD BOOK 1

Aircraft difference table

Base aircraft

Candidate aircraft

Determination elements	Existing difference from base aircraft	Description of identified differences	Impact assessment			
			(a)		(b)	
	Yes		1. Impact on description of the element	2. Impact on operation of the element	1. Potential impact on procedures	2. Combined impact on operation of the element and potentially on procedures
normal operations or on emergency operations or on both normal and emergency operations relevant to the aircraft type						

CS-CCD BOOK 1

SUBPART C

TYPE SPECIFIC DATA FOR CABIN CREW

CS CCD.300 Data required from the applicant

- (a) The applicant includes the following in the type specific data for cabin crew:
- (1) all necessary data in accordance with CS CCD.310 to support the development of type specific training programme(s); and
 - (2) all necessary data in accordance with CS CCD.205 to support the development of differences training programmes.

CS CCD.305 Supplementary data provided at request of the applicant

In addition to CS CCD.300, the applicant may elect to provide supplementary data to support the development of relevant training programme(s) by end user(s), such as:

- (a) data which can include, but is not limited to, additional equipment and components, when supplied by the applicant:
- (1) portable safety and emergency equipment;
 - (2) passenger seat (seatbelt; seat operation; passenger control unit (PCU); body support floatation equipment where relevant);
 - (3) overhead stowage compartment (direction of opening/closing; weight limit);
 - (4) galley components (steam/microwave oven; bakery warmer; freezer; supplemental cooling system; hot beverage brewers/steamers; trash compactor);
 - (5) layout/description and use of installed galley compartments/components;
- (b) data used on a non-mandatory (recommendations) basis by end user(s), such as information that may be based on the training provided to cabin crew members participating in the emergency evacuation demonstration required by CS 25.803:
- (1) theoretical and practical modules for training programmes;
 - (2) delivery methods of the relevant training elements;
 - (3) duration of training to ensure the attainment of required knowledge and skills.

CS CCD.310 Type specific data content

The applicant includes in the type specific data for cabin crew at least the following elements in accordance with Appendix 1 to CS CCD.310, as applicable:

- (a) aircraft description, including:
- (1) general;
 - (2) flight crew compartment;
 - (3) cabin compartment; and
- (b) aircraft systems including associated equipment.

CS-CCD BOOK 1

Appendix 1 to CS CCD.310 Type specific data content

Type specific data content

The type specific data for cabin crew include the following, as relevant to the candidate aircraft:

Aircraft description

General

- (a) type of aircraft – narrow/wide-bodied; single/multi passenger deck;
- (b) range of operation and maximum operating altitude;
- (c) principal dimensions (length; height; width; wing span);
- (d) main characteristics (engines; landing gear; fuel tanks; flight controls; speed; maximum take-off weight);
- (e) engine danger area;
- (f) general information (air conditioning; pressurisation system; electrical power; auxiliary power unit (APU); slats; flaps);
- (g) location of cargo compartments and un-pressurised areas;
- (h) entrances and emergency exits (entrance and service doors; emergency exits; flight crew compartment window; flight crew compartment emergency hatch; avionics compartment);
- (i) passenger seating capacity (as determined during the relevant TC, change to TC or STC process);
- (j) required number of flight crew, number and location of cabin crew stations (required and additional);
- (k) aircraft crash estimated attitudes (e.g. nose or main landing gear retracted; afloat following a ditching).

Flight crew compartment

- (a) layout - number and type of installed seats (e.g. column mounted; comfort seat; folding seat);
- (b) description and operation of installed seat type (electrical/ manual; vertical/horizontal/recline/rotating movement; restraint system, i.e. seat belt/crotch strap/shoulder harness and locking mechanism);
- (c) oxygen system (stowage; type and description of mask; smoke goggles; N/100 % and Emergency pressure selector; operation);
- (d) flight crew compartment door and its monitoring system:
 - (1) door type (e.g. intrusion/penetration resistant);
 - (2) door components (e.g. locking latches; mortise lock; escape/decompression panel; viewing lens);
 - (3) door access control panel (in the case of installed security bullet proof door);
 - (4) door operation – normal/emergency access;
 - (5) means of monitoring (viewing lens; CCTV system);
- (e) exits and escape routes (primary/secondary; sliding window; emergency exit hatch; door escape panel) and escape devices (escape rope; inertia reels);
- (f) avionics compartment (location; purpose; operation of avionics access hatch; access from inside/outside).

CS-CCD BOOK 1

Cabin compartment

- (a) layout:
 - (1) number and type of installed crew seats (e.g. swivel/high-comfort/folding seat);
 - (2) description and operation of installed crew seats (restraint system, i.e. seat belt/shoulder harness; quick release buckle; shoulder harness inertial mechanism);
- (b) doors and exits - entrance/service doors/emergency exits:
 - (1) type(s) and number of door(s)/exit(s)/location/sill height;
 - (2) description of features/controls/operation – manual/electrical and malfunction;
 - (3) operation from inside in normal/emergency modes;
 - (4) operation from outside;
 - (5) arm/disarm system;
 - (6) power assist system and malfunction;
 - (7) integral stair;
 - (8) crew assist space;
 - (9) life lines;
 - (10) access door/opening port to cargo compartment from cabin compartment;
 - (11) critical surfaces on aircraft wings requiring 'no step' precautions;
 - (12) water level door clearance;
- (c) escape slide/slide raft/ramp slide/life raft:
 - (1) location and stowage;
 - (2) type and number of units (single/multi lane; single/multi buoyancy chamber/length and width);
 - (3) description and operation;
 - (4) slide arm/disarm;
 - (5) deployment and duration (automatic/manual);
 - (6) signalling means of slide readiness (e.g. stop sign/barber pole);
 - (7) capacity and overload;
 - (8) detaching and separating from aircraft;
 - (9) canopy installation;
 - (10) limitation/operation of inverted slide/life raft;
 - (11) slide/life raft equipment (description/operation/use);
 - (12) attached survival kit (location/content/operation);
 - (13) malfunction (transfer of slide/raft to another door; use as a hand held chute);
 - (14) emergency signalling system (e.g. attached ELT, built-in radio locator beacon (RLB) – operation on land/in water);
- (d) crew rest compartment:
 - (1) location(s) and layout;
 - (2) description and operation of entrance door and applicable access control panel;
 - (3) escape routes/emergency exit hatch – description/location/operation from the crew rest/cabin compartment;

CS-CCD BOOK 1

- (4) systems (fire/smoke detection and prevention; oxygen; communication; lighting; air conditioning);
- (5) crew control panels;
- (6) cabin signs;
- (e) lavatories:
 - (1) smoke detection system;
 - (2) built-in automatic extinguishing system;
 - (3) water system (water supply/water shut-off/water heater);
 - (4) waste system;
 - (5) flush/vacuum reset;
 - (6) electrical power;
 - (7) lavatory service unit (LSU);
 - (8) lavatory door - lock/unlock system from inside/outside;
 - (9) operation of waste bin flap;
- (f) passenger service unit (PSU) (oxygen container; pictogram(s); loudspeaker; reading light; call light; seat row identifier; air vent);
- (g) lift - location; description and operation; control panel; malfunction;
- (h) galley - description of galley systems.

Aircraft systems including associated equipment

- (a) lighting system:
 - (1) location and operation;
 - (2) interior normal and emergency lighting (ceiling; door sill; over wing exit handle light; exit location/marketing sign; floor proximity escape path marking);
 - (3) exterior emergency lighting (slide/raft integrated emergency lights; over wing lights);
- (b) evacuation alarm signal system:
 - (1) description, location and operation of activation/signal panel(s) (flight crew/cabin compartment);
 - (2) aural/visual alert indications;
 - (3) horn silence at cabin door/exit and flight crew compartment;
- (c) smoke detection system:
 - (1) location and function (passenger cabin/lavatory/crew rest compartment(s)/cargo compartment);
 - (2) location and description of aural/visual indications (warning chime/light; signalling means; reset);
 - (3) potential cause of smoke alarm activation;
 - (4) smoke barrier/removal (e.g. crew rest compartment staircase hatch; smoke curtain - description/operation/pre-flight check);

CS-CCD BOOK 1

- (d) fire prevention system:
 - (1) type – automatic/manual (e.g. temperature sensor; FES Discharge switch (fire extinguishing system));
 - (2) location and function of built-in fire extinguishing system (crew rest compartment(s); lavatory/cargo compartment/engines);
 - (3) built-in fire extinguishers – type of agent/content/operation/duration;
- (e) oxygen system:
 - (1) location (passenger cabin/crew station/crew rest compartment(s)/ lavatory/galley);
 - (2) number and distribution of masks in container unit(s);
 - (3) activation/operation/duration of oxygen system and malfunction;
 - (4) aural and visual indications associated with activation of oxygen system;
 - (5) medical oxygen port;
- (f) electrical system:
 - (1) galley - hot water container; control panel – control switches; circuit breakers; galley emergency power off switch;
 - (2) lift (unit operation; control panel; circuit breakers systems);
 - (3) door electrical warning system (cabin pressure/slide armed/safeguard sensor);
 - (4) power socket (flight crew/cabin compartment);
 - (5) lavatory (razor outlet; built-in hairdryer; water heating system);
 - (6) passenger seat (electrical operation; seat power outlet);
 - (7) video control centre/passenger individual screen/cabin main screen;
 - (8) aircraft own electrical power and APU;
- (g) communication system:
 - (1) location of handset unit(s) (crew station/flight crew/crew rest compartment(s));
 - (2) description and use of interphone integrated keys;
 - (3) operation of interphone and initiating calls in normal and emergency circumstances (calls: cabin to flight crew compartment; cabin crew to cabin crew station; cabin/flight crew compartment to crew rest compartment(s); cabin crew/flight crew to purser and vice versa);
 - (4) aural/visual indications associated with interphone calls in normal and emergency circumstances;
 - (5) location and description of signalling panels associated with communication system;
 - (6) emergency communication alert system (ECAS) – description/location/operation in cabin and flight crew compartment;
- (h) passenger address system:
 - (1) location/description/operation of handset unit(s) (crew station/flight crew compartment/crew rest compartment(s));
 - (2) description of operation in cabin/flight crew/crew rest compartment(s);
 - (3) description/operation of the public announcements broadcast to the entire/individual cabin compartment(s);
 - (4) availability of loudspeakers in passenger cabin/flight crew/crew rest compartment(s)/galley/lavatory and muted volume;

CS-CCD BOOK 1

- (5) description of the priority order of public announcement system (e.g. flight crew handset/purser handset/any other cabin crew handset/evacuation signal alarm);
- (6) automatic broadcast of public announcements (description / operation);
- (i) passenger call system:
 - (1) location of activation (passenger seat/lavatory);
 - (2) way to initiate/cancel/disable passenger call system;
 - (3) signalling system (indication (aural/visual); control panels);
- (j) water system:
 - (1) areas of supply;
 - (2) location and operation of water supply manual shut-off valve (galley/lavatory; partial or entire cabin supply);
 - (3) water tanks (location of checking water tanks status);
- (k) waste system:
 - (1) location (galley/lavatory);
 - (2) waste tanks (location of checking waste tanks status);
- (l) air conditioning/ventilation/pressurisation – source of supply (engines/external ground power (EGP)/APU); control management);
- (m) control panels:
 - (1) cabin crew panel (cabin management system) – main/additional panel(s); location; description of installed functions; operation; malfunction;
 - (2) cabin crew indication panel - type (i.e. area indication panel/area call panel); location (crew station/galley/crew rest compartment(s)); description of functions;
 - (3) cabin air/floor temperature control panel – location and operation; areas of effect;
 - (4) cabin signs – location (door/exit area; passenger cabin; crew station; crew rest compartment(s); galley; LSU); type (e.g. fasten seatbelt/no smoking/return to seat/lavatory occupied/exit sign); aural/visual indication;
- (n) other systems – installed emergency locator transmitter.

CS-CCD BOOK 1

SUBPART D

CABIN ASPECTS OF SPECIAL EMPHASIS

CS CCD.400 Cabin aspects of special emphasis

The applicant includes, as applicable, any information relevant to the aircraft that cabin crew and end users should be aware of. Such information can include, but is not limited to:

- (a) information identified during emergency evacuation demonstration required by CS 25.803, such as:
 - (1) passenger movement during evacuation including door/exit overload,
 - (2) dried up door/exit and subsequent re-direction,
 - (3) door/exit by-pass recommendations,
 - (4) general crowd control,
 - (5) seating location of cabin crew members,
- (b) other unique elements identified during the certification process, e.g. direct view, trolley lift barrier, external viewing means, remote cabin areas, etc.

CS-CCD

Book 2


Guidance Material

CS-CCD BOOK 2

SUBPART A GENERAL

GM1 CCD.110 OSD box concept – status of provided data

OSD BOX CONCEPT DIAGRAM



Box 1: required from the applicant; mandatory for end users

Box 2: required from the applicant; non-mandatory (recommendations) for end users

Box 3: at request of the applicant; mandatory for end users

Box 4: at request of the applicant; non-mandatory (recommendations) for end users

CS-CCD BOOK 2

SUBPART B

DETERMINATION OF A NEW TYPE AND A VARIANT

GM1 CCD.205(b)(2)(vi) Determination elements

ASSISTING EVACUATION MEANS

Assisting evacuation means include, but are not limited to, escape slide, slide raft, ramp slide, life raft, life lines, signalling means of slide readiness, e.g. barber pole or stop sign.

GM1 CCD.205(b)(4) Determination elements

NORMAL AND EMERGENCY OPERATIONS

Design related elements that could impact either on normal operations or on emergency operations or on both normal and emergency operations include, but are not limited to, cabin interior stairs, smoke barrier, e.g. smoke curtain.

GM1 to Appendix 1 to CS CCD.200(b)(1) Aircraft difference table

INSTRUCTIONS

The ADT may be used by the applicant to include, in addition to the listed elements, a detailed list of differences between the base and the candidate aircraft. For the purpose of filling in the aircraft difference table to identify differences between the base and the candidate aircraft, the following instructions should apply:

1. Differences to any of the specified determination elements should be identified in column 'Existing differences from the base aircraft';
2. Identified differences should be described in column 'Description of identified differences';
3. The corresponding sub-column(s) should be marked in the part 'Impact assessment', as relevant to the assessed element.

GM2 to Appendix 1 to CS CCD.200(b)(1) Aircraft difference table

IMPACT ASSESSMENT (a)

Part 'Impact assessment (a)' represents required provision from the applicant and mandatory application by the end user.

1. Column '*Impact on description of the element*' should be marked when there is an identified difference and the information of the identified difference needs to be provided to the user (cabin crew), e.g. location of manual water shut-off valve, location of emergency lighting control button on cabin management system panel. The column implies a knowledge requirement.
2. Column '*Impact on operation of the element*' should be marked if the identified difference affects the operation of the element, e.g. power assist mechanism on door/exit, detaching and separating slide raft from the aircraft, installation of canopy, controls related to evacuation, smoke, emergency lights on cabin crew control panel. The column implies knowledge and hands-on training requirement.

CS-CCD BOOK 2

GM3 to Appendix 1 to CS CCD.200(b)(1) Aircraft difference table

IMPACT ASSESSMENT (b)

Part 'Impact assessment (b)' represents provision at request of the applicant and mandatory application by the end user. The applicant may elect to provide the information to support the operator in identifying those areas which may require a review of procedures by the operator in relation to the identified difference.

1. Column '*Potential impact on procedures*' should be marked to indicate that operators, in relation to the identified difference, may need to assess if their procedures need to be amended, or new procedures be developed, e.g. built-in fire extinguishing system, evacuation alarm alert indications, capacity and overload of slide raft. Identification implies knowledge requirement attained by aided instruction.
2. Column '*Combined impact on operation of the element and potentially on procedures*' should be marked to indicate that the identified difference affects the operation of the element and may require the operators to assess if their procedures need to be amended or new procedures be developed, e.g. function of smoke detection system, door/exit electrical warning system, communication system. Identification implies knowledge requirement attained by aided instruction and hands-on training.

CS-CCD BOOK 2

SUBPART C

TYPE SPECIFIC DATA FOR CABIN CREW

GM1 to Appendix 1 to CS CCD.310 Type specific data content

SOURCE DOCUMENTS FOR TYPE SPECIFIC DATA

Type specific data for cabin crew need not be developed new by the applicant. They may originate from any technical documentation issued by the original manufacturer of the aircraft, aeronautical products, parts or appliances (e.g. aircraft flight manual (AFM), aircraft operating manual (AOM), aircraft maintenance manual (AMM), component maintenance manual (CMM), design documentation).

TYPE SPECIFIC DATA

Type specific data required by this Appendix contain detailed technical information useful for cabin crew to obtain general knowledge on the type of aircraft they are to be qualified on.