



EUROPEAN AVIATION SAFETY AGENCY
AGENCE EUROPÉENNE DE LA SÉCURITÉ AÉRIENNE
EUROPÄISCHE AGENTUR FÜR FLUGSICHERHEIT

Continuous Friction Measuring Equipment Use on Contaminated Runways

Vasileios Stefanioros
EASA – Airport Rulemaking Officer

Your safety is our mission.
easa.europa.eu



Background

- In 2011 AIB Norway issued a report of a theme investigation focused on the general framework for operations on contaminated and slippery runways
- The report is based on 30 reports of accidents and incidents related to operations on contaminated and slippery runways over a 10-year period
- AIB found that aircraft braking coefficient was not in accordance with the measured/ estimated runway friction coefficient



Background

- AIB Norway Safety Recommendation 2011/08T:

"...The AIB Norway recommends that ICAO, FAA, EASA and CAA Norway review and validate the permitted measuring (validity) ranges for approved friction measuring devices"

- EASA accepted the recommendation and in 2012 initiated a study through a public tender process

- Study concluded in 2013 and the final report has been presented at the beginning of October 2013



ICAO Provisions

- Current friction measurement equipment is not considered appropriate to provide friction values on runways contaminated by slush, wet snow or wet ice
- ICAO Annex 14, Amendment 11 (*effective Nov 13*)
 - *"2.9.7A Recommendation: Runway surface friction measurements made on a runway that is contaminated by slush, wet snow or wet ice should not be reported unless the reliability of the measurement relevant to its operational use can be assured."*



EASA Study

- Study has been divided into three parts:
 - Part 1 - Mathematical model of the motion of tyres on dry and contaminated surfaces and the means by which the decelerating forces acting on the tyres are determined
 - Part 2 – Design philosophy of a CFME to provide the data required to enable an appropriate relationship to be established between a friction device and aircraft braking action
 - Part 3 – Proposal for regulation of the operational use of CFME



EASA Study – Part 1

- Semi-empirical model substantiated by test data
- Calculation of decelerating forces acting on aircraft tyres when rolling or braking on dry or contaminated runway surface
- The force is taken to be the sum of the following:
 - Rolling resistance, since the tyre carcass absorbs energy
 - Movement of the tyre through or compressing a contaminant
 - Friction interaction between the tyre compound and the runway surface



EASA Study – Part 1

➤ The model depends upon knowledge of the following independent variables:

- Surface texture depth
- Depth of contaminant
- Density of the contaminant
- Tyre inflation pressure
- Nominal tyre width
- Nominal tyre diameter
- Vertical loading on the tyre
- Ground speed of aircraft



EASA Study – Part 1

- The first three variables are related to the runway and its conditions
- All the other variables are part of conventional performance calculations
- The variables together with a knowledge of aircraft braking system provides sufficient knowledge to determine decelerating forces
- The model can also be used to link the performance of aircraft and ground vehicles



EASA Study – Part 2

- The report assesses a pre-production device, both from laboratory tests and some field trials
- The device is shown to be capable of providing information on runways contaminated with substantial depths of water, slush or snow
- Apart from the conventional output, measurements enable the deduction of:
 - Depth of contaminating water
 - Equivalent water depth of contaminating slush, or
 - Depth and relevant mechanical properties of snow
- The device can be operated satisfactorily and safely in depths of water in excess of 20 mm at speeds up to 13.5 m/sec



EASA Study – Part 3

- The Regulatory approach covers the following:
 - Outline description of the various types of CFME
 - Regulatory objectives and regulatory framework when using CFME
 - Discusses the contents of an aircraft flight manual in relation to the use of CFME
- An appendix describes in broad terms the following
 - CFME regulation
 - Design specifications and applicability
 - Certification, design objectives and approval together with operational and runway maintenance use
 - Regulatory impact assessment and cost-benefit analysis



Way forward

- The Agency will evaluate the report and hold internal discussions
- Extensive field trials are required in order to validate the model
- Coordination with ICAO Friction Task Force
- Presentation and consultation with the Member States and Industry Stakeholders



EUROPEAN AVIATION SAFETY AGENCY
AGENCE EUROPÉENNE DE LA SÉCURITÉ AÉRIENNE
EUROPÄISCHE AGENTUR FÜR FLUGSICHERHEIT

Thank you very much for your
attention

Your safety is our mission.
easa.europa.eu