



EUROPEAN AVIATION SAFETY AGENCY
AGENCE EUROPÉENNE DE LA SÉCURITÉ AÉRIENNE
EUROPÄISCHE AGENTUR FÜR FLUGSICHERHEIT

PBN – Airworthiness Compliance

How have my aeroplane capabilities been
assessed?

Hette Hoekema
Avionics Expert – Certification Directorate

Your safety is our mission.
easa.europa.eu

The logo features a stylized yellow and orange starburst on the left, followed by the text 'PBN Manual: Navigation Specifications' in white on a blue background.

PBN Manual: Navigation Specifications

RNAV 10 (RNP-10)	→ AMC 20-12
RNAV 5 (BRNAV)	→ AMC 20-4
RNAV 2	--
RNAV 1 (~PRNAV)	→ JAA TGL-10 Rev. 1
RNP 4	--
RNP 2	--
RNP 1	--
Advanced RNP	--
RNP APCH:	
LNAV / LNAV/VNAV	→ AMC 20-27
LP / LPV	→ AMC 20-28 (LPV Only)
RNP AR APCH	→ AMC 20-26
RNP 0.3	--



PBN: Aircraft Qualification

- ICAO Nav. Specs, EASA AMCAs and FAA ACs all require that the following aspects to be considered:
 - Continuity
 - Integrity
 - Functional criteria
 - Performance
 - Aeroplane Flight Manual (AFM)

➤ Continuity:

- Continuity requirements define the allowable probability of failure conditions that lead to *loss of a function*.
- Requires an applicant to perform both quantitative and qualitative assessments as per CS/FAR XX.1309 and associated guidance material.
- Continuity is usually not a major issue in certification of aircraft for PBN.



PBN: Aircraft Qualification

➤ Integrity:

- Integrity requirements define the allowable probability of failure conditions that lead to *output (and display) of erroneous information*.
- Requires an applicant to perform both quantitative and qualitative assessments as per CS/FAR XX.1309 and associated guidance material.
- Integrity is often a major concern with certification of aircraft for RNP AR (details to follow) and sometimes LPV.

➤ Functional Criteria:

- Requirements for functional criteria address both the *functional capabilities* of the aeroplane and the *pilot-machine interface*: Displays, controls etc.
- Display of deviations from the path, in particular vertical deviations, are often reason for concern. Some designs are deemed marginally acceptable.
- Mitigation by procedure (not ideal).
- Industry to improve.

- Performance:
 - Performance requirements address the track-keeping capability of the aeroplane.
 - Often defined as: “...within () NM for 95% of the time”.
 - Where applicable these include vertical performance, for instance Baro-VNAV.
 - RNP AR criteria demand that the performance of the aeroplane under failure conditions be assessed.

- **Aeroplane Flight Manual (AFM):**
 - Contains both an overview of standards for which the aeroplane was qualified and flight crew procedures.
 - Both the qualifications and the procedures need to be accurate and clear and match the design.
 - RNP AR: The AFM will often refer to a separate document, e.g.:
 - Airbus: Airworthiness Compliance Document
 - Boeing: RNP Capabilities Document

- Aeroplane Flight Manual (AFM):
 - If compliance with a TGL or AMC is stated in the AFM, EASA will have verified airworthiness compliance of the aircraft against the applicable criteria.
 - E.g. sections 5 through 9 of AMC 20-27

- Absence of EASA AMC:
 - Not all ICAO Nav. Specs have matching TGLs or AMCs
 - Certification Review Item (CRI) process may provide solution in those cases.
 - The AFM will not refer to a TGL or AMC but instead to the ICAO concept, e.g. RNAV 2, RNP 4 etc.
 - Alternatively, the AFM may refer to an existing FAA AC, e.g. AC 20-138C.



PBN: Specific Aspects to Consider

- Baro-VNAV
 - Aircraft certified to older standards.
- RNP AR
 - Low RNP operations (RNP < 0.3 NM)



PBN: Specific Aspects to Consider

➤ Baro-VNAV Operations

- Most aircraft have been certified to standards that date back to the 1950s: ICAO PBN Manual, FAA AC 20-129.
- Not consistent with PANS-OPS criteria.
- AMC 20-27 and FAA AC 20-138C are more stringent and match PANS OPS.
- Not necessarily a problem, IATA/AEA study: Operations can safely be conducted to aerodromes with field elevation of 6000 ft MSL or less.
- Limited number of aerodromes affected.

➤ Baro-VNAV Operations

- When considering approval of AC 20-129 certified aircraft:
 - Functional criteria of AMC 20-27, in particular display of deviations, need to be considered in the OPS approval process.
- EASA Safety Information Bulletin (SIB) in preparation.



PBN: Specific Aspects to Consider

- RNP AR with RNP < 0.3 NM:
 - FMS software qualification of many aeroplanes does not comply with integrity requirements for low RNP OPS.
 - Otherwise aeroplanes are very capable (Performance)
 - AFM will contain certified values (e.g. 0.3 NM)
 - Airworthiness Compliance Document or similar document may state demonstrated values (e.g. 0.15 NM)



PBN: Specific Aspects to Consider

- RNP AR with RNP < 0.3 NM:
 - RNP AR, or SAAAR in the early days, started as special operations with specific approvals, limited in numbers.
 - Mostly in mountainous terrain.
 - Today however, AR operations have become much more commonplace. (Hundreds of procedures in US)
 - Quite often for noise abatement or traffic separation.



PBN: Specific Aspects to Consider

- RNP AR with RNP < 0.3 NM:
 - The differentiation between certified and demonstrated values reflects this trend:
 - *Certified* values:
 - Recognition of more generic nature of most current AR procedures.
 - Simplifies the Flight Operations Safety Assessment (FOSA)
 - *Demonstrated* values:
 - Recognition of special nature of a more limited number of procedures
 - Comprehensive FOSA required.

PBN: Specific Aspects to Consider

- ▶ RNP AR with RNP < 0.3 NM:
 - ▶ Example: Atlantic Airways, Vagar, Faroer.





PBN: Specific Aspects to Consider

- RNP AR with RNP < 0.3 NM.
 - Procedure: RNP 0.1 NM, MA < 1 NM
 - Aeroplane: A319
 - Certified to RNP 0.3
 - Demonstrated RNP: 0.1
 - Very extensive FOSA, considers a.o:
 - Flight crew training and excellent knowledge of terrain and weather conditions (home base)
 - Verification of *effectiveness* of TAWS*
 - Use of ground infrastructure for verification (DME distance)
 - Operational Approval granted.
(Courtesy Danish CAA)

PBN: Specific Aspects to Consider

- RNP AR with RNP < 0.3 NM:
 - * TAWS as mitigation (airworthiness):
 - TAWS was developed as a safety-net.
 - In order to generically serve as an effective means of mitigation, the TAWS should:
 - Be independent (positioning).
 - Be demonstrated to provide timely alerts, *when required*.
 - Issues:
 - Grid sizes too large
 - Terrain Database integrity
 - No applicant had been able to comply.
 - But: TAWS may have value in specific cases.





EUROPEAN AVIATION SAFETY AGENCY
AGENCE EUROPÉENNE DE LA SÉCURITÉ AÉRIENNE
EUROPÄISCHE AGENTUR FÜR FLUGSICHERHEIT

Thank you.

Your safety is our mission.
easa.europa.eu