



EUROPEAN AVIATION SAFETY AGENCY
AGENCE EUROPÉENNE DE LA SÉCURITÉ AÉRIENNE
EUROPÄISCHE AGENTUR FÜR FLUGSICHERHEIT

LoA (Letter of Acceptance) Type 1 and Type 2 databases

Friedhelm Runge
Avionics Systems Section Manager
15.1.2014

Your safety is our mission.
easa.europa.eu

- History
- Regulatory recognition
- Applicable Requirements
- Main Objectives
- Difference between LoA Type 1 and 2
- International recognition

LoA ↔ Letter of Acceptance

- From the beginning there is the expectation to verify data used for navigation against state published data (AIP)
- Easy during flight for B-RNAV demanding the handling of 3 waypoints
- Non practical for P-RNAV procedures and TGL 10 had checking requirements especially in the area of obstacle clearance
- Big airlines had AIP collections and checked each AIRAC cycle the FMS content against the AIP but approach did not work for smaller organisations
- Need for easier approach lead to LOA system



Regulatory recognition


- 2005: Navigation data requirements added to ICAO Annex 6 Part 1 section 7.4 => data integrity and meet intended function.
Reference to ED-76/DO-200A
- 2008: Introduction of EU OPS 1.873
Electronic navigation data management referring to LOA Type 2
- 2012: IR (EU) No 965/2012 recognition e.g. in AMC material CAT.IDE.A.355 Electronic navigation data management

- Defined in Opinion 1/2005
 - Not legal binding
 - Purely voluntary service
- Based on Production Organisation Approval (POA) principles and requirements
 - Paragraph numbering aligned with Part 21 Subpart G
 - AMC to Part 21 is applicable as well including principles for the oversight
- Includes EUROCAE ED-76/RTCA DO 200A compliance

- Provide AIP data content to the aircraft systems for use as intended
- Use a well managed and defined process able to deliver a database representing AIP data
- Ability to respect data quality requirements derived from the certified intended function
- Ability to handle customised/tailored data separated from other data
- Well managed reporting lines for anomalies and identified deficiencies



Aeronautical Data Chain (simplified)





LOA Type 1 vs Type 2

- LOA Type 2 delivers to the user, is linked to the equipment using the data
- LOA Type 1 (optional) delivers in an intermediate (e.g. ARINC 424) data format and is not linked to a dedicated use case



International recognition

- US: LOA acceptance is addressed in bilateral; Acceptance from one side is automatically accepted by the other side without further activities
- Canada:
GM1 CAT.IDE.A.355 Electronic navigation data management
(b) Equivalent to a Type 2 LoA is the FAA Type 2 LoA, issued in accordance with the Federal Aviation Administration (FAA) Advisory Circular AC 20-153 or AC 20-153A, and the Transport Canada Civil Aviation (TCCA) 'Acknowledgement Letter of an Aeronautical Data Process', which uses the same basis.



EUROPEAN AVIATION SAFETY AGENCY
AGENCE EUROPÉENNE DE LA SÉCURITÉ AÉRIENNE
EUROPÄISCHE AGENTUR FÜR FLUGSICHERHEIT

Questions?

Your safety is our mission.
easa.europa.eu