



TYPE-CERTIFICATE DATA SHEET

NO. EASA.A.599

for

ASG 32

Type Certificate Holder

Alexander Schleicher GmbH & Co. Segelflugzeugbau

Alexander-Schleicher-Str. 1
36163 Poppenhausen
Germany

For model: ASG 32
ASG 32 EI
ASG 32 Mi



Intentionally left blank



Contents

Section A: ASG 32	4
A.I General	4
A.II EASA Certification Basis	4
A.III Technical Characteristics and Operational Limitations	5
A.IV Operating and Service Instructions	7
A.V Notes	8
Section B: ASG 32 El.	9
B.I General	9
B.II EASA Certification Basis	9
B.III Technical Characteristics and Operational Limitations	10
B.IV Operating and Service Instructions	13
B.V Notes	14
Section C: ASG 32 Mi	15
C.I General	15
C.II EASA Certification Basis	15
C.III Technical Characteristics and Operational Limitations	16
C.IV Operating and Service Instructions	19
C.V Notes	20
Section D: Administrative Section	21
D.I Acronyms & Abbreviations	21
D.II Type Certificate Holder Record	21
D.III Change Record	21



Section A: ASG 32

A.I General

- | | |
|---|--|
| 1. Type/ Model/ Variant | |
| 1.1 Type: | ASG 32 |
| 1.2 Model: | ASG 32 |
| 2. Airworthiness Category | Sailplane, CS-22 - Utility |
| 3. Manufacturer | Alexander Schleicher GmbH & Co. Segelflugzeugbau |
| 4. EASA Type Certification Application Date | 01 November 2012 |
| 5. EASA Type Certification Date | 11 Februray 2016 |

A.II EASA Certification Basis

- | | |
|---|---|
| 1. Reference Date for determining the applicable requirements | |
| 2. Airworthiness Requirements | Certification Specification for Sailplanes and Powered Sailplanes, issued 24. September 2008 (CS-22, Amdt. 2) |
| 3. Special Conditions | EASA SC A.22.1-01 - 850 kg MTOM |
| 4. Exemptions | None |
| 5. (Reserved) Deviations | None |
| 6. Equivalent Safety Findings | CS 22.335 (f) calculation of V_D according to OSTIV
CS 22.585(a) reduced by factor 1.2 |
| 7. Environmental Protection | None |



A.III Technical Characteristics and Operational Limitations

1. Type Design Definition List of the drawing files ASG 32, issue 31.01.2016
2. Description Double-seat, mid-wing CRP/GRP/ARP-composite construction for FAI 20m class with flaps, double-panel Schempp-Hirth airbrakes on upper wing surface, winglets, water ballast tanks in the wing and optional in the fuselage, retractable landing gear with hydraulic disc brake, T-shaped horizontal tail (fixed horizontal stabilizer with elevator) fin and rudder.
3. Equipment
Min. required Equipment:
1 Air speed indicator (up to 300 km/h) (front seat)
1 Altimeter (front seat)
1 Outside air temperature gauge (front seat)
2 4-Point safety harness (symmetrical)
2 Parachute or Cushion for back rest (~ 8cm thickness)
Additional Equipment refer to Flight and Maintenance Manual
4. Dimensions
Span: 20,00 m
Wing area: 15,70 m²
Length: 9,07 m
Height: 1,84 m
5. Launching Hooks
Nose tow hook "E 22", LBA Datasheet No. 11.402/9
NTS
Safety hook „Europa G 88“, LBA Datasheet No. 60.230/2
6. Weak Links
Ultimate Strength:
- for winch- and auto-tow launching max. 1100 daN
- for aero-tow max. 1100 daN
7. Load Factors
+5,3 / -2,65 (up to V_A)
+4,0 / -1,5 (up to V_{NE})
8. Air Speeds
Manoeuvring Speed V_A 180 km/h
Never Exceed Speed V_{NE} 270 km/h
Maximum permitted Speeds
- with flaps at 1, 2, 3, 4 V_{FE} 270 km/h
- with flaps at 5,6 V_{FE} 180 km/h
- with flaps at L V_{FE} 150 km/h
- in rough air V_{RA} 180 km/h
- for winch launching V_W 140 km/h
- for aerotowing V_T 180 km/h
- for gear operation V_{LO} 180 km/h



9. Approved Operations Capability	VFR-Day only Cloud flying not permitted Aerobatic manoeuvres not permitted, except Spinning
10. Launch methods	Aerotow Winch and Auto-Tow
11. Maximum Masses	Max. Mass: 850 kg Max. Mass of Non-Lifting Parts: 550 kg
12. Centre of Gravity Range	156 mm – 385 mm aft of datum
13. Datum	Wing leading edge at root rib
14. Levelling Means	Slope 1000 : 27 placed on upper side of fuselage boom horizontal
15. Control Surface Deflections	Refer to Maintenance Manual
16. Minimum Flight Crew	1
17. Maximum Passenger Seating Capacity	1
18. Baggage/ Cargo Compartments	9 kg
19. Lifetime limitations	Refer to Maintenance Manual



A.IV Operating and Service Instructions

1. Flight Manual Flight Manual ASG 32, issue 01.12.2015, or later EASA approved revisions
2. Maintenance Manual Maintenance Manual ASG 32, issue 15.01.2016, or later revisions
3. Structural Repair Manual General Repair Manual for Alexander Schleicher Sailplanes and Powered Sailplanes, latest revision
4. Manual for the TOST Release, latest approved version



A.V Notes

1. Manufacturing is confined to industrial production.
2. The surface colour of all fibre reinforced parts, which are exposed to sun radiation, must be painted either in
 - White
 - RAL 2004 (Reinorange)
 - RAL 2009 (Verkehrsorange)
 - RAL 3020 (Verkehrsrrot)
 - or other colours listed in the maintenance manual section 13.4, maintenance instruction “coloured surfaces”Exceptions are the areas for markings and registration, engine bay and cockpit.
3. Alexander Schleicher TM 11 changes the Variant ASG 32 Mi into the Model ASG 32 Mi for which Section C of this TCDS applies



Section B: **ASG 32 EI**

B.I **General**

- | | |
|---|--|
| 1. Type/ Model/ Variant | |
| 1.1 Type: | ASG 32 |
| 1.2 Model: | ASG 32 EI |
| 2. Airworthiness Category | Sailplane, CS-22 - Utility |
| 3. Manufacturer | Alexander Schleicher GmbH & Co. Segelflugzeugbau |
| 4. EASA Type Certification Application Date | 28 October 2013 |
| 5. EASA Type Certification Date | 22 December 2017 |

B.II **EASA Certification Basis**

- | | |
|---|--|
| 1. Reference Date for determining the applicable requirements | |
| 2. Airworthiness Requirements | Certification Specification for Sailplanes and Powered Sailplanes, issued 24. September 2008 (CS-22, Amdt. 2) |
| 3. Special Conditions | SC 22.2014-01 – Electrical Propulsion
SC E-01 – Electrical Engine
SC B22.151-01 – Sustainer Assisted Aerotow |
| 4. Exemptions | None |
| 5. (Reserved) Deviations | None |
| 6. Equivalent Safety Findings | CS 22.335 (f) calculation of V_D according to OSTIV
CS 22.585(a) reduced by factor 1.2 |
| 7. Environmental Protection | ICAO Annex 16 (details refer to TCDSN EASA.A.599) |



B.III Technical Characteristics and Operational Limitations

1. Type Design Definition List of the drawing files ASG 32 EI, issue 15.12.2017
2. Description
Double-seat, mid-wing CRP/GRP/ARP-composite construction for FAI 20m class with flaps, double-panel Schempp-Hirth airbrakes on upper wing surface, winglets, water ballast tanks in the wing and optional in the fuselage, retractable landing gear with hydraulic disc brake, T-shaped horizontal tail (fixed horizontal stabilizer with elevator) fin and rudder.

Self-sustaining, electrical power-plant mounted in the centre fuselage.
3. Equipment
Min. required Equipment:
1 Air speed indicator (up to 300 km/h) (front seat)
1 Altimeter (front seat)
1 Magnetic compass (front seat)
1 Power-plant instrument (front seat)
1 Rear view mirror
1 Outside air temperature gauge (front seat)
1 4-Point safety harness (symmetrical) for each occupant
1 Parachute or Cushion for back rest (~ 8cm thickness) for each occupant
Additional Equipment refer to Flight and Maintenance Manual

Additionally required for instruction or of the pilot in command sits in the rear seat:
1 Air seed indicator in the rear seat (up to 300 km/h)
1 Altimeter in the rear seat
4. Dimensions
Span: 20,00 m
Wing area: 15,70 m²
Length: 9,07 m
Height: 1,84 m
5. Engine
 - 5.1 Model Alexander Schleicher EA900/1-25LK
 - 5.2 Type Certificate n/a (accepted as part of the airframe)
 - 5.3 Limitations Maximum Power: 25 kW at 3000 rpm
 - 5.4 Max. continuous revs 2500 rpm
 - 5.5 Max. overspeed revs 3000 rpm
 - 5.6 Max. motor temperature 110°C
 - 5.7 Max. power electronics temperature 80°C



6. Propeller

6.1 Model	Alexander Schleicher AS2F1-4/L155-88-N3
6.2 Type Certificate	EASA.P.004
6.3 Number of blades	2
6.4 Diameter	1550 mm +3mm / -10 mm
6.5 Sense of Rotation	Left

7. Battery

7.1 Battery capacity	26 Ah
7.2 Non-usable battery capacity	10 Ah (39%)
7.3 Max battery discharge temperature	60°C
7.4 Min battery discharge temperature	-20°C
7.5 Max battery charge temperature	50°C
7.6 Min battery charge temperature	0°C
7.7 Range of permissible cell voltage	3 – 4,15 V

8. Launching Hooks

Nose tow hook "E 22", LBA Datasheet No. 11.402/9
NTS
Safety hook „Europa G 88“, LBA Datasheet No.
60.230/2

9. Weak Links

Ultimate Strength:
- for winch- and auto-tow launching max. 1100 daN
- for aero-tow max. 1100 daN

10. Load Factors

+5,3 / -2,65 (up to V_A)
+4,0 / -1,5 (up to V_{NE})

11. Air Speeds

Manoeuvring Speed	V_A	180 km/h
Never Exceed Speed	V_{NE}	270 km/h
Maximum permitted Speeds		
- with flaps at 1, 2, 3, 4	V_{FE}	270 km/h
- with flaps at 5,6	V_{FE}	180 km/h
- with flaps at L	V_{FE}	150 km/h
- in rough air	V_{RA}	180 km/h
- for winch launching	V_W	140 km/h
- for aerotowing	V_T	180 km/h
- for sustainer assisted aerotow	V_{TA}	180 km/h
- for gear operation	V_{LO}	180 km/h
- for propeller operation	V_{PO}	120 km/h
- with propeller extended	V_{PE}	180 km/h

12. Approved Operations Capability

VFR-Day only
Cloud flying not permitted
Aerobatic manoeuvres are not permitted, except spinning

13. Launch methods

Aerotow including Sustainer Assisted Aerotow
Winch and Auto-Tow

14. Maximum Masses

Max. Mass: 850 kg



	Max. Mass of Non-Lifting Parts: 550 kg
15. Centre of Gravity Range	156 mm – 385 mm aft of datum
16. Datum	Wing leading edge at root rib
17. Levelling Means	Slope 1000 : 27 placed on upper side of fuselage boom horizontal
18. Control Surface Deflections	Refer to Maintenance Manual
19. Minimum Flight Crew	1
20. Maximum Passenger Seating Capacity	1
21. Baggage/ Cargo Compartments	9 kg
22. Lifetime limitations	Refer to Maintenance Manual



B.IV Operating and Service Instructions

1. Flight Manual ASG 32 EI, issue 15.09.2017, or later EASA approved revisions
2. Maintenance Manual ASG 32 EI, issue 01.04.2017, or later revisions
3. General Repair Manual for Alexander Schleicher Sailplanes and Powered Sialplanes, latest revision
4. Operating Manual and Maintenance Manual for Engine Alexander Schleicher EA900, latest approved version *)
5. Operating Manual and Maintenance Manual for Propeller Alexander Schleicher AS2F1-4, latest approved version *)
6. Manual for the TOST Release, latest approved version

*) The operation and maintenance manuals are elements of the operation instructions of the ASG 32 EI. For revisions refer to the engine and propeller manufacturer.



B.V Notes

1. Manufacturing is confined to industrial production.
2. The surface colour of all fibre reinforced parts, which are exposed to sun radiation, must be painted either in
 - White
 - RAL 2004 (Reinorange)
 - RAL 2009 (Verkehrsorange)
 - RAL 3020 (Verkehrsrrot)
 - or other colours listed in the maintenance manual section 13.4, maintenance instruction “coloured surfaces”Exceptions are the areas for markings and registration, engine bay and cockpit.
3. Sustainer Assited Aerotow is only permitted after embodiment of Alexander Schleicher ASG 32 Technical Note Nr. 12.



Section C: ASG 32 Mi

C.I General

- | | |
|---|--|
| 1. Type/ Model/ Variant | |
| 1.1 Type: | ASG 32 |
| 1.2 Model: | ASG 32 Mi |
| 2. Airworthiness Category | Sailplane, CS-22 - Utility |
| 3. Manufacturer | Alexander Schleicher GmbH & Co. Segelflugzeugbau |
| 4. EASA Type Certification Application Date | 01 November 2012 |
| 5. EASA Type Certification Date | 11 Februray 2016 |

C.II EASA Certification Basis

- | | |
|---|---|
| 1. Reference Date for determining the applicable requirements | |
| 2. Airworthiness Requirements | Certification Specification for Sailplanes and Powered Sailplanes, issued 24. September 2008 (CS-22, Amdt. 2) |
| 3. Special Conditions | None |
| 4. Exemptions | None |
| 5. (Reserved) Deviations | None |
| 6. Equivalent Safety Findings | CS 22.335 (f) calculation of V_D according to OSTIV
CS 22.585(a) reduced by factor 1.2 |
| 7. Environmental Protection | ICAO Annex 16 (details refer to TCDSN EASA.A.599) |



C.III Technical Characteristics and Operational Limitations

1. Type Design Definition List of the drawing files ASG 32 Mi, issue 31.01.2016
2. Description Double-seat, self-launching powered sailplane, mid-wing CRP/GRP/ARP-composite construction for FAI 20m class with flaps, double-panel Schempp-Hirth airbrakes on upper wing surface, winglets, water ballast tanks in the wing and optional in the fuselage, retractable landing gear with hydraulic disc brake, T-shaped horizontal tail (fixed horizontal stabilizer with elevator) fin and rudder. Retractable power-plant mounted in the centre fuselage.
3. Equipment
Min. required Equipment:
 - 1 Air speed indicator (up to 300 km/h) (front seat)
 - 1 Altimeter (front seat)
 - 1 Outside air temperature gauge (front seat)
 - 2 4-Point safety harness (symmetrical)
 - 2 Parachute or Cushion for back rest (~ 8cm thickness)Additional Equipment refer to Flight and Maintenance Manual

With engine installed:
 - 1 Magnetic compass (front seat)
 - 1 Power-plant instrument, type ILEC MCU ASH 30Mi (front seat)
 - 1 Rear view mirror (front seat)
4. Dimensions
Span: 20,00 m
Wing area: 15,70 m²
Length: 9,07 m
Height: 1,84 m
5. Engine
 - 5.1 Model Austro Engine IAE50R-AA
 - 5.2 Type Certificate EASA.E.085
 - 5.3 Limitations Maximum Take-off Power (max. 3 min.): 37,3 kW at 7750 rpm
 - 5.4 Maximum Continuous Power 35,8 kW at 7100 rpm



6. Propeller

6.1 Model	Alexander Schleicher AS2F1-1/R153-92-N1
6.2 Type Certificate	EASA.P.004
6.3 Number of blades	2
6.4 Diameter	1530 mm \pm 5 mm
6.5 Sense of Rotation or	Right
6.6 Model	Alexander Schleicher AS2F1-5/R153-88-N1
6.7 Type Certificate	EASA.P.004
6.8 Number of blades	2
6.9 Diameter	1530 mm \pm 5 mm
6.10 Sense of Rotation	Right

7. Fuel capacities/Battery

7.1 Tank in the fuselage	14 l
7.2 Tank in right wing	15 l
7.3 Tank in left wing	15 l
7.4 Non-usable fuel	0,4 l

8. Launching Hooks

Nose tow hook "E 22", LBA Datasheet No. 11.402/9
NTS
Safety hook „Europa G 88“, LBA Datasheet No.
60.230/2

9. Weak Links

Ultimate Strength:
- for winch- and auto-tow launching max. 1100 daN
- for aero-tow max. 1100 daN

10. Load Factors

+5,3 / -2,65 (up to V_A)
+4,0 / -1,5 (up to V_{NE})

11. Air Speeds

Manoeuvring Speed	V_A	180 km/h
Never Exceed Speed	V_{NE}	270 km/h
Maximum permitted Speeds		
- with flaps at 1, 2, 3, 4	V_{FE}	270 km/h
- with flaps at 5,6	V_{FE}	180 km/h
- with flaps at L	V_{FE}	150 km/h
- in rough air	V_{RA}	180 km/h
- for winch launching	V_W	140 km/h
- for aerotowing	V_T	180 km/h
- for gear operation	V_{LO}	180 km/h
- for propeller operation	V_{PO}	120 km/h
- with propeller extended	V_{PE}	180 km/h

12. Approved Operations Capability

VFR-Day only
Cloud flying not permitted
Aerobatic manoeuvres not permitted, except Spinning

13. Launch methods

Aerotow
Winch and Auto-Tow
Self-Launch



14. Maximum Masses	Max. Mass: 850 kg Max. Mass of Non-Lifting Parts: 550 kg
15. Centre of Gravity Range	156 mm – 385 mm aft of datum
16. Datum	Wing leading edge at root rib
17. Levelling Means	Slope 1000 : 27 placed on upper side of fuselage boom horizontal
18. Control Surface Deflections	Refer to Maintenance Manual
19. Minimum Flight Crew	1
20. Maximum Passenger Seating Capacity	1
21. Baggage/ Cargo Compartments	9 kg
22. Lifetime limitations	Refer to Maintenance Manual



C.IV Operating and Service Instructions

1. Flight Manual Flight Manual ASG 32 Mi, issue 01.12.2015, or later EASA approved revisions; or
Flight Manual ASG 32 Mi, issue 15.09.2017, or later EASA approved revisions
2. Maintenance Manual Maintenance Manual ASG 32 Mi, issue 15.01.2016, or later revisions
3. Structural Repair Manual General Repair Manual for Alexander Schleicher Sailplanes and Powered Sailplanes, latest revision
4. Operating Manual and Maintenance Manual for Engine Austro Engine IAE50R-AA series, latest approved version *)
5. Operating Manual and Maintenance Manual for Propeller Alexander Schleicher AS2F1-1, latest approved version *), or as applicable
6. Operating Manual and Maintenance Manual for Propeller Alexander Schleicher AS2F1-5, latest approved version *)
7. Manual for the TOST Release, latest approved version

*) The operation and maintenance manuals are elements of the operation instructions of the ASG 32 Mi. For revisions refer to the engine and propeller manufacturer.



C.V Notes

1. Manufacturing is confined to industrial production.
2. The surface colour of all fibre reinforced parts, which are exposed to sun radiation, must be painted either in
 - White
 - RAL 2004 (Reinorange)
 - RAL 2009 (Verkehrsorange)
 - RAL 3020 (Verkehrsrrot)
 - or other colours listed in the maintenance manual section 13.4, maintenance instruction “coloured surfaces”Exceptions are the areas for markings and registration, engine bay and cockpit.
3. The model ASG 32 Mi has previously been addressed by Section A as variant ASG 32 Mi. The optional implementation of the AS Technical Note 11 converts the variant ASG 32 Mi into the model ASG 32 Mi.



Section D: Administrative Section

D.I Acronyms & Abbreviations

AS	Alexander Schleicher GmbH & Co. Segelflugzeugbau
EASA	European Union Aviation Safety Agency
MTOM	Maximum Take-off Mass
TC	Type Certificate
TCDS	Type Certificate Data Sheet
VFR	Visual Flight Rules

D.II Type Certificate Holder Record

Alexander Schleicher GmbH & Co. Segelflugzeugbau
Alexander-Schleicher-Str. 1
36163 Poppenhausen
Germany

D.III Change Record

Issue	Date	Changes	TC Issue No. & Date
Issue 01	11 February 2016	Initial Issue	Initial Issue, 11 February 2016
Issue 02	17 March 2016	Correction missing SC in A.II.3, separate manuals for both variants.	
Issue 03	11 January 2018	Addition of model ASG 32 EI	11 January 2018
Issue 04	06 June 2019	Alternative propeller for model ASG 32 Mi	
Issue 05	23 August 2021	Split of model ASG 32 with its variants ASG 32 and ASG 32 Mi into two models: ASG 32 and ASG 32 Mi See notes of Section A and C.	16 August 2021
Issue 06	13 January 2022	Model ASG 32 EI, addition to launch methods: Sustainer Assisted Aerotow, Note B.V.3	
Issue 07	24 July 2024	Model ASG 32 Mi: correction of applicable Flight Manuals	

-END-

