



TYPE-CERTIFICATE DATA SHEET

No. IM.E.090

for
PW1500G Series Engines

Type Certificate Holder
Pratt & Whitney
400 Main Street
East Hartford, CT 06118
United States of America

For Models:

PW1519G

PW1521G

PW1524G

PW1525G

PW1521G-3

PW1524G-3

PW1525G-3

PW1521GA

PW1919G

PW1921G

PW1922G

PW1923G

PW1923G-A



Intentionally left blank



TABLE OF CONTENTS

I. General	4
1. Type/ Model.....	4
2. Type Certificate Holder	4
3. Manufacturer	4
4. Date of Application.....	4
5. EASA Type Certification Date	5
1. State of Design Authority Certification Basis.....	5
2. Reference Date for determining the applicable airworthiness requirements	5
3. EASA Certification Basis	5
3.1. Airworthiness Standards	5
3.2. Special Conditions (SC)	5
3.3. Equivalent Safety Findings	6
3.4. Deviations	6
3.5. Environmental Protection.....	6
III. Technical Characteristics	6
1. Type Design Definition	6
2. Description.....	6
3. Equipment.....	7
4. Dimensions	7
5. Dry Weight	7
6. Ratings	7
7. Control System	8
8. Fluids (Fuel, Oil, Coolant, Additives)	8
9. Aircraft Accessory Drives	9
10. Maximum Permissible Air Bleed Extraction	9
IV. Operating Limitations (see also Note 7)	10
1. Temperature Limits	10
2. Speed Limits	10
3. Torque Limits	11
4. Pressure Limits	11
5. Time Limited Dispatch (TLD)	11
6. ETOPS.....	11
V. Operating and Service Instructions	12
VI. Notes	14
SECTION: ADMINISTRATIVE	15
I. Acronyms and Abbreviations.....	15
II. Type Certificate Holder Record	15
III. Change Record	15



I. General

1. Type/ Model

Type	Models
PW1500G	PW1519G
	PW1521G
	PW1524G
	PW1525G
	PW1521G-3
	PW1524G-3
	PW1525G-3
	PW1521GA
	PW1919G
	PW1921G
	PW1922G
	PW1923G
	PW1923G-A

2. Type Certificate Holder

Pratt & Whitney
400 Main Street
East Hartford, CT 06118
United States of America

3. Manufacturer

Pratt & Whitney Canada Corp.
1000 Marie-Victorin
Longueuil, Quebec J4G1A1
Canada

4. Date of Application

Models	Application Date
PW1519G	08 August 2011
PW1521G	02 February 2010
PW1524G	02 February 2010
PW1525G	11 December 2015
PW1521G-3 / PW1524G-3 / PW1525G-3	13 July 2016
PW1919G / PW1921G / PW1922G / PW1923G	09 May 2017
PW1521GA / PW1923G-A	18 December 2018



5. EASA Type Certification Date

Models	EASA Certification Date
PW1519G / PW1521G / PW1524G / PW1525G	18 May 2016
PW1521G-3 / PW1524G-3 / PW1525G-3	14 September 2016
PW1919G / PW1921G / PW1922G / PW1923G	27 February 2018
PW1521GA / PW1923G-A	20 March 2019

II. Certification Basis

1. State of Design Authority Certification Basis

Models	State of Design Authority Certification Basis
All Models	See FAA TCDS Number E00090EN

2. Reference Date for determining the applicable airworthiness requirements

Models	Reference Date for Applicable Airworthiness Requirements
All Models	8 February 2010

3. EASA Certification Basis

3.1. Airworthiness Standards

Models	EASA Airworthiness Standards
PW1519G / PW1521G / PW1524G / PW1525G, PW1521G-3 / PW1524G-3 / PW1525G-3 / PW1521GA	-CS-E Amendment 3, dated 23 December 2010 (Decision No. 2010/015/R of the Executive Director of the European Aviation Safety Agency) -For paragraph CS-E 1040 only: CS-E Amendment 5 dated 13 December 2018 (Decision No. 2018/014/R of the Executive Director of the European Aviation Safety Agency).
PW1919G / PW1921G / PW1922G / PW1923G / PW1923G-A	- CS-E Amendment 3, dated 23 December 2010 (Decision No. 2010/015/R of the Executive Director of the European Aviation Safety Agency) -For paragraph CS-E 1050 only: CS-E Amendment 4 dated 12 March 2015 (Decision No. 2015/009/R of the Executive Director of the European Aviation Safety Agency).

3.2. Special Conditions (SC)

None



3.3. Equivalent Safety Findings

Models	Equivalent Safety Findings
All Models	CS-E 790(a)(1) Ingestion of Rain and Hail – Large hailstone ingestion

3.4. Deviations

Models	Deviations
PW1519G / PW1521G / PW1524G / PW1525G, PW1521G-3 / PW1524G-3 / PW1525G-3 / PW1521GA	None
PW1919G / PW1921G / PW1922G / PW1923G / PW1923G-A	M-TS-0000342 Issue 2: Inhibition of electronic engine shaft shear overspeed protection system, ref. CS-E 840 & CS-E 850

3.5. Environmental Protection

Models	Environmental Protection Requirements
All Models	<p>Smoke, gaseous and particulate matter engine emissions requirements established in ICAO Annex 16 Volume II, Amendment 10 applicable 1 January 2021 as implemented into EU legislation 27 April 2021:</p> <ul style="list-style-type: none"> • NOx standard in accordance with Part III, Chapter 2, § 2.3.2 e) (CAEP/8). • Maximum nvPM mass concentration levels in compliance with Part III, Chapter 4, paragraph 4.2.2.1. • nvPM mass and number emissions in compliance with Part III, Chapter 4, paragraph 4.2.2.2 a) 1) and 4.2.2.2 b) 1) (CAEP/11 In-Production standard).

III. Technical Characteristics

1. Type Design Definition

Models	Type Design Definition
PW1519G / PW1521G / PW1524G / PW1525G / PW1521G-3 / PW1524G-3 / PW1525G-3 / PW1521GA	Installation Drawing 5310001
PW1919G / PW1921G / PW1922G / PW1923G / PW1923G-A	Installation Drawing 5350001

2. Description

High bypass ratio, axial-airflow, twin spool turbofan engine, is controlled by a Full Authority Digital Engine Control (FADEC). The Low Pressure spool consists of a three-stage Low Pressure Turbine that drives a three-stage Low Pressure Compressor, and single stage high bypass Fan through the ratio Fan Drive Gear speed reduction System. The High Pressure Compressor has eight axial stages driven by a two-stage cooled High Pressure Turbine.



3. Equipment

See III. 1. Type Design Definition.

4. Dimensions

Models	Dimensions (m)			
	Overall Length (flange to flange)	Overall Length (fan spinner face to aft #6 comp. bolt)	Nominal Diameter (fan case)	Maximum Radial Projection (at drain mast)
All Models	3.045	3.184	2.006	1.160

5. Dry Weight

Models	Dry Weight kg (lbs)
All Models	2177 kg (4800 lbs)

The above dry weight value applies to the basic engine and includes standard equipment.

6. Ratings

See Notes 1 and 2.

Models	Sea Level Static Thrust			
	Take-off (5 minutes) daN (lbf)	Flat Rating Ambient Temperature °C (°F)	Maximum Continuous daN (lbf)	Flat Rating Ambient Temperature °C (°F)
PW1519G	8796 (19775)	30 (86)	8312 (18685)	25 (77)
PW1521G / PW1521G-3 / PW1521GA	9773 (21970)	30 (86)	9235 (20760)	25 (77)
PW1524G / PW1524G-3	10854 (24400)	30 (86)	10253 (23050)	25 (77)
PW1525G / PW1525G-3	10854 (24400)	30 (86)	10253 (23050)	25 (77)

Models	Sea Level Static Thrust			
	Normal Take-off (5 minutes) daN (lbf)	Flat Rating Ambient Temperature °C (°F)	Maximum Take-off (5 minutes) daN (lbf)	Flat Rating Ambient Temperature °C (°F)
PW1919G	9279 (20860)	30 (86)	10031 (22550)	30 (86)
PW1921G	10031 (22550)	30 (86)	10724 (24110)	33 (92)
PW1922G	10593 (23815)	35 (95)	10593 (23815)	35 (95)
PW1923G / PW1923G-A	10593 (23815)	PW1923G: 35 (95) PW1923G-A: 30 (86)	10724 (24110)	34 (93)



Models	Sea Level Static Thrust	
	Maximum Continuous daN (lbf)	Flat Rating Ambient Temperature °C (°F)
PW1919G	9032 (20305)	25 (77)
PW1921G	9699 (21805)	25 (77)
PW1922G	9032 (20305)	25 (77)
PW1923G / PW1923G-A	9699 (21805)	25 (77)

Models	Data Storage Unit (Ratings Plug) PN
PW1519G	5325208 or 5327258
PW1521G	5325206 or 5327259
PW1524G	5325211 or 5327260
PW1525G	5325209 or 5327257
PW1521G-3	5325207 or 5327261
PW1524G-3	5325205 or 5327263
PW1525G-3	5325212 or 5327262
PW1521GA	5325781 or 5327264
PW1919G	5327459 or 5327587
PW1921G	5322353 or 5327583
PW1922G	5327453 or 5327578
PW1923G	5322354 or 5327584
PW1923G-A	5328019

7. Control System

Full Authority Digital Engine Control (FADEC)

8. Fluids (Fuel, Oil, Coolant, Additives)

Fuel: For models PW1519G, PW1521G, PW1524G, PW1525G, PW1521G-3, PW1524G-3, PW1525G-3 and PW1521GA refer to Service Bulletin PW1000G-A-73-00-0010-00A-930A-D for approved fuels and fuel additives.

For models PW1919G, PW1921G, PW1922G, PW1923G and PW1923G-A refer to Service Bulletin PW1000G- A-73-00-0001-00B-930A-D for approved fuels and fuel additives.

Oil: For models PW1519G, PW1521G, PW1524G, PW1525G, PW1521G-3, PW1524G-3, PW1525G-3 and PW1521GA refer to Service Bulletin PW1000G-A-79-00-0001-00A-930A-D for approved oils.

For models PW1919G, PW1921G, PW1922G, PW1923G and PW1923G-A refer to Service Bulletin PW1000G- A-79-00-0001-00B-930A-D for approved oils.



9. Aircraft Accessory Drives

For models PW1519G, PW1521G, PW1524G, PW1525G, PW1521G-3, PW1524G-3, PW1525G-3 and PW1521GA:

Drive Pad	Rotation	Speed Ratio to N2	Torque-Continuous daNm (lb.-in.)	Torque-Overload daNm (lb.-in.)	Torque-Static daNm (lb.-in.)	Overhung Moment daNm (lb.-in.)
Hydraulic Pump	CW	0.1835:1	9.15 (810)	18.64 (1650)	40.67 (3600)	1.97 (175)
Integrated Drive Generator (IDG)	CW	0.8595:1	6.32 (560)	18.30 (1620)	62.14 (5500)	10.45 (925)

CW: Clockwise

*: Maximum allowable continuous torque values are at any engine speed unless otherwise specified, provided no destructive forces resulting from accessory torsional vibration are present.

Maximum allowable continuous overhung bending moments of accessories about drive face are as shown above provided no destructive forces resulting from vibration are present.

For models PW1919G, PW1921G, PW1922G, PW1923G and PW1923G-A:

Drive Pad	Rotation	Speed Ratio to N2	Torque-Continuous daNm (lb.-in.)	Torque-Overload daNm (lb.-in.)	Torque-Static daNm (lb.-in.)	Overhung Moment daNm (lb.-in.)
Hydraulic Pump	CW	0.1835:1	4.74 (420)	4.52 (400)	40.67 (3600)	2.09 (185.5)
Integrated Drive Generator (IDG)	CW	0.8595:1	3.16 (280)	12.65 (1120)	62.14 (5500)	10.45 (925)

CW: Clockwise

Maximum allowable continuous overhung bending moments of accessories about drive face are as shown above provided no destructive forces resulting from vibration are present.

Refer to the applicable Installation and Operating Manual Section 11 additional information on provisions and connections for airframe provided components.

10. Maximum Permissible Air Bleed Extraction

Maximum permissible bleed air extraction limits are specified in the applicable Installation and Operating Manual (see section V.).



IV. Operating Limitations (see also Note 6.)

1. Temperature Limits

Models	Maximum Permissible Indicated Turbine Temperature (ITT)		
	Take-off (5 minutes)*, ** - see Note 2 - °C (°F)	Maximum Continuous °C (°F)	Maximum Starting °C (°F)
All models	1054 (1929)	1017 (1863)	1054 (1929)
	1054 (1929)	1017 (1863)	1054 (1929)
	1054 (1929)	1017 (1863)	1054 (1929)
	1054 (1929)	1017 (1863)	1054 (1929)

*: For models PW1919G, PW1921G, PW1922G, PW1923G and PW1923G-A, the above shown Take-off (5 minutes) ITT limits are applicable to both the normal and the maximum Take-off ratings.

** : All take-off ratings may be extended to 10 minutes for engine out contingency.

Fuel Temperatures:

Refer to the applicable Installation and Operating Manual Section 5 for fuel temperature limits.

Oil Temperatures:

Refer to the applicable Installation and Operating Manual Section 2 for oil temperature limits.

2. Speed Limits

Models	Maximum Permissible Speeds			
	Low Pressure Spool (N1)		High Pressure Spool (N2)	
	Take-off (5 minutes) - see Note 2 - rpm	Maximum Continuous rpm	Take-off (5 minutes) - see Note 2 - rpm	Maximum Continuous rpm
All Models	10600	10600	24470	24470
	10600	10600	24470	24470
	10600	10600	24470	24470
	10600	10600	24470	24470

Note:

Power setting, power checks, and control of engine thrust output in all operations are based on Low Rotor Speed (N1). The Fan Speed (NFAN) is directly proportional to N1 by a gear ratio of 1:3.0625.



Models	Minimum Speeds			
	Low Pressure Spool (N1)		High Pressure Spool (N2)	
	Ground Idle rpm	Flight Idle rpm	Ground Idle rpm	Flight Idle rpm
All models	1574	1991	13264	13264

Note:

For all models, the minimum N1 certified for in-flight operation in icing conditions is 1991 rpm. The Electronic Engine Control will prevent rotor speeds below this value while in flight.

3. Torque Limits

Not applicable

4. Pressure Limits

Fuel Pressures:

Refer to the applicable Installation and Operating Manual Section 5 for fuel pressure limits.

Oil Pressures:

Refer to the applicable Installation and Operating Manual Section 2 for oil pressure limits.

Oil pressure is measured relative to main lube pressure. Temporary interruption associated with negative “g” operation is limited to 7 seconds maximum. Normal oil pressure will be restored rapidly once the negative “g” effect has been eliminated.

5. Time Limited Dispatch (TLD)

All models are approved for Time Limited Dispatch (TLD) in accordance with CS-E 1030. The dispatch criteria are contained in the applicable Airworthiness Limitation Manual (AWL, see reference in paragraph V.)

6. ETOPS

When compliant with Pratt & Whitney Service Bulletin PW1000G-A-72-00-0070-00A-930A-D latest approved revision, engine models PW1519G, PW1521G, PW1524G, PW1525G, PW1521G-3, PW1524G-3, PW1525G-3 and PW1521GA are approved for ETOPS capability in accordance with CS-E 1040 Amendment 5 for a Maximum Approved Diversion Time of 180 minutes at MCT thrust plus 15 minutes at hold power. This approval does not constitute an approval to conduct ETOPS operations.

Engine models PW1919G, PW1921G, PW1922G, PW1923G and PW1923G-A are not eligible for approved for Extended Twin Engine Operations (ETOPS).



V. Operating and Service Instructions

Manuals	PW1519G / PW1521G / PW1524G / PW1525G / PW1521G-3 / PW1524G-3 / PW1525G-3 / PW1521GA
Engine Installation and Operating Manual	PWA-8828

Instructions for Continued Airworthiness (ICA)	PW1519G / PW1521G / PW1524G / PW1525G / PW1521G-3 / PW1524G-3 / PW1525G-3 / PW1521GA
Airworthiness Limitation Manual (AWL)*	P/N 5305816
Engine Maintenance Manual (EMM)	P/N 5305818
Engine Manual (EM)	P/N 5305815
Cleaning, Inspection and Repair Manual (CIR)	P/N 5305817
Fault Isolation Procedures Manual (FIM)	P/N 5319822
Standard Practices Manual (SPM)	P/N 585005
Special Procedures – Fan Drive Gear System (FDGS) Manual	P/N 5317957
Special Procedures – High Pressure Compressor (HPC) Module	P/N 5317961
Special Procedures – High Pressure Turbine (HPT) Module	P/N 5317960
Special Procedures – High Pressure Turbine (HPT) Core	P/N 5324688
Special Procedures – High Pressure Turbine (HPT) Nut	P/N 5324694



Manuals	PW1919G / PW1921G / PW1922G / PW1923G / PW1923G-A
Engine Installation and Operating Manual	PWA-10649

Instructions for Continued Airworthiness (ICA)	PW1919G / PW1921G / PW1922G / PW1923G / PW1923G-A
Airworthiness Limitation Manual (AWL)*	P/N 5321709
Engine Maintenance Manual (EMM)	P/N 5321705
Engine Manual (EM)	P/N 5321708
Cleaning, Inspection and Repair Manual (CIR)	P/N 5321706
Fault Isolation Procedures Manual (FIM)	P/N 5324697
Standard Practices Manual (SPM)	P/N 585005
Special Procedures – Fan Drive Gear System (FDGS) Manual	P/N 5321702
Special Procedures – High Pressure Compressor (HPC) Module	P/N 5321703
Special Procedures – High Pressure Turbine (HPT) Module	P/N 5321704
Special Procedures – High Pressure Turbine (HPT) Core	P/N 5324689
Special Procedures – High Pressure Turbine (HPT) Nut	P/N 5324695

* The EASA approved Airworthiness Limitation Section of the Instructions for Continued Airworthiness is published in the Chapter 5 of the AWL.



VI. Notes

1. The engine ratings are based on calibrated test stand performance under the following conditions:
 - Sea level static, standard pressure 1.01 bar (14.696 psia), up to the flat rating ambient temperature.
 - No customer bleed or customer horsepower extraction.
 - Ideal inlet, 100% ram recovery.
 - Production aircraft flight cowling.
 - Production instrumentation.
 - Fuel lower heating value 42798 KJoule/kg (18400 BTU/lb).
2. The take-off ratings that are nominally limited to 5 minutes duration may be used for up to 10 minutes for one engine inoperative operations.
3. Engine mount provisions for models PW1519G, PW1521G, PW1524G, PW1525G, PW1521G-3, PW1524G-3, PW1525G-3 and PW1521GA are specified in Installation Drawing 5310001 and Mount and Manoeuvre Load Drawing 5310003.

Engine mount provisions for models PW1919G, PW1921G, PW1922G, PW1923G and PW1923G-A are specified in Installation Drawing 5350001 and Mount and Manoeuvre Load Drawing 5350003.
4. The thrust reverser is not engine of type design and is certified as part of the aircraft. Information for installation of a thrust reverser is contained in the applicable Installation and Operating Manual (see section V.).
5. Lightning protection requirements and electromagnetic interference emitted by the electronic engine control system, including cables, are specified in the applicable Installation and Operating Manual (see section V.).
6. Requirements and limitations for ground operation in icing conditions are specified in the applicable Installation and Operating Manual (see section V.).
7. The engine TC has been transferred from Pratt & Whitney Canada Corp. to Pratt & Whitney on 6 December 2016.



SECTION: ADMINISTRATIVE

I. Acronyms and Abbreviations

CS-E	Certification Specifications for Engines
EASA	European Aviation Safety Agency
EBU	Engine Build-up Unit
ECS	Environmental Control System
FAA	Federal Aviation Administration
FADEC	Full Authority Digital Engine Control
HP	High Pressure
ICAO	International Civil Aviation Organisation
ITT	Indicated Turbine Temperature
LP	Low Pressure
P&WC	Pratt & Whitney Canada
PN	Part Number
TC	Type Certificate
TCDS	Type Certificate Data Sheet
W25	Core Engine Air Mass Flow
WAI	Wing Anti-Ice

II. Type Certificate Holder Record

Not applicable

III. Change Record

Issue	Date	Changes	TC issue
Issue 01	18 May 2016	Initial Issue	18 May 2016
Issue 02	08 June 2016	Includes approval statement for Time Limited Dispatch (TLD).	As for Issue 01 above
Issue 03	14 September 2016	Addition of PW1521G-3, PW1524G-3 and PW1525G-3 models	14 September 2016
Issue 04	06 December 2016	-Change of Type Certificate Holder from PW Canada to PW -Change reference for fluids (see 8.)	06 December 2016
Issue 05	27 February 2018	-Addition of models PW1919G, PW1921G, PW1922G and PW1923G -Various editorial changes	27 February 2018
Issue 06	20 March 2019	-Addition of models PW1521GA and PW1923G-A -Revision of Maximum Continuous ITT limits in paragraph IV.1. -Various editorial changes	20 March 2019
Issue 07	12 December 2019	Update of emission requirement compliance (certificate 10072019)	20 March 2019
Issue 08	24 February 2021	-Update with respect to approval for Extended Twin Engine Operations (ETOPS), EASA certificate No. 10075713 refers. -Various editorial changes	20 March 2019
Issue 09	24 November 2022	Update of emission requirement compliance (certificate 10080719)	20 March 2019



Issue 10	14 August 2025	-Update of Environmental Protection Requirements with direct reference to ICAO requirements (no technical changes) -Addition of deviation for Inhibition of electronic engine shaft shear overspeed protection system for PW1900G family (certificate 10087672) -Various editorial changes	20 March 2019
----------	----------------	--	---------------

-END-

