



TYPE-CERTIFICATE DATA SHEET

No. IM.E.096

for

PW800 Series Engines

Type Certificate Holder

Pratt & Whitney Canada Corp.

1000 Marie-Victorin

Longueuil, Quebec J4G1A1

Canada

For Models:

PW814GA

PW815GA

PW812D

PW812GA



Intentionally left blank



TABLE OF CONTENTS

I. General	4
1. Type/Model	4
2. Type Certificate Holder	4
3. Manufacturer	4
4. Date of Application	4
5. EASA Type Certification Date	4
II. Certification Basis	5
1. State of Design Authority Certification Basis	5
2. Reference Date for determining the applicable airworthiness requirements	5
3. EASA Certification Basis	5
3.1 Airworthiness Standards	5
3.2 Special Conditions (SC)	5
3.3 Equivalent Safety Findings	5
3.4 Deviations	5
3.5 Environmental Protection	6
III. Technical Characteristics	6
1. Type Design Definition	6
2. Description	6
3. Equipment	7
4. Dimensions	7
5. Dry Weight	7
6. Ratings	8
7. Control System	8
8. Fluids (Fuel, Oil, Coolant, Additives)	8
9. Aircraft Accessory Drives	8
10. Maximum Permissible Air Bleed Extraction	8
IV. Operating Limitations	9
1. Temperature Limits	9
2. Speed Limits	9
3. Torque Limits	9
4. Pressure Limits	9
5. Time Limited Dispatch (TLD)	10
6. ETOPS	10
V. Operating and Service Instructions	10
VI. Notes	11
SECTION ADMINISTRATIVE	13
I. Acronyms and Abbreviations	13
II. Type Certificate Holder Record	13
III. Change Record	14



I. General

1. Type/Model

Type	Models
PW800	PW814GA
	PW815GA
	PW812D
	PW812GA

These models are approved for use on multi-engine civil aircraft at the ratings and within the operating limitations specified below, subject to compliance with the aircraft powerplant installation requirements.

2. Type Certificate Holder

Pratt & Whitney Canada Corp.
1000 Marie-Victorin Longueuil,
Quebec J4G1A1 Canada

3. Manufacturer

Pratt & Whitney Canada Corp.
1000 Marie-Victorin Longueuil,
Quebec J4G1A1 Canada

4. Date of Application

Models	Application Date
PW814GA	8 March 2013
PW815GA	
PW812D	11 February 2019
PW812GA	13 April 2018

5. EASA Type Certification Date

Models	EASA Certification Date
PW814GA	31 August 2017
PW815GA	
PW812D	05 August 2022
PW812GA	08 October 2025



II. Certification Basis

1. State of Design Authority Certification Basis

Models	State of Design Authority Certification Basis (<i>see also Canadian TC E-39</i>)
PW814GA	<ul style="list-style-type: none"> AWM Chapter 533 at Change 533-13; and Subchapter B of AWM Chapter 516 – Aircraft Engine Emissions, which refers to ICAO Annex 16, Volume II
PW815GA	
PW812D	<ul style="list-style-type: none"> AWM Chapter 533 at Change 533-16; and Subchapter B of AWM Chapter 516 – Aircraft Engine Emissions at Change 516-15; including ICAO annex 16 Volume II – Aircraft Engine Emissions, as amended up to and referring to Amendment 10 (CAEP/11).
PW812GA	

2. Reference Date for determining the applicable airworthiness requirements

Models	Reference Date for Applicable Airworthiness Requirements
PW814GA	31 March 2012
PW815GA	
PW812D	30 November 2018
PW812GA	

3. EASA Certification Basis

3.1 Airworthiness Standards

Models	EASA Airworthiness Standards
PW814GA	CS-E Amendment 3, dated 23 December 2010 (Decision No. 2010/015/R of the Executive Director of the European Aviation Safety Agency)
PW815GA	
PW812D	CS-E Amendment 4, dated 12 March 2015
PW812GA	

3.2 Special Conditions (SC)

None

3.3 Equivalent Safety Findings

ESF to CS-E 810 – Compressor and Turbine Blade Failure / Fan Integrally-Bladed Rotor (IBR) Airfoil release.

3.4 Deviations

None



3.5 Environmental Protection

Models	Environmental Protection Requirements
PW814GA	CS-34 Amendment 4 as implemented by ED Decision 2021/011/R (applicable 25 July 2021), ICAO Annex 16 Volume II, Amendment 10 applicable 1 January 2021 as implemented into EU legislation 27 April 2021. NOx standard in accordance with ICAO Annex 16 Volume II, Part III, Chapter 2, § 2.3.2 e) (CAEP/8). Maximum nvPM mass concentration levels in compliance with Part III, Chapter 4, paragraph 4.2.2.1. nvPM mass and number emissions in compliance with Part III, Chapter 4, paragraph 4.2.2.2 a) 1) and 4.2.2.2 b) 1) (CAEP/11 In-Production standard).
PW815GA	
PW812D	
PW812GA	<p>ICAO Annex 16 Volume II, Amendment 10, implemented in Art. 9 of Regulation (EU) 2018/1139 as amended by Regulation (EU) 2021/1087;</p> <ul style="list-style-type: none"> - NOx standard in accordance with ICAO Annex 16 Volume II, Part III, Chapter 2, § 2.3.2 e) (CAEP/8); - Maximum nvPM mass concentration levels in accordance with Part III, Chapter 4, § 4.2.2.1 (CAEP/10); - nvPM mass and number emissions in accordance with Part III, Chapter 4, § 4.2.2.2 a) 1) and § 4.2.2.2 b) 1) (CAEP/11 In-Production standard). <p><i>Note: See ICAO Annex 16 Volume II for the full list of regulated emissions. The aforementioned details for Nox and nvPM further specify the regulatory levels to which compliance was demonstrated.</i></p>

III. Technical Characteristics

1. Type Design Definition

Models	Type Design Definition
PW814GA	Configuration of the PW814GA and PW815GA engine is defined by Engine Assembly Drawing 33B1170*
PW815GA	
PW812D	Configuration of the PW812D engine is defined by Engine Assembly Drawing 33B9100*
PW812GA	Configuration of the PW812GA engine is defined by Engine Assembly Drawing 33B5180*

* and subsequent approved revisions

2. Description

PW814GA and PW815GA

The PW814GA and PW815GA engine models are high bypass ratio two spool turbofan engines, straddle mounted across two bearings and consisting of an eight-stage axial High-Pressure Compressor (HPC), a straight flow annular low emission combustor and a two-stage High Pressure Turbine (HPT). The low-pressure rotor consists of a fan, two boost stages and an axial five-stage Low Pressure Turbine (LPT) connected by a one-piece shaft. The engine is controlled by an engine mounted dual channel engine control (FADEC). The only difference between the PW814GA and the PW815GA is thrust de-rate by means of software selection.



PW812D and PW812GA

The PW812D and PW812GA engine models are scaled down versions of the PW814GA and PW815GA engines. The PW812 engine models are high bypass ratio two spool turbofan engines, straddle mounted across two bearings and consisting of an eight-stage axial High-Pressure Compressor (HPC), a straight flow annular low emission combustor and a two-stage High Pressure Turbine (HPT). The low-pressure rotor consists of a fan, two boost stages and an axial four-stage Low Pressure Turbine (LPT) connected by a one-piece shaft. The engine is controlled by an engine mounted dual channel engine control (FADEC).

3. Equipment

See III. 1. Type Design Definition. See also Note 1.

4. Dimensions

	Dimensions (m)			
Models	Overall Length (flange to flange)	Overall Length (fan spinner face to aft tail cone)	Nominal Diameter (fan case)	Maximum Radial Projection (at drain mast)
PW814GA	2.685	3.313	1.255	0.990
PW815GA				
PW812D	2.608	2.874	1.109	0.930
PW812GA	2.608	2.874	1.109	0.930

5. Dry Weight

Models	Dry Weight kg (lbs)
PW814GA	1408* kg (3105 lbs)
PW815GA	
PW812D	1233* (2719 lbs)
PW812GA	1219* (2687 lbs)

The above dry weight value applies to the basic engine and includes standard equipment.

* This is the weight at time of certification, subject to change $\pm 2\%$ max



6. Ratings

See Notes 2 and 3.

Models	Sea Level Static Thrust			
	Take-off (5 minutes)		Maximum Continuous	
	Thrust - see Note 3 - daN (lbf)	Ambient Limit Temperature °C (°F)	Thrust daN (lbf)	Ambient Limit Temperature °C (°F)
PW814GA	6863 (15,429)	33 (91.4)	6296 (14,155)	28 (82.4)
PW815GA	7122 (16,011)	33 (91.4)	6925 (15,568)	28 (82.4)
PW812D	6161 (13,850)	35 (95)	5778 (12,989)	25 (77)
PW812GA	6101 (13,716)	30 (86)	5057 (11,368)	25 (77)

7. Control System

Models	FADEC Hardware P/N
PW814GA	33B3787*
PW815GA	
PW812D	33B7751*
PW812GA	33B7753*

* and subsequent released part number extensions

8. Fluids (Fuel, Oil, Coolant, Additives)

Fuel: Refer to the Engine Maintenance Manual for the list of approved fuels and fuel additives.
Oil: Refer to the Engine Maintenance Manual for the list of approved oils.

9. Aircraft Accessory Drives

Refer to the Installation and Operating Manual Section 11 for additional information on provisions and connections for airframe provided components.

10. Maximum Permissible Air Bleed Extraction

Customer ECS/WAI + Nacelle Anti Ice: 24% and 23.5% of core flow P2.8/P3.1 combined for PW814GA/PW815GA and PW812D/PW812GA, respectively.

For detailed information see Installation and Operating Manual, Section 11.2



IV. Operating Limitations

1. Temperature Limits

Models	Maximum Permissible Indicated Turbine Temperature (ITT)		
	Take-off (5 minutes) - see Note 3 - °C (°F)	Maximum Continuous °C (°F)	Maximum Starting °C (°F)
PW814GA	965 (1769)	956 (1753)	975 (1787)
PW815GA			
PW812D	985 (1805)	920 (1688)	
PW812GA	979 (1794)	897 (1647)	

Fuel Temperatures:

Refer to of the Installation and Operating Manual Section 6 for fuel temperature limits.

Oil Temperatures:

Refer to Installation and Operating Manual Section 2 for oil temperature limits.

2. Speed Limits

Models	Low Pressure Spool (N1)		High Pressure Spool (N2)	
	Take-off/ Max. Continuous (see Note 3 – rpm)	Transient Max. Permissible (20 seconds) rpm	Take-off/ Max. Continuous (see Note 3 - rpm)	Transient Max. Permissible (20 seconds) rpm
PW814GA	6315 (101.2%)	6378 (102.2 %)	24043 (100%)	24283 (101%)
PW815GA				
PW812D	7572 (100.4%)	7678 (101.8%)	24919 (100%)	25368 (101.8%)
PW812GA				

Note:

Power setting, power checks, and control of engine thrust output in all operations are based on Low Rotor Speed (N1).

3. Torque Limits

Not applicable

4. Pressure Limits

Fuel Pressures:

Refer to Installation and Operating Manual, Section 6 for fuel pressure limits.



Oil Pressures:

Refer to Installation and Operating Manual, Section 2 for oil pressure limits.

Oil pressure is measured relative to #4 bearing compartment pressure. Temporary interruption associated with negative “g” operation is limited to 7 seconds maximum. Normal oil pressure will be restored rapidly once the negative “g” effect has been eliminated.

5. Time Limited Dispatch (TLD)

The PW814GA engines and PW815GA engines, equipped with EEC Part number 33B3787-08 and subsequent part numbers, are approved for Time Limited Dispatch (TLD) capability in accordance with CS-E 1030. The dispatch status is referred in the Airworthiness Limitations Manual (ALM) 33B1391 Engine Systems Faults Time Limited Dispatch.

The PW812D engines, equipped with EEC Part number 33B7751-04 and subsequent part numbers, are approved for Time Limited Dispatch (TLD) capability in accordance with CS-E 1030. The dispatch status is referred in the Airworthiness Limitations Manual (ALM) 33B7516 Engine Systems Faults Time Limited Dispatch.

The PW812GA engine model is not approved for TLD.

6. ETOPS

The PW800 series engines are not approved for Extended Twin Engine Operations (ETOPS) capability in accordance with CS-E 1040.

V. Operating and Service Instructions

Manuals	PW814GA/PW815GA	PW812D	PW812GA
Engine Installation and Operating Manual	P/N 33B1410*	P/N 33B9460*	P/N 33B6360
Control System Interface Control Document (CSICD)	P/N 33B1286*	P/N 33B7438*	P/N 33B6446

* and subsequent approved amendments or issues

Instructions for Continued Airworthiness (ICA)	PW814GA/PW815GA	PW812D	PW812GA
Airworthiness Limitations Manual	P/N 33B1391	P/N 33B7516	P/N 33B1431
Engine Maintenance Manual	P/N 33B1390	P/N 33B7515	P/N 33B1430
Engine Shop Manual	P/N 33B1393	P/N 33B7518	P/N 33B1433
Clean, Inspect and Repair Manual	P/N 33B1401		
Components Maintenance Manuals	As published by P&WC		
Service Bulletins (SB)	As published by P&WC		

** The EASA approved Airworthiness Limitation Section of the Instructions for Continued Airworthiness is the Airworthiness Limitations Manual.



VI. Notes

- Note 1:** The following are standard equipment as itemized in the engine type design definition.
- Full authority digital engine control system comprising electronic engine control with dedicated power source from a permanent magnetic alternator/generator; integrated fuel pump and associated fuel flow metering, filtering with bypass indication, and flow transmission; bleed valve and variable compressor vane actuation; engine harnesses; and speed, temperature, and pressure sensors.
 - Dual igniters and dual channel ignition exciter using airframe supplied power.
 - Oil and fuel temperature management comprising fuel-oil heat exchanger, air-oil cooler. PW814GA/PW815GA engines also include an integrated drive generator air-oil cooler.
 - Lubrication system comprising oil supply and scavenge pump, variable oil pressure valve; temperature, pressure, and level sensors; oil filtering with bypass indication; and chip detection.
 - Air Turbine and Starter
 - Vibration sensors

- Note 2:** The engine ratings declared in the TCDS and Installation Manual are based on:
- ICAO standard atmospheric conditions
 - Sea level static conditions, ISA ambient temperature
 - No customer bleed power extraction.
 - Ideal inlet (100% recovery)
 - Exhaust nozzle with no leakage and with velocity coefficient equal to 1.0.

Refer to the Installation and Operating Manual Section 11 for accessory power extraction provisions and additional information on provisions and connections for airframe provided components.

- Note 3:** The take-off ratings that are nominally limited to 5 minutes duration may be used for up to 10 minutes for one engine inoperative operations without adverse effects upon engine airworthiness. Such operations are anticipated on an infrequent basis (*as engine failure events during take-off are uncommon*) and no limits or special inspections have been imposed.

- Note 4:** Oil Capacity:

PW814GA/PW815GA			
	Litres	Imp. Gallons	U.S. Gallons
Total	9.5	2.09	2.51
Useable	3.6	0.79	0.95

PW812D			
	Litres	Imp. Gallons	U.S. Gallons
Total	10.6	2.33	2.80
Useable	4.6	1.01	1.22



PW812GA			
	Litres	Imp. Gallons	U.S. Gallons
Total	8.6	1.89	2.27
Useable	2.3	0.51	0.61

Note 5: Refer to Installation and Operating Manual Section 7 for High Intensity Radiated Fields (HIRF) and Lightning qualification and conformance. Refer to Electrical drawing referred to in the Installation and Operating Manual and Control System Interface Control Document (CSICD) for functional and electrical descriptions.

Note 6: Engine mount system provisions are specified in Installation Drawing (PW814GA/PW815GA: P/N 33B1172, PW812D: P/N 33B7509, and PW812GA: P/N 33B7074) and Installation and Operating Manual Section 5.

Note 7: Requirements and limitations for ground operation in icing conditions are specified in the Installation and Operating Manual.

Note 8: The engine bill of material does not include a thrust reverser. Considerations for installation of a thrust reverser are contained in the Installation and Operating Manual.

Note 9: The EEC software has been developed and verified in accordance with RTCA/DO-178C respectively ED-12B, Level A, with system Development assurance carried out in accordance with ED79A/ARP4754A.

For PW812D, compliance with ED-202A/DO-326A and ED-204/DO-355 was demonstrated (airworthiness information security).

Note 10: Instructions for Continued Airworthiness (ICA) for Model PW812GA are incomplete at the time of issue of this revision of the TCDS. No overhaul or shop maintenance is permitted for the PW812GA



SECTION ADMINISTRATIVE

I. Acronyms and Abbreviations

AEO	All Engines Operative
CS-E	Certification Specifications for Engines
CW	Clockwise
EASA	European Union Aviation Safety Agency
EBU	Engine Build-up Unit
ECS	Environmental Control System
FADEC	Full Authority Digital Engine Control
HP	High Pressure
ICAO	International Civil Aviation Organisation
LP	Low Pressure
N1	Rotational Speed of the Low-Pressure Rotor
N2	Rotational Speed of the High-Pressure Rotor
OEI	One Engine Inoperative
P&WC	Pratt & Whitney Canada
PN	Part Number
psi	Pounds per square inch
psia	Pounds per square ambient
psig	Pounds per Square inch gauge
rpm	Revolutions per Minute
TCCA	Transport Canada Civil Aviation
TCDS	Type Certificate Data Sheet
W25	Core Engine Air Mass Flow
WAI	Wing Anti-Ice

II. Type Certificate Holder Record

Not applicable



III. Change Record

Issue	Date	Changes	TC issue
Issue 01	31 August 2017	Initial Issue	31 August 2017
Issue 02	23 August 2019	Introduction of an ESF to CS-E 810; increase of N1 speed; increase of the max ITT for Max Continuous Thrust and introduction of TLD according to CS-E 1030 (EASA Major Change Approvals 10070794 & 10070796); as well as several administrative corrections	
Issue 03	11 December 2019	Introduction of CAEP/10 for nvPM compliance (EASA Major Change approval 10071972)	
Issue 04	05 August 2022	Adding PW812D model to TC, minor updates to PW814GA/PW815GA	05 August 2022
Issue 05	17 January 2023	Introduction of CAEP/11 for nvPM compliance (EASA Major Change approvals 10080808 and 10080811)	05 August 2022
Issue 06	29 June 2023	Introduction of EEC software 6.3.0.3 according to EASA Major Change approval 10082263 and some corrections.	
Issue 07	08 October 2025	Adding PW812GA model to TC, minor updates to PW812D and PW814GA/PW815GA. Changed reference and wording of the Environmental Protection requirements.	08 October 2025

-END-

