



SPECIFIC AIRWORTHINESS SPECIFICATION

NO. EASA.SAS.A.085

**FOR
PIK-20 E, PIK-20 E II**

AS SPECIFIED IN SECTION I

This Specific Airworthiness Specification is issued in accordance with Regulation (EC) 1592/2002 Article 15(1)(b). There is no valid Type Certificate for this aircraft type. The former type certificate holder was EIRI, Eino Riihelä Ky (former holder Eiriavion Oy (formerly Molino Oy))



CONTENT

SECTION 1: Aircraft Design Definition

Variant 1 PIK-20 E

1.I General

POWERED SAILPLANE SPECIFICATION No.P-7

This specification which is a part of the Type Certificate No.P-7 prescribes conditions and limitations under which the product, for which the Type Certificate was issued, meets the Airworthiness Requirements of Finland.

Type Certificate Holder EIRI, Eino Riihelä Ky
Kisällinkatu 8
FI-15170 Lahti
Finland
(Former Holder: Eiriavion Oy)

1.II Certification Basis

OSTIV Airworthiness Requirements for Sailplanes, September 1976, Utility Category, Powered Sailplanes. German Airworthiness Requirements for Sailplanes and Powered Sailplanes (LFSM), October 1975, Utility Category, Powered Sailplanes.

ICAO Annex 16, Third Edition, Chapter 6, July 1978.

1.III Technical Characteristics and Operational Limitations

Model PIK-20 E, Approved December 27, 1978

Serial Nos. eligible 20203 to 20265 and 20267 to 20293

Maximum Weight 470 kg (1036 lbs) including water ballast

Maximum weight of
Non-Lifting Parts 328 kg (723 lbs)

Water Ballast Two water ballast tanks at station 2270 mm (89.4 in). Tanks' capacity: S/N:S 20203 to 20246, 60 kg (132 lbs) each, S/N:S 20247 to 20265 and 20267 to 20293, 40 kg (88 lbs) each.

Engine Manufacturer: Bombardier-Rotax GmbH, Gunskirchen, Austria
Model: Rotax 501
Type: Retractable, aircooled, 500 ccm, two-stroke, two-cylinder, single-magneto ignition engine with 2:1 toothed belt transmission to the propeller
Max rpm: 6800
Max continuous rpm: 6000
Max available take-off power: 31.7 kW (43 hp) at 6200 rpm and 100 km/h (62 mph, 54 knots)

Fuel Two-stroke fuel. Normal automobile gasoline, min octane number 96, or aviation gasoline, AVGAS 100 LL, mixed with two-stroke super-quality oil. Mixture ratio 1:40

Propeller Manufacturer: Propellerwerk Hoffmann GmbH, Rosenheim, Federal Republic of Germany
Model: H0 11* - 127 B 87



Manufacturer: Lentokonekorjaamo Pankkonen, Nummenkylä, Finland
 Model: EP P127/87
 Diameter: 1270 mm (50 in) (both models)
 Type: Two-blade, wooden, fixed pitch propeller (both models)

Control Surface Movements

		Up	Down
Flaps		12° ± 1°	16° ± 1°
Ailerons	+16° flap	13° ^{+2°} _{-1°}	12,5° ^{+2°} _{-1°}
	0° flap	12° ^{+2°} _{-1°}	11° ^{+2°} _{-1°}
	-12° flap	11° ^{+2°} _{-1°}	9,5° ^{+2°} _{-1°}

Aileron neutral position travels with flaps up 12° ± 1° thru down 16° ± 1°

Elevator	Up 20° ± 1°	Down 20° ± 1°
Rudder	Right 33° ± 2°	Left 33° ± 2°

Airspeed Limits (I.A.S.)

Never exceed (V _{NE})	280 km/h	(174 mph, 151 kts)
In rough air (V _B)	215 km/h	(134 mph, 116 kts)
Maneuvering (V _A)	190 km/h	(118 mph, 103 kts)
In aero tow (V _T) *	190 km/h	(118 mph, 103 kts)
In winch tow (V _W) *	125 km/h	(78 mph, 67 kts)
With engine extended	195 km/h	(121 mph, 105 kts)
Extending and retracting the engine	135 km/h	(84 mph, 73 kts)

*) Aerotow and winch tow are allowed only if the original tow hook kit is installed. Winch tow is allowed only with the tow hook at rear station 1850 mm (72,8 in), see note 4.

With deflected flaps as follows:

δ_i °		+16	+12...+2	0...-12
	km/h	155	215	280
V	mph	96	134	174
	kts	84	116	151



C.G. Range	19 % to 44 % MAC, 2267 mm to 2443 mm (89.3 in to 96.2 in) Retracting the engine adds 16.5 kgm (1432 lb.in) to the mass moment.
Empty Weight C.G. Range	None
Fuel Capacity	S/N:s 20203 to 20214 and 20216 to 20220: Total 33 litres (8,72 gall U.S.), of which usable 32 litres (8,45 gall U.S.) S/N:s 20215, 20221 to 20265 and 20267 to 20293: Total 29 litres (7,66 gall U.S.) of which usable 28 litres (7,40 gall U.S.), see note 4. Fuel tank is at position 1900 mm (74.8 in).
Datum	Vertical plane 2113 mm (83.19 in) forwards of the first wing fitting tube forward surface.
Levelling Means	Slope of rear top surface of fuselage between stations 4500 mm (177.2 in) and 5500 mm (216.5 in), 1000 to 28 tail down
No. of Seats	One adjustable seat, pilot's C.G. range 1420 mm to 1500 mm (56.0 in. to 59.0 in)
Fixed Ballast	1. Nose station 255 mm (10.0 in), max 10 kg (22 lbs) 2. Tail wheel spring station 6100 mm (240.2 in), max 3 kg (6.6 lbs) 3. In addition on S/N:s 20203 to 20227: Battery compartment station 3730 mm (146,8 in), max 11 kg (24 lbs) including battery Ballast attaching by bolts and nuts or inserts.
Rated Load on Winch and Aero Tow	6000 N (1320 lbs)

1.IV **Operating and Service Instructions**

Required Equipment

The basic required equipment as prescribed in the application airworthiness regulations (see Certification Basis) must be installed in the sailplane for standard airworthiness certification. In addition the following equipment must be installed:

1. Basic instruments and equipment
 - (a) Airspeed indicator
 - (b) Altimeter
 - (c) Magnetic compass
 - (d) Ball type slip indicator
 - (e) Tachometer
 - (f) Fuel quantity indicator
 - (g) Cylinder head temperature indicator
 - (h) Engine hourmeter
 - (i) Seat belts
 - (j) Seat cushion
 - (k) Mirror for checking the propeller position
2. Additional instruments for cloud flying
 - (a) Turn indicator
 - (b) Variometer
3. PIK-20 E Flight Manual approved by the National Board of Aviation, Finland.



Inspections, Maintenance, Repairs and Repainting must be accomplished in accordance with EIRI, Eino Riihelä Ky's PIK-20 E Flight Manual and Service Manual and PIK-20 E Repair Manual.

Major repairs must be performed in accordance with repair methods approved by EIRI, Eino Riihelä Ky.



1.V **Notes, including serial number applicability**

Note 1. The following placards and markings must be displayed in a conspicuous place on the sailplane:

a. Maximum Speeds, Weights and Operational Limits

- i. S/N:s 20203 to 20214 and 20216 to 20220, same as the placard in ii), but without the winch tow limit.
- ii. S/N:s 20215, 20221 to 20265 and 20267 to 20293:

Maximum speed

In calm weather (V_{NE})	280 km/h	174 mph	151 kts
In rough air (V_B)	215 km/h	134 mph	116 kts
Maneuvering (V_A)	190 km/h	118 mph	103 kts
On aero tow (V_T)	190 km/h	118 mph	103 kts
On winch tow (V_W)	125 km/h	78 mph	67 kts
With engine extended	195 km/h	121 mph	105 kts
Extending and retracting the engine	135 km/h	84 mph	73 kts

Weights

Gross weight 470 kg (1036 lbs) including water ballast.

If the pilot's weight with the parachute is below 70 kg (154 lbs) ballast weight must be installed in the nose (see Flight Manual and Weight and Balance Record).

Operational Limitations

This sailplane must be operated in compliance with the operating limits as stated in the form of markings, placards and in the PIK-20 E Flight Manual. All acrobatic maneuvers including spins must be accomplished in accordance with PIK-20 E Flight Manual

NO SMOKING



Maximum airspeed with deflected flaps				
δ_f °		+16	+12...+2	0...-12
	km/h	155	215	280
V	mph	96	134	174
	kts	84	116	151

c. Other placards and markings

- Adjacent to tow coupling RATED LOAD 6000 N (1320 lbs)
- Above the main wheel 2.5 bar (35 psi)
- Adjacent to static pressure entry on fuselage skin STATIC PRESSURE KEEP CLEAR
- Adjacent to oxygen control valve (if installed) DURATION TABLE
- On fuselage nose (inside) BALLAST
- Near the luggage compartment MAX RATED LOAD 15 kg (33 lbs)
- Near the fuel filler opening
S/N:s 20203 to 20214 and 20216 to 20220:
2-STROKE FUEL OIL MIXTURE RATIO 1:40
MIN 96 OCTANE (RON) SUPER GASOLINE
OR AVGAS 100 LL, USABLE CAPACITY 32 L.
S/N:s 20215 and 20221 and up:
same as above but USABLE CAPACITY 28 L
- Near the fuel valve ON... OFF
- Near the draining valve
(S/N:s 20203 to 20214 and 20216 to 20220) DRAIN... OFF
- Near the fuel tank vent
(S/N:s 20215 and 20221 and up) VENT, KEEP CLEAN

The controls or handles for tow coupling release, canopy opening and jettisoning, landing gear, flaps, airbrakes, trim, pedals, ventilation, water ballast draining, engine doors, engine retracting mechanism, fuel cock and engine controls and switches must be equipped with unmistakable symbols or text placards.

The flight speed limitations must be marked on the air speed indicator in accordance with the Flight Manual.



Engine gauges must be marked in accordance with the Flight Manual.



- Note 2. Inspections, Maintenance, Repairs and Repainting must be accomplished in accordance with EIRI, Eino Riihelä Ky's PIK-20 E Flight Manual and Service Manual and PIK-20 E Repair Manual.
- Note 3. Major repairs must be performed in accordance with repair methods approved by EIRI, Eino Riihelä Ky.
- Note 4. On S/N:s 20215 and 20221 and up, the tow hook has been moved backwards to facilitate winch tow operations. Simultaneously the capacity of the fuel tank has been decreased and its vent and drain systems have been modified.

Modification of S/N:s 20203 to 20214 and 20216 to 20220 is feasible in accordance with EIRI, Eino Riihelä Ky's drawings No:s 0-20E-51-100a, 1-20E-31-001a and 3-20E-21-200-26a.

- Note 5. For painting of exterior surfaces must be used only two component polyurethane paints with an aliphatic isocyanate hardener, based on National CAA STC grandfather rights (July 26th 1999).
- Note 6. In addition to the original resin material Rütapox L 02 (L20) + H 91/SL (H91, SL50, SL) the following resins are approved data based on National CAA STC grandfather rights:
- a. Ciba-Geigy – Araldite LY 5052 + HY 5052 (June 29th 2000)
 - b. Scheufler – L285 + Hä285 (March 21st 2000)

- Note 7. Repair methods guided in the Structural Repair Manual of PIK-20's are:

- i. broken monocoque structure
- ii. broken outer surface of sandwich plate
- iii. hole in sandwich plate

In addition the following repair instructions have been approved data based on National CAA STC grandfather rights:

- iv. defect in sandwich core material (June 29th 2000)
- v. depression in sandwich core (December 10th 1993)
- vi. repairing fuselage belly by bevelling (July 26th 1999)
- vii. repairing of ribs and inner structures (December 10th 1993)
- viii. repairing of wing spar flange (July 27th 1983)
- ix. heat-treatment of repaired area (July 27th 1983)
- x. finishing (July 26th 1999)
- xi. general instructions for composite structure repairs

as described in document:

Korhonen H., LUJITEMUOVI ILMA-ALUSTEN MATERIAALINA JA SEN KORJAUSMENETELMÄT, Raisio 2007, 141 p. (in Finnish, title in English: Composites as aircraft structural material and its repair methods).

- Note 8. There has been a maintenance requirement of 1000 hours life limit for rudder cables. The following alternative method to maintenance requirements is approved data based on National CAA STC grandfather rights:



In annual inspection

(July 2nd 1998)

- Check the condition of rudder cables on both ends and especially on the pedal S-curved diversion. If 1/3 of wire thickness has been consumed or if any wires are cut then replace the cable in whole.

Note 9. Manuals and other support documents are available here:

<https://www.traficom.fi/en/pik-20-support>



Variant 2 PIK-20E II

2.I General

POWERED SAILPLANE SPECIFICATION No.P-7

This specification which is a part of the Type Certificate No.P-7 prescribes conditions and limitations under which the product, for which the Type Certificate was issued, meets the Airworthiness Requirements of Finland.

Type Certificate Holder EIRI, Eino Riihelä Ky
Kisällinkatu 8
FI-15170 Lahti
Finland
(Formerly Holder: Eiriavion Oy)

2.II Certification Basis

OSTIV Airworthiness Requirements for Sailplanes, September 1976, Utility Category, Powered Sailplanes. German Airworthiness Requirements for Sailplanes and Powered Sailplanes (LFSM), October 1975, Utility Category, Powered Sailplanes.

ICAO Annex 16, Third Edition, Chapter 6, July 1978.

2.III Technical Characteristics and Operational Limitations

Model PIK-20 E II, Approved August 22, 1980

Serial Nos. eligible 20266, 20294 and up

Maximum Weight 470 kg (1036 lbs) including water ballast

Maximum weight of
Non-Lifting Parts 328 kg (723 lbs)

Water Ballast Two water ballast tanks at station 2270 mm (89.4 in). Tanks' capacity 40 kg (88 lbs) each.

Engine Manufacturer: Bombardier-Rotax GmbH, Gunskirchen, Austria
Model: Rotax 505
Type: Retractable, aircooled, 500 ccm, two-stroke,
two-cylinder, dual-magneto ignition engine with 2:1 toothed
belt transmission to the propeller
Max rpm: 6800
Max continuous rpm: 6000
Max available take-off power: 31,7 kW (43 hp) at 6200
rpm and 100 km/h (62 mph, 54 knots)

Fuel Two-stroke fuel. Normal automobile gasoline, min octane number 96, or aviation gasoline, AVGAS 100 LL, mixed with two-stroke super-quality oil. Mixture ratio 1:40

Propeller Manufacturer: Propellerwerk Hoffmann GmbH, Rosenheim,
Federal Republic of Germany
Model: H0 11* - 127 B 87
Manufacturer: Lentokonekorjaamo Pankkonen, Nummenkylä,
Finland
Model: EP P127/87
Diameter: 1270 mm (50 in) (both models)
Type: Two-blade, wooden, fixed pitch propeller (both models)



Control Surface Movements

		Up	Down
Flaps		12° ± 1°	16° ± 1°
Ailerons	+16° flap	13° ^{+2°} _{-1°}	12,5° ^{+2°} _{-1°}
	0° flap	12° ^{+2°} _{-1°}	11° ^{+2°} _{-1°}
	-12° flap	11° ^{+2°} _{-1°}	9,5° ^{+2°} _{-1°}

Aileron neutral position travels with flaps up 12° ± 1° thru down 16° ± 1°

Elevator	Up 20° ± 1°	Down 20° ± 1°
Rudder	Right 33° ± 2°	Left 33° ± 2°

Airspeed Limits (I.A.S.)

Never exceed (V _{NE})	280 km/h	(174 mph, 151 kts)
In rough air (V _B)	215 km/h	(134 mph, 116 kts)
Maneuvering (V _A)	190 km/h	(118 mph, 103 kts)
In aero tow (V _T) *)	190 km/h	(118 mph, 103 kts)
In winch tow (V _W) *)	125 km/h	(78 mph, 67 kts)
With engine extended	195 km/h	(121 mph, 105 kts)
Extending and retracting the engine	135 km/h	(84 mph, 73 kts)

*) Aerotow and winch tow are allowed only if the original tow hook kit is installed.

With deflected flaps as follows:

δ _f °		+16	+12...+2	0...-12
	km/h	155	215	280
V	mph	96	134	174
	kts	84	116	151

C.G. Range 19 % to 44 % MAC, 2267 mm to 2443 mm (89.3 in to 96.2 in)
Retracting the engine adds 16.5 kgm (1432 lb.in) to the mass moment.

Empty Weight C.G. Range None



Fuel Capacity	Total 29 litres (7,66 gall U.S.) of which usable 28 litres (7,40 gall U.S.) Fuel tank is at position 1900 mm (74.8 in).
Datum	Vertical plane 2113 mm (83.19 in) forwards of the first wing fitting tube forward surface.
Levelling Means	Slope of rear top surface of fuselage between stations 4500 mm (177.2 in) and 5500 mm (216.5 in), 1000 to 28 tail down
No. of Seats	One adjustable seat, pilot's C.G. range 1420 mm to 1500 mm (56.0 in. to 59.0 in)
Fixed Ballast	1. Nose station 255 mm (10.0 in), max 10 kg (22 lbs) 2. Tail wheel spring station 6100 mm (240.2 in), max 3 kg (6.6 lbs) Ballast attaching by bolts and nuts or inserts.
Rated Load on Winch and Aero Tow	6000 N (1320 lbs)

2.IV Operating and Service Instructions

Required Equipment

The basic required equipment as prescribed in the application airworthiness regulations (see Certification Basis) must be installed in the sailplane for standard airworthiness certification. In addition the following equipment must be installed:

1. Basic instruments and equipment
 - (a) Airspeed indicator
 - (b) Altimeter
 - (c) Magnetic compass
 - (d) Ball type slip indicator
 - (e) Tachometer
 - (f) Fuel quantity indicator
 - (g) Cylinder head temperature indicator
 - (h) Engine hourmeter
 - (i) Seat belts
 - (j) Seat cushion
 - (k) Mirror for checking the propeller position
2. Additional instruments for cloud flying
 - (a) Turn indicator
 - (b) Variometer
3. PIK-20 E II Flight Manual approved by the National Board of Aviation, Finland.

Inspections, Maintenance, Repairs and Repainting must be accomplished in accordance with EIRI, Eino Riihelä Ky's PIK-20 E II Flight Manual and Service Manual and PIK-20 E Repair Manual.

Major repairs must be performed in accordance with repair methods approved by EIRI, Eino Riihelä Ky.



2.V **Notes, including serial number applicability**

Note 1. The following placards and markings must be displayed in a conspicuous place on the sailplane:

a. Maximum Speeds, Weights and Operational Limits

Maximum speed

In calm weather (V_{NE})	280 km/h	174 mph	151 kts
In rough air (V_B)	215 km/h	134 mph	116 kts
Maneuvering (V_A)	190 km/h	118 mph	103 kts
In aero tow (V_T)	190 km/h	118 mph	103 kts
In winch tow (V_W)	125 km/h	78 mph	67 kts
With engine extended	195 km/h	121 mph	105 kts
Extending and retracting the engine	135 km/h	84 mph	73 kts

Weights

Gross weight 470 kg (1036 lbs) including water ballast.

If the pilot's weight with the parachute is below 70 kg (154 lbs) ballast weight must be installed in the nose (see Flight Manual and Weight and Balance Record).

Operational Limitations

This sailplane must be operated in compliance with the operating limits as stated in the form of markings, placards and in the PIK-20 E II Flight Manual. All acrobatic maneuvers including spins must be accomplished in accordance with PIK-20 E II Flight Manual

NO SMOKING



Maximum airspeed with deflected flaps				
δ_f °		+16	+12...+2	0...-12
	km/h	155	215	280
V	mph	96	134	174
	kts	84	116	151

c. Other placards and markings

- Adjacent to tow coupling RATED LOAD 6000 N (1320 lbs)
- Above the main wheel 2.5 bar (35 psi)
- Adjacent to static pressure entry on fuselage skin STATIC PRESSURE KEEP CLEAR
- Adjacent to oxygen control valve (if installed) DURATION TABLE
- On fuselage nose (inside) BALLAST
- Near the luggage compartment MAX RATED LOAD 15 kg (33 lbs)
- Near the fuel filler opening 2-STROKE FUEL OIL MIXTURE RATIO 1:40
MIN 96 OCTANE (RON) SUPER GASOLINE
OR AVGAS 100 LL, USABLE CAPACITY 28 L.
- Near the fuel valve ON... OFF
- Near the fuel tank vent VENT, KEEP CLEAN

The controls or handles for tow coupling release, canopy opening and jettisoning, landing gear, flaps, airbrakes, trim, pedals, ventilation, water ballast draining, engine doors, engine retracting mechanism, fuel cock and engine controls and switches must be equipped with unmistakable symbols or text placards.

The flight speed limitations must be marked on the air speed indicator in accordance with the Flight Manual.

Engine gauges must be marked in accordance with the Flight Manual.

Note 2. Inspections, Maintenance, Repairs and Repainting must be accomplished in accordance with EIRI, Eino Riihelä Ky's PIK-20 E II Flight Manual and Service Manual and PIK-20 E Repair Manual.

Note 3. Major repairs must be performed in accordance with repair methods approved by EIRI, Eino Riihelä Ky.



Note 4. On S/N:s 20215 and 20221 and up, the tow hook has been moved backwards to facilitate winch tow operations. Simultaneously the capacity of the fuel tank has been decreased and its vent and drain systems have been modified.

Note 5. For painting of exterior surfaces must be used only two component polyurethane paints with an aliphatic isocyanate hardener, based on National CAA STC grandfather rights (July 26th 1999).

Note 6. In addition to the original resin material Rütapox L 02 (L20) + H 91/SL (H91, SL50, SL) the following resins are approved data based on National CAA STC grandfather rights:

c. Ciba-Geigy – Araldite LY 5052 + HY 5052 (June 29th 2000)

d. Scheufler – L285 + Hä285 (March 21st 2000)

Note 7. Repair methods guided in the Structural Repair Manual of PIK-20's are:

- xii. broken monocoque structure
- xiii. broken outer surface of sandwich plate
- xiv. hole in sandwich plate

In addition the following repair instructions are approved data based on National CAA STC grandfather rights:

- xv. defect in sandwich core material (June 29th 2000)
- xvi. depression in sandwich core (December 10th 1993)
- xvii. repairing fuselage belly by bevelling (July 26th 1999)
- xviii. repairing of ribs and inner structures (December 10th 1993)
- xix. repairing of wing spar flange (July 27th 1983)
- xx. heat-treatment of repaired area (July 27th 1983)
- xxi. finishing (July 26th 1999)
- xxii. general instructions for composite structure repairs

as described in document:

Korhonen H., LUJITEMUOVI ILMA-ALUSTEN MATERIAALINA JA SEN KORJAUSMENETELMÄT, Raisio 2007, 141 p. (in Finnish, title in English: Composites as aircraft structural material and its repair methods).

Note 8. There has been a maintenance requirement of 1000 hours life limit for rudder cables. The following alternative method to maintenance requirements is approved data based on National CAA STC grandfather rights:

In annual inspection (July 2nd 1998)

- Check the condition of rudder cables on both ends and especially on the pedal S-curved diversion. If 1/3 of wire thickness has been consumed or if any wires are cut then replace the cable in whole.

Note 9. Manuals and other support documents are available here:

<https://www.traficom.fi/en/pik-20-support>



SECTION 2: **Airworthiness Directives**

The following ADs and additional data can be found at
<https://www.traficom.fi/en/pik-20-airworthiness-directives-and-service-bulletins>

Variant 1 **PIK-20E**

AD	Date	Heading	Ref.
746	1.8.1977	Safety belts (sn: all)	M15
	9.7.1979	Special requirement for the United Kingdom (sn: 20213, 20214, 20217, 20218)	M20E-2
	17.12.1979	Chafe of fuel tank (sn: 20215, 20221-20233, 20235)	M20E-3
	14.2.1980	Flughandbuch, Betriebs- und Wartungshandbuch	
	17.3.1980	Insufficient fuel flow (sn: 20103-20259)	M20E-4
	17.3.1980	Flight Manual	
	16.4.1980	Service Manual	
	14.10.1980	Saving battery power when soaring (sn: 20213, 20214, 20217-20265, 20267-20293)	H20E-1a
	6.11.1980	Warning system for the open engine doors (sn: 20203-20293)	H20E-2
	10.11.1980	Lubricating and removing the propeller drive gear bearings (sn: all)	H20E-3
	18.11.1980	Huolto-ohjekirja	
	20.11.1980	Auxiliary spring for safety cable (sn: 20203-20256)	H20E-4
	24.11.1980	Transfer of cylinder head temperature (CHT) sensor (sn: 20203-20248)	H20E-5
1200	31.10.1983	Inspection of the fuel system inlets (sn: all)	
1737-1	15.10.1990	Propeller hub mounting (sn: all)	LTA90-239



SECTION 3: **Occurrence Reporting**

The Specific Airworthiness Specification may be used as a basis for the issue of a Restricted Certificate of Airworthiness in accordance with 21.A.173 (b)2 under the following conditions:

- a) The holder of a Restricted Certificate of Airworthiness based on this Specific Airworthiness Specification shall report to the Agency any identified condition of the aircraft, which endangers flight safety.
- b) Reports shall be made as soon as practicable, but in any case, within 72 hours by using the reporting tool at <http://www.aviationreporting.eu/>
Please select "EASA" when being asked to select the State to report to.

SECTION 4: **Other Limitations**

This aircraft is limited to non-commercial operation.

SECTION 5: **Change record**

Issue 1: Initial issue dated 22 August 2007

Issue 2: 28 April 2011. Addition of notes 5 to 8 for PIK-20E and PIK-20E II, fallen out by mishap in the previous issue.

Issue 3: 27 August 2021. URL to PIK 20 support updated, Section 2. Occurrence Reporting in Section 3 updated.

Issue 4: 12 April 2022. Note 9 introduced: Support URL: <https://www.traficom.fi/en/pik-20-support>

