



TYPE-CERTIFICATE DATA SHEET

No. EASA.R.002

for

SA 330 / AS 332 / EC 225

Type Certificate Holder

Airbus Helicopters

Aéroport International Marseille – Provence

13725 Marignane CEDEX

France

For Models: SA 330 J
AS 332 C, AS 332 L, AS 332 C1, AS 332 L1, AS 332 L2
EC 225 LP





TABLE OF CONTENTS

SECTION 1: SA 330 J.....	4
I. General.....	4
II. Certification Basis	4
III. Technical Characteristics and Operational Limitations.....	4
IV. Operating and Service Instructions.....	6
V. Notes.....	7
SECTION 2: AS 332 C, C1, L, L1	8
I. General.....	8
II. Certification Basis	8
III. Technical Characteristics and Operational Limitations.....	9
IV. Operating and Service Instructions.....	12
V. Notes.....	13
SECTION 3: AS 332 L2	16
I. General.....	16
II. Certification Basis	16
III. Technical Characteristics and Operational Limitations.....	17
IV. Operating and Service Instructions.....	19
V. Notes.....	19
SECTION 4: EC 225 LP	20
I. General.....	20
II. Certification Basis	20
III. Technical Characteristics and Operational Limitations.....	22
IV. Operating and Service Instructions.....	24
V. Notes.....	25
SECTION 5: OPERATIONAL SUITABILITY DATA (OSD)	26
OSD Elements	26
SECTION: ADMINISTRATIVE.....	27
I. Acronyms and Abbreviations.....	27
II. Type Certificate Holder Record	27
III. Change Record.....	28



SECTION 1: SA 330 J**I. General**

1. Type/ Model/ Variant	
1.1 Type	SA 330
1.2 Model	SA 330 J (for memory of SA 330 F and SA 330 G, see Note 5)
2. Airworthiness Category	Large Rotorcraft, Category A and B
3. Manufacturer	See SECTION: ADMINISTRATIVE, II. for manufacturer record
4. DGAC FR Type Certification Application Date	not recorded
5. State of Design Authority	EASA (pre EASA: DGAC FR, France)
6. DGAC FR Type Certificate Date	29 April 1976
7. DGAC FR Type Certificate n°	56
8. DGAC FR Type Certificate Data Sheet n°	127 issue 9 dated September, 1994
9. EASA Type Certification Date	28 September 2003, in accordance with CR (EU) 1702/2003, Article 2, 3., (a), (i), 2 nd bullet, 1 st indented bullet.

II. Certification Basis

1. Reference Date for determining the applicable requirements	not recorded
2. Airworthiness Requirements	According to DGAC letter 02827 SFACT/TC, dated 30 March 1978: FAR 29, Amdts. 29-1 to 29-9 inclusive and the addition of FAR 29.951 (c), 29.1183, 29.1305 (a)(16) of Amdt. 29-10 for SA 330 J equipped with white anti-collision light.
3. Special Conditions	DGAC-F CS n°1 – Icing; DGAC-F CS n°2 – Lightning
4. Deviations	For SA 330 J fitted with red anti-collision light FAR 29 Amdt. 29-7 is excluded
5. Equivalent Safety Findings	none
6. Environmental Protection Requirements	
6.1 Noise Requirements	See TCDSN EASA.R.002
6.2 Emission Requirements	n/a
7. Operational Suitability Data (OSD)	Not required for rotorcraft that are no longer in production. CR (EU) 748/2012, as amended by CR (EU) 69/2014 does not require OSD elements for this model (see Article 7a, 1.).

III. Technical Characteristics and Operational Limitations

1. Type Design Definition	SA 330 J definition is obtained by applying modifications mentioned in note 330A.05.0065 to the definition of former SA 330 G model, which consisted itself of SA 330 F previous model with design changes as listed in note 330A.05.0060 (see also Note 5)
---------------------------	---



2. Description	Large twin-engine rotorcraft; SA 330 J model is a derivative design of former SA 330 G, which is originally derived from SA 330 F model (see also Note 5)
3. Equipment	As per compliance with applicable FAR 29 airworthiness requirements and referenced in approved RFM
4. Dimensions	
4.1 Fuselage	Length: 14.82 m Width stabiliser: 3.00 m Height: 5.14 m
4.2 Main Rotor	Diameter: 15.09 m (4 blades)
4.3 Tail Rotor	Diameter: 3.04 m (5 blades)
5. Engine	
5.1 Model	Safran Helicopter Engines (former: Turbomeca) 2 x Model TURMO IV C
5.2 Type Certificate	DGAC FR n°: M8 EASA TC/TCDS n°: EASA.E.074
5.3 Limitations	
5.3.1 Installed Engine Limits	Refer to approved RFM
5.3.2 Transmission Torque Limits	Refer to approved RFM
6. Fluids	
6.1 Fuel	Refer to approved RFM
6.2 Oil	Refer to approved RFM
6.3 Additives	Refer to approved RFM
7. Fluid capacities	
7.1 Fuel	Fuel tank capacity: 1 565 litres (413 US gal) Usable fuel: 1 544 litres (408 US gal)
7.2 Oil	Engines: 2 x 12.0 litres MGB: 22.0 litres IGB: 0.75 litre TGB: 1.4 litre
7.3 Coolant System Capacity	n/a
8. Air Speeds Limits	$V_{NE\ PWR\ ON}$: 310 km/h (167 KIAS) at ISA sea level for 4 000 kg. See RFM for other approved airspeed limits.
9. Rotor Speed Limits	Power on: Nominal governed 265 rpm \pm 7 rpm Minimum transient 220 rpm Power off: Maximum 310 rpm Minimum (< 108 KIAS) 220 rpm (> 108 KIAS) 240 rpm
10. Maximum Operating Altitude and Temperature	
10.1 Altitude	TKOF/LDG: -1 650 ft to +13 000 ft PA Enroute: +16 500 ft PA
10.2 Temperature	- 40°C to + 50°C
11. Operating Limitations	VFR day and night, IFR, Non-icing conditions
12. Maximum Mass	TKOF/LDG: 7 400 kg (16 314 lb)



13. Centre of Gravity Range	Refer to approved RFM
14. Datum	Longitudinal: STA 0: 4.700 m (185.04 in) forward of main rotor centreline Lateral: aircraft symmetry plane
15. Levelling Means	Levelling plate on right side of the fuselage and graduated plate for plumb line on cabin floor (left side door)
16. Minimum Flight Crew	VFR: 1 pilot in Category B 1 pilot + 1 crew member in Category A IFR: 2 pilots in Categories A and B
17. Maximum Passenger Seating Capacity	19
18. Passenger Emergency Exit	Refer to approved RFM
19. Maximum Baggage/ Cargo Loads	The cabin floor (from +2.48 m to +7.63 m) is provided with the structural strength required for a load of 800 kg/m ² evenly distributed in cargo configuration
20. Rotor Blade Control Movement	For rigging information refer to AMM
21. Auxiliary Power Unit (APU)	n/a
22. Life-limited Parts	Refer to approved Airworthiness Limitations Section
23. Wheels and Tyres	Wheels: NLG Messier Bugatti C20525000 (two) MLG Messier Bugatti C20525000 (two each side) Tyres: NLG 7.00-6 (two) MLG 7.00-6 (two each side)

IV. Operating and Service Instructions

1. Flight Manual	SA 330 J Flight Manual approved on 29 April 1976 by DGAC FR, or subsequent DGAC FR or EASA approved revisions.
2. Maintenance Manual	SA 330 Maintenance Manual including: - Maintenance programme as per Maintenance Servicing Recommendations (PRE); - Airworthiness Limitations Section as per PRE Chapter 05.99 approved by DGAC FR, or subsequent DGAC FR or EASA approved revisions;
3. Structural Repair Manual	SA 330 Structural Repair Manual
4. Weight and Balance Manual	Refer to approved RFM
5. Illustrated Parts Catalogue	SA 330 J Illustrated Parts Catalogue
6. Service Letters and Service Bulletins	As published by Aérospatiale, Eurocopter or Airbus Helicopters
7. Required Equipment	<ul style="list-style-type: none"> - As per compliance with applicable FAR 29 requirements and in accordance with the original Type Design standard, refer also to the approved RFM; - Approved equipment items are covered by document No 330A.04.1155 dated 17 September 1970 updated to issue J on 26 March 1981; - Approved equipment items required for the flight in icing conditions are covered by document 330A.04.1483



V. Notes

1. Manufacturer's serial numbers:
S/N 1371, and subsequent of model SA 330 J are eligible.
2. The certified "optional" installations are each approved independently of the basic helicopter and an approved Flight Manual Supplement is associated to each optional installation if necessary.
3. Cabin Interior and Seating Configurations must be approved.
4. Commercial designation: PUMA
5. Upon Eurocopter request for its surrender, the Type Certificate of both models SA 330 G and SA 330 F has been revoked by EASA as of 12 November 2009 (see EASA Certification Information No. 2009-17, dated 16 November 2009).

* * *



SECTION 2: AS 332 C, C1, L, L1I. General

1. Type/ Model/ Variant	
1.1 Type	AS 332
1.2 Model	AS 332 C, AS 332 C1, AS 332 L, AS 332 L1
2. Airworthiness Category	Large Rotorcraft, Category A and B
3. Manufacturer	See SECTION: ADMINISTRATIVE, II. for manufacturer record
4. DGAC FR Type Certification Application Date	AS 332 C: 4 April 1978 AS 332 L: 16 July 1980 AS 332 C1 and L1: 18 June 1984
5. State of Design Authority	EASA (pre EASA: DGAC FR, France)
6. DGAC FR Type Certificate Date	AS 332 C: 24 April 1981 AS 332 L: 2 December 1981 AS 332 C1 and L1: 14 March 1985
7. DGAC FR Type Certificate n°	56
8. DGAC FR Type Certificate Data Sheet n°	127 issue 9 dated September, 1994
9. EASA Type Certification Date	28 September 2003, in accordance with CR (EU) 1702/2003, Article 2, 3., (a), (i), 2 nd bullet, 1 st indented bullet.

II. Certification Basis

1. Reference Date for determining the applicable requirements	For Airworthiness and Environmental Protection: not recorded for OSD elements: 17 February 2014 (grandfathering date)
2. Airworthiness Requirements	For AS 332 C, C1, L, L1 (*): FAR 29 with Amdts. 29-1 to 29-16 included. (*) according to DGAC letter 53.904, dated 18 August 1980 and document 'Airworthiness Criteria for Helicopter Instrument Flight', dated 15 December 1978 for IFR flight. For AS 332 C1 and L1 equipped with AHCAS (commercial reference AS 332 C1e and AS 332 L1e): according to A-01 (see also Note 8). For AS 332 C, C1, L, L1 equipped with FFMP (MOD 07.53061): FAR 29.1309(b)(2) Amdt. 24 and FAR 29.1309(d) Amdt. 24 are applicable (A-01) for the areas affected by the design change.



3. Special Conditions

For AS 332 C, C1, L, L1; see note identified with (*) in item 2 above:

- DGAC-F SC n°1 (Icing) and DGAC-F SC n°2 (Lightning) as applicable to previous SA 330 J model and notified by DGAC-F letter 02827 SFACT/TC, dated 30 March 1978.
- DGAC-F SC n°20.2, dated 11 May 1982 for category II, IFR flight.

For AS 332 C1 and L1 equipped with AHCAS (commercial reference AS 332 C1e and AS 332 L1e, see also Note 8):

- Minimum in-flight experience (B-01).
- Search and Rescue system (B-02).
- Protection from the effects of High Intensity Radiated Fields (HIRF) (F-02).

For AS 332 C1 and L1: Non-rechargeable Lithium Battery Installations (F-09).

4. Deviations

none

5. Equivalent Safety Findings

For AS 332 C, C1, L, L1; see note identified with (*) in item 2 above:

- Endurance Tests of redesigned Tail Rotor Hub pitch change control assembly (MOD 07.66205) (E-01).

For AS 332 C1 and L1 equipped with AHCAS (commercial reference AS 332 C1e and AS 332 L1e, see also Note 8):

- IFR Static Longitudinal Stability – Airspeed Stability (B-04).
- V_{NE} aural warning (F-01).
- Airspeed indicator markings (G-01).
- Powerplant instrument markings (G-02).

6. Environmental Protection Requirements

6.1 Noise Requirements See TCDSN EASA.R.002

6.2 Emission Requirements n/a

7. Operational Suitability Data (OSD) (For OSD elements see SECTION 5)

7.1 Master Minimum Equipment List (MMEL) JAR-MMEL/MEL Section 1, Subpart A and B, Amdt. 1, dated 1 August 2005

7.2 Flight Crew Data (FCD) CS-FCD Initial Issue, dated 31 January 2014 (refer to EASA approval 10060827)

7.3 Simulation Data (SIMD) reserved

7.4 Maintenance Certifying Staff Data (MCSD) reserved

7.5 Cabin Crew Data (CCD) reserved

III. Technical Characteristics and Operational Limitations

1. Type Design Definition

For AS 332 C:

as per document 332A04.0009 and modifications list in doc. 332A04.3269 for 8 350 kg

For AS 332 L:

as per doc. 332A04.0010 for 8 350 kg

For AS 332 C, L:

as per doc. 332A04.3300 for 8 600 kg

For AS 332 C1, L1:

as per doc. 332A04.3305 for 8 600 kg

For AS 332 C1 and L1 equipped with AHCAS (commercial reference AS 332 C1e and AS 332 L1e): see Note 8



2. Description	Large twin-engine rotorcraft; derivative design of former type certified SA 330 models, featuring: - two fuselage length configurations (standard for AS 332 C, C1; extended for AS 332 L, L1), - two engines configurations (MAKILA 1A for AS 332 C, L; MAKILA 1A1 for AS 332 C1, L1)
3. Equipment	As per compliance with applicable FAR 29 airworthiness requirements and referenced in approved RFM
4. Dimensions	
4.1 Fuselage	for AS 332 C, C1: Length: 15.53 m Width stabiliser: 3.79 m Height: 4.94 m for AS 332 L, L1: Length: 16.29 m Width stabiliser: 3.79 m Height: 4.95 m
4.2 Main Rotor	Diameter: 15.60 m (4 blades)
4.3 Tail Rotor	Diameter: 3.05 m (5 blades)
5. Engine	
5.1 Model	Safran Helicopter Engines (former: Turbomeca) for AS 332 C, L: 2 x Model MAKILA 1A for AS 332 C1, L1: 2 x Model MAKILA 1A1
5.2 Type Certificate	EASA TC/TCDS n°: EASA.E.072
5.3 Limitations	
5.3.1 Installed Engine Limits	Refer to approved RFM
5.3.2 Transmission Torque Limits	Refer to approved RFM
6. Fluids	
6.1 Fuel	Refer to approved RFM
6.2 Oil	Refer to approved RFM
6.3 Additives	Refer to approved RFM
7. Fluid capacities	
7.1 Fuel	For AS 332 C, C1: Standard configuration: 1 556 litres (411 US gal) with optional internal 6th tank 324 litres (86 US gal) with optional sponson tanks <u>650 litres (172 US gal)</u> Total available fuel: 2 530 litres (669 US gal) For AS 332 L, L1: Standard configuration: 2 043 litres (540 US gal) with optional internal 7 th tank 324 litres (86 US gal) with optional sponson tanks <u>650 litres (172 US gal)</u> Total available fuel: 3 017 litres (798 US gal) <u>Note to all models:</u> see RFM for other approved optional fuel tanks configurations and for unusable fuel quantities.
7.2 Oil	Engines: 2 x 7.6 litres MGB: 19.6 litres IGB: 0.62 litre TGB: 1.44 litre



7.3 Coolant System Capacity	n/a																
8. Air Speeds Limits	<p>At ISA sea level for mass \leq 8 350 kg (18 409 lb): $V_{NE\ PWR\ ON}$: 310 km/h (167 KIAS) $V_{NE\ PWR\ OFF}$: 278 km/h (150 KIAS)</p> <p>At ISA sea level for mass $>$ 8 350 kg (18 409 lb): $V_{NE\ PWR\ ON}$: 278 km/h (150 KIAS) $V_{NE\ PWR\ OFF}$: 268 km/h (145 KIAS)</p>																
9. Rotor Speed Limits	<p>Power on:</p> <table> <tr><td>Maximum</td><td>275 rpm</td></tr> <tr><td>Nominal</td><td>265 rpm</td></tr> <tr><td>Minimum</td><td>245 rpm</td></tr> <tr><td>Minimum transient</td><td>220 rpm</td></tr> </table> <p>Power off:</p> <table> <tr><td>Maximum transient (20 sec)</td><td>310 rpm</td></tr> <tr><td>Maximum</td><td>290 rpm</td></tr> <tr><td>Minimum (> 100 KIAS)</td><td>245 rpm</td></tr> <tr><td>Minimum (< 100 KIAS)</td><td>220 rpm</td></tr> </table>	Maximum	275 rpm	Nominal	265 rpm	Minimum	245 rpm	Minimum transient	220 rpm	Maximum transient (20 sec)	310 rpm	Maximum	290 rpm	Minimum (> 100 KIAS)	245 rpm	Minimum (< 100 KIAS)	220 rpm
Maximum	275 rpm																
Nominal	265 rpm																
Minimum	245 rpm																
Minimum transient	220 rpm																
Maximum transient (20 sec)	310 rpm																
Maximum	290 rpm																
Minimum (> 100 KIAS)	245 rpm																
Minimum (< 100 KIAS)	220 rpm																
10. Maximum Operating Altitude and Temperature	<p>For AS 332 C, L:</p> <p>TKOF/LDG: 15 000 ft PA for mass \leq 8 350 kg (18 409 lb) 6 000 ft PA for mass $>$ 8 350 kg (18 409 lb)</p> <p>Enroute: 20 000 ft PA</p> <p>For AS 332 C1, L1:</p> <p>TKOF/LDG: -1 640 ft PA / +15 000 ft DA</p> <p>Enroute: -1 640 ft/+25 000 ft PA</p> <p>for mass \leq 8 350 kg (18 409 lb) -1 640 ft/+9 500 ft PA for mass $>$ 8 350 kg (18 409 lb)</p>																
10.2 Temperature	-30°C to ISA +35°C, limited to 50°C. See relevant RFMS for colder operation down to -45°C.																
11. Operating Limitations	VFR day and night, IFR, Non-icing conditions Flight in full icing conditions is permitted on AS 332 C, L and L1 models only when equipment items listed in relevant flight manual supplement are installed. Flight in limited icing conditions is permitted on AS 332 L and L1 models only when equipment items listed in relevant approved RFMS are installed (see Note 6).																
12. Maximum Mass	<p>TKOF/LDG for AS 332 C, L:</p> <p>8 350 kg (18 409 lb), prior SB 01.03 embodiment</p> <p>8 600 kg (18 960 lb), after SB 01.03 embodiment</p> <p>TKOF/LDG for AS 332 C1, L1:</p> <p>8 600 kg (18 960 lb)</p>																
13. Centre of Gravity Range	Refer to approved RFM																
14. Datum	Longitudinal: STA 0: 4.670 m (183.86 in) forward of main rotor centreline Lateral: aircraft symmetry plane																
15. Levelling Means	Levelling plate on right side of the fuselage and graduated plate for plumb line on cabin floor (left side door)																



16. Minimum Flight Crew	For AS 332 C, L: VFR: 1 pilot + 1 qualified crew member (*) IFR: 2 pilots For AS 332 C1, L1: VFR: < 20 000 ft, 1 pilot + 1 qualified crew member (*) > 20 000 ft, 2 pilots IFR: 2 pilots (*) the qualified crew member is not required if, at least, one lane of each AP channel is in operation AS 332 C1 and L1 equipped with AHCAS (commercial reference AS 332 C1e and AS 332 L1e): VFR: 1 pilot IFR: 2 pilots
17. Maximum Passenger Seating Capacity	For AS 332 C, C1: 19 For AS 332 L, L1: 24
18. Passenger Emergency Exit	Refer to approved RFM
19. Maximum Baggage/ Cargo Loads	The cabin floor (from +2.48 m to +7.63 m) is provided with the structural strength required for a load of 800 kg/m ² evenly distributed in cargo configuration
20. Rotor Blade Control Movement	For rigging information refer to AMM
21. Auxiliary Power Unit (APU)	n/a
22. Life-limited Parts	Refer to approved Airworthiness Limitations Section
23. Wheels and Tyres	Wheels: NLG Messier Bugatti C20525000 (two) MLG Messier Bugatti C20147200 (one each side) Tyres: NLG 7.00-6 (two) MLG 615 x 225-10 (one each side)

IV. Operating and Service Instructions

1. Flight Manual

AS 332 C:
Flight Manual approved on 24 April 1981 by DGAC-F, or subsequent DGAC-F, or EASA approved revisions
AS 332 L:
Flight Manual approved on 2 December 1981 by DGAC-F, or subsequent DGAC-F, or EASA approved revisions
AS 332 C1:
Flight Manual approved on 14 March 1985 by DGAC-F, or subsequent DGAC-F, or EASA approved revisions
AS 332 L1:
Flight Manual approved on 14 March 1985 by DGAC-F, or subsequent DGAC-F, or EASA approved revisions
AS 332 L1 equipped with AHCAS (commercial reference AS 332 L1e):
Flight Manual approved on 14 June 2012 by EASA or subsequent approved revisions.
AS 332 C1 equipped with AHCAS (commercial reference AS 332 C1e):
Flight Manual approved on 13 November 2013 by EASA or subsequent approved revisions.



2. Maintenance Manual	Maintenance Programme: - AS 332 C, C1, L, L1 Maintenance Servicing Recommendations (PRE), - AS 332 C, C1, L, L1 Aircraft Maintenance Manual (AMM)
3. Structural Repair Manual	AS 332 C, C1, L, L1 Repair Manual
4. Weight and Balance Manual	Refer to approved RFM
5. Illustrated Parts Catalogue	AS 332 C, C1, L, L1 Illustrated Parts Catalogue
6. Service Letters and Service Bulletins	As published by Aérospatiale, Eurocopter or Airbus Helicopters
7. Required Equipment	<ul style="list-style-type: none"> - As per compliance with applicable FAR 29 requirements and in accordance with the original Type Design standard; - Approved equipment items are covered by document No 332A.04.3254, dated 14 May 1981 - Refer to approved Flight Manual, MMEL and also to Note 7 below.

V. Notes

1. Manufacturer's serial numbers:
- AS 332 C: s/n 2001, and subsequent;
- AS 332 C1: see Note 2;
- AS 332 L: s/n 2004; and subsequent;
- AS 332 L1: s/n 2132, and subsequent; see Note 2;
are eligible.
2. Conversion from AS 332 C, L models to AS 332 C1, L1 models possible through SB 01.00.26.
3. The certified 'optional' installations are each approved independently of the basic helicopter and an approved Flight Manual Supplement is associated to each optional installation, if necessary.
4. Cabin Interior and Seating Configurations must be approved.
5. Commercial designation 'SUPER PUMA Mk I' corresponds to AS 332 C, C1, L and L1 models.
Commercial references AS 332 C1e and AS 332 L1e are used for AS 332 C1 and AS 332 L1 equipped with AHCAS system and modifications listed below in Note 8.
Since 1 Jan 2016, H215 is the new commercial designation for AS 332 C1e and AS 332 L1e, the two versions being respectively differentiated as H215 short version / H215 long version.
6. Flight in "icing conditions of limited severity":
- permitted on AS 332 L and L1 models only, with relevant Flight Manual Supplement at revisions approved by DGAC-F or EASA;
- The Flight Manual Supplement does not constitute operational approval and operations must be conducted in accordance with applicable operational regulation.
7. AS 332 C, L and L1 helicopters without MGB fire detection system are those modified by AMS 07-21653.



8. For AS 332 C1, L1 aircraft with the following modifications installed (commercial reference AS 332 C1e, AS 332 L1e), the design change was classified as 'significant' per 21.A.101 and the certification basis is listed below:

- MOD 07.26640 - Hydraulic and flight control adaptation for AFCS integration;
- MOD 07.26641 - VMS installation;
- MOD 07.26642 - AFCS installation;
- MOD 07.26643 - FDS installation;
- MOD 07.26644 - Primary references installation;
- MOD 07.26645 - Cockpit adaptation for AHCAS installation;
- MOD 07.26646 - Cockpit lighting;
- MOD 07.26647 - Electrical wiring and connections adaptation;
- MOD 07.26648 - Electrical power distribution modification;
- MOD 07.26649 - Warnings/Cautions and ancillaries adaptation;
- MOD 07.26650 - Equipment installation structure adaptation.

Affected Area

The affected area (primary design change) is aircraft avionics referring to the integration of the avionic systems on cockpit instrument panel: AFCS, VMS, MFD, ISIS, ADU and AHRS.

Installation of the avionic equipment includes the display of the information (vehicle parameters, engine parameters and piloting parameters, AFCS modes and upper modes as an option) through:

- MFD on instrument panel (part of the FDS integration);
- EID on instrument panel (part of the VMS integration);
- ISIS on instrument panel (part of the sensors integration).

For this affected area, CS-29 Amdt. 2, dated 17 November 2008, is applicable and the requirements impacted are listed below (see reference A-01):


CS 29.0771	Pilot compartment
CS 29.0773	Pilot compartment view
CS 29.0777	Cockpit controls
CS 29.1301	Function and installation
CS 29.1303	Flight and navigation instruments
CS 29.1305	Power plant instruments
CS 29.1309	Equipment, systems, and installations
CS 29.1321	Arrangement and visibility
CS 29.1327	Magnetic direction indicator
CS 29.1329	Automatic pilot system
CS 29.1333	Instrument systems
CS 29.1335	Flight director systems
CS 29.1543	Instrument markings: general
CS 29.1545	Airspeed indicator
CS 29.1547	Magnetic direction indicator
CS 29.1549	Power plant instruments
Appendix B	Airworthiness Criteria For Helicopter Instrument Flight

Special Conditions:

- Minimum in flight experience (B-01).
- Search and Rescue system (B-02).
- Protection from the effects of High Intensity Radiated Fields (HIRF) (F-02).

Equivalent Safety Finding:

- IFR Static Longitudinal Stability – Airspeed Stability (B-04).
- V_{NE} aural warning (F-01).
- Airspeed indicator markings (G-01).
- Powerplant instrument markings (G-02).



Secondary Change

To integrate these systems on Super Puma MK1 AS 332 C1, L1, the following secondary changes have to be applied:

- Electrical integration of the avionic systems,
- Mechanical integration of the avionic systems,
- Adaptation of hydraulic and flight controls systems,
- AFCS modifications,
- Cockpit lighting modifications,
- Other structural modifications of the airframe,
- Warnings and cautions modifications.

For these secondary changes, the certification basis to be applied is the existing certification basis for the AS 332 C1, L1.

Nevertheless, Eurocopter decided to comply with the requirements of affected area, completed by the ones of CS-29 Amdt. 2 listed below:

CS 29.0161	Trim control
CS 29.0671	General
CS 29.0672	Stability augmentation, automatic, and power-operated systems
CS 29.1322	Warning, caution, and advisory lights
CS 29.1381	Instrument lights
CS 29.1523	Minimum flight crew
CS 29.1525	Kinds of operation

Unaffected Area

- The existing certification basis (FAR 29 Amdt. 16 and DGAC special conditions) as listed in TCDS EASA.R.002, is applicable, except for helicopters equipped with FFMP (MOD 07.53061) where FAR 29.1309(b)(2) Amdt. 24 and FAR 29.1309(d) Amdt. 24 are applicable (A-01) for the areas affected by the design change.



SECTION 3: AS 332 L2I. General

1. Type/ Model/ Variant	
1.1 Type	AS 332
1.2 Model	AS 332 L2
2. Airworthiness Category	Large Rotorcraft, Category A and B
3. Manufacturer	See SECTION: ADMINISTRATIVE, II. for manufacturer record
4. DGAC FR Type Certification Application Date	3 March 1986
5. State of Design Authority	EASA (pre EASA: DGAC FR, France)
6. DGAC FR Type Certificate Date	12 June 1991
7. DGAC FR Type Certificate n°	56
8. DGAC FR Type Certificate Data Sheet n°	127 issue 9 dated September, 1994
9. EASA Type Certification Date	28 September 2003, in accordance with CR (EU) 1702/2003, Article 2, 3., (a), (i), 2 nd bullet, 1 st indented bullet.

II. Certification Basis

1. Reference Date for determining the applicable requirements	For Airworthiness and Environmental Protection: 3 March 1986 for OSD elements: 17 February 2014 (grandfathering date)
2. Airworthiness Requirements	FAR 29 with Amdts. 29-1 to 29-24 included According to DGAC letters 53445/SFACT/TC, dated 27 April 1989, and 53610/SFACT/N.HE, dated June 1991
3. Special Conditions	<ul style="list-style-type: none"> - Flight Endurance - Bird and Foreign Object strikes - Protection against external electro-magnetic disturbances - 30 Sec and 2 Min contingency ratings - Maintenance assistance system (not applicable to basic type design definition)
4. Deviations	<ul style="list-style-type: none"> - reversion to FAR 29 original requirements (*) for FAR 29.605, FAR 29.671 and FAR 29.1323 (*): reversion to FAR29.1 original amendment removed by means of major change approved by EASA under reference 10079751 dated July, 21st 2022. - reversion to FAR 29 Amdt. 12 for FAR 29.603 - reversion to FAR 29 Amdt. 14 for FAR 29.1303 - reversion to FAR 29 Amdt. 14 for FAR 29.1309 regarding equipment used on previous AS 332 models - FAR 29.923, FAR 29.927 Endurance and additional tests by test rig (E-03)
5. Equivalent Safety Findings	
6. Environmental Protection Requirements	



6.1	Noise Requirements	See TCDSN EASA.R.002
6.2	Emission Requirements	n/a
7.	Operational Suitability Data (OSD)	(For OSD elements see SECTION 5)
7.1	Master Minimum Equipment List (MMEL)	JAR-MMEL/MEL Section 1, Subpart A and B, Amdt. 1, dated 1 August 2005
7.2	Flight Crew Data (FCD)	CS-FCD Initial Issue, dated 31 January 2014 (refer to EASA approval 10060827)
7.3	Simulation Data (SIMD)	reserved
7.4	Maintenance Certifying Staff Data (MCSD)	reserved
7.5	Cabin Crew Data (CCD)	reserved

III. Technical Characteristics and Operational Limitations

1.	Type Design Definition	Documents ref. 332 A 89 1031 and 332 A 89 1046
2.	Description	Large twin-engine rotorcraft; derivative design of former type certified AS 332 models
3.	Equipment	As per compliance with applicable FAR 29 airworthiness requirements and referenced in approved RFM
4.	Dimensions	
	4.1 Fuselage	Length: 16.49 m Width stabiliser: 3.38 m Height: 4.97 m
	4.2 Main Rotor	Diameter: 16.20 m (4 blades)
	4.3 Tail Rotor	Diameter: 3.15 m (4 blades)
5.	Engine	
	5.1 Model	Safran Helicopter Engines (former: Turbomeca) 2 x Model MAKILA 1A2
	5.2 Type Certificate	EASA TC/TCDS n°: EASA.E.072
	5.3 Limitations	
	5.3.1 Installed Engine Limits	Refer to approved RFM
	5.3.2 Transmission Torque Limits	Refer to approved RFM
6.	Fluids	
	6.1 Fuel	Refer to approved RFM
	6.2 Oil	Refer to approved RFM
	6.3 Additives	Refer to approved RFM
7.	Fluid capacities	
	7.1 Fuel	Standard configuration: 2 043 litres (540 US gal) with optional internal 6th tank 324 litres (86 US gal) with optional sponson tanks 600 litres (158 US gal) Total available fuel: 2 967 litres (784 US gal) <u>Note:</u> see RFM for other approved optional fuel tanks configurations and for unusable fuel quantities.
	7.2 Oil	Engines: 2 x 4.9 litres MGB: 24.0 litres IGB: 0.75 litre TGB: 1.50 litre



7.3 Coolant System Capacity	n/a																
8. Air Speeds Limits	<p>V_{NE PWR ON}: 315 km/h (170 KIAS) V_{NE PWR OFF}: 278 km/h (150 KIAS) Refer to RFM for other approved airspeed limits.</p>																
9. Rotor Speed Limits	<p>Power on:</p> <table> <tr><td>Maximum</td><td>275 rpm</td></tr> <tr><td>Nominal</td><td>265 rpm</td></tr> <tr><td>Minimum</td><td>245 rpm</td></tr> <tr><td>Minimum transient</td><td>220 rpm</td></tr> </table> <p>Power off:</p> <table> <tr><td>Maximum transient (20 sec)</td><td>310 rpm</td></tr> <tr><td>Maximum</td><td>290 rpm</td></tr> <tr><td>Minimum (> 100 KIAS)</td><td>245 rpm</td></tr> <tr><td>Minimum (< 100 KIAS)</td><td>220 rpm</td></tr> </table>	Maximum	275 rpm	Nominal	265 rpm	Minimum	245 rpm	Minimum transient	220 rpm	Maximum transient (20 sec)	310 rpm	Maximum	290 rpm	Minimum (> 100 KIAS)	245 rpm	Minimum (< 100 KIAS)	220 rpm
Maximum	275 rpm																
Nominal	265 rpm																
Minimum	245 rpm																
Minimum transient	220 rpm																
Maximum transient (20 sec)	310 rpm																
Maximum	290 rpm																
Minimum (> 100 KIAS)	245 rpm																
Minimum (< 100 KIAS)	220 rpm																
10. Maximum Operating Altitude and Temperature																	
10.1 Altitude	TKOF/LDG: -2 000 ft to +7 200 ft PA Enroute: -2 000 ft to +20 000 ft PA																
10.2 Temperature	-30°C to ISA +35°C, limited to 50°C																
11. Operating Limitations	VFR day and night, IFR, Non-icing conditions																
	Flight in limited icing conditions is permitted when equipment items listed in relevant approved Flight Manual supplements are installed (see Note 5)																
12. Maximum Mass	TKOF/LDG: 9 300 kg (20 503 lb)																
13. Centre of Gravity Range	Refer to approved RFM																
14. Datum	<p>Longitudinal: STA 0: 4.670 m (183.86 in) forward of main rotor centreline</p> <p>Lateral: aircraft symmetry plane</p>																
15. Levelling Means	Levelling plate on right side of the fuselage and graduated plate for plumb line on cabin floor (left side door)																
16. Minimum Flight Crew	VFR: 1 pilot IFR: 2 pilots																
17. Maximum Passenger Seating Capacity	25																
18. Passenger Emergency Exit	Refer to approved RFM																
19. Maximum Baggage/ Cargo Loads	The cabin floor (from +2.48 m to +7.63 m) is provided with the structural strength required for a load of 800 kg/m ² evenly distributed in cargo configuration																
20. Rotor Blade Control Movement	For rigging information refer to AMM																
21. Auxiliary Power Unit (APU)	Optional; to be used on ground only. Refer to approved RFMS.																
22. Life-limited Parts	Refer to approved Airworthiness Limitations Section																
23. Wheels and Tyres	<p>Wheels: NLG Messier Bugatti C20525000 (two) MLG Messier Bugatti C20147200 (one each side)</p> <p>Tyres: NLG 7.00-6 (two) MLG 615 x 225-10 (one each side)</p>																



IV. Operating and Service Instructions

1. Flight Manual	AS 332 L2 Flight Manual, DGAC-F approved on 2 April 1992, or subsequent DGAC-F or EASA approved revisions.
2. Maintenance Manual	Maintenance Programme: - AS 332 L2 Maintenance Servicing Recommendations (PRE), - AS 332 L2 Aircraft Maintenance Manual (AMM)
	Airworthiness Limitations: AS 332 L2 Maintenance Servicing Recommendations, Chapter 05.99 (currently known as Chapter 04 approved by EASA), edition 2003.04.24, Rev.000, DGAC-F approved on 25 June 2003, or subsequent approved revisions
3. Structural Repair Manual	AS 332 L2 Structural Repair Manual
4. Weight and Balance Manual	Refer to approved RFM
5. Illustrated Parts Catalogue	AS 332 L2 Illustrated Parts Catalogue
6. Service Letters and Service Bulletins	As published by Aérospatiale, Eurocopter or Airbus Helicopters
7. Required Equipment	<ul style="list-style-type: none"> - As per compliance with applicable FAR 29 requirements and in accordance with the original Type Design standard; - Refer to approved Flight Manual, MMEL and also to Note 6 below.

V. Notes

1. Manufacturer's serial numbers:
S/N 2338, and subsequent of AS 332 L2 model are eligible.
2. The certified "optional" installations are each approved independently of the basic helicopter and an approved Flight Manual Supplement is associated to each optional installation if necessary.
3. Cabin Interior and Seating Configurations must be approved.
4. Commercial designation 'SUPER PUMA Mk II' corresponds to AS 332 L2 model.
5. Flight in 'icing conditions of limited severity':
 - permitted with relevant Flight Manual Supplement.
 - Flight Manual Supplement does not constitute operational approval and operations must be conducted in accordance with applicable operational regulation.
6. The AS 332 L2 helicopters without MGB fire detection system are those modified by AMS 07-25208.

* * *



SECTION 4: EC 225 LPI. General

1. Type/ Model/ Variant	
1.1 Type	EC 225
1.2 Model	EC 225 LP
2. Airworthiness Category	Large Rotorcraft, Category A and B (see Note 6)
3. Manufacturer	See SECTION: ADMINISTRATIVE, II. for manufacturer record
4. DGAC FR Type Certification Application Date	7 November 2000
5. State of Design Authority	EASA
6. EASA Type Certification Date	27 July 2004

II. Certification Basis

1. Reference Date for determining the applicable requirements	For Airworthiness and Environmental Protection: 7 November 2000, for OSD elements: 17 February 2014 (grandfathering date).
2. Airworthiness Requirements	JAR 29, Change 1 effective 1 December 1999 CS 29.1465 Amdt.3 - Vibration Health Monitoring for Airworthiness Credit (F-09), see Note 7 For helicopters equipped with MOD 07-53048 MGB modification, see Note 8.
3. Special Conditions	<ul style="list-style-type: none"> - Minimum in flight experience (B-01). - SAR (Search and Rescue) system (B-02). - Water Bombing System (B-05). - External loads, JAR 29.865 Amdt. 2 (D-06). - Protection from the effects of High Intensity Radiated Field (HIRF) (F-02). - Non-rechargeable Lithium Battery Installations (F-13). - Helicopter limited icing approval (O-01).
4. Exemptions	<ul style="list-style-type: none"> - JAR 29.562 Emergency dynamic landing conditions (C-02). - JAR 29.952(a)(c)(d)(e)(f)(g) Fuel system crash resistance (E-01). - JAR 29.955(b) Fuel transfer (E-05). - partial exemption: JAR 29.963(b) Fuel tanks: general; Puncture resistance (E-02).



5. Deviations

- ADS-B Out Extended Squitter & EHS Installation with Transponder TDR-94D equipment (MOD 332P690408.05) (F-11).
- Reversion to FAR 29, Amdt. 24 as follows:
 - FAR 29.561 (b)(3) Emergency landing conditions-general (C-01).
- Partial reversions to FAR 29, Amdt. 24 as follows:
 - FAR 29.571 Fatigue evaluation of structure (C-03).
 - FAR 29.785 Seat, berth, safety belts, and harnesses (D-01).
- JAR 29.785 (a), Installation of side-facing seats (D-09).
- JAR 29.562 (a), Installation of side-facing seats (D-09).

6. Equivalent Safety Findings

- JAR 29.173, JAR 29.175 Static longitudinal Stability (B-03).
- JAR 29 App B §IV IFR Static longitudinal Stability – Airspeed stability (B 04).
- JAR 29.571 Fatigue evaluation of structure for changed metallic PSE (C-04).
- JAR 29.807 (c)(1) Passenger emergency exits other than side-of-fuselage (D-02).
- JAR 29.813 (a), JAR 29.815 Emergency exit access - Main aisle width (D-03).
- JAR 29.807 (d)(2) Ditching emergency exits for passengers (D-07).
- JAR 29.601, JAR 29.603, JAR 29.605, JAR 29.865 Hoist installation (D-10)
- JAR 29.923 (a)(2) Rotor drive system and control mechanism tests (E-03).
- JAR 29.1303 (j) V_{NE} aural warning (F-01).
- JAR 29.1545 (b)(4) Airspeed indicators markings (G-01).
- JAR 29.1549 (b) Powerplant instruments markings (G-02).
- CS 29.923 and CS 29.927 Amdt. 4 (E-09), for helicopters equipped with MOD 07-53048.
- CS 29.923 and CS 29.927 Amdt. 4 (E-10), for helicopters equipped with design change SP07.53069 or SP07.53070.

7. Environmental Protection Requirements

7.1 Noise Requirements	See TCDSN EASA.R.002
7.2 Emission Requirements	Compliant with ICAO Annex 16 Volume 2 - Fuel Discharge
8. Operational Suitability Data (OSD)	(For OSD elements see SECTION 5 below)
8.1 Master Minimum Equipment List (MMEL)	JAR-MMEL/MEL Section 1, Subpart A and B, Amdt. 1, dated 1 August 2005
8.2 Flight Crew Data (FCD)	CS-FCD Initial Issue, dated 31 January 2014 (refer to EASA approval 10060827)
8.3 Simulation Data (SIMD)	<i>reserved</i>
8.4 Maintenance Certifying Staff Data (MCSD)	<i>reserved</i>
8.5 Cabin Crew Data (CCD)	<i>reserved</i>



III. Technical Characteristics and Operational Limitations

1. Type Design Definition	For EC 225 LP Standard: Document ref. 332 A 89 2120 EC 225 LP MPAI equipped: when EC 225 LP standard definition is completed with design change ref. AMS OP 23554 EC 225 LP equipped with MFD ROSE: when EC 225 LP standard definition is completed with design changes 07.28626, 07.28938 and 07.28875
2. Description	Large twin-engine rotorcraft, derivative design of former type certified AS 332 L2 model Standard configuration consists of grid-type engine air intakes installation, while MPAI configuration is optional and consists of Multi-Purpose Air Intakes
3. Equipment	As required by JAR 29 and referenced in approved RFM
4. Dimensions	
4.1 Fuselage	Length: 16.49 m Width stabiliser: 3.96 m Height: 4.97 m
4.2 Main Rotor	Diameter: 16.20 m (5 blades)
4.3 Tail Rotor	Diameter: 3.15 m (4 blades)
5. Engine	
5.1 Model	Safran Helicopter Engines (former: Turbomeca) 2 x Model MAKILA 2A, or, 2 x Model MAKILA 2A1
5.2 Type Certificate	EASA TC/TCDS n°: EASA.E.006
5.3 Limitations	
5.3.1 Installed Engine Limits	Refer to approved RFM
5.3.2 Transmission Torque Limits	Refer to approved RFM
6. Fluids	
6.1 Fuel	Refer to approved RFM
6.2 Oil	Refer to approved RFM
6.3 Additives	Refer to approved RFM
7. Fluid capacities	
7.1 Fuel	Standard configuration: 2 588 litres (682 US gal) with optional internal 6th tank 320 litres (84 US gal) Total available fuel: 2 908 litres (766 US gal) <u>Note:</u> see RFM for other approved optional fuel tanks configurations and for unusable fuel quantities.
7.2 Oil	Engines: 2 x 4.92 litres MGB: 27.0 litres IGB: 0.62 litre TGB: 1.50 litre
7.3 Coolant System Capacity	n/a



8. Air Speeds Limits	$V_{NE\ PWR\ ON}$: 175 KIAS below 5 000 ft DA, above 5 000 ft: -3 KIAS/1 000 ft $V_{NE\ PWR\ OFF}$: 150 KIAS Refer to RFM for other approved airspeed limits.														
9. Rotor Speed Limits	<p>Power on:</p> <table> <tr><td>Maximum</td><td>275 rpm</td></tr> <tr><td>Minimum</td><td>246 rpm</td></tr> <tr><td>Minimum transient</td><td>220 rpm</td></tr> </table> <p>Power off:</p> <table> <tr><td>Maximum transient (20 sec)</td><td>310 rpm</td></tr> <tr><td>Maximum</td><td>290 rpm</td></tr> <tr><td>Minimum (> 100 KIAS)</td><td>246 rpm</td></tr> <tr><td>Minimum (< 100 KIAS)</td><td>220 rpm</td></tr> </table>	Maximum	275 rpm	Minimum	246 rpm	Minimum transient	220 rpm	Maximum transient (20 sec)	310 rpm	Maximum	290 rpm	Minimum (> 100 KIAS)	246 rpm	Minimum (< 100 KIAS)	220 rpm
Maximum	275 rpm														
Minimum	246 rpm														
Minimum transient	220 rpm														
Maximum transient (20 sec)	310 rpm														
Maximum	290 rpm														
Minimum (> 100 KIAS)	246 rpm														
Minimum (< 100 KIAS)	220 rpm														
10. Maximum Operating Altitude and Temperature	<p>TKOF/LDG for EC 225 LP Standard:</p> <p>OAT from -45°C to -12°C: -6 000 ft DA to +7 400 ft DA OAT from -12°C to ISA +40°C (without exceeding +50°C): -2 000 ft PA to +7 400 ft DA</p> <p>TKOF/LDG for EC 225 LP MPAI equipped:</p> <p>OAT from -45°C to -12°C: -6 000 ft DA to +11 000 ft DA OAT from -12°C to ISA +40°C (without exceeding +50°C): -2 000 ft PA to +11 000 ft DA</p> <p>Enroute for EC 225 LP Standard/MPAI equipped:</p> <p>OAT from -45°C to -12°C: -6 000 ft DA to +20 000 ft PA OAT from -12°C to ISA +40°C (without exceeding +50°C): -2 000 ft PA to +20 000 ft PA</p> <p>-30°C to ISA +40°C, limited to 50°C See RFMS SUPP 2 for lower temperature operation down to -45°C.</p>														
10.1 Altitude															
10.2 Temperature															
11. Operating Limitations	<p>VFR day and night, IFR, non-icing conditions</p> <p>Flight in full icing conditions is permitted only when other equipment items as listed in relevant approved RFMS are installed.</p> <p>Flight in limited icing conditions is permitted only when equipment items listed in relevant approved RFMS are installed (see Note 5).</p>														
12. Maximum Mass	<p>TKOF/LDG: 11 000 kg (24 251 lb)</p> <p>For helicopters equipped with MAKILA 2A1 engine and MOD 07.28724:</p> <p>TKOF/LDG: 11 160 kg (24 604 lb)</p>														
13. Centre of Gravity Range	Refer to approved RFM														
14. Datum	<p>Longitudinal: STA 0: 4.670 m (183.86 in) forward of main rotor centreline</p> <p>Lateral: aircraft symmetry plane</p>														
15. Levelling Means	Levelling plate on right side of the fuselage and graduated plate for plumb line on cabin floor (left side door)														



16. Minimum Flight Crew	VFR: 1 pilot IFR: 2 pilots <u>Note:</u> Pilot and suitably trained crew member in day VFR for water bombing operations.
17. Maximum Passenger Seating Capacity	25
18. Passenger Emergency Exit	one (1) door, the dimensions of which exceed those of Type II exit + two (2) Type IV exits on each side
19. Maximum Baggage/ Cargo Loads	The cabin floor (from +2.48 m to +7.63 m) is provided with the structural strength required for a load of 800 kg/m ² evenly distributed in cargo configuration
20. Rotor Blade Control Movement	For rigging information refer to AMM
21. Auxiliary Power Unit (APU)	Optional; to be used on ground only. Refer to approved RFMS.
22. Life-limited Parts	Refer to approved Airworthiness Limitations Section
23. Wheels and Tyres	Wheels: NLG Messier Bugatti C 20525 000 (two) MLG Messier Bugatti C 20147 200 (one each side) Tyres: NLG 466 x 173-10 (two) MLG 615 x 225-10 (one each side)

IV. Operating and Service Instructions

1. Flight Manual	For EC 225 LP Standard: EC 225 LP Flight Manual, normal revision RN0 (04-20), EASA approved 27 July 2004, or subsequent approved revisions. For EC 225 LP equipped with MPAI: EC 225 LP MPAI Flight Manual, normal revision RN2 (04-44), EASA approved 21 December 2004, or subsequent approved revisions For EC 225 LP equipped with MFD ROSE: EC 225 LP Flight Manual ROSE AVIONICS, normal revision RN 0 (22-22), or subsequent approved revisions. For EC 225 LP equipped with MFD ROSE and MPAI: EC 225 LP Flight Manual ROSE AVIONICS and MPAI, normal revision RN 0 (22-22), or subsequent approved revisions.
2. Maintenance Manual	Maintenance Programme: - EC 225 LP Maintenance Servicing Recommendations (PRE), - EC 225 LP Aircraft Maintenance Manual (AMM) Airworthiness Limitations: EC 225 LP Maintenance Servicing Recommendations, Chapter 05.99 (currently known as Chapter 04 approved by EASA), edition 2004.05.31, Rev. 000, EASA approved on 27 July 2004, or subsequent approved revisions
3. Structural Repair Manual	EC 225 LP Structural Repair Manual
4. Weight and Balance Manual	Refer to approved RFM
5. Illustrated Parts Catalogue	EC 225 LP Illustrated Parts Catalogue
6. Service Letters and Service Bulletins	As published by Eurocopter or Airbus Helicopters



7. Required Equipment

- As per compliance with applicable JAR 29 requirements and in accordance with the original Type Design standard;
- Refer to approved Flight Manual and MMEL.

V. Notes

1. Manufacturer's eligible serial numbers:
s/n 2600, and subsequent of EC 225 LP model are eligible.
2. The certified "optional" installations are each approved independently of the basic helicopter and an approved Flight Manual Supplement is associated to each optional installation if necessary (some optional installations are specific to the EC 225 LP equipped with MPAI and the relevant RFMS are approved for that particular EC 225 LP type design definition only).
3. Cabin Interior and Seating Configurations must be approved. Passenger transport is not permitted in both operational and non-operational configurations of the Water Bombing System. Except while performing Water Bombing operations, the EC 225 LP is not approved for the carriage of cargo-only in the cabin.
4. Commercial designation 'SUPER PUMA Mk II+' or 'LP' corresponds to EC 225 LP model.
Since 1 Jan 2016, H225 is the new commercial designation for EC 225 LP model.
5. Flight in limited icing conditions and water bombing operations:
The relevant approved Flight Manual Supplements do not constitute operational clearance approvals and operations must be conducted in accordance with applicable operational regulation.
6. The EC 225 LP is certified as Category A rotorcraft with operating limitations as defined in the relevant approved RFMS.
7. For EC 225 LP helicopters equipped with M'ARMS (optional Vibration Health Monitoring system), the associated mandatory design change MOD 0726978 / 0726994 (defined as 'M'ARMS MOD45 monitoring') is certified in compliance with CS 29.1465 of CS 29 Amdt. 3 – see above in section II.2
8. For EC 225 LP helicopters equipped with MOD 07-53048, the design change is certified in compliance with the following CS 29 Amdt. 4 paragraphs and subparagraphs: CS29.29, CS29. 301 (a), CS29.303, CS29.305, CS29.307, CS29.361, CS29.547 (d)(2), CS29.561, CS29.571, CS29.601 (a), CS29.601 (b), CS29.602, CS29.603, CS29.605, CS29.607, CS29.609, CS29.611, CS29.613, CS29.619, CS29.623, CS29.625, CS29.917 (a), CS29.917 (b), CS29.917 (c), CS29.923, CS29.927 (a), CS29.927 (b)(1), CS29.927 (c), CS29.927 (d), CS29.927 (e), CS29.927 (f), CS29.1027, CS29.1041 (b), CS29.1041 (c), CS29.1301, CS29.1305 (a)(23), CS29.1309 (b)(2)(i), CS29.1309 (b)(2)(ii), CS29.1309 (d)(1), CS29.1309 (d)(2), CS29.1309 (d)(3), CS29.1309 (d)(4), CS29.1529.
9. The EC 225 LP Category A vertical take-offs and landings from an elevated heliport are not approved.

* * *



SECTION 5: OPERATIONAL SUITABILITY DATA (OSD)

The OSD elements listed below are approved by the European Union Aviation Safety Agency as per Commission Regulation (EU) 748/2012, as amended by Commission Regulation (EU) No 69/2014.

OSD Elements

1. MMEL

For SA 330 J: n/a

For AS 332 C, L, C1, L1:

MMEL AS 332 C-C1-L-L1 Normal Revision 3, Issue 2, Date Code 13-04, dated 13 June 2013, or later EASA approved revisions.

For AS 332 C1, L1 equipped with AHCAS (commercial reference AS 332 C1e and AS 332 L1e):

MEL Supplement AS 332 C1-L1

Post MOD 07 26640 to 07 22650

Normal Revision 0 Issue 1 Date-Code 14-02, dated 27 January 2014, or later EASA approved revisions.

For AS 332 L2:

MMEL AS 332 L2 Normal Revision 1, Issue 2, Date Code 10-10, dated 20 October 2010, or later EASA approved revisions.

For EC 225 LP:

MMEL EC 225 LP Normal Revision 4, Issue 2, Date Code 13-25, dated 24 October 2013, or later EASA approved revisions.

2. Flight Crew Data

All models, except SA 330 J:

OSD-FCD Super Puma Fleet RN 2 Date Code 16-50, or later EASA approved revision.

3. SIM Data

reserved

4. Maintenance Certifying Staff Data

reserved

5. Cabin Crew Data - Certification Basis

reserved

* * *



SECTION: ADMINISTRATIVE

I. Acronyms and Abbreviations

ADU	Air Data Unit	LDG	Landing Gear
AFCS	Automatic Flight Control System	M'ARMS	EC 225's Vibration Health Monitoring System
AHCAS	Advanced Helicopter Cockpit Avionics System	MFD	Multi Function Display
AHRS	Attitude and Heading Reference System	MGB	Main Gear Box
Amdt.	Amendment	MLG	Main Landing Gear
AMM	Aircraft Maintenance Manual	MMEL	Master Minimum Equipment List
AMS	Aircraft Modification	MPAI	Multi-Purpose Air Intakes
APU	Auxiliary Power Unit	NLG	Nose Landing Gear
DA	Density Altitude	OAT	Outside Air Temperature
DGAC FR	Direction Générale de l'Aviation Civile - France	OSD	Operational Suitability Data
EASA	European Union Aviation Safety Agency	P/N	Part number
FAR	Federal Aviation Regulations	PA	Pressure Altitude
FCD	Flight Crew Data	RFM	Rotorcraft Flight Manual
FFMP	Full Flow Magnetic Plug	S/N	Serial Number
HIRF	High Intensity Radiated Field	SB	Service Bulletin
ICAO	International Civil Aviation Organisation	SIM	Simulator
IFR	Instrument Flight Rules	TC	Type Certificate
IGB	Intermediate Gear Box	TCDS	Type Certificate Data Sheet
ISA	International Standard Atmosphere	TCDSN	Type Certificate Data Sheet Noise
ISIS	Integrated Standby Instrument System	TGB	Tail Gear Box
JAR	Joint Airworthiness Requirements	TKOF	Take-Off
KIAS	Knots Indicated Air Speed	VFR	Visual Flight Rules
		VMS	Vehicle Management System
		V _{NE}	Never Exceed Speed

II. Type Certificate Holder Record

Type Certificate Holder and Manufacturer	Period
Aérospatiale 37, Boulevard de Montmorency 75781 Paris CEDEX 16, France	From 29 April 1976 until 31 December 1991
Eurocopter France Aéroport International Marseille – Provence 13725 Marignane CEDEX, France	From 1 January 1992 until 30 May 1997
Eurocopter Aéroport International Marseille – Provence 13725 Marignane CEDEX, France	From 1 June 1997 until 6 January 2014
Airbus Helicopters Aéroport International Marseille – Provence 13725 Marignane CEDEX, France	Since 7 January 2014



III. Change Record

Issue	Date	Changes	TC issue
Issue 1	27 Jul 2004	Initial Issue; EC 225 LP model type certification	Initial EASA Issue 27 July 2004
Issue 2	21 Apr 2006	Legacy Models added (SA 330 and AS 332)	Re-issued on 21 April 2006
Issue 3	6 Oct 2009	EC 225 LP: Makila 2A1 engines added; update of altitude and temperature limitations	---
Issue 4	13 Dec 2009	TC surrendering for SA 330 models F and G; EC 225 LP certification basis update for Water Bombing kit approval	---
Issue 5	25 Feb 2010	Clarification of s/n applicability for former SA 330 F and G models converted into SA 330 J	---
Issue 6	9 May 2010	Extended EC 225 LP take-off and landing altitude flight envelope	---
Issue 7	4 Jan 2011	Extended EC 225 LP temperature envelope (very cold weather); error correction: AS 332 L2 hydraulic fluid capacity; new EC 225 LP icing envelope approval	---
Issue 8	20 Jan 2011	Update on EASA engine TCDS EASA.E.072 reference	---
Issue 9	14 Jun 2012	Updated to add AS 332 L1 with AHCAS commercial designation AS 332 L1e	---
Issue 10	29 Jun 2012	TCDS format update; minor corrections	---
Issue 11	10 Jul 2013	EC 225 LP certification basis update for "M'ARMS MOD45 monitoring" approval	---
Issue 12	7 Jan 2014	TC Holder's name changed to "Airbus Helicopters"	Re-issued on 7 January 2014
Issue 13	25 Jun 2015	Updated to add AS 332 C1 with AHCAS commercial designation AS 332 C1e; new EC 225 deviation D-09 and new MSM Chapter 04 (previously 05.99).	---
Issue 14	17 Jul 2015	1 st page updated – Section 5 for OSD added	---
Issue 15	10 Dec 2015	OSD elements added in Section 5	---
Issue 16	26 Jul 2017	Flight Crew Data and FCD Certification Basis updated based on EASA Approval 10060827; TCDS format updated; minor corrections	---



Issue	Date	Changes	TC issue
Issue 17	13 Oct 2021	<p>All: I.1.3, II.4, II.7 deleted/updated i.a.w. TCDS policy</p> <p>Section 1 (SA 330 J) amended:</p> <ul style="list-style-type: none"> - I.3: editorial - III.12.: lb value corrected. <p>Section 2 (AS 332 C, C1, L, L1) amended:</p> <ul style="list-style-type: none"> - I.3, II.1, II.7, OSD: editorial - II.2., II.3., II.6., V.: SC and ESF references amended. - II.2, V.: Elect to Comply for AS 332 C, C1, C1e, L, L1, L1e equipped with a FFMP (MOD 07.53061) added. - II.3: AS 332 C1 and L1 Certification Basis updated to introduce the Special Condition F-09. - III.7.: fuel values correction. - III.8., III.10., III.12.: lb values corrected. - IV.2.: MM original approval date added. - V.5.: new commercial designation added. - V.8.: unaffected area updated <p>Section 3 (AS 332 L2) amended:</p> <ul style="list-style-type: none"> - I.3, II.1, II.7, OSD: editorial - III.12.: lb value corrected. - IV.2.: MM original approval date added. <p>Section 4 (EC 225 LP) amended:</p> <ul style="list-style-type: none"> - I.3, II.1, II.7, OSD: editorial - II.2.: EC 225 LP Certification Basis updated to introduce the reference to Note 8 for helicopters equipped with MOD 07-53048. - II.3.: EC 225 LP Certification Basis updated to introduce the Special Condition F-13. - II.3., II.4., II.5., II.6., II.7.: SC and ESF references amended. - II.5: EC 225 LP Certification Basis updated to introduce the deviation F-11. - II.6: EC 225 LP Certification Basis updated to introduce ESFs D-10 and E-09. - II.8: noise requirement wording corrected. - III.12: maximum mass updated for helicopters equipped with MAKILA 2A1 engine and MOD 07.28724. - IV.2: typo corrected. - V.4.: new commercial designation added. - V.8.: new Note 8 added. <p>Section 5: OSD amended:</p> <ul style="list-style-type: none"> - I. deleted/shifted to II. Certification Basis <p>Section ADMINISTRATIVE amended:</p> <ul style="list-style-type: none"> - II.: table title updated. <p>Applicable to all Sections:</p> <ul style="list-style-type: none"> - I.3.: clarification on manufacturer record added. - III.8.: speed units clarification. 	---



Issue	Date	Changes	TC issue
Issue 18	07 Oct 2025	<p>Whole document reformatted with editorial changes not indicated below.</p> <p>In various sections, paragraph IV</p> <ul style="list-style-type: none"> - References to "other Flight Manuals" removed as this is the EASA TCDS. - Mentions to overhaul manual removed as it is not an ICA. <p>Section 3 AS 332 L2</p> <ul style="list-style-type: none"> - II.4: "FAR 29.1" removed from Deviations list following a dedicated major change approval. - II.5: ESF E-03 added <p>Section 4 (EC 225 LP)</p> <ul style="list-style-type: none"> - II.6 ESF E-10 added - III.1: MFD ROSE added - IV.1: MFD ROSE added - IV.5: Illustrated Parts Catalogue reference added - V.9: new Note 9 added <p>Section administrative: update of the acronyms and abbreviations table</p>	---

- end of file -

