



ICAO ENGINE nvPM EMISSIONS DATA SHEET

SUBSONIC ENGINES

ENGINE IDENTIFICATION: PW307A BYPASS RATIO (-): 4.3
 UNIQUE ID NUMBER: 01P16PW143 PRESSURE RATIO π_{c0} (-): 20.2
 COMBUSTOR: TALON II
 ENGINE TYPE: MTF RATED OUTPUT F_{00} (kN): 28.5

REGULATORY DATA

CHARACTERISTIC VALUES:	LTO_{mass}/F_{00} (mg/kN)	LTO_{num}/F_{00} (particles/kN)	NVPM MASS CONCENTRATION ($\mu\text{g}/\text{m}^3$)
LTO/F_{00} AND MAX $nvPM_{mass}$	746.5	6.05E+15	1250
AS % OF CAEP/10 LIMIT	-	-	9.0
AS % OF CAEP/11 LIMIT (InP)	18.5	25.8	
AS % OF CAEP/11 LIMIT (NT)			

MEASURED DATA

MODE	POWER SETTING (% F_{00})	TIME minutes	FUEL FLOW kg/s	EMISSIONS INDICES*		NVPM MASS CONCENTRATION PEAK $nvPM_{mass}$ ($\mu\text{g}/\text{m}^3$)
				EI_{mass} (mg/kg)	EI_{num} (particles/kg)	
TAKE-OFF	100	0.7	0.327	57.0	6.46E+14	
CLIMB OUT	85	2.2	0.272	36.0	6.29E+14	
APPROACH	30	4.0	0.102	6.7	2.88E+14	
IDLE	7	26.0	0.045	272.7	1.92E+15	
LTO TOTAL (kg, mg, number of particles)			144	21268	1.72E+17	-
NUMBER OF ENGINES				3	3	3
NUMBER OF TESTS				1	1	1
AVERAGE LTO/F_{00} VALUES (mg/kN, particles/kN)				746.5	6.05E+15	-
MAX EI VALUES (mg/kg, particles/kg) AND MAX MASS CONC. ($\mu\text{g}/\text{m}^3$)				272.7	1.92E+15	971

* Emissions Indices are corrected for thermophoretic loss and fuel hydrogen content

DATA FOR EMISSIONS INVENTORIES (ESTIMATIONS FOR ENGINE EXIT PLANE VALUES)

MODE	POWER SETTING (% F_{00})	CORRECTED EMISSIONS INDICES	
		$EI_{mass,SL}$ (mg/kg)	$EI_{num,SL}$ (particles/kg)
TAKE-OFF	100	72.4	2.00E+15
CLIMB OUT	85	47.5	2.19E+15
APPROACH	30	10.2	1.48E+15
IDLE	7	335.1	5.23E+15

AMBIENT CONDITIONS

	From	To	FUEL	
BAROMETER (kPa)	99.4	100.6	HEAT OF COMBUSTION (MJ/kg)	43.06
TEMPERATURE (K)	288.7	291.3	HYDROGEN CONTENT (%mass)	13.46
HUMIDITY (kg water/kg dry air)	0.0071	0.0099	AROMATICS CONTENT (%vol)	21.6
			NAPHTHALENE CONTENT (%vol)	0.71
			SULPHUR CONTENT (ppm by mass)	41

MANUFACTURER: Pratt & Whitney Canada
 TEST ORGANIZATION: Pratt & Whitney Canada
 TEST LOCATION: Mississauga, Ontario, Canada
 TEST DATES: 30/09/2016-03/10/2016

REMARKS

1. Data acquired using procedures and systems prescribed in Annex 16 Volume II, Amd. 9
2. Thermophoretic correction applied as described in Annex 16 Volume II, Amd. 9, Appendix 7, Section 6.2.1
3. Data corrected for fuel hydrogen content according to CAEP11.WP91 App.A
4. Export Classification: Technical Data: Yes / ECL: NSR / ECCN: N/A / P-ECCN: 9E991
5. Data reported in ER9043 Part II Rev. C

** DATA SUPERSEDED **

SEE FOLLOWING UID FOR REVISED DATA:

03P16PW192