



## ICAO ENGINE EXHAUST EMISSIONS DATA SHEET

## SUBSONIC ENGINES

ENGINE IDENTIFICATION: Trent7000-68 BYPASS RATIO: 9.2  
UNIQUE ID NUMBER: 04P24RR144 PRESSURE RATIO ( $\pi_{co}$ ): 42.3  
COMBUSTOR: Phase5 Tiled (Improved nvPM combustor)  
ENGINE TYPE: TF RATED THRUST ( $F_{co}$ ) (kN): 308.7

## REGULATORY DATA

CHARACTERISTIC VALUE:	HC	CO	NO <sub>x</sub>	SMOKE NUMBER
D <sub>p</sub> /F <sub>co</sub> (g/kN) or SN	0.0	11.8	62.1	11.0
AS % OF ORIGINAL LIMIT	0.0	10.0	49.9	63.3
AS % OF CAEP/2 LIMIT (NO <sub>x</sub> )			62.3	
AS % OF CAEP/4 LIMIT (NO <sub>x</sub> )			67.9	
AS % OF CAEP/6 LIMIT (NO <sub>x</sub> )			74.4	
AS % OF CAEP/8 LIMIT (NO <sub>x</sub> )			83.2	

For non-volatile particulate matter (nvPM) emissions, please refer to the ICAO Engine nvPM Emissions Data Sheet.

## DATA STATUS

- PRE-REGULATION  
x CERTIFICATION  
- REVISED (SEE REMARKS)

## TEST ENGINE STATUS

- NEWLY MANUFACTURED ENGINES  
x DEDICATED ENGINES TO PRODUCTION STANDARD  
- OTHER (SEE REMARKS)

## EMISSIONS STATUS

x DATA CORRECTED TO REFERENCE  
(ANNEX 16 VOLUME II)

## CURRENT ENGINE STATUS

(IN PRODUCTION, IN SERVICE UNLESS OTHERWISE NOTED)

- OUT OF PRODUCTION (DATE: - )  
- OUT OF SERVICE (DATE: - )

## MEASURED DATA

MODE	POWER	TIME	FUEL FLOW	EMISSIONS INDICES (g/kg)			SMOKE NUMBER
	SETTING (%F <sub>co</sub> )	(minutes)	(kg/s)	HC	CO	NO <sub>x</sub>	
TAKE-OFF	100	0.7	2.294	0.00	0.42	47.58	7.5
CLIMB OUT	85	2.2	1.881	0.00	0.49	36.53	9.4
APPROACH	30	4.0	0.631	0.00	0.92	14.54	3.8
IDLE	7	26.0	0.247	0.00	7.93	5.85	1.7
LTO TOTAL FUEL (kg) or EMISSIONS (g)			881	0	3355	18110	-
NUMBER OF ENGINES				3	3	3	3
NUMBER OF TESTS				5	5	5	5
AVERAGE D <sub>p</sub> /F <sub>co</sub> (g/kN) or AVERAGE SN (MAX)				0.0	10.9	58.7	10.0
SIGMA (D <sub>p</sub> /F <sub>co</sub> in g/kN, or SN)				0.0	1.4	1.4	1.6
RANGE (D <sub>p</sub> /F <sub>co</sub> in g/kN, or SN)				0.0	9.69-12.41	57.88-60.22	8.6-11.7

## ACCESSORY LOADS

POWER EXTRACTION 0 (kW)  
STAGE BLEED 0 (% CORE FLOW)

AT - POWER SETTINGS  
AT - POWER SETTINGS

## ATMOSPHERIC CONDITIONS

BAROMETER (kPa)	100.2-101.6
TEMPERATURE (K)	291.4-299.6
ABS HUMIDITY (kg/kg)	0.00473-0.00986

## FUEL

SPEC	
H/C	1.94
AROM (%)	15.76

MANUFACTURER: Rolls-Royce plc  
TEST ORGANIZATION: Rolls-Royce plc  
TEST LOCATION: Derby  
TEST DATES: 06/05/2020-26/08/2020

NO<sub>x</sub> REGULATION PARAGRAPH

	2.3.2 c) (CAEP/4)
	2.3.2 d) (CAEP/6)
x	2.3.2 e) (CAEP/8)

## REMARKS

- EDNS01000945619
- Improved nvPM combustor

Compliance with Fuel Venting requirements:

x ('x' if complies, 'PR' if pre-regulation, '-' if information is not available)