



ICAO ENGINE nvPM EMISSIONS DATA SHEET

SUBSONIC ENGINES

ENGINE IDENTIFICATION: PW1129G-JM BYPASS RATIO (-): 12.0
 UNIQUE ID NUMBER: 01P18PW154 PRESSURE RATIO π_{co} (-): 34.0
 COMBUSTOR: TALON X, Block-C
 ENGINE TYPE: TF RATED OUTPUT F_{co} (kN): 130.1

REGULATORY DATA

CHARACTERISTIC VALUES:	LTO_{mass}/F_{co} (mg/kN)	LTO_{num}/F_{co} (particles/kN)	NVPM MASS CONCENTRATION ($\mu\text{g}/\text{m}^3$)
LTO/ F_{co} AND MAX nvPM _{mass}	93.2	2.50E+15	2375
AS % OF CAEP/10 LIMIT	-	-	40.9
AS % OF CAEP/11 LIMIT (InP)	5.0	20.8	
AS % OF CAEP/11 LIMIT (NT)	26.5	57.0	

MEASURED DATA

MODE	POWER SETTING (% F_{co})	TIME minutes	FUEL FLOW kg/s	EMISSIONS INDICES*		NVPM MASS CONCENTRATION PEAK nvPM _{mass} ($\mu\text{g}/\text{m}^3$)
				EI _{mass} (mg/kg)	EI _{num} (particles/kg)	
TAKE-OFF	100	0.7	0.880	77.5	9.23E+14	
CLIMB OUT	85	2.2	0.730	45.7	8.34E+14	
APPROACH	30	4.0	0.255	6.8	3.96E+14	
IDLE	7	26.0	0.080	8.4	7.70E+14	
LTO TOTAL (kg, mg, number of particles)			318	8724	2.34E+17	-
NUMBER OF ENGINES				1	1	1
NUMBER OF TESTS				3	3	3
AVERAGE LTO/ F_{co} VALUES (mg/kN, particles/kN)				67.1	1.80E+15	-
MAX EI VALUES (mg/kg, particles/kg) AND MAX MASS CONC. ($\mu\text{g}/\text{m}^3$)				77.5	9.64E+14	1845

* Emissions Indices are corrected for thermophoretic loss and fuel hydrogen content

DATA FOR EMISSIONS INVENTORIES (ESTIMATIONS FOR ENGINE EXIT PLANE VALUES)

MODE	POWER SETTING (% F_{co})	CORRECTED EMISSIONS INDICES	
		EI _{mass_SL} (mg/kg)	EI _{num_SL} (particles/kg)
TAKE-OFF	100	94.9	3.20E+15
CLIMB OUT	85	59.0	3.47E+15
APPROACH	30	9.8	3.10E+15
IDLE	7	17.0	7.58E+15

AMBIENT CONDITIONS

	From		To	
	BAROMETER (kPa)	100.8	103.0	HEAT OF COMBUSTION (MJ/kg)
TEMPERATURE (K)	266.7	277.2	HYDROGEN CONTENT (%mass)	13.84
HUMIDITY (kg water/kg dry air)	0.0004	0.0017	AROMATICS CONTENT (%vol)	15.3
			NAPHTHALENE CONTENT(%vol)	1.87
			SULPHUR CONTENT (ppm by mass)	705

MANUFACTURER: Pratt & Whitney
 TEST ORGANIZATION: Pratt & Whitney
 TEST LOCATION: East Hartford, CT
 TEST DATES: 02/03/2017-04/03/2017

REMARKS

1. Data from certification report PWA-12243
2. 1 engine tested
3. TALON-X, Block-C* combustor
4. Certification in accordance with ICAO Annex 16 Vol. II., Part III, Chapter 2.
5. nvPM levels in accordance with ICAO Annex 16 Vol. II, Part III, Chapter 4 and Appendices 7 and 8. (CAEP/10)