



TYPE-CERTIFICATE DATA SHEET

No. EASA.IM.A.120

for
BOEING 737

Type Certificate Holder:
The Boeing Company
1901 Oakesdale
Ave SW 737 Logan Ave N Renton,
WA 98057-0000 2623
USA

| For Models: | “Classic”: | “Next Generation”: | “Max”: |
|-------------|------------|--------------------|----------|
| | 737-100 | 737-600 | 737-8 |
| | 737-200 | 737-700 | 737-9 |
| | 737-200C | 737-800 | 737-8200 |
| | 737-300 | (737-800BCF) | |
| | 737-400 | 737-900 | |
| | 737-500 | 737-900ER | |



Intentionally left blank



TABLE OF CONTENTS

| | |
|---|-----------|
| TABLE OF CONTENTS | 3 |
| SECTION 1: 737-100, -200, -200C, -300, -400, -500 VARIANTS | 5 |
| I. General | 5 |
| II. Certification Basis | 6 |
| III. Technical Characteristics and Operational Limitations | 7 |
| IV. Operating and Service Instructions | 9 |
| V. Operational Suitability Data (OSD) | 10 |
| VI. Part 26 compliance information | 10 |
| VII. Notes | 11 |
| SECTION 2: PERTINENT TO ALL NEXT GENERATION SERIES (NG: 737-600, -700, -800, -900, -900ER) | 12 |
| I. General | 12 |
| II. Certification Basis | 12 |
| III. Technical Characteristics and Operational Limitations | 12 |
| IV. Operating and Servicing Instructions | 15 |
| V. Operational Suitability Data (OSD) | 15 |
| VI. Part 26 compliance information | 16 |
| VII. Notes: | 16 |
| SECTION 3: 737-700 Series | 17 |
| I. General | 17 |
| II. Certification Basis | 17 |
| III. Technical Characteristics and Operational Limitations | 22 |
| IV. Operating and Servicing Instructions | 24 |
| V. Operational Suitability Data (OSD) | 25 |
| VI. Notes | 25 |
| SECTION 4: 737-800 Series | 26 |
| 4.1 B737-800 Model | 26 |
| I. General | 26 |
| II. Certification Basis | 26 |
| III. Technical Characteristics and Operational Limitations | 27 |
| IV. Operating and Servicing Instructions | 29 |
| V. Operational Suitability Data (OSD) | 29 |
| VI. Notes | 30 |
| 4.2 B737-800 Model – Boeing Converted Freighter Major Change | 31 |
| I. General | 31 |
| II. Certification Basis | 31 |
| III. Technical Characteristics and Operational Limitations | 33 |
| IV. Operating and Service Instructions | 34 |
| V. Operating Suitability Data (OSD) | 34 |
| VI. Notes | 35 |
| SECTION 5: 737-600 Series | 36 |
| I. General | 36 |
| II. Certification Basis | 36 |
| III. Technical Characteristics and Operational Limitations | 36 |
| IV. Operating and Servicing Instructions | 38 |
| V. Operational Suitability Data (OSD) | 39 |
| VI. Notes | 39 |



| | |
|--|-----------|
| SECTION 6: 737-900 Series | 40 |
| I. General | 40 |
| II. Certification Basis | 40 |
| III. Technical Characteristics and Operational Limitations | 45 |
| IV. Operating and Servicing Instructions | 47 |
| V. Operational Suitability Data (OSD) | 47 |
| VI. Notes | 47 |
| SECTION 7: 737-900ER | 48 |
| I. General | 48 |
| II. Certification Basis | 48 |
| III. Technical Characteristics and Operational Limitations | 54 |
| IV. Operating and Servicing Instructions | 56 |
| V. Operational Suitability Data (OSD) | 57 |
| VI. Notes | 57 |
| SECTION 8: 737-8, 737-9, 737-8200 | 58 |
| I. General | 58 |
| II. Certification Basis | 59 |
| III. Technical Characteristics and Operational Limitations | 67 |
| IV. Operating and Service Instructions | 73 |
| V. Operating Suitability Data (OSD) | 73 |
| VI. Part 26 compliance information | 74 |
| VII. Notes | 75 |
| SECTION: ADMINISTRATIVE | 76 |
| I. Acronyms and Abbreviations | 76 |
| II. Type Certificate Holder Record | 77 |
| III. Change Record | 78 |
| Appendix A Detailed Certification Basis of the 737-8/-9/-8200 | 83 |



SECTION 1: 737-100, -200, -200C, -300, -400, -500 VARIANTS

I. General

1. Type / Model / Variant: Boeing 737-100, -200, -200C, -300, -400, -500
2. Performance Class: A
3. Certifying Authority: Federal Aviation Administration (FAA)
BASOO Branch 2200 S 216th St

Des Moines, WA 98198
United States of America
4. Manufacturer: The Boeing Company
P.O. Box 3707
Seattle, WA 98124-2207
United States of America
5. EASA Validation Application Date The 737-100, -200, -200C, -300, -400 and -500 series were not subject to a validation by JAA prior to EASA, therefore they are accepted by EASA under the provisions of EU Regulation 1702/2003.
6. FAA Type Certification Date: December 15, 1967 (737-100)
(First Type Certificate issuance)
December 21, 1967 (737-200)
October 29, 1968 (737-200C)
November 14, 1984 (737-300)
September 02, 1988 (737-400)
February 12, 1990 (737-500)
7. EASA Type Validation Date January 23, 1968 (737-130)
(First TC issued within EU MS by LBA Germany)
July 12, 1968 (737-204)
(First TC issued within EU MS by UKCAA)
September 9, 1969 (737-248C)
(First TC issued within EU MS by IAA Ireland)
January 29, 1985 (737-3T5)
(First TC issued within EU MS by UKCAA)
September 14, 1988 (737-4Y0)
(First TC issued within EU MS by UKCAA)
March 7, 1990 (737-505)
(First TC issued within EU MS by CAA Norway)



SECTION 1: 737-100, -200, -200C, -300, -400, -500 VARIANTS – continued

II. Certification Basis

1. FAA Type Certificate Data Sheet: No. A16WE
2. FAA Certification Basis: Refer to FAA Type Certificate Data Sheet (TCDS) No. A16WE
3. JAA/EASA Airworthiness Requirements: In accordance with Regulation (EC) 1702/2003 FAR Part 25 as defined in FAA TCDS A16WE
4. Special Conditions: for adopted special conditions refer to FAA TCDS A16WE, as supplemented by the following:

CRI PTC/E-10 Flammability Reduction System
INT/POL/25/12: Affected requirement FAR 25.981 (c),
JAR 25.1309, NPA 10-2004, JAR 21.16(a)(1)
(not applicable to the 737-100)

CRI E-15 PTC Fuel Tank Safety – Including Lightning Protection
for Structure
INT/POL/25/12: Affected requirement CS 25.981 Amdt 1,
CS 25.981(a)(3), CS
25.954
(applicable to the 737-300/-400/-500 only)

CRI E-16/PTC Fuel Tank Safety
INT/POL/25/12: Affected requirement CS 25.981 Amdt 1
(not applicable to 737-600)

CRI F-GEN10 PTC Non-rechargeable Lithium Batteries Installations
CS 25.601, 25.863, 25.869, 25.1301, 25.1309, 25.1353(c),
25.1529, 25.1360 (b)

CRI H-01 “Instructions for Continued Airworthiness (ICA) on
Electrical Wiring Interconnecting Systems (EWIS)”
Affected requirement Part 21A.16(b)(3), 21A.21(c)(3),
CS 25.1529 & Appendix H

5. Adopted FAA Exemptions: Refer to FAA TCDS A16WE
6. Adopted FAA Equivalent Safety Findings: Refer to FAA TCDS A16WE supplemented by the following:

CRI F-GEN9-1 Minimum Mass Flow of Supplemental Oxygen
“Component Qualification”
Equivalent Safety with JAR 25.1443(c)
(not applicable to the 737-100/-200C)

CRI F-GEN9-3 Crew Determination of Quantity of Oxygen in
Passenger Oxygen System
Equivalent Safety with JAR 25.1441(c)
(not applicable to the 737-100/-200/-
200C)



SECTION 1: 737-100, -200, -200C, -300, -400, -500 VARIANTS – continued

7. Environmental Protection Standards: Noise: ICAO Annex 16, Volume I Special Federal Aviation Regulation 27
See also TCDSN EASA.IM.A.120

III. Technical Characteristics and Operational Limitations

1. Type Design Definition: Boeing Top Collector Drawing No. 65-73701
2. Description: Low wing jet transport with a conventional tail unit configuration, powered by two high bypass turbofan engines mounted on pylons beneath the wings
3. Equipment: The basic required equipment as prescribed in the applicable airworthiness regulations (see Certification Basis) must be installed in the aircraft for certification.
4. Dimensions:

| Series | -100 | -200/200C | -300 | -400 | -500 |
|----------|---------|-----------|---------|---------|---------|
| Length | 28.65 m | 30.48 m | 33.4 m | 36.45 m | 31.01 m |
| Wingspan | 28.35 m | 28.35 m | 28.88 m | | |
| Height | 11.28 m | 11.28 m | 11.13 m | | |

5. Engines
- 737-100, 200, and 200C: 2 Pratt and Whitney Turbofan Engines JT8D-7, JT8D-7A, JT8D-7B, T8D-9, JT8D-9A, JT8D-15, JT8D-15A, JT8D-17, and JT8D-17A
- 737-300, -400, -500: 2 CFM-56-3-B1, CFM-56-3-B2 or CFM-56-3-C1 Turbofan Engines.

Refer to the Approved Airplane Flight Manual for aircraft engine and engine intermix eligibility.

For limitations see FAA TCDS no E3NE (Pratt and Whitney engines) or E2GL/E21EU (CFM engines) or approved Airplane Flight Manual.

6. Auxiliary Power Unit: Honeywell GTCP 85-129
Honeywell GTCP 36-280
Hamilton Sundstrand APS 2000
7. Propellers: N/A
8. Fluids (Fuel, Oil, Additives, Hydraulics) See FAA TCDS A16WE and approved Airplane Flight Manual
9. Fluid Capacities: See appropriate Weight and Balance Manual, Boeing Document D6-15066
10. Airspeed Limits: See approved Airplane Flight Manual
11. Maximum Operating Altitude: See approved Airplane Flight Manual
12. All Weather Capability: See approved Airplane Flight Manual



SECTION 1: 737-100, -200, -200C, -300, -400, -500 VARIANTS – continued

13. Maximum Certified Masses: See approved Airplane Flight Manual for actual approved weights of individual airplanes

| | -100/200 | | -300 | | -400 | | -500 | |
|------|----------|-------|--------|-------|--------|-------|--------|-------|
| | lbs | Kg | lbs | Kg | lbs | Kg | lbs | Kg |
| MTW | 128600 | 58331 | 140000 | 63502 | 150500 | 68265 | 136500 | 61915 |
| MTOW | 128100 | 58105 | 139500 | 63276 | 150000 | 68038 | 136000 | 61688 |
| MLW | 107000 | 48534 | 116600 | 52888 | 124000 | 56245 | 110000 | 49895 |
| MZFW | 99000 | 44905 | 109600 | 49713 | 117000 | 53070 | 103000 | 46720 |

(Specified weights are Increased Design Weights approved post-initial Type Validation)

14. Centre of Gravity Range: See approved Airplane Flight Manual

15. Datum: See appropriate Weights and Balance Manual

The airplane reference origin of coordinates is a point located 540 inches forward of the center section wing front spar centerline, at buttock line zero, (i.e., aircraft fore/aft centerline as viewed in plane view) and at water line zero. (737-100 Series) All production body stations coincide numerically with moment arms. Horizontal distance of datum to nose gear jack point is 286 inches for the 737-100 Series, 250 inches for the 737-200 Series, and 207.7 inches for the 737-300 Series, 135.7 inches for the 737-400 Series, 261.7 inches for the 737-500 Series.

16. Mean Aerodynamic Chord: (MAC) See appropriate Weights and Balance Manual Boeing Document No. D6-15066

17. Levelling Means: See approved Airplane Flight Manual

18. Minimum Flight Crew: Two (2): Pilot and Co-pilot, for all types of flight

19. Minimum Cabin Crew

The tables below provide the certified Maximum Passenger Seating Capacities (MPS), the corresponding cabin configuration (exit arrangement and modifications) and the associated numbers of cabin crew members used to demonstrate compliance with the evacuation certification requirements of CS 25.803. Additional cabin crew members may be required to comply with other regulatory requirements (e.g., cabin attendant direct view).

B737-300

| Passenger Seating Capacity & Cabin Configuration | Cabin crew |
|--|------------|
| From 101 to 149 passengers: (l, III, l) exit arrangement | 3 |
| 100 or fewer passengers: (l, III, l) exit arrangement | 2 |



SECTION 1: 737-100, -200, -200C, -300, -400, -500 VARIANTS – continued

B737-400

| Passenger Seating Capacity & Cabin Configuration | Cabin crew |
|---|------------|
| From 151 to 188 passengers: (I, III, III, I) exit arrangement | 4 |
| From 101 to 150 passengers: (I, III, III, I) exit arrangement | 3 |
| 100 or fewer passengers: (I, III, III, I) exit arrangement | 2 |

B737-500

| Passenger Seating Capacity & Cabin Configuration | Cabin crew |
|--|------------|
| From 101 to 140 passengers: (I, III, I) exit arrangement | 3 |
| 100 or fewer passengers: (I, III, I) exit arrangement | 2 |

20. Maximum Seating Capacity: For maximum number of passengers see item 20. Exits

Note: The maximum number of passengers approved for emergency evacuation is dependant on door configuration, see 20) below. See interior layout drawing for the maximum passenger capacities approved for each aeroplane delivered.

21. Exits:

| | Type (LH and RH) | Maximum Passenger |
|------|------------------|-------------------|
| -100 | I-III-I | 113 (124) * |
| -200 | I-III-I | 119 (136) * |
| -300 | I-III-I | 149 |
| -400 | I-III-III-I | 188 |
| -500 | I-III-I | 140 |

* See FAA TCDS A16WE for details

22. Baggage/Cargo Compartment: See appropriate Weights and Balance Manual
Boeing Document No. D6-1506

23. Wheels and Tyres:

Nose Assy (Qty 2)
Main Assy (Qty 4)
Speed Rating: See approved Airplane Flight Manual
Refer to Boeing Wheel/Tire/Brake Interchangeability Drawing for further details.

IV. Operating and Service Instructions

1. Flight Manual:

Since validation of the Boeing 737-100/-200/-200C/-300/-400/-500 model was conducted by individual NAAs and not under JAA process, there is no generic JAA AFM format. It is the responsibility of the State of Registry to establish that



SECTION 1: 737-100, -200, -200C, -300, -400, -500 VARIANTS – continued
the AFM for an individual aircraft contains appropriate and relevant data and limitations.

2. Mandatory Maintenance Instructions: See FAA TCDS A16WE
Life Limited Parts and required inspection intervals are listed in the EASA approved Airworthiness Limitations Section (Section 9) of the Boeing Maintenance Planning Data Document D6-38278.
3. Service Letters and Service Bulletins: As Published by Boeing and approved by the FAA
4. Required Equipment:

V. Operational Suitability Data (OSD)

The Operational Suitability Data elements listed below are approved by the European Union Aviation Safety Agency under the EASA Type Certificate IM.A.120 as per Commission Regulation (EU) 748/2012 as amended by Commission Regulation (EU) No 69/2014.

1. Master Minimum Equipment List
No MMEL available (Not required per Commission Regulation (EU) No 69/2014 of 27 January 2014)
2. Flight Crew Data
No FCD available (Not required per Commission Regulation (EU) No 69/2014 of 27 January 2014)
3. Cabin Crew Data
No CCD available (Not required per Commission Regulation (EU) No 69/2014 of 27 January 2014)

VI. Part 26 compliance information

For all variants in this section, compliance with point 26.300(a) of Part 26 is demonstrated by complying with points:

- 26.301 Compliance Plan for (R)TC holders
- 26.302 Fatigue and damage tolerance evaluation
- 26.303 Limit of Validity
- 26.304 Corrosion prevention and control program
- 26.305 Validity of the continuing structural integrity program
- 26.306 Fatigue critical baseline structure
- 26.307 Damage tolerance data for existing changes to fatigue critical structure
- 26.308 Damage tolerance data for existing repairs to fatigue critical structure
- 26.309 Repair Evaluation Guidelines



SECTION 1: 737-100, -200, -200C, -300, -400, -500 VARIANTS – continued

VII. Notes

1. Cabin Interior and Seating Configuration must be approved.
2. Additional information is provided in FAA Type Certificate Data Sheet A16WE.



SECTION 2: PERTINENT TO ALL NEXT GENERATION SERIES
(NG: 737-600, -700, -800, -900, -900ER) – continued

SECTION 2: PERTINENT TO ALL NEXT GENERATION SERIES (NG: 737-600, -700, -800, -900, -900ER)

I.General

1. Type / Model / Variant: Boeing 737-600, -700, -800, -900, -900ER
“Next Generation”, NG – Series
2. Performance Class: A
3. Certifying Authority:
Federal Aviation Administration (FAA) BASOO Branch
2200 S 216th St
Des Moines, WA 98198
United States of America
4. Manufacturer:
The Boeing Company
P.O. Box 3707
Seattle, WA 98124-2207
United States of America
5. FAA Certification Application Date: See individual data (Section 3 to 7)
6. EASA Validation Application Date: See individual data (Section 3 to 7)
7. FAA Type Certification Date: See individual data (Section 3 to 7)
8. EASA Type Validation Date: See individual data (Section 3 to 7)

II.Certification Basis

See individual data (Sections 3 to 7).

III.Technical Characteristics and Operational Limitations

1. Production Basis: Manufactured under Production Certificate 700
2. Type Design Definition: See individual data (Section 3 to 7)
3. Description: Low wing jet transport with a conventional tail unit configuration, powered by two high bypass turbofan engines mounted on pylons beneath the wings.



SECTION 2: PERTINENT TO ALL NEXT GENERATION SERIES
(NG: 737-600, -700, -800, -900, -900ER) – continued

4. Dimensions:

| Series | -700 | -800 | -600 | -900 | -900ER |
|--------------------|--------------------------|-------------------------|-------------------------|-------------------------|-------------------------|
| Length | 32.18 m (105 ft 7 in) | 39.5 m (129 ft 6 in) | 31.2 m (102 ft 6 in) | 42.1 m (138 ft 2 in) | 42.1 m (138 ft 2 in) |
| Wingspan | 34.32 m (112 ft 7 in) | | | | |
| Span with Winglets | 35.79 m (117 ft 5 in) | | | | |
| Height | 12.57 m (41 ft 3 in) | | | | |

5. Engines:

2 CFM 56-7B or -7B/2 or -7B/3 or -7BE Series Turbofan Engines. Refer to the Approved Airplane Flight Manual for engine limitations. The CFM56-7B/2 series have double annular combustors and provide the same thrust as the CFM56-7B series engines at the respective engine ratings and are approved for all models except the CFM56-7B-18/2 engine rating.

The CFM56-7B/3 series are the so-called “Tech Insertion” engines, they have single annular combustors and provide the same thrust as the CFM56-7B series at the respective engine ratings.

The CFM56-7BE series have single annular combustors and provide the same thrust as the CFM56-7B series at the respective engine ratings.

Engine ratings and all approved models are referred to in: EASA TCDS E.004 “CFM International CFM56-7B Engines”

6. Auxiliary Power Unit:

Auxiliary Power Unit (APU): Honeywell 131-9 [B]
Limitations: Refer to the APU TCDS / TSO

7. Propellers:

N/A

8. Fluids (Fuel, Oil, Additives, Hydraulics):

Eligible Fuels:
ASTM Specification D-1655 Jet A, JAR A1
MIL-T-5624G; JP-5
MIL-T-83133; JP-8
Refer to Airplane Flight Manual for other approved fuels.

Eligible Oils: See CFM 56-7B Service Bulletin 79-001 as revised.

9. Fluid Capacities:

Fuel Capacity:
26024 litres (6875 US Gallons), consisting of two wing tanks, each of 4875 litres (1288 US Gallons) capacity, and one centre tank, capacity 16274 litres (4299 US Gallons).

Oil Capacity: 10.3 litres useable

10. Air Speeds:

See Airplane Flight Manual



SECTION 2: PERTINENT TO ALL NEXT GENERATION SERIES
(NG: 737-600, -700, -800, -900, -900ER) – continued

11. Maximum Operating Altitude: 12,497 m (41,000 ft) pressure altitude
12. All Weather Capability: Cat 3
13. Maximum Certified Masses: See individual data (Section 3 to 7)
14. Centre of Gravity Range: See Airplane Flight Manual
15. Datum: See Weights and Balance Manual
16. Mean Aerodynamic Chord:
(MAC) 3.96m (155.81 in)
17. Levelling Means: See approved Airplane Flight Manual
18. Minimum Flight Crew: Two (Pilot and Co-pilot) for all types of flight
19. Maximum Seating Capacity: See individual data (Section 3 to 7)
20. Exits: See individual data (Section 3 to 7)
21. Baggage/Cargo Compartment: See individual data (Section 3 to 7)
22. Wheels and Tyres: Speed Rating: 225 MPH, (-900ER: 235 MPH)
Nose Assy (Qty 2) Tyre: 27 x 7.75 - 15 or 27 x 7.75 - R15
Wheel: 27 x 7.75 – 15
Main Assy (Qty 4) Tyre: H43.5 x 16.0 - 21 or
H44.5 x 16.5 – 21
Wheel: HR44.5 x 16.5 – 21
- Refer to Boeing Wheel/Tire/Brake Interchangeability
Drawing for further details
23. ETOPS: 737-600 / -700 / -800 / -900 / -900ER
The type design reliability and performance of this airplane has been evaluated in accordance with AMC 20-6 and found suitable for extended range operations when configured in accordance with Boeing Document D044A007 "737-600/-700/-800/-900/-900ER ETOPS Configuration, Maintenance and Procedures". This finding does not constitute approval to conduct extended range operations. ETOPS approval for the -600, -700, -800, -900, and -900ER is determined by NAA operating policies
737-800BCF
The type design reliability and performance of this airplane has been evaluated in accordance with AMC 20-6 and CS 25.1535 and found suitable for extended range operations when configured in accordance with Boeing Document D044A007 "737-600/-700/-800/-900/-900ER ETOPS Configuration, Maintenance and Procedures". This finding does not constitute approval to conduct extended range



SECTION 2: PERTINENT TO ALL NEXT GENERATION SERIES
(NG: 737-600, -700, -800, -900, -900ER) – continued
operations. ETOPS approval for the -800BCF is determined
by NAA operating policies.

IV. Operating and Servicing Instructions

1. Flight Manual: Since validation of the 737-700 model was conducted under JAA process, there is a generic JAA/EASA AFM format.
2. Mandatory Maintenance Instructions: CMRs
Model 737 MRB Report
Life Limited Parts and required inspection intervals are listed in the EASA approved Airworthiness Limitations Section (Section 9) of the Boeing Maintenance Planning Data Document D626A001.
3. Service Letters and Service Bulletins: As published by Boeing and approved by FAA.
4. Required Equipment: All equipment as prescribed in Section II (Certification Basis) above must be installed in the aircraft.

V. Operational Suitability Data (OSD)

The Operational Suitability Data elements listed below are approved by the European Union Aviation Safety Agency under the EASA Type Certificate IM.A.120 as per Commission Regulation (EU) 748/2012 as amended by Commission Regulation (EU) No 69/2014.

1. Master Minimum Equipment List
 - a. Master Minimum Equipment List (MMEL):
The applicable certification specifications for the Boeing B737-600/-700/-800/-900/-900ER MMEL, reference D6-32545-ESEM, consist of JAR-MMEL/MEL Amendment 1, Section 1, Subpart A & B as recorded in CRI A-MMEL.
 - b. Required for entry into service by EU operator.
2. Flight Crew Data
 - a. The Flight Crew data, With regard to the transition of the OEB recommendations to OSD FC documents for the Boeing B737-600/-700/-800/-900/-900ER, reference D626A014, the data are agreed on the basis of elect to comply with CS-FCD, Initial Issue, dated 31 Jan 2014.
 - b. Required for entry into service by EU operator.
 - c. Pilot Type Rating: "B737-300-900".

Note: These data cover the models B737-300/400/500/600/700/800/900/900ER. Differences are addressed in D926A105

3. Cabin Crew Data
 - a. The Cabin Crew Data has been approved as per the defined Operational Suitability Data Certification Basis recorded in CRI A-CCD, and as demonstrated by the "Boeing Document D611A099 Operational Suitability Data - Cabin Crew Data - Boeing 737NG" certification basis for the



SECTION 2: PERTINENT TO ALL NEXT GENERATION SERIES

(NG: 737-600, -700, -800, -900, -900ER) – continued

establishment of Operational Suitability Data (OSD) Cabin Crew for B737-600/-700/-800/-900/-900ER is CS-CCD, Initial Issue dated 31 January 2014.

- b. Required for entry into service by EU operator.
- c. The “Next Generation” B737-600; B737-700; B737-800; 737-900 aircraft models are determined to be variants to the aircraft model B737-900ER (with Mid Exit Door (MED) activated).

VI. Part 26 compliance information

For all variants in this section, compliance with point 26.300(a) of Part 26 is demonstrated by complying with points:

- 26.301 Compliance Plan for (R)TC holders
- 26.302 Fatigue and damage tolerance evaluation
- 26.303 Limit of Validity
- 26.304 Corrosion prevention and control program
- 26.305 Validity of the continuing structural integrity program
- 26.306 Fatigue critical baseline structure
- 26.307 Damage tolerance data for existing changes to fatigue critical structure
- 26.308 Damage tolerance data for existing repairs to fatigue critical structure
- 26.309 Repair Evaluation Guidelines

VII. Notes:

1. Cabin Interior and Seating Configuration must be approved.
2. Additional information is provided in FAA Type Certificate Data Sheet A16WE.



SECTION 3: 737-700 Series

I.General

- | | |
|--|-------------------|
| 1. Type / Model / Variant: | Boeing 737-700 |
| 2. FAA Certification Application Date: | February 04, 1993 |
| 3. JAA Validation Application Date: (Reference date for JAA validation) | August 04, 1993 |
| 4. FAA Type Certification Date: | November 07, 1997 |
| 5. EASA/JAA Type Validation Date: | February 18, 1998 |

II.Certification Basis

- | | |
|---|--|
| 1. FAA Type Certificate Data Sheet: | No. A16WE |
| 2. FAA Certification Basis: | FAR Part 25 Amendment 25-77 except where modified by the FAA Issue Paper G-1 |
| 3. JAA/EASA Airworthiness Requirements: | JAR 25 Change 13, effective 5 October 1989 Orange Paper 90/1, effective 11 May 1990 Orange Paper 91/1, effective 12 April 1991 JAR AWO Chg. 1, effective 29 November 1985 Orange Paper AWO/91/1, effective 28 November 1991 (Note also see AWO Change 2) JAA IL-23 RVSM, effective April 1994 - (Boeing letter B-T111-96-1357 dated Dec 12, 1996) |

The following NPAs have been applied:

| | | | |
|------------------|-------------|--|---|
| NPA 25,B,D,G-244 | CRI A.11-17 | 25.109 | Accelerate Stop Distances and Related Performances |
| NPA 25C-213 | CRI C-17 | 25.571(e); 25.903 | Discrete source damage due to rotor burst |
| NPA 25B215 | CRI B-02 | 25.103; 25.107; 25.119; 25.125; 25.143; 25.207 | Stall and Stall Warning Speeds and Manoeuvre Capability |
| NPA 25B-217 | CRI B-04 | 25.101-25.123; 25.149; 25.1582- 25.1591 | Reduced Thrust |
| NPA AWO 2 | | | All Weather Operations |
| NPA AWO 5 | | | All Weather Operations |
| NPA 25.B,C,D-236 | CRI C-05 | 25.629 | Flutter, Deformation and Fail Safe Criteria |
| NPA 25J-246 | CRI J-03 | 25B1305 | APU Instruments |
| NPA 25C260 | CRI C-06 | 25.335(b)(2) with ACJ | Design Dive Speed (JAR 25.335(b)(2) plus ACJ at Ch.14) |



SECTION 3: 737-700 SERIES – continued

| | | | |
|------------|------------------------|-----------------------------|---|
| NPA 25C260 | | 25.499(e) | Nose Wheel Steering (JAR 25.499(e)) |
| NPA 25B261 | B-08; B-11; B-13; B-15 | Flight requirements+ 201(d) | Harmonisation of JAR/FAR 25 Flight Requirements |

In addition, the following requirements have been applied:

JAR AWO Change 2: All Weather Operations
Special Condition JAA/737-700/SC/C-07 (JAR 25.427(b)(3) FAA/JAA Harmonised version) in place of JAR 25.427(b)(3)
Static Ground Load Conditions (Jacking): JAR 25.519(b) in accordance with JAR 25 Amendment 25/96/1
Stalling Speeds for Structural Design (defined in CRI C-12)
Type III Emergency Exit Operating Handle Illumination JAR 25.811(e) at JAR 25 Chg. 14

3.1. Reversions:

The following reversions from the defined certification basis have been applied:

| | |
|-------------------------------|---|
| CRI A. 11-02 JAR 25.365 | Pressurised Cabin Loads Reversion to FAR 25.365 Amendment 0 |
| CRI A. 11-04 JAR 25.562 | Emergency Landing Dynamic Loads Reversion to JAR 25 Change 12 which excludes para .562 |
| CRI A. 11-05 JAR 25.571 | Fatigue and Damage Tolerance Partial Reversion to FAR 25.571 Amendment 0 |
| CRI A. 11-06 JAR 25.607(a) | Fasteners Reversion to FAR 25.607(a) Amendment 0 |
| CRI A. 11-08 JAR 25.699(a) | Lift and Drag Device Indicator Reversion to FAR 25.699 Amendment 0 |
| CRI A. 11-11 JAR 25.783(f) | Doors Reversion to FAR 25.783 Amendment 15 |
| CRI A. 11-12 JAR 25.785(a) | Seat, Berths, Safety Belts and Harness Reversion to JAR 25.785(a) Change 12 |
| CRI A. 11-16 JAR 25.1309 | Equipment Systems and Installations Reversion to FAR 25.1309 Amendment 0 |
| CRI A.11-23 JAR 25.775(d) | Windshields and Windows Reversion to FAR 25.775(d) Amendment 0 |
| CRI J-04 JAR 25A1141(f)(2) | APU Fuel Shut Off Valve Indication Reversion to FAR 25.1141 Amendment 11 |



SECTION 3: 737-700 SERIES – continued

4. Special Conditions:

The following JAA Special Conditions have been applied defined in their respective CRI:

| | |
|---------------------------------|--|
| CRI B-10 JAA/737-700/SC/B-10 | Stall Warning Thrust Bias Affected JAR 25.207(c) as amended by NPA 25B-215 |
| CRI C-01 JAA/737-700/SC/C-01 | Pressurised Cabin Loads INT/POL/25/7 Affected requirement JAR 25.365 |
| CRI C-11 JAA/737-700/SC/C-11 | Interaction of Systems and Structure Affected requirement JAR 25.302 |
| CRI D-01 JAA/737-700/SC/D-01 | Brakes Requirements Qualification and Testing INT/POL/25/6: Affected requirement JAR 25.735 |
| CRI D-04 JAA/737-700/SC/D-04 | Landing Gear Warning INT/POL/25/1: Affected requirement JAR 25.729(e)(2) to (4) |
| CRI D-14 JAA/737-700/SC/D-14 | Exit Configuration Affected requirement JAR 25.807, JAR 25.562, JAR 25.813 |
| CRI D-GEN01 PTC | Fire Resistance of Thermal Insulation Material Affected requirement CS25.856 & Appendix F |
| CRI D-GEN02 PTC | Application of Heat Release and Smoke Density Requirements to Seat Materials Affected Requirement CS 25.853(d) Appendix F Part IV & V Part 21 §21A.16B |
| CRI E-10 | Installation of Seat Inflatable Restraint Systems |
| CRI PTC/E-10 | Flammability Reduction Systems (FRS) INT/POL/25/12: Affected requirement FAR 25.981 (c), JAR 25.1309, NPA 10-2004, JAR 21.16(a)(1) Affected requirement JAR 25.1301 |
| CRI E-16/PTC | Fuel Tank Safety Affected requirement CS 25.981 Amdt 1 |
| CRI F-01 JAA/737-700/SC/F-01 | High Intensity Radiated Field (HIRF) INT/POL/25/2: Affected requirement JAR 25.1431(a) |
| CRI F-02 JAA/737-700/SC/F-02 | Protection from Effects of Lightning Strike; Direct Effects INT/POL/25/3: Affected requirement JAR 25X899 and ACJ 25X899 |
| CRI F-03 JAA/737-700/SC/F-03 | Protection from Effects of Lightning Strike; Indirect Effects INT/POL/25/4: Affected requirement JAR 25.581, 25.899 25.954, 25.1309 |
| CRI PTC/F-17 | EGPWS Airworthiness Approval |



SECTION 3: 737-700 SERIES – continued

| | |
|-----------------|--|
| | Affected requirement JAR 25.1301, JAR 25.1309(b)(c)(d), JAR 25.1431(a)(c), JAR 25.1459 |
| CRI PTC/F-18 | Multi-Sensor Navigation Systems for specified operational use Affected requirement JAR 25.1301, .1303, .1309, .1321, .1322, .1331, .1431, .1457, .1541, .X1524, .1583 |
| CRI PTC F-23 | CIAP/IRNAV and NPS Human Factors Evaluation Affected requirement INT/POL 25/14, JAR 25.771(a) and (e), 25.777(a), 25.1301, 25.1303, 25.1309, 25.1523 |
| CRI PTC/F-27 | GNSS Landing System (GLS) – Airworthiness Approval for Category I Approach Operations Affected requirement 25.1301, 25.1309, 25.1322, 25.1329, 25.1335, 25.1431, 25.1459, 25.1581, JAR-AWO, JAR-AWO NPA AWO-9 |
| CRI F-29 | Lithium Ion Batteries Affected requirement JAR 25.601, 25.863, 25.1309, 25.1353(c) and 25.1529 |
| CRI F-30 | Data Link Services for the Single European Sky EUROCAE ED-120, ED-78A, ED-110B, ED-92A (Radio VDL/M2); Affected Requirements: JAR/FAR 25.1301, 25.1307, 25.1309, 25.1321, 25.1322, 25.1431, 25.1459, 25.1581, 25.1585, Commission Regulation (EC) No 29/2009 |
| CRI F-31(PTC) | Security Protection of Aircraft Systems and Networks Affected requirement JAR 25.1309 |
| CRI F-GEN10 PTC | Non-rechargeable Lithium Batteries Installations CS 25.601, 25.863, 25.869, 25.1301, 25.1309, 25.1353(c), 25.1529, 25.1360 (b) (only for installation of Honeywell CVR P/N 980-6032-003 and FDR P/N 980-4750-003) |
| CRI F-GEN-11 | Non-rechargeable Lithium Batteries Installations CS 25.601, 25.863, 25.1353(c) (for all installations not covered by F-GEN 10) |
| CRI G-01 | ETOPS Approval (180 minutes) Affected Requirements JAA Information Leaflet No. 20 |
| CRI H-01 | “Instructions for Continued Airworthiness (ICA) on Electrical Wiring Interconnecting Systems (EWIS)” Affected requirement Part 21A.16(b)(3), 21A.21(c)(3), CS 25.1529 & Appendix H |

5. Exemptions/Deviations:

The following Partial JAA Exemption has been applied:

| | |
|---------------------------------|---|
| CRI D-02 JAA/737-700/PE/D-02 | Hydraulic System Proof Pressure Testing Partial Exemption Against JAR 25 |
|---------------------------------|---|



SECTION 3: 737-700 SERIES – continued
1435(b)(1)

The following EASA Deviation has been applied:

| | |
|--------------|--|
| CRI PTC D-22 | Tech Insertion engines and New Thrust Reverser Cascades Intermix for 737-600/-700/-800/-900 LN No. 1 Thru 2230 Deviation Against 25.305, 25.307(a), 25.601, 25.603(c), 26.613(a)(b), 25.1103(d) at Ch 13 |
| CRI D-29 | CFM 56-7B Technology Insertion Engines and new Thrust Reverser Cascades |

6. Equivalent Safety Findings:

The following JAA Equivalent Safety Findings have been applied:

CRI PTC C-14 Landing Gear Safe Lives – Fatigue Scatter Factors
Equivalent Safety with JAR 25.571 Change 15

CRI D-06 Towbarless Towing
JAA/737-700/ES/D-06 Equivalent Safety with JAR 25X745(d)

CRI D-08 Forward and Aft Door Escape Slide Low Sill Height
JAA/737-700/ES/D-08 Equivalent Safety with JAR 25.809(f)(1)(ii)

CRI D-10 Overwing Hatch Emergency Exit Signs
JAA/737-700/ES/D-10 Equivalent Safety with JAR 25.812(b)(1)(i)

CRI D-16 Automatic Overwing Exit
JAA/737-700/ES/D-16 Equivalent Safety with JAR 27.783(f)

CRI D-17 Oversized Type I Exits, Maximum Number of Passengers
JAA/737-700/ES/D-17 Equivalent Safety with JAR 25.807

CRI D-18 Slide/Raft Inflation Gas Cylinders
JAA/737-700/ES/D-18 Equivalent Safety with JAR 25X1436

CRI PTC/ D-19 Door Sill Reflectance
JAA/757-300/ES/D-19 Equivalent Safety with JAR 25.811(f)

CRI PTC/D-21 Emergency Exit Marking
Equivalent Safety with JAR 25.811(f)

CRI 9ER/ D-21 Door Sill Reflectance
Equivalent Safety with JAR 25.811(f)

CRI PTC/ D-23 Passenger Information Signs
JAA/737-700/ES/D-23 Equivalent Safety with JAR 853(d)

CRI E-09 Automatic Fuel Shut Off
JAA/737-700/ES/E-09 Equivalent Safety with JAR 25.979(b)(1)

CRI E-11 New Interior Arrangement with Passenger Service Unit
Life Vest Stowage
Equivalent Safety with JAR 25.1411(f) (not applicable to the 737-600)

CRI F-15 Wing Position Lights
JAA/737-700/ES/F-15 Equivalent Safety with JAR 25.1389(b)(3)

CRI F-GEN 9-1 Minimum Mass Flow of Supplemental Oxygen “Component



SECTION 3: 737-700 SERIES – continued

| | |
|--------------|---|
| | Qualification” Equivalent Safety with JAR 25.1443(c) |
| CRI F-GEN9-3 | Crew Determination of Quantity of Oxygen in Passenger Oxygen System Equivalent Safety with JAR 25.1441(c) |
| CRI G-GEN1 | Instructions for Continued Airworthiness Equivalent Safety with CS 25.1529, CD25 Appendix H |

7. OSD requirements

- As defined in CRI A-MMEL issue 1: for B737-600/-700/-800/-900/-900ER, JAR-MMEL/MEL Amendment 1, Section 1, Subpart A & B is applicable.
- As defined in document D926A105: B737-600/-700/-800/-900/-900ER, CS-FCD, Initial Issue, dated 31 Jan 2014 is applicable
- As defined in CRI A-CCD issue 1: for B737-600/-700/-800/-900/-900ER, CS-CCD, Initial Issue dated 31 January 2014 is applicable.

8. Environmental Protection Standards: Noise: ICAO Annex 16, Volume I (Third Edition)
Fuel: ICAO Annex 16, Volume II (Second Edition)
See also TCDSN EASA.IM.A.120

III. Technical Characteristics and Operational Limitations

1. Production Basis: Manufactured under Production Certificate 700

2. Type Design Definition: Defined by Boeing Top Drawing No. 001A0001-700 Rev. AG, dated January 12, 1998, and later approved changes and Production Revision Record (PRR) No. 38280.

(737-700 IGW) Boeing Top Drawing No. 001A0001-2703 Rev. CA, dated October 13, 1998, and later approved changes and Production Revision Record (PRR) No. 38280

3. Description: Refer to Section 2 (data pertinent to all NG Series)

4. Dimensions: Refer to Section 2 (data pertinent to all NG Series)

5. Engines:

| | | | | | |
|--------|-----------------------------------|-------------------------|-----------------------------------|---|---------------------------------|
| CFM56- | 7B20 7B20/2 7B20/3 7B20E | 7B22 7B22/3 7B22E | 7B24 7B24/2 7B24/3 7B24E | 7B26 7B26/B1 7B26/3F 7B26E 7B26E/B1 7B26E/B2 7B26E/B2F 7B26E/F | 7B27/B3 7B27/3B3 7B27E/B3 |
|--------|-----------------------------------|-------------------------|-----------------------------------|---|---------------------------------|

6. Auxiliary Power Unit: Refer to Section 2 (data pertinent to all NG Series)

7. Propellers: N/A



SECTION 3: 737-700 SERIES – continued

- 8. Fluids (Fuel, Oil, Additives, Hydraulics): Refer to Section 2 (data pertinent to all NG Series)
- 9. Fluid Capacities: Refer to Section 2 (data pertinent to all NG Series)
- 10. Airspeed Limits: See Airplane Flight Manual
- 11. Maximum Operating Altitude: 12,497 m (41,000 ft) pressure altitude
- 12. All Weather Capability: See Airplane Flight Manual
- 13. Maximum Certified Masses:

| | 737-700* | | 737-700 IGW** | |
|---------------|--------------|------------|---------------|------------|
| Taxi and Ramp | 155,000 lbs. | 70,306 kg, | 171,500 lbs. | 77,791 kg. |
| Take-off | 154,500 lbs. | 70,080 kg. | 171,000 lbs. | 77,564 kg. |
| Landing | 129,200 lbs. | 58,604 kg. | 134,000 lbs. | 60,781 kg. |
| Zero Fuel | 121,700 lbs. | 55,202 kg. | 126,000 lbs. | 57,152 kg. |

* Specified weights for -700 are Increased Design Weights approved post-initial Type Validation

** Reference Boeing PLOD B-T111-98-2097 (737-700 IGW Revision F)

- 14. Centre of Gravity Range: Refer to Airplane Flight Manual
- 15. Datum: See Weights and Balance Manual
- 16. Mean Aerodynamic Chord: 3.96 m (155.81 in) (MAC)
- 17. Levelling Means: See Weight and Balance Manual
- 18. Minimum Flight Crew: Two (Pilot and Co-pilot) for all types of flight
- 19. Minimum Cabin Crew

The table below provides the certified Maximum Passenger Seating Capacities (MPS), the corresponding cabin configuration (exit arrangement and modifications) and the associated numbers of cabin crew members used to demonstrate compliance with the evacuation certification requirements of CS 25.803. Additional cabin crew members may be required to comply with other regulatory requirements (e.g., cabin attendant direct view).

| Passenger Seating Capacity & Cabin Configuration | Cabin crew |
|--|------------|
| From 101 to 149 passengers: (I, III, I) exit arrangement | 3 |
| 100 or fewer passengers: (I, III, I) exit arrangement | 2 |

- 20. Maximum Seating Capacity: (-) Passengers

Note: The maximum number of passengers approved for emergency evacuation is 149 with JAA / 737-700/SC/D- 14 applicable, otherwise 145. See interior layout drawing for the maximum passenger capacities approved for each aeroplane delivered.



SECTION 3: 737-700 SERIES – continued
21. Exits:

| B737-700 | Number | Type | Size mm (inches) |
|-------------------------------|--------|----------|-------------------------------|
| 1 Main Fwd LH | 1 | Type I | 864W x 1829H (34 x 72), |
| 2 Main Aft LH | 1 | Type I | 762W x 1829H (30 x 72), |
| 3 Service (Fwd, RH, Aft, RH) | 1+1 | Type I | 762W x 1651H (30 x 65 - both) |
| 4 Overwing/Emergency left | 1 | Type III | 508W x 914H (20 x 36) |
| 5 Overwing/Emergency right | 1 | Type III | 508W x 914H (20 x 36) |
| 6 Flight Crew Emergency Exits | 1 + 1 | Sliding | 483W x 508H (19 x 20 - both) |

22. Baggage/Cargo Compartment:

| Location | Class | Volume m ³ (ft ³) |
|------------|-------|--|
| Front Fwd | C | 11.37 (406) |
| Middle | N/A | N/A |
| Rear Aft | C | 16.7 (596) |
| Underfloor | N/A | N/A |

23. Wheels and Tyres: Refer to Section 2 (data pertinent to all NG Series)

24. ETOPS Operation: Refer to Section 2 (data pertinent to all NG Series)

25. Fuel Tank Flammability Reduction System (FRS): Aircraft which have made their first flight after 1 January 2012 must be equipped with a fuel tank Flammability Reduction System (EASA SIB 2010-10)

Flammability Reduction Systems have been installed on aircraft line numbers 1820 and 1831 in December 2005, and then since mid 2008 on aircraft line number 2517, 2620 and on.

This system shall remain installed and operative and can only be dispatched inoperative in accordance with the provisions of the MMEL

IV. Operating and Servicing Instructions

1. Flight Manual:
2. Service Information:
3. Required Equipment:
4. Universal Airplane Network Security Operator Guidance (UANSOG)

The Boeing Commercial Airplanes Universal Airplane Network Security Operator Guidance, D925W704-04, contains required Instructions for Continued Airworthiness and security guidance that when followed meets compliance requirements of the Network Cybersecurity Special Conditions.



SECTION 3: 737-700 SERIES – continued
V.Operational Suitability Data (OSD)

The Operational Suitability Data elements listed below are approved by the European Union Aviation Safety Agency under the EASA Type Certificate IM.A.120 as per Commission Regulation (EU) 748/2012 as amended by Commission Regulation (EU) No 69/2014. Applicable OSD requirements are detailed in section 3.II.7.

1. Master Minimum Equipment List
(see section 2.V)
2. Flight Crew Data
(see section 2.V)
3. Cabin Crew Data
(see section 2.V)

VI. Notes

1. Airplanes modified by Boeing design change “Lower Cabin Altitude” are capable of maintaining a cabin altitude of 6500 feet in lieu of the standard 8000 feet when operating at a cruising altitude of 41,000 feet. This modification has been approved by EASA STC 10042295.



SECTION 4: 737-800 SERIES – continued

SECTION 4: 737-800 Series

4.1 B737-800 Model

I. General

- 1. Type / Model / Variant: Boeing 737-800
- 2. FAA Certification Application Date: February 04, 1993
- 3. JAA Validation Application Date: August 04, 1993
(Reference date for JAA validation)
- 4. FAA Type Certification Date: March 13, 1998
- 5. EASA/JAA Type Validation Date: April 09, 1998

II. Certification Basis

- 1. FAA Type Certificate Data Sheet: No. A16WE
- 2. FAA Certification Basis: As for Boeing 737-700, see Section 3
- 3. JAA/EASA Airworthiness Requirements:
 - a. For aircraft without in-production winglets: As for Boeing 737-700, see Section 3
 - b. For aircraft with in-production winglets:
 - i. Applicable requirements for affected area:
The affected area are the wingtip position and anti-collision lights, light fixtures and wiring within the wingtip, the winglets, wing box, wing spars and wing skins.

The applicable requirements are defined in JAR 25 Change 14, effective 27 May 1994, Orange Paper 96/1, effective 19 April 1996, JAR AWO Change 2, effective 1st August 1996 and JAA IL-23-RVSM, effective April 1994.

Two Equivalent Safety Findings apply:
JAA/737-800/ES/F-01
(PTC) CRI F-01 Forward Wingtip (Winglet) 8.5v Position Lights-Intensities
Equivalent Safety with JAR 25.1389(b)(1), 25.1389(b)(2) 25.1391, 25.1395

JAA/737-800/ES/F-02
(PTC) CRI F-02 Forward Wingtip (Winglet) 8.5v Position Lights-Overlapping Intensities: Equivalent Safety with JAR 25.1389(b)(3) and 25.1395
 - ii. Applicable requirements for non-affected area
The non-affected area are in particular (but not limited to) engine struts, fuselage, empennage, landing gear.
The applicable requirements are those defined for Boeing 737-700 in Section 3



SECTION 4: 737-800 SERIES – continued

4. Special Conditions: As for Boeing 737-700, see Section 3

5. Exemptions/Deviations: As for Boeing 737-700, see Section 3

6. Equivalent Safety Findings: As for Boeing 737-700, see Section 3 and the following:

CRI C-15/PTC Structural Certification Criteria for Large Antenna Installations Equivalent Safety with JAR 25.23, 25.251, 25.301, 25.365, 25.571, 25.581, 25.603, 25.605, 25.609, 25.613, 25.629, 25.631, 25.841, 25.901, 25.1419, 25.1529, and Appendix H

CRI F-01 PTC Forward Wingtip (Winglet) 8.5 volt Position Light Intensities Equivalent Safety with JAR 25.1389(b), 25.1391, 25.1395

CRI F-02 PTC Forward Wingtip (Winglet) 8.5 volt Position Lights – Overlapping Intensities Equivalent Safety with Jar 25.1389(b)(3) and 25.1395

7. OSD requirements

- As defined in CRI A-MMEL issue 1: for B737-600/-700/-800/-900/-900ER, JAR-MMEL/MEL Amendment 1, Section 1, Subpart A & B is applicable.
- As defined in document D926A105: B737-600/-700/-800/-900/-900ER, CS-FCD, Initial Issue, dated 31 Jan 2014 is applicable
- As defined in CRI A-CCD issue 1: for B737-600/-700/-800/-900/-900ER, CS-CCD, Initial Issue dated 31 January 2014 is applicable.

8. Environmental Protection Standards: As for Boeing 737-700, see Section 3

III. Technical Characteristics and Operational Limitations

1. Production Basis: Manufactured under Production Certificate 700
2. Type Design Definition: Defined by Boeing Top Drawing No. 001A0001-800 Rev. AK, dated February 27, 1998, and later approved changes and Production Revision Record (PRR) No. 38280.
3. Description: Refer to Section 2 (data pertinent to all NG Series)
4. Dimensions: Refer to Section 2 (data pertinent to all NG Series)
5. Engines:

| | | | | |
|--------|----------|---------|-----------|-----------|
| CFM56- | 7B24 | 7B26 | 7B27 | 7B27/B1 |
| | 7B24/3 | 7B26/2 | 7B27/2 | 7B27/3B1 |
| | 7B24/3B1 | 7B26/3 | 7B27/3 | 7B27/3B1F |
| | 7B24E | 7B26/3F | 7B27/3F | 7B27/3B3 |
| | 7B24E/B1 | 7B26E | 7B27E | 7B27E/B1 |
| | 7B26E/F | 7B27E/F | 7B27E/B1F | 7B27E/B3 |

6. Auxiliary Power Unit: Refer to Section 2 (data pertinent to all NG Series)



SECTION 4: 737-800 SERIES – continued

7. Propellers: N/A
8. Fluids (Fuel, Oil, Additives, Hydraulics): Refer to Section 2 (data pertinent to all NG Series)
9. Fluid Capacities: Refer to Section 2 (data pertinent to all NG Series)
10. Airspeed Limits: See Airplane Flight Manual
11. Maximum Operating Altitude: 12,497 m (41,000 ft) pressure altitude
12. All Weather Capability: See Airplane Flight Manual
13. Maximum Certified Masses:

| | | |
|---------------|--------------|------------|
| Taxi and Ramp | 174,900 lbs. | 79,333 kg. |
| Take-off | 174,200 lbs. | 79,015 kg. |
| Landing | 146,300 lbs. | 66,360 kg. |
| Zero Fuel | 138,300 lbs. | 62,731 kg. |

* Specified weight approved post-initial Type Validation

14. Centre of Gravity Range: Refer to Airplane Flight Manual
15. Datum: See Weights and Balance Manual
16. Mean Aerodynamic Chord (MAC): 3.96 m (155.81 in)
17. Levelling Means: See Weight and Balance Manual
18. Minimum Flight Crew: Two (Pilot and Co-pilot) for all types of flight
19. Minimum Cabin Crew

The table below provides the certified Maximum Passenger Seating Capacities (MPS), the corresponding cabin configuration (exit arrangement and modifications) and the associated numbers of cabin crew members used to demonstrate compliance with the evacuation certification requirements of CS 25.803. Additional cabin crew members may be required to comply with other regulatory requirements (e.g., cabin attendant direct view).

| Passenger Seating Capacity & Cabin Configuration | Cabin crew |
|---|------------|
| From 151 to 189 passengers: (I, III, III, I) exit arrangement | 4 |
| From 101 to 150 passengers: (I, III, III, I) exit arrangement | 3 |
| 100 or fewer passengers: (I, III, III, I) exit arrangement | 2 |

20. Maximum Seating Capacity: (-) Passengers

Note: The maximum number of passengers approved for emergency evacuation is 189 (with JAA/737-700/SC/D-14 applicable - or otherwise: 180).

See interior layout drawing for the maximum passenger capacities approved for each aeroplane delivered.

21. Exits:



SECTION 4: 737-800 SERIES – continued

| B737-800 | Number | Type | Size mm (inches) |
|------------------------------|--------------------------|----------|-----------------------------|
| 1 Main Fwd LH | 1 | Type I | 864W x 1829H (34 x 72), |
| 2 Main Aft LH | 1 | Type I | 762W x 1829H (30 x 72), |
| 3 Service (Fwd, RH, Aft, RH) | 1+1 | Type I | 762W x 1651H (30 x 65-both) |
| 4 Overwing/Emergency left | 2 | Type III | 508W x 914H (20 x 36) |
| 5 Overwing/Emergency right | 2 | Type III | 508W x 914H (20 x 36) |
| 6 Cockpit side window (2) | Flight Crew Emerg. Exits | | 483W x 508H (19 x 20) |

For crew emergency evacuation purposes, the side windows are available on both sides.

22. Baggage/Cargo Compartment:

| Location | Class | Volume m ³ (ft ³) |
|------------|-------|--|
| Front Fwd | C | 19.6 (692) |
| Middle | N/A | N/A |
| Rear Aft | C | 25.46 (899) |
| Underfloor | N/A | N/A |

23. Wheels and Tyres: Refer to Section 2 (data pertinent to all NG Series)

24. ETOPS Operation: Refer to Section 2 (data pertinent to all NG Series)

24. Fuel Tank Flammability Reduction System (FRS):

Aircraft which have made their first flight after 1 January 2012 must be equipped with a fuel tank Flammability Reduction System (EASA SIB 2010-10)

Flammability Reduction Systems have been installed on aircraft line numbers 1820 and 1831 in December 2005, and then since mid 2008 on aircraft line number 2517, 2620 and on.

This system shall remain installed and operative and can only be dispatched inoperative in accordance with the provisions of the MMEL

IV. Operating and Servicing Instructions

1. Flight Manual: Airplane Flight Manual, Document No. D631A001.J02

2. Service Information: Maintenance Manual, Document No. D633A101

Maintenance Review Board Report Revision 1; 19 November 1997 or subsequent JAA/EASA approved revision

Airworthiness Limitations and Certification Maintenance Requirements: 737-600/700/800 Maintenance Planning Document (MPD) Document Section 9 Ref.: D626A001, Revision Dated September 1997, and later revisions thereof

Service Letters and Service Bulletins

3. Required Equipment: The approved equipment is listed in: (737-700) CRI A-10

V. Operational Suitability Data (OSD)

SECTION 4: 737-800 SERIES – continued

The Operational Suitability Data elements listed below are approved by the European Union Aviation Safety Agency under the EASA Type Certificate IM.A.120 as per Commission Regulation (EU) 748/2012 as amended by Commission Regulation (EU) No 69/2014.

Applicable OSD requirements are detailed in section 4.II.7.

1. Master Minimum Equipment List
(see section 2.V)
2. Flight Crew Data
(see section 2.V)
3. Cabin Crew Data
(see section 2.V)

VI. Notes

None



SECTION 4: 737-800 SERIES – continued

4.2 B737-800 Model – Boeing Converted Freighter Major Change**I. General**

The 737-800 BCF (Boeing Converted Freighter) is a 737-800 series passenger airplane that has been modified to operate in a freighter configuration.

This is a major change to the B737-800 model, not a new model. These aircraft remain 737-800 model aircraft for documentation purposes on this TCDS and with regard to the applicability of airworthiness directives.

Because of the magnitude of this design change, the certification basis for the changed aspects was required to be established and documented in accordance with section 21.101 (Changed Product Rule).

Paragraph numbering is consistent with that of section 4. Any paragraph not included in this section for the B737-800BCF is therefore unchanged from the B737-800 (including noise and emissions requirements).

- | | |
|--|---|
| 1. Type-Model Variant: | Boeing 737-800 BCF (Boeing Converted Freighter) |
| 2. FAA Certification Application Date: | October 29, 2014 |
| 3. EASA Validation Application Date: | March 23, 2016 |
| 4. FAA Type Certificate Date: | April 06, 2018 |
| 5. EASA Type Validation Date: | April 12, 2018 |

II. Certification Basis

- | | |
|---|---|
| 1. FAA Type Certification Data Sheet: | No. A16WE |
| 2. FAA Certification Basis: | 14 CFR Part 25 Amendment 25-0 through 25-138 except where modified by the FAA Issue Paper G-1 |
| 3. EASA Airworthiness Requirements for non-affected Area: | |

As for Boeing 737-800 baseline model, see Section 4.1.

4 EASA Airworthiness Requirements for affected Area:

Affected Area definition:

- Main Deck Cargo Door (MDCD).
- Modification of fuselage surround structure for installation of MDCD: MDCD surround structure perimeter located from STA 360 to STA 500H (S-4R to S24L) with the MDCD located from STA 440 to STA 500D (S-3L to S-17L.)
- Modification of floor structure to accommodate cargo loads and handling: floor structure modified in Sections 41, 43, 44, 46 and 47. (STA 344 – STA 986)
- Removal of passenger interior configuration for installation of main deck Class E cargo compartment and supernumerary area.
- Installation of Class E main deck cargo Fire Detection System.



SECTION 4: 737-800 SERIES – continued

- Installation of new main deck Cargo Handling System (CHS) and Rigid Cargo Barrier (RCB) placards via third party STC.
- Airplane environmental control systems, mechanical, hydraulic, electrical systems revisions to support passenger to freighter modification.

Applicable JAR/CS Requirements:

CS-25 Amendment 15, effective July 21, 2014 with reversions identified in section 9.II.8.

CS-AWO, effective October 17 2003

5. Special Conditions:

The following Special Conditions have been defined in their respective CRI:

| | |
|--------------|---|
| CRI D-30 PTC | Courier Compartment Affected requirement CS 25.857(e) amdt 15 |
| CRI D-31 PTC | Access to class E cargo compartment in flight Affected requirement CS 25.855, 25.857, 25.1309, 25.1439, 25.1443 at amdt 15 |
| CRI F-GEN-11 | Non-Rechargeable Lithium Batteries Installations Affected requirement CS 25.601, 25.863, 25.1353(c) |

5. Deviations:

N/A

6. Equivalent Safety Findings:

The following JAA/EASA Equivalent Safety Findings have been applied:

| | |
|--------------|---|
| CRI F-39 PTC | 737-800 BCF installation of a common supplemental oxygen system for flight crew and supernumeraries Equivalent Safety with CS 25.1445(a) amdt 15 |
|--------------|---|

7. Operational Suitability Requirements:

As for Boeing 737-800, see Section 4.

8. Reversions

All reversions from the applicable airworthiness standards to earlier standard, as per Part 21.101(b), are listed below.

The following reversions from the applicable airworthiness standards contain additional requirements that can be found in the associated CRI.

| Applicable paragraph | Reversion | Conditions associated to the reversions are given in the following CRIs |
|----------------------|---|---|
| CS 25.365(e)(1)(2) | Pressurised Compartment loads, Engine disintegration fragments Reversion to FAR 25.365 Amendment 0 | 737-700 CRI A.11- 02, plus JAA/737- 700/SC/C-1 |
| CS 25.734 | Protection Against Wheel and Tyre | |



SECTION 4: 737-800 SERIES – continued

| Applicable paragraph | Reversion | Conditions associated to the reversions are given in the following CRIs |
|----------------------------------|--|---|
| | Failures Reversion to JAR 25.729(f) at Change 13 | |
| CS 25.795(b)(1) | Security Considerations Not applicable | |
| CS 25.1301 | Function and installation Reversion to JAR 25.1301 at Change 13 EWIS Components: reversion to 25.1703-1733, except for 1707(c) | CRI F-GEN-11, CRI F-GEN9-4 |
| CS 25.1301(b) | Function and installation: EWIS Not applicable | CRI H-01 |
| CS 25.1309 | Equipment Systems and Installations Reversion to JAR 25.1309 at Change 13 with OP 90/1 | CRI A.11-16, CRI F-GEN-11, CRI F-GEN9-4 |
| CS 25.1309(d) | Equipment Systems and Installations: EWIS Not applicable | CRI H-01 |
| CS 25.1322 | Flight Crew Alerting Reversion to JAR 25.1322 at Change 13/14 | |
| CS 25.1703-1733 excepted 1707(c) | Electrical Wiring Interconnection Systems (EWIS) Not applicable | CRI H-01 |

III. Technical Characteristics and Operational Limitations

(Characteristics not mentioned below are identical to those of the B737-800 baseline model)

1. Type Design Definition: Boeing Top Project Drawing 800A0003
2. Maximum Certified Masses: There are no increases to the 737-800 Operational Weights.

| | | |
|---------------|--------------|------------|
| Taxi and Ramp | 174,900 lbs. | 79,333 kg. |
| Take-off | 174,200 lbs. | 79,015 kg. |
| Landing | 146,300 lbs. | 66,360 kg. |
| Zero Fuel | 138,300 lbs. | 62,731 kg. |

3. Maximum Seating Capacity

Maximum Passenger Capacity 0 (Zero) Passengers. Up to 6 (six) Supernumeraries within the Flight Deck and courier compartment. 2 (two) Flight Crew members.

4. Exits

| B737-800BCF | Number | Type | Size mm (inches) |
|---------------------------|--------------------------|--------|-----------------------------|
| 1 Main Fwd LH | 1 | Type I | 864W x 1829H (34 x 72), |
| 3 Service (Fwd, RH) | 1 | Type I | 762W x 1651H (30 x 65-both) |
| 6 Cockpit side window (2) | Flight Crew Emerg. Exits | | 483W x 508H (19 x 20) |



SECTION 4: 737-800 SERIES – continued

For crew emergency evacuation purposes, the side windows are available on both sides. Overwing and Aft exits are deactivated.

5. Baggage/Cargo Compartment:

| Location | Class | Volume m ³ (ft ³) |
|------------|-------|--|
| Main Deck | E | 144.4 (5100) |
| Front Fwd | C | 19.0 (670) |
| Middle | N/A | N/A |
| Rear Aft | C | 25.0 (883) |
| Underfloor | N/A | N/A |

6. ETOPS Operation: Refer to Section 2 (data pertinent to all NG Series)

7. Other limitations: None

IV. Operating and Service Instructions

1. Airplane Flight Manual (AFM): Boeing Document D631A001

2. Service Information: Airworthiness Limitations and Certification Maintenance Requirements: 737-600/700/800 Maintenance Planning Document (MPD) Document Section 9 Ref.: D626A001, Revision Dated September 1997, and later revisions thereof.

Service Letters and Service Bulletins as published by Boeing and approved by the FAA.

4. Weight and Balance (WBM): Boeing Document D043A584

5. Universal Airplane Network Security Operator Guidance (UANSOG)

The Boeing Commercial Airplanes Universal Airplane Network Security Operator Guidance, D925W704-04, contains required Instructions for Continued Airworthiness and security guidance that when followed meets compliance requirements of the Network Cybersecurity Special Conditions.

V. Operating Suitability Data (OSD)

The Operational Suitability Data elements listed below are approved by the European Union Aviation Safety Agency under the EASA Type Certificate IM.A.120 as per Commission Regulation (EU) 748/2012 as amended by Commission Regulation (EU) No 69/2014. Applicable OSD requirements are detailed in section 9.II.7.

1. Master Minimum Equipment List

OSD MMEL requirements as per section 2.V.

The EASA MMEL is defined in Boeing document D6-32545-ESEM, revision 4 dated April 05th, 2018, or later approved revisions.

2. Flight Crew Data

OSD FCD requirements as per section 2.V.

The Flight Crew Data is defined in Boeing document D626A014, revision A dated 19 February 2021 or later approved revisions.



SECTION 4: 737-800 SERIES – continued

3. Cabin Crew Data

OSD CCD requirements as per section 2.V .

VI. Notes

Following STC must be installed in conjunction with this installation:

- EASA.IM.A.S01078 LiteAir Aviation Products Inc. Window plugs (10015384)
- 10065167 Ventura Aerospace Inc. 9g Rigid Cargo barrier
- 10065171 Ancra International LLC Cargo Loading system

1. Airplanes modified by Boeing design change “Lower Cabin Altitude” are capable of maintaining a cabin altitude of 6500 feet in lieu of the standard 8000 feet when operating at a cruising altitude of 41,000 feet. This modification has been approved by EASA STC 10042295.



SECTION 5: 737-600 Series – continued

SECTION 5: 737-600 Series

I.General

- | | |
|--|--------------------|
| 1. Type / Model / Variant: | Boeing 737-600 |
| 2. FAA Certification Application Date: | February 04, 1993 |
| 3. JAA Validation Application Date: (Reference date for JAA validation) | August 04, 1993 |
| 4. FAA Type Certification Date: | August 12, 1998 |
| 5. EASA/JAA Type Validation Date: | September 09, 1998 |

II.Certification Basis

- | | |
|---|--------------------------------------|
| 1. FAA Type Certificate Data Sheet: | No. A16WE |
| 2. FAA Certification Basis: | As for Boeing 737-700, see Section 3 |
| 3. JAA/EASA Airworthiness Requirements: | As for Boeing 737-700, see Section 3 |
| 4. Special Conditions: | As for Boeing 737-700, see Section 3 |
| 5. Exemptions/Deviations: | As for Boeing 737-700, see Section 3 |
| 6. Equivalent Safety Findings: | As for Boeing 737-700, see Section 3 |
| 7. Operational Suitability Data: | As for Boeing 737-700, see Section 3 |
| 8. Environmental Protection Standards: | As for Boeing 737-700, see Section 3 |

III.Technical Characteristics and Operational Limitations

- | | |
|----------------------------|---|
| 1. Production Basis: | Manufactured under Production Certificate 700 |
| 2. Type Design Definition: | Defined by Boeing Top Drawing No. 001A0001-600 Rev. AW, dated June 08, 1998, and later approved changes and Production Revision Record (PRR) No. 38280. |
| 3. Description: | Refer to Section 2 (data pertinent to all NG Series) |
| 4. Dimensions: | Refer to Section 2 (data pertinent to all NG Series) |
| 5. Engines: | |

| | | | | |
|--------|--|--------|-----------------------------------|-----------------------------------|
| CFM56- | | 7B18/3 | 7B20 7B20/2 7B20/3 7B20E | 7B22 7B22/2 7B22/3 7B22E |
|--------|--|--------|-----------------------------------|-----------------------------------|

- | | |
|--------------------------|--|
| 6. Auxiliary Power Unit: | Refer to Section 2 (data pertinent to all NG Series) |
| 7. Propellers: | N/A |



SECTION 5: 737-600 Series – continued

- 8. Fluids (Fuel, Oil, Additives, Hydraulics): Refer to Section 2 (data pertinent to all NG Series)
- 9. Fluid Capacities: Refer to Section 2 (data pertinent to all NG Series)
- 10. Airspeed Limits: See Airplane Flight Manual
- 11. Maximum Operating Altitude: 12,497 m (41,000 ft) pressure altitude
- 12. All Weather Capability: See Airplane Flight Manual
- 13. Maximum Certified Masses:

| | | |
|---------------|--------------|------------|
| Taxi and Ramp | 146,000 lbs. | 66,224 kg. |
| Take-off | 145,500 lbs. | 65,997 kg. |
| Landing | 120,500 lbs. | 54,657 kg. |
| Zero Fuel | 114,000 lbs. | 51,709 kg. |

- 14. Centre of Gravity Range: Refer to Airplane Flight Manual
- 15. Datum: See Weights and Balance Manual
- 16. Mean Aerodynamic Chord: 3.96 m (155.81 in) (MAC)
- 17. Levelling Means: See Weight and Balance Manual
- 18. Minimum Flight Crew: Two (Pilot and Co-pilot) for all types of flight
- 19. Minimum Cabin Crew

The table below provides the certified Maximum Passenger Seating Capacities (MPS), the corresponding cabin configuration (exit arrangement and modifications) and the associated numbers of cabin crew members used to demonstrate compliance with the evacuation certification requirements of CS 25.803. Additional cabin crew members may be required to comply with other regulatory requirements (e.g., cabin attendant direct view).

| Passenger Seating Capacity & Cabin Configuration | Cabin crew |
|--|------------|
| From 101 to 145 passengers: (I, III, I) exit arrangement | 3 |
| 100 or fewer passengers: (I, III, I) exit arrangement | 2 |

- 20. Maximum Seating Capacity: (-) Passengers

Note: The maximum number of passengers approved for emergency evacuation is 149 (with JAA/737-700/SC/D-14 applicable - or otherwise: 145).
See interior layout drawing for the maximum passenger capacities approved for each aeroplane delivered.



SECTION 5: 737-600 Series – continued
21. Exits:

| B737-600 | Number | Type | Size mm (inches) |
|------------------------------|--------------------------|----------|-----------------------------|
| 1 Main Fwd LH | 1 | Type I | 864W : 1829H (34 x 72), |
| 2 Main Aft LH | 1 | Type I | 762W : 1829H (30 x 72), |
| 3 Service (Fwd, RH, Aft, RH) | 1+1 | Type I | 762W : 1651H (30 x 65-both) |
| 4 Overwing/Emergency left | 1 | Type III | 508W : 914H (20 x 36) |
| 5 Overwing/Emergency right | 1 | Type III | 508W : 914H (20 x 36) |
| 6 Cockpit side window (2) | Flight Crew Emerg. Exits | | 483W : 508H (19 x 20) |

For crew emergency evacuation purposes, the side windows are available on both sides.

22. Baggage/Cargo Compartment:

| Location | Class | Volume m ³ (ft ³) |
|------------|-------|--|
| Front Fwd | C | 7.59 (268) |
| Middle | N/A | N/A |
| Rear Aft | C | 13.8 (488) |
| Underfloor | N/A | N/A |

23. Wheels and Tyres: Refer to Section 2 (data pertinent to all NG Series)

24. ETOPS Operation: Refer to Section 2 (data pertinent to all NG Series)

25. Fuel Tank Flammability Reduction System (FRS): Aircraft which have made their first flight after 1 January 2012 must be equipped with a fuel tank Flammability Reduction System (EASA SIB 2010-10)

Flammability Reduction Systems have been installed on aircraft line numbers 1820 and 1831 in December 2005, and then since mid 2008 on aircraft line number 2517, 2620 and on.

This system shall remain installed and operative and can only be dispatched inoperative in accordance with the provisions of the MMEL

IV. Operating and Servicing Instructions

1. Flight Manual: Airplane Flight Manual, Document No. D631A001.J03

2. Service Information: Maintenance Manual, Document No. D633A101

Maintenance Review Board Report Revision 1;
19 November 1997 or subsequent JAA/EASA approved revision

Airworthiness Limitations and Certification Maintenance Requirements: 737-600/700/800 Maintenance Planning Document (MPD) Document Section 9 Ref.: D626A001, Revision dated September 1997, and later revisions thereof
Service Letters and Service Bulletins

3. Required Equipment: The approved equipment is listed in: (737-700) CRI A-10



SECTION 5: 737-600 Series – continued

V.Operational Suitability Data (OSD)

The Operational Suitability Data elements listed below are approved by the European Union Aviation Safety Agency under the EASA Type Certificate IM.A.120 as per Commission Regulation (EU) 748/2012 as amended by Commission Regulation (EU) No 69/2014. Applicable OSD requirements are detailed in section 5.II.7.

1. Master Minimum Equipment List
(see section 2.V)
2. Flight Crew Data
(see section 2.V)
3. Cabin Crew Data
(see section 2.V)

VI. Notes

None



SECTION 6: 737-900 Series

I.General

- | | |
|--|------------------|
| 1. Type / Model / Variant: | Boeing 737-900 |
| 2. FAA Certification Application Date: | October 14, 1997 |
| 3. JAA Validation Application Date: (Reference date for JAA validation) | October 14, 1997 |
| 4. FAA Type Certification Date: | April 17, 2001 |
| 5. EASA/JAA Type Validation Date: | April 19, 2001 |

II.Certification Basis

- | | |
|---|--|
| 1. FAA Type Certificate Data Sheet: | No. A16WE |
| 2. FAA Certification Basis: | FAR Part 25 Amendment 25-91 except where modified by the FAA Issue Paper G-1 |
| 3. JAA/EASA Airworthiness Requirements: | Applicable JAR Requirements (Reference CRI 9/A-01) JAR 25 Change 14, effective 27 May 1994 Orange Paper 96/1, effective 19 April 1996 JAR AWO Change 2, effective 01 August 1996 JAA IL-23 RVSM, effective April 1994 |

The following NPAs have been applied:

| | | | |
|------------------|-------------|--|---|
| NPA 25,B,D,G-244 | CRI A.11-17 | 25.109 | Accelerate Stop Distances and Related Performances |
| NPA 25C-213 | CRI C-17 | 25.571(e); 25.903 | Discrete source damage due to rotor burst |
| NPA 25B215 | CRI B-02 | 25.103; 25.107; 25.119; 25.125; 25.143; 25.207 | Stall and Stall Warning Speeds and Manoeuvre Capability |
| NPA 25B-217 | CRI B-04 | 25.101-25.123; 25.149; 25.1582- 25.1591 | Reduced Thrust |
| NPA AWO 2 | | | All Weather Operations |
| NPA AWO 5 | | | All Weather Operations |
| NPA 25.B,C,D-236 | CRI C-05 | 25.629 | Flutter, Deformation and Fail Safe Criteria |
| NPA 25J-246 | CRI J-03 | 25B1305 | APU Instruments |
| NPA 25C260 | CRI C-06 | 25.335(b)(2) with ACJ | Design Dive Speed (JAR 25.335(b)(2) plus ACJ at Ch.14) |
| NPA 25C260 | | 25.499(e) | Nose Wheel Steering (JAR 25.499(e)) |



SECTION 6: 737-900 Series – continued

| | |
|-----------------------------|---|
| CRI 9/A.11-01 JAR 25.365 | Pressurised Cabin Loads Reversion to FAR 25.365 Amendment 0 |
| CRI 9/A.11-02 | Fuel Tank Access Covers |
| JAR 25.963(g)(1) | Reversion to FAR 25 963 (e)(1) Amendment 69 |
| CRI 9/A11-03 JAR 25.1329 | Automatic Pilot System Reversion to JAR 25.1329 Change 13 and associated ACJ |
| CRI 9/A11-04 AMJ 25-11 | Electronic Display Systems Reversion to JAR 25 Change 13 and associated ACJ |

4. Special Conditions:

The following JAA Special Conditions have been applied defined in their respective CRI:

| | |
|---------------------------------|--|
| JAA/737-700/SC/B-10 CRI B-10 | Stall Warning Thrust Bias Affected Requirement JAR 25.207(c) as amended by NPA 25B-215 |
| JAA/737-700/SC/C-01 CRI C-01 | Pressurized Cabin Loads INT/POL/25/7 Affected requirement JAR 25.365 |
| JAA/737-700/SC/C-11 CRI C-11 | Interaction of Systems and Structure Affected requirement JAR 25.302 |
| JAA/737-700/SC/D-01 CRI D-01 | Brakes Requirements Qualification and Testing INT/POL/25/6 Affected requirement JAR 25.735 |
| JAA/737-700/SC/D-04 CRI D-04 | Landing Gear Warning INT/POL/25/1: Affected requirement JAR 25.729(e)(2) to (4) |
| JAA/737-700/SC/D-14 CRI D-14 | Exit Configuration Affected Requirement: JAR 25.807, JAR 25.562, JAR 25.813 |
| CRI PTC/E-10 | Flammibility Reduction Systems (FRS) INT/POL/25/12: Affected requirement FAR 25.981 (c), JAR 25.1309, NPA 10-2004, JAR 21.16(a)(1) |
| CRI E-16/PTC | Fuel Tank Safety Affected requirement CS 25.981 Amdt 1 |
| JAA/737-700/SC/F-01 CRI F-01 | High Intensity Radiated Field (HIRF) INT/POL/25/2: Affected requirement JAR 25.1431(a) |
| JAA/737-700/SC/F-02 CRI F-02 | Protection from Effects of Lightning Strike; Direct Effects INT/POL/25/3: Affected requirement JAR 25X899 and ACJ 25X899 |
| JAA/737-700/SC/F-03 CRI F-03 | Protection from Effects of Lightning Strike; Indirect Effects INT/POL/25/4: Affected requirement JAR 25.581, 25.899, |



SECTION 6: 737-900 Series – continued

25.954, 25.1309

CRI PTC F-23 CIAP/IRNAV and NPS Human Factors Evaluation
Affected requirement INT/POL 25/14, JAR 25.771(a) and (e)
25.777(a), 25.1301, 25.1303, 25.1309, 25.1523

CRI PTC/F-27 GNSS Landing System (GLS) – Airworthiness Approval for
Category I Approach Operations
Affected requirement 25.1301, 25.1309, 25.1322, 25.1329,
25.1335, 25.1431, 25.1459, 25.1581, JAR-AWO, JAR-AWO
NPA AWO-9

CRI F-29 Lithium Ion Batteries
Affected requirement JAR 25.601, 25.863, 25.1309,
25.1353(c) and 25.1529

CRI F-30 Data Link Services for the Single European Sky
EUROCAE ED-120, ED-78A, ED-110B, ED-92A (Radio
VDL/M2); Affected Requirements: JAR/FAR 25.1301,
25.1307, 25.1309, 25.1321, 25.1322, 25.1431, 25.1459,
25.1581, 25.1585, Commission Regulation (EC) No 29/2009

CRI F-31(PTC) Security Protection of Aircraft Systems and Networks
Affected requirement JAR 25.1309
(not applicable to 737-600)

CRI F-GEN10 PTC Non-rechargeable Lithium Batteries Installations
CS 25.601, 25.863, 25.869, 25.1301, 25.1309, 25.1353(c),
25.1529, 25.1360 (b) (only for installation of Honeywell CVR
P/N 980-6032-003 and FDR P/N 980-4750-003)

CRI F-GEN-11 Non-rechargeable Lithium Batteries Installations
CS 25.601, 25.863, 25.1353(c) (for all installations not
covered by F-GEN 10)

CRI H-01 “Instructions for Continued Airworthiness (ICA) on Electrical
Wiring Interconnecting Systems (EWIS)”
Affected requirement Part 21A.16(b)(3), 21A.21(c)(3),
CS 25.1529 & Appendix H

5. Exemptions/Deviations:

The following partial JAA Exemption has been applied:

JAA/737-700/PE/D-02 Hydraulic System Pressure Testing
CRI D-02 Partial Exemption Against JAR 25 1435(b)(1)

The following EASA Deviation has been applied:

CRI PTC D-22 Tech Insertion Engines and New Thrust Reverser Cascades
Intermix for 737-600/-700/-800/-900 LN: 1 through 2230
Deviation Against 25.305, 25.307(a), 25.601, 25.603(c),
26.613(a)(b), 25.1103(d) at Ch 13



SECTION 6: 737-900 Series – continued

CRI D-29 CFM 56-7B Technology Insertion Engines and new Thrust Reverser Cascades

6. Equivalent Safety Findings:

| | |
|--------------------------------------|---|
| JAA/737-900/ES/9/C-01 CRI 9/C-01 | Material Strength Properties and Design Values Equivalent Safety with JAR 25.613 |
| JAA/737-900/ES/9/C-04 CRI 9/C-04 | Control Systems Equivalent Safety with JAR 25.395(a) |
| CRI PTC C-14 | Landing Gear Safe Lives – Fatigue Scatter Factors Equivalent Safety with JAR 25.571 Change 15 |
| JAA/737-900/ES/9/D-02 CRI 9/D-02 | Environmental Control Systems (Packs Off Take-Off) Equivalent Safety with JAR 25.831 (a) |
| JAA/737-700/ES/D-08 CRI D-08 | Forward and Aft Door Escape Slide Low Sill Height Equivalent Safety with JAR 25.809(f)(1)(ii) |
| JAA/737-700/ES/D-16 CRI D-16 | Automatic Overwing Exit Equivalent Safety with JAR 25.783(f) |
| JAA/737-700/ES/D-17 CRI D-17 | Oversized Type I Exits, Maximum Number of Passengers |
| JAA/737-700/ES/D-18 CRI D-18 | Slide/Raft Inflation Gas Cylinders Equivalent Safety with JAR 25X1436 |
| CRI PTC/D-21 | Emergency Exit Marking Equivalent Safety with JAR 25.811(f) |
| JAA/737-700/ES/D-21 CRI 9ER/ D-21 | Door Sill Reflectance Equivalent Safety with JAR 25.811(f) |
| JAA/737-700/ES/D-23 CRI PTC/D-23 | Passenger Information Signs Equivalent Safety with JAR 25.853(d) |
| JAA/737-700/ES/E-09 CRI E-09 | Automatic Fuel Shut Off Equivalent Safety with JAR 25.979(b)(1) |
| JAA/737-700/ES/F-15 CRI F-15 | Wing Tip Position Lights Equivalent Safety with JAR 25.1389(b)(3) |
| CRI F-GEN 9-1 | Minimum Mass Flow of Supplemental Oxygen “Component Qualification” Equivalent Safety with JAR 25.1443(c) |
| CRI F-GEN9-3 | Crew Determination of Quantity of Oxygen in Passenger Oxygen System Equivalent Safety with JAR 25.1441(c) |



SECTION 6: 737-900 Series – continued

CRI G-GEN1

Instructions for Continued Airworthiness
Equivalent Safety with CS 25.1529, CS25 Appendix H

7. OSD requirements

- As defined in CRI A-MMEL issue 1: for B737-600/-700/-800/-900/-900ER, JAR-MMEL/MEL Amendment 1, Section 1, Subpart A & B is applicable.
- As defined in document D926A105: B737-600/-700/-800/-900/-900ER, CS-FCD, Initial Issue, dated 31 Jan 2014 is applicable
- As defined in CRI A-CCD issue 1: for B737-600/-700/-800/-900/-900ER, CS-CCD, Initial Issue dated 31 January 2014 is applicable.

8. Environmental Protection Standards: As for Boeing 737-700, see Section 3

III. Technical Characteristics and Operational Limitations

1. Production Basis: Manufactured under Production Certificate 700
2. Type Design Definition: Defined by Boeing Top Drawing No. 001A0001-900 Rev. HK, dated March 06, 2001, and later approved changes and Production Revision Record (PRR) No. 38906.
3. Description: Refer to Section 2 (data pertinent to all NG Series)
4. Dimensions: Refer to Section 2 (data pertinent to all NG Series)
5. Engines:

| | | | | |
|--------|---|---|---|---|
| CFM56- | 7B24 7B24/3 7B24/3B1 7B24E 7B24E/B1 | 7B26 7B26/3 7B26/3F 7B26E 7B26E/F | 7B27 7B27/3 7B27/3F 7B27E 7B27E/F | 7B27/B1 7B27/3B1 7B27/3B3 7B27E/B1 7B27E/B3 |
|--------|---|---|---|---|

6. Auxiliary Power Unit: Refer to Section 2 (data pertinent to all NG Series)
7. Propellers: N/A
8. Fluids (Fuel, Oil, Additives, Hydraulics): Refer to Section 2 (data pertinent to all NG Series)
9. Fluid Capacities: Refer to Section 2 (data pertinent to all NG Series)
10. Airspeed Limits: See Airplane Flight Manual
11. Maximum Operating Altitude: 12,497 m (41,000 ft) pressure altitude
12. All Weather Capability: See Airplane Flight Manual
13. Maximum Certified Masses:

| | | |
|---------------|--------------|------------|
| Taxi and Ramp | 174,700 lbs. | 79,242 kg. |
| Take-off | 174,200 lbs. | 79,015 kg. |
| Landing | 147,300 lbs. | 66,814 kg. |
| Zero Fuel | 140,300 lbs. | 63,639 kg. |

14. Centre of Gravity Range: Refer to Airplane Flight Manual



SECTION 6: 737-900 Series – continued

15. Datum: See Weights and Balance Manual

16. Mean Aerodynamic Chord 3.96 m (155.81 in) (MAC):

17. Levelling Means: See Weight and Balance Manual

18. Minimum Flight Crew: Two (Pilot and Co-pilot) for all types of flight

19. Minimum Cabin Crew

The table below provides the certified Maximum Passenger Seating Capacities (MPS), the corresponding cabin configuration (exit arrangement and modifications) and the associated numbers of cabin crew members used to demonstrate compliance with the evacuation certification requirements of CS 25.803. Additional cabin crew members may be required to comply with other regulatory requirements (e.g., cabin attendant direct view).

| Passenger Seating Capacity & Cabin Configuration | Cabin crew |
|---|------------|
| From 151 to 189 passengers: (I, III, III, I) exit arrangement | 4 |
| From 101 to 150 passengers: (I, III, III, I) exit arrangement | 3 |
| 100 or fewer passengers: (I, III, III, I) exit arrangement | 2 |

20. Maximum Seating Capacity: (-) Passengers

Note: The maximum number of passengers approved for emergency evacuation is 189 (with JAA/737-700/SC/D-14 applicable) or otherwise: 180
See interior layout drawing for the maximum passenger capacities approved for each aeroplane delivered.

21. Exits:

| B737-900 | Number | Type | Size mm (inches) |
|------------------------------|--------------------------|----------|-------------------------|
| 1 Main Fwd LH | 1 | Type I | 864W x 1829H (34 x 72), |
| 2 Main Aft LH | 1 | Type I | 762W x 1829H (30 x 72), |
| 3 Service (Fwd, RH, Aft, RH) | 1+1 | Type I | 762W x 1651H (30 x 65- |
| 4 Overwing/Emergency left | 2 | Type III | 508W x 914H (20 x 36) |
| 5 Overwing/Emergency right | 2 | Type III | 508W x 914H (20 x 36) |
| 6 Cockpit side window (2) | Flight Crew Emerg. Exits | | 483W x 508H (19 x 20) |

For crew emergency evacuation purposes, the side windows are available on both sides.

22. Baggage/Cargo Compartment:

| Location | Class | Volume m ³ (ft ³) |
|------------|-------|--|
| Front Fwd | C | 23.5 (830) |
| Middle | N/A | N/A |
| Rear Aft | C | 28.2 (996) |
| Underfloor | N/A | N/A |

23. Wheels and Tyres: Refer to Section 2 (data pertinent to all NG Series)

24. ETOPS Operation: Refer to Section 2 (data pertinent to all NG Series)

25. Fuel Tank Flammability Reduction System (FRS): Aircraft which have made their first flight after 1 January



SECTION 6: 737-900 Series – continued

2012 must be equipped with a fuel tank Flammability Reduction System (EASA SIB 2010-10)

Flammability Reduction Systems have been installed on aircraft line numbers 1820 and 1831 in December 2005, and then since mid 2008 on aircraft line number 2517, 2620 and on.

This system shall remain installed and operative and can only be dispatched inoperative in accordance with the provisions of the MMEL

IV. Operating and Servicing Instructions

1. Flight Manual: Airplane Flight Manual, Document No. D631A001.J04
2. Service Information: Maintenance Manual, Document No. D633A101

Maintenance Review Board Report Revision 3 together with MRBR Supplement for 737-900 as JAA Approved 12 January 2000; subsequent JAA approved revision

Airworthiness Limitations and Certification Maintenance Requirements: 737-600/700/800 Maintenance Planning Document (MPD) Document Section 9 Ref.: D626A001, Revision dated March 2001, and later revisions thereof

Service Letters and Service Bulletins.
3. Required Equipment: The approved equipment is listed in:
(737-900) CRI 9/A-10

V. Operational Suitability Data (OSD)

The Operational Suitability Data elements listed below are approved by the European Union Aviation Safety Agency under the EASA Type Certificate IM.A.120 as per Commission Regulation (EU) 748/2012 as amended by Commission Regulation (EU) No 69/2014. Applicable OSD requirements are detailed in section 6.II.7.

1. Master Minimum Equipment List
(see section 2.V)
2. Flight Crew Data
(see section 2.V)
3. Cabin Crew Data
(see section 2.V)

VI. Notes

None



SECTION 7: 737-900ER

I. General

1. Type / Model / Variant: Boeing 737-900ER
2. FAA Certification Application Date: June 05, 2002
3. JAA Validation Application Date: January 10, 2002
(Reference date for JAA validation) June 05, 2002
4. FAA Type Certification Date: April 20, 2007
5. EASA/JAA Type Validation Date: April 22, 2008

II. Certification Basis

1. FAA Type Certificate Data Sheet: No. A16WE
2. FAA Certification Basis: FAR Part 25 Amendment 25-108 except where modified by the FAA Issue Paper G-1
3. JAA/EASA Airworthiness Requirements: Applicable JAR Requirements
(Reference CRI 9ER/A-01)*
JAR 25 Change 15, effective 01 October 2000
JAR AWO Change 2, effective 01 August 1996
JAA IL-23 RVSM, effective April 1994

In addition to the -900 model the following NPAs have been applied in various CRIs:

| | |
|---------------------|--|
| NPA 25B, C, D-236 | Flutter, Deformation and Fail Safe Criteria |
| NPA 25C, D, F-314 | Better Plan for Harmonization – Cabin Safety |
| NPA 25F-274 | Introduction of MLS and Upgrade of Equipment Software Standards |
| NPA 25D-301 Issue 1 | Doors |
| NPA 25D-336 | Reinforced Cockpit Doors to Enhance Aeroplane Security |
| NPA 25D-320 | Revised Standards for Cargo or Baggage Compartments in Transport Category Aeroplanes |

* *NOTE: CRIs initially raised for the model -700 as cross-referenced in CRI 9ER/A-01 as applicable do not have a prefix. CRIs initially raised for the model -900 as cross-referenced therein as applicable are identified by the prefix "9/". CRIs which are specific to the Boeing 737 submodel -900ER are identified by the prefix "9ER/".*



SECTION 7: 737-900ER Series – continued

3.1. Reversions:

The following Reversions as defined by the respective (-700 or -900) CRI's, were identified and accepted as part of the JAA Validation of the Boeing 737-700 and -900 models and are requested by Boeing and agreed by EASA for the certification basis for the validation of the Boeing 737-900ER design change:

| | |
|--|--|
| CRI A.11-06 JAR 25.607(a) | Fasteners Reversion to FAR 25.607(a) Amendment 0 |
| CRI A. 11-08 JAR 25.699(a) | Lift and Drag Device Indicator Reversion to FAR 25.699 Amendment 0 |
| CRI A.11-11 JAR 25.783(f) | Doors Reversion to FAR 25.783(f) Amendment 15 |
| CRI A. 11-16 JAR 25.1309 | Equipment, Systems and Installations Reversion to FAR 25.1309 Amendment 0 |
| CRI A. 11-23 JAR 25.775(d) CRI 9/A. 11-03 JAR 25.1329 | Windshields and Windows Reversion to FAR 25.775(d) Amendment 0 Automatic Pilot System Reversion to JAR 25.1329 Change 13 and associated ACJ |
| CRI 9/A. 11-04 AMJ 25-11 | Electronic Display Systems Reversion to JAR 25 Change and associated ACJ |
| CRI J-04 JAR 25A1141(f)(2) | APU Fuel Shut Off Valve Indication Reversion to FAR 25.1141 Amendment 11 |

Note: The CRI A.11-13 is applicable to the 737-900ER as well. This CRI A.11-13 has been reclassified from reversion to means of compliance and for this reason is not directly included in the list but remains applicable.

The following reversions as defined by the respective CRI's have been identified to be not applicable for the EASA Validation of the Boeing 737-900ER model:

| | |
|-----------------------------------|--|
| JAR 25.571 ch. 15 (CRI A.11-5) | Fatigue and Damage Tolerance Boeing requested re-reversion to Chg 15. |
|-----------------------------------|--|

The following reversions as defined by the respective CRI's have been identified and accepted as part of the EASA Validation of the Boeing 737-900ER model:

| | |
|--|---|
| JAR 25.571(c) CRI 9ER/C-14 | Fatigue Safe-Life Scatter Factors – Harmonized Scatter Factor – JAR 25 Chg 15 |
| JAR 25.365 CRI 9/A. 11-01 CRI 9ER/C-19 | Pressurized Cabin Loads (partly) Reversion to FAR 25.365 Amendment 0 (with exception to the aft pressure bulkhead area, which is a significant change) JAR 25 Chr 15, CRI 9ER/C-19 applies |
| JAR 25.493 CRI 9ER/C-21 | Braked Roll Conditions Reversion to Chg 14 based on unchanged area. |
| JAR 25.562 | Emergency Landing Dynamic Loads |



SECTION 7: 737-900ER Series – continued

| | |
|---------------------------|---|
| CRI 9ER/A.11-04 | Partly reversion to JAR 25 Change 12 excluding Paragraph 25.562. Partly NPA 25C,D, F-314 except for (c)(5) and (c)(6) |
| JAR 25.729(f) and 25.1309 | Protection of Equipment on the Landing Gear and in Wheel Wells. Reversion to Change 14 including OP 96/1 |

3.2. Elect to Comply:

Boeing elected to comply with the following requirements as part of the Models 737-700 and 737-900 JAA Validation. These updated CRIs are for the model (-900ER):

| | |
|---|---|
| CRI 9ER/B-07 | All Weather Operations JAR NPAs AWO 2 dtd. Nov 1991 and AWO 5 dtd. Jul 1994 |
| CRI 9ER/C-05 | Flutter, Deformation and Fail Safe Criteria JAR 25.629 in accordance with NPA-25B, C, D – 236 dated Dec 1996, SSG(98/8) |
| CRI 9ER/C-12 JAR 25.333, 335(c)(d)(e), 479(a), 481(a), 729(a) | Stalling Speeds for Structural Design TGM/25/6 is to be used for B737-900ER while Boeing proposed to use CRI C-12. JAR 25 Chg 15 applies |
| CRI 9ER/D-02 | Towbarless Towing JAR 25X745(d) Introduce Special Condition CRI be reopened. INT/POL/25/13 instead of RNPA 25D-275 |
| CRI 9ER/F-04 | Software Policy JAR 25.1309 Chg 15 applies |
| CRI PTC G-01 (Rev. Sep/1999) | ETOPS Approval (180 minutes) AMC 20-6 |
| CRI PTC G-02 | Aeroplane Flight Manual JAR 25.1581, ACJ and AMJ 25.1581 |
| CRI PTC G-03 | ETOPS Approval (Performance Charts) |
| JAR 25.335(b)(2) | Design Dive Speed JAR 25 Chg 15 applies |
| JAR 25.427(b)(3) No CRI issued | Round the Clock Gust JAR 25 Chg 15 applied – CRI C-07 not applicable |
| JAR 25.499(e) | Nose Wheel Steering JAR 25 Chg 15 applies |
| JAR 25.519(b) | Jacking JAR 25 Chg 15 applies |
| JAR 25.415 | Ground Gust JAR 25 Chg 15 applies |

4. Special Conditions:



SECTION 7: 737-900ER Series – continued

The following JAA Special Conditions as defined by the respective (-700) CRI's, were identified as part of the JAA Validation of the Boeing 737-700 model and are applicable to, and form part of, the EASA Certification Basis for the Validation Boeing 737-900ER model:

| | |
|--|--|
| JAA/737-700/SC/B-10 CRI B-10 | Stall Warning Thrust Bias Affected Requirement JAR 25-207(c) |
| JAA/737-700/SC/D-01 CRI D-01 Interim Policy INT/POL/25/6 | Brakes requirements qualification and testing Affected requirements JAR 25.735/NPA 25B,D,G-244 and JAA |
| JAA/737-700/SC/D-04 CRI D-04 | Landing gear warning Affected requirements JAR 25.729 (e)(2) to (4) |
| JAA/737-700/SC/D-14 CRI D-14 | Exit Configuration Affected requirements JAR 25.807, JAR 25.562 and JAR 25.813(c)(1) |
| JAA/737-700/SC/F-01 CRI F-01 | High Intensity Radiated Field (HIRF) INT/POL/25/2: Affected requirement JAR 25.1431(a) |
| JAA/737-700/SC/F-02 CRI F-02 ACJ 25X899 | Protection from Effects of Lightning Strike; Direct Effects INT/POL/25/3: Affected requirements: JAR 25X899 and |
| JAA/737-700/SC/F-03 CRI F-03 | Protection from Effects of Lightning Strike; Indirect Effect INT/POL/25/4 Affected requirements: JAR 25.581, 25.899, J5.954, 25.1309 |
| CRI F-GEN10 PTC | Non-rechargeable Lithium Batteries Installations CS 25.601, 25.863, 25.869, 25.1301, 25.1309, 25.1353(c), 25.1529, 25.1360 (b) (only for installation of Honeywell CVR P/N 980-6032-003 and FDR P/N 980-4750-003) |
| CRI F-GEN-11 | Non-rechargeable Lithium Batteries Installations CS 25.601, 25.863, 25.1353(c) (for all installations not covered by F-GEN 10) |

The following EASA Special Conditions have been applied defined in their respective CRI:

| | |
|-----------------|--|
| CRI D-GEN01 PTC | Fire Resistance of Thermal Insulation Material Affected requirement CS25.856 & Appendix F |
| CRI D-GEN02 PTC | Application of Heat Release and Smoke Density Requirements for Seat Materials Affected Requirements: CS 25.853(d); Appendix F part IV and V; Part 21 §21A.16B |
| CRI PTC/E-10 | Flammability Reduction Systems (FRS) INT/POL/25/12: Affected requirement FAR 25.981 (c), JAR 25.1309, NPA 10-2004, JAR 21.16(a)(1) |
| CRI E-16/PTC | Fuel Tank Safety Affected requirement CS 25.981 Amdt 1 |



SECTION 7: 737-900ER Series – continued

| | |
|---------------|--|
| CRI PTC F-23 | CIAP/IRNAV and NPS Human Factors Evaluation Affected requirement INT/POL 25/14, JAR 25.771(a) and (e), 25.777(a), 25.1301, 25.1303, 25.1309, 25.1523 |
| CRI F-29 | Lithium Ion Batteries Affected requirement JAR 25.601, 25.863, 25.1309, 25.1353(c) and 25.1529 |
| CRI F-30 | Data Link Services for the Single European Sky EUROCAE ED-120, ED-78A, ED-110B, ED-92A (Radio VDL/M2); Affected Requirements: JAR/FAR 25.1301, 25.1307, 25.1309, 25.1321, 25.1322, 25.1431, 25.1459, 25.1581, 25.1585, Commission Regulation (EC) No 29/2009 |
| CRI F-31(PTC) | Security Protection of Aircraft Systems and Networks Affected requirement JAR 25.1309 |
| CRI H-01 | “Instructions for Continued Airworthiness (ICA) on Electrical Wiring Interconnecting Systems (EWIS)” Affected requirement Part 21A.16(b)(3), 21A.21(c)(3), CS 25.1529 & Appendix H |

The following Special Conditions have been identified which are specific to the model 737-900ER:

| | |
|--------------|---|
| CRI 9ER/C-11 | Interaction of Systems and Structure Affected requirement JAR 25.302 |
|--------------|---|

5. Exemptions/Deviations:

The following Partial Deviation/Exemption has been applied:

| | |
|---------------------------------|--|
| JAA/737-700/PE/D-02 CRI D-02 | Hydraulic System Proof Pressure Testing Partial Deviation against JAR 25 1435(b)(1) |
|---------------------------------|--|

6. Equivalent Safety Findings:

The following Equivalent Safety Findings were identified as part of the JAA Validation of the models -700/-900 or 757-300 and have been requested by Boeing and agreed by EASA to be applicable for model -900ER:

| | |
|---------------------------------|--|
| CRI C-15/PTC | Structural Certification Criteria for Large Antenna Installations Equivalent Safety with JAR 25.23, 25.251, 25.301, 25.365, 25.571, 25.581, 25.603, 25.605, 25.609, 25.613, 25.629, 25.631, 25.841, 25.901, 25.1419, 25.1529, and Appendix H |
| JAA/737-700/ES/D-16 CRI D-16 | Automatic Overwing Exit (AOE) Equivalent Safety with JAR 25.783(f) |
| JAA/737-700/ES/D-17 CRI D-17 | Oversized Type I Exits, Maximum Number of Passengers up to 145/145/180 Equivalent Safety with JAR 25.807 |
| JAA/737-700/ES/D-18 | Slide/Raft Inflation Gas Cylinders CRI |



SECTION 7: 737-900ER Series – continued

| | |
|--|---|
| D-18 | Equivalent Safety with JAR 25X1436 |
| JAA/757-300/ES/D-19 CRI D-19 | Emergency Exit Markings JAR 25.811(f) |
| JAA/737-700/ES/E-09 CRI E-09 | Automatic Fuel Shut Off Equivalent Safety with JAR 25.979(b)(1) |
| JAR 25.1411(f) CRI E-11 | New Interior Arrangement with Passenger Service Unit Life Vest Stowage Equivalent Safety with JAR 25.1411(f) |
| JAA/737-700/ES/F-15 CRI F-15 | Wing Tip Position Lights Equivalent Safety with JAR 25.1389(b)(3) |
| JAR 25.1443(c) CRI F-GEN 9-1 | Minimum Mass Flow of Supplemental Oxygen “Component Qualification” Equivalent Safety with JAR 25.1443(c) |
| JAR 25.1441(c) CRI F-GEN9-3 | Crew Determination of Quantity of Oxygen in Passenger Oxygen System Equivalent Safety with JAR 25.1441(c) |
| CS 25.1529 CRI G-GEN1 | Instructions for Continued Airworthiness Equivalent Safety with CS 25.1529, CS25 Appendix H |
| JAA/737-900/ES/9/C-01 CRI 9/C-01 | Material Strength Properties and Design Values Equivalent Safety with JAR 25.613 |
| JAA/737/900/ES/9/C-04 CRI 9/C-04 | Control Systems Equivalent Safety with JAR 25.395(a) |
| JAA/737-900/ES/9/D-02 CRI 9/D-02 | Environmental Control Systems (Packs Off Take-Off) Equivalent Safety with JAR 25.831(a) |
| The following Equivalent Safety Findings have been agreed between Boeing and EASA specific to the model 737-900ER: | |
| JAR25.810(a)(1)(ii)ch 15 For JAR 25.809(f)(1)(ii) CRI 9ER/D-08 | Forward and Aft Door Escape Slide Low Sill Height Equivalent Safety with JAR 25.810(a)(1)(ii) |
| JAA/737-700/ES/D-16 CRI 9ER/D-16 | Automatic Overwing Exit Equivalent Safety with JAR 25.783(f) |
| JAR 25.963(g) CRI 9ER/C-20 | Fuel Tank Access Covers Equivalent Safety with JAR 25.963(g) |
| JAR 25.807(d) CRI 9ER/D-12 | Maximum Passenger Seating Configuration |
| JAR 25.813(a) CRI 9ER/D-20 | Over Sized Type II Exit Passageway Dimension Equivalent Safety with JAR 25.813(a) |
| JAR 25.811(f) | Door Sill Reflectance |



SECTION 7: 737-900ER Series – continued
CRI 9ER/D-21

JAR 25.795(a)(2)
CRI 9ER/D-22 Reinforced Cockpit Doors
Acceptance of FAA Memorandum
PS-ANM100-2001-115-11

JAR 25.791(a)
CRI 9ER/D-23 Passenger Information Signs and Placards Use of
Electrically Illuminated Signs in lieu of Placards

7. OSD requirements

- As defined in CRI A-MMEL issue 1: for B737-600/-700/-800/-900/-900ER, JAR-MMEL/MEL Amendment 1, Section 1, Subpart A & B is applicable.
- As defined in document D926A105: B737-600/-700/-800/-900/-900ER, CS-FCD, Initial Issue, dated 31 Jan 2014 is applicable
- As defined in CRI A-CCD issue 1: for B737-600/-700/-800/-900/-900ER, CS-CCD, Initial Issue dated 31 January 2014 is applicable.

8. Environmental Protection Standards: As for Boeing 737-700, see Section 3

III. Technical Characteristics and Operational Limitations

1. Production Basis: Manufactured under Production Certificate 700
2. Type Design Definition: Defined by Boeing Document 737-900ER Amended Type Design Configuration, DDL 737-900ER Rev B, and later approved changes
3. Description: Refer to Section 2 (data pertinent to all NG Series)
4. Dimensions: Length 42.1m (138 ft 2 in)
Span 34.32 m (112 ft 7 in)
Height 12.57 m (41 ft 3 in)

5. Engines:

| | | | | | |
|--------|---|---|---|---|---------------------------------|
| CFM56- | 7B24 7B24/3 7B24/3B1 7B24E 7B24E/B1 | 7B26 7B26/3 7B26/3F 7B26E 7B26E/F | 7B27 7B27/3 7B27/3F 7B27E 7B27E/F | 7B27/B1 7B27/3B1 7B27/3B1F 7B27E/B1 7B27E/B1F | 7B27/B3 7B27/3B3 7B27E/B3 |
|--------|---|---|---|---|---------------------------------|

6. Auxiliary Power Unit: Refer to Section 2 (data pertinent to all NG Series)
7. Propellers: N/A
8. Fluids (Fuel, Oil, Additives, :
Hydraulics) Refer to Section 2 (data pertinent to all NG Series)
9. Fluid Capacities: Refer to Section 2 (data pertinent to all NG Series)
10. Airspeed Limits: See Airplane Flight Manual



SECTION 7: 737-900ER Series – continued

11. Maximum Operating Altitude: 12,497 m (41,000 ft) pressure altitude

12. All Weather Capability: See Airplane Flight Manual

13. Maximum Certified Masses:

| | | |
|---------------|--------------|------------|
| Taxi and Ramp | 188,200 lbs. | 85,366 kg. |
| Take-off | 187,700 lbs. | 85,139 kg. |
| Landing | 157,300 lbs. | 71,350 kg. |
| Zero Fuel | 149,300 lbs. | 67,721 kg. |

14. Centre of Gravity Range: Refer to Airplane Flight Manual

15. Datum: See Weight and Balance Manual

16. Mean Aerodynamic Chord: 3.96 m (155.81 in)
(MAC)

17. Levelling Means: See Weight and Balance Manual

18. Minimum Flight Crew: Two (Pilot and Co-pilot) for all types of flight

19. Minimum Cabin Crew

The table below provides the certified Maximum Passenger Seating Capacities (MPS), the corresponding cabin configuration (exit arrangement and modifications) and the associated numbers of cabin crew members used to demonstrate compliance with the evacuation certification requirements of CS 25.803. Additional cabin crew members may be required to comply with other regulatory requirements (e.g., cabin attendant direct view).

| Passenger Seating Capacity & Cabin Configuration | Cabin crew |
|--|------------|
| From 216 to 220 passengers: (C, III, III, I, C) exit arrangement | 5 |
| From 201 to 215 passengers: (C, III, III, II, C) or (C, III, III, I, C) exit arrangement | 5 |
| From 190 to 200 passengers: (C, III, III, II, C) or (C, III, III, I, C) exit arrangement | 4 |
| From 151 to 189 passengers: (I, III, III, I), (C, III, III, II, C) or (C, III, III, I, C) exit arrangement | 4 |
| From 101 to 150 passengers: (I, III, III, I), (C, III, III, II, C) or (C, III, III, I, C) exit arrangement | 3 |
| 100 or fewer passengers: (I, III, III, I) exit arrangement | 2 |

20. Maximum Seating Capacity: (-) Passengers

Note: The maximum number of passengers approved for emergency evacuation is 220 (with Passenger Passageway acc. CRI 9ER/D-20), or otherwise: 215 (with downsized Passageway acc. CRI 9ER/D-20), or otherwise with blocked MED unserviceable: 189.

See interior layout drawing for the maximum passenger capacities approved for each aeroplane delivered.



SECTION 7: 737-900ER Series – continued

21. Exits:

| B737-900ER | Number | Type | Size mm (inches) |
|------------------------------|--------------------------|------------|-------------------------------|
| 1 Main Fwd LH | 1 | Type I | 864W ; 1829H (34 x 72), |
| 2 Main Aft LH | 1 | Type I | 762W ; 1829H (30 x 72), |
| 3 Service (Fwd, RH, Aft, RH) | 1+1 | Type I | 762W ; 1651H (30 x 65 – both) |
| 4 Overwing/Emergency left | 2 | Type III | 508W ; 914H (20 x 36) |
| 5 Overwing/Emergency right | 2 | Type III | 508W ; 914H (20 x 36) |
| 6 Mid Emergency Door LH/RH | 1+1 | Type I(II) | 660W ; 1295H (26 x 51) |
| 7 Cockpit side window (2) | Flight Crew Emerg. Exits | | 483W ; 508H x 2019 |

For crew emergency evacuation purposes, the side windows are available on both sides.

22. Baggage/Cargo Compartment:

| Location | Class | Volume m ³ (ft ³) |
|------------|-------|--|
| Front Fwd | C | 23.4 (825) |
| Middle | N/A | N/A |
| Rear Aft | C | 28.2 (996) |
| Underfloor | N/A | N/A |

23. Wheels and Tyres: Nose Assy (Qty 2) Tyre: 27 x 7.75 - 15 or 27 x 7.75 - R15
 Wheel: 27 x 7.75 – 15
 Main Assy (Qty 4) Tyre: H44.5 x 16.5 –
 21 Wheel: H44.5 x 16.5 – 21
 Speed Rating: 235 MPH refer to Section 2 (data pertinent to all NG Series)

24. ETOPS Operation: Refer to Section 2 (data pertinent to all NG Series)

25. Fuel Tank Flammability Reduction System (FRS):

Aircraft which have made their first flight after 1 January 2012 must be equipped with a fuel tank Flammability Reduction System (EASA SIB 2010-10)

Flammability Reduction Systems have been installed on aircraft line numbers 1820 and 1831 in December 2005, and then since mid 2008 on aircraft line number 2517, 2620 and on.

This system shall remain installed and operative and can only be dispatched inoperative in accordance with the provisions of the MMEL.

IV. Operating and Servicing Instructions

1. Flight Manual: Airplane Flight Manual, Document No. D631A001.J05 (04)
2. Service Information: Maintenance Manual, Document No. D633A101
 Maintenance Review Board Document D626A001-MRBR with MRBR Supplement for 737-900ER as EASA approved June 12, 2006



SECTION 7: 737-900ER Series – continued

Airworthiness Limitations and Certification Maintenance Requirements: 737-600/700/800/900 Maintenance Planning Document (MPD) Document Section 9 Ref.: D626A001, Revision (R2) dated March 2007, and later revisions

Service Letters and Service Bulletins.

3. Required Equipment: The approved equipment is listed in: (737-700) CRI A-10
4. Universal Airplane Network Security Operator Guidance (UANSOG)

The Boeing Commercial Airplanes Universal Airplane Network Security Operator Guidance, D925W704-04, contains required Instructions for Continued Airworthiness and security guidance that when followed meets compliance requirements of the Network Cybersecurity Special Conditions.

V.Operational Suitability Data (OSD)

The Operational Suitability Data elements listed below are approved by the European Union Aviation Safety Agency under the EASA Type Certificate IM.A.120 as per Commission Regulation (EU) 748/2012 as amended by Commission Regulation (EU) No 69/2014. Applicable OSD requirements are detailed in section 7.II.7.

1. Master Minimum Equipment List
(see section 2.V)
2. Flight Crew Data
(see section 2.V)
3. Cabin Crew Data
(see section 2.V)

VI. Notes

1. Airplanes modified by Boeing design change “Lower Cabin Altitude” are capable of maintaining a cabin altitude of 6500 feet in lieu of the standard 8000 feet when operating at a cruising altitude of 41,000 feet. This modification has been approved by EASA STC 10042295.



SECTION 8: 737-8, 737-9, 737-8200

I.General

1. Type/ Model/ Variant: Boeing 737-8, -9, -8200 "MAX"
2. Performance Class A
3. Certifying Authority Federal Aviation Administration (FAA)
BASOO Branch
2200 S 216th St
Des Moines, WA 98198
United States of America
4. Manufacturer The Boeing Company
P.O. Box 3707
Seattle, WA 98124-2207
United States of America
5. FAA Type Certification Application Date:

| Model | FAA Type Certification Application Date |
|----------|---|
| 737-8 | January 26, 2012 |
| 737-9 | June 12, 2013 |
| 737-8200 | September 28, 2015 |

6. EASA Type Validation Application Date:

| Model | EASA Type Validation Application Date |
|----------|---------------------------------------|
| 737-8 | June 27, 2012 |
| 737-9 | June 12, 2013 |
| 737-8200 | October 22, 2015 |

7. FAA Type Certificate Date:

| Model | FAA Type Certificate Date |
|----------|---------------------------|
| 737-8 | March 8, 2017 |
| 737-9 | February 15, 2018 |
| 737-8200 | March 31, 2021 |

8. EASA Type Validation Date:

| Model | EASA Type Validation Date |
|----------|---------------------------|
| 737-8 | March 27, 2017 |
| 737-9 | Oct. 17 2018 |
| 737-8200 | April 06, 2021 |



SECTION 8: 737-8/-9/-8200 - continued

II. Certification Basis

1. Reference Date for Determining the Applicable Airworthiness Requirements:

| Model | Reference Date for Determining the Applicable Airworthiness Requirements |
|----------|--|
| 737-8 | June 30, 2012 |
| 737-9 | June 12, 2013 |
| 737-8200 | April 17, 2016 |

2. Reference Date for Determining the Applicable Operational Suitability Requirements:

| Model | Reference Date for Determining the Applicable Operational Suitability Requirements |
|----------|--|
| 737-8 | June 30, 2012 |
| 737-9 | June 12, 2013 |
| 737-8200 | April 17, 2016 |

3. FAA Type Certification Data Sheet: No. A16WE

4. FAA Certification Basis

| Model | FAA Certification Basis |
|----------|---|
| 737-8 | 14 CFR Part 25 Amendment 25-0 through 25-137 plus 25-141 except where modified by the FAA Issue Paper G-1 |
| 737-9 | Same as 737-8 |
| 737-8200 | 14 CFR Part 25 Amendment 25-0 through 25-141 except where modified by the FAA Issue Paper G-1 |

5. EASA Airworthiness Requirements:

| Model | EASA Airworthiness Requirements |
|----------|---|
| 737-8 | Applicable JAR/CS Requirements (Reference CRI A-01)* CS-25 Amendment 11, effective July 4, 2011 with exceptions identified in <u>Table A</u> in Appendix A CS-AWO, effective October 17, 2003 |
| 737-9 | Applicable JAR/CS Requirements (Reference CRI A-01)* CS-25 Amendment 12, effective July 13, 2012 with exceptions identified in <u>Table A</u> in Appendix A. CS-AWO, effective October 17, 2003 |
| 737-8200 | Applicable JAR/CS Requirements (Reference CRI A-01)* CS-25 Amendment 17, effective July 15, 2015 with exceptions identified in <u>Table A</u> in Appendix A CS-AWO, effective October 17, 2003 |



SECTION 8: 737-8/-9/-8200 - continued
5.1 Special Conditions

The following Special Conditions have been defined in their respective CRI for 737-8/-9/-8200:

| CRI – Special Condition | Title/ Applicable requirement | -8 | -9 | -8200 |
|-------------------------------------|---|----|----|-------|
| CRI C-02/MAX | Design Manoeuvre Requirements Affected requirement 25.331, 25.349, 25.351 | X | X | X |
| CRI D-04/MAX | Towbarless Towing Affected requirement 25.745(d), 25.1309, 25.1322 | X | X | X |
| CRI D-15/MAX | Emergency Exits Configuration Affected requirement 25.807, 25.562, 25.813 | X | X | X |
| CRI D-27/MAX | Installation of Inflatable Restraint Systems Affected requirement 25.562, 25.785 | X | X | X |
| CRI D-GEN02 PTC | Application of Heat Release and Smoke Density Requirements to Seat Materials Affected Requirement 25.853(d) Appendix F | X | X | X |
| CRI D-GEN 9 | Incorporation of Inertia Locking Device in Dynamic Seats | X | X | X |
| CRI E-05/MAX | Engine Cowl Retention Affected Requirement 25.901(b)(2), 25.901(c), 25.1193(f)(3) | X | X | X |
| CRI E-27/MAX | Fan blade loss, effects at airplane level Affected Requirement 25.901(c), 25.903(d)(1), 25.1309(b) | X | X | X |
| CRI E-32/MAX | Fire Extinguishing Plumbing and Wiring Connections Affected Requirement 25.901, 25.903, 25.1195 | X | X | X |
| CRI PTC F-01 JAA/737-700/SC/F-01 | High Intensity Radiated Fields (HIRF) Affected requirement JAR 25.1431(a) | X | X | X |
| CRI PTC F-03 JAA/737-700/SC/F-03 | Protection from the Effects of Lightning Strike; Indirect Effects Affected requirement 25.581, 25X899, 25.954, 25.1309, 25.1316 Note: 25.1316 is affected but the CRI does not list this regulation. | X | X | X |
| CRI F-03/MAX | HIRF Protection INT POL 25/2 Issue 2: Affected requirement CS 25 | X | X | |
| CRI F-11/MAX | Airworthiness standard for aircraft operations under falling and blowing snow Affected requirement 25.1093(b), 25J1093(b) | X | X | X |
| CRI F-GEN-11 | Non-Rechargeable Lithium Batteries Installations Affected requirement 25.601, 25.863, 25.1353(c) | X | X | X |



SECTION 8: 737-8/-9/-8200 - continued

| CRI – Special Condition | Title/ Applicable requirement | -8 | -9 | -8200 |
|-------------------------|--|----|----|-------|
| CRI PTC F-17 | EGPWS Airworthiness Approval Affected requirement 25.1301, 25.1309, 25.1322, 25.1431(a)(c), 25.1459, AMJ 25-11, AMJ 25.1309, AMJ 25.1322 | X | X | X |
| CRI PTC F-27 | Global Navigation Satellite System (GNSS) Landing System (GLS) - Airworthiness Approval for Category I Approach Operations Affected requirement 25.1301, 25.1309, 25.1322, 25.1329, 25.1431, 25.1459, 25.1581, JAR-AWO, JAR-AWO NPA AWO-9 | X | X | X |
| CRI PTC F-29 | Lithium – Ion batteries Affected requirement 25.601, 25.863, 25.1309, 25.1353(c), and 25.1529 | X | X | X |
| CRI PTC F-30 | Data Link Services for the Single European Sky Affected requirements: CS 25.1301, 25.1307, 25.1309, 25.1321, 25.1322, 25.1431, 25.1459, 25.1581, 25.1585, or equivalent of CS 23, Commission Regulation (EC) No 29/2009 | X | X | X |
| CRI PTC F-31 | Security Protection of Aircraft Systems and Networks Affected requirement 25.1309 | X | X | X |
| CRI PTC F-37 | Flight Recorders and Data Link Recording Affected requirement 25.1301, 25.1457, 25.1459 | X | X | X |

5.2 Deviations:

The following EASA deviations have been applied for 737-8/-9/-8200:

| CRI - Deviation | Title/ Affected Requirement | -8 | -9 | -8200 |
|-----------------|--|----|----|-------|
| CRI E-30/MAX | Time Limited Deviation to Special Condition CRI E-05/MAX (Engine cowl retention) Affected requirement: 737-7/-8/-9 CRI E-05/MAX, 25.901(b)(2), 25.901(c), 25.1193 | X | X | |
| CRI E-31/MAX | Fuel Quantity Indication System (FQIS) Electrostatics Threat Affected requirement: 25.899, 25.901(c), 25.981(a)(3), and 25.1309(b)(1) | X | X | |
| CRI E-36/MAX | Right Main Fuel Tank Indication of Refuel System Failure at Full Fuel Tank Level Affected requirement: 25.979(b)(2) | | X | X |

Notes:

CRI E-30/MAX is a time limited Deviation. EASA has accepted to delay to June 30,2022 the initial limit in this deviation, therefore individual Certificates of Airworthiness for 737-8/-9 airplanes become



SECTION 8: 737-8/-9/-8200 - continued

invalid after June 30, 2022, unless the Boeing Service Bulletin 737-71-1894 revision 1 or later revision is incorporated by the owner or operator.

CRI E-31/MAX is a line number limited Deviation only for the first (36) 737MAX models for the -8/-9 only. It is not needed for the 737-8200 those models all have resistors.

CRI E-36/MAX is a line number limited Deviation. This line number limited deviation is for 737-9 and 737-8200 airplanes delivered to EASA customers before line number 7650. Line number 7650 estimated delivery is late June or early July 2019. This deviation is also time limited: The 737-9 and 737-8200 airplanes delivered to EASA customers before line number 7650 cannot be operated after October 05th 2022 (4 years after EASA certification), unless the appropriate design changes are incorporated by the owner or operator.

5.3 Equivalent Safety Findings:

The following JAA/EASA Equivalent Safety Findings have been applied:

| CRI - ESF | Title/ Equivalent Safety Requirement | -8 | -9 | -8200 |
|--------------------------------------|--|----|----|-------|
| CRI B-05/MAX | Longitudinal Trim at Vmo Equivalent Safety with 25.161(a), 25.161(c)(3), 25.1301 | x | x | x |
| CRI B-06/MAX | En route Climb Equivalent Safety with CS 25.123(a) and (b) | x | x | x |
| CRI D-08 JAA/737-700/ES/D-08 | Forward and Aft Door Escape Slide Low Sill Height Equivalent Safety with 25.810(a)(1)(ii) | x | | |
| CRI 9ER/D-08 | Forward and Aft Door Escape Slide Low Sill Height Equivalent Safety with 25.810(a)(1)(ii) | | x | x |
| CRI D-16/NG JAA/737-700/ES/D-16 | Automatic Overwing Exit Equivalent Safety with 27.783(f) | x | x | x |
| CRI 9ER/D-16 | Fuselage Doors Equivalent Safety with 25.783 | | x | x |
| CRI D-17/NG JAA/737-700/ES/D-17 | Oversized Type I Exits, Maximum Number of Passengers Equivalent Safety with 25.807 | x | x | x |
| CRI D-17/MAX | Packs off operation Equivalent Safety with 25.831(a)(b)(c)(d), 25.855(h)(2), 25.857(c)(1)(3), 25.858(d), 25.1309(b)(1), 25.1322 | x | x | x |
| CRI D-18/NG JAA/737-700/ES/D-18 | Slide/Raft Inflation Gas Cylinders Equivalent Safety with 25.1436 | x | x | x |
| CRI D-18/MAX | Wing Flap Lever Position Equivalent Safety with 25.777(e) | x | x | x |
| CRI PTC/ D-19 JAA/757-300/ES/D-19 | Emergency Exit Marking Equivalent Safety with 25.811(f) | x | x | x |
| CRI 9ER/D-20 | Over Sized Type II Exit Passageway Dimension Equivalent Safety with 25.813(a) | | x | x |
| CRI 9ER/ D-21 | Door Sill Reflectance Equivalent Safety with 25.811(f) | x | x | x |



SECTION 8: 737-8/-9/-8200 - continued

| CRI - ESF | Title/ Equivalent Safety Requirement | -8 | -9 | -8200 |
|--------------------------------------|--|-----------|-----------|--------------|
| CRI PTC/ D-23 JAA/737-700/ES/D-23 | Passenger Information Signs Equivalent Safety with 25.791(a) | X | X | X |
| CRI D-28/MAX | Increased Number of Passenger Seats with an Optional Pair of Mid-Cabin Type III Exits Door | | X | X |
| CRI D-31/MAX | Seat Cushion Protrusion into the Clear Opening of Type III Overwing Exits | | | X |
| CRI D-GEN7 | Flammability Testing Hierarchy Equivalent Safety with 25.853(a) | X | X | X |
| CRI E-09 JAA/737-700/ES/E-09 | Automatic Fuel Shut Off Equivalent Safety with 25.979(b)(1) | X | X | X |
| CRI E-10/MAX | Strut and Aft Strut Fairing Compartments Equivalent Safety with 25.1183(a) (as invoked by 25.1182(a)) | X | X | X |
| CRI E-11 | New Interior Arrangement with Passenger Service Unit Life Vest Stowage Equivalent Safety with 25.1411(b)(1) | X | X | X |
| CRI E-12/MAX | Thrust Reverser Testing Equivalent Safety with 25.934 | X | X | X |
| CRI E-20/MAX | LEAP_1B Fuel Filter Location Equivalent Safety with 25.997(d), 25.1305(c)(6) | X | X | X |
| CRI E-22/MAX | LEAP-1B areas adjacent to Designated Fire Zone (CS- 25.1182) Equivalent Safety with 25.1103, 25.1165, 25.1183, 25.1185, 25.1187, 25.1189, 25.1195, 25.1197, 25.1199, 25.1201, 25.1203 (as invoked by 25.1182(a)) | X | X | X |
| CRI E-24/MAX | Wing Leading Edge Slats Equivalent Safety with 25.867(a) | X | X | X |
| CRI E-28/MAX | Fire Testing of Firewall Sealants Equivalent Safety with 25.1191 | X | X | X |
| CRI E-29/MAX | Fueling Float Switch Installation Equivalent Safety with 25.901(c), 25.981(a)(3), 25.981(d), 25.1309(b)(1) | X | X | X |
| CRI E-33/MAX | Fuel Tank Ignition Prevention - Hot Surface Ignition Temperature Equivalent Safety with 25.1103, 25.863, 25.901, 25.981(d) | X | X | X |
| CRI F-07/MAX | Green Arc for Powerplant Instrument Equivalent Safety with 25.1549(b) | X | X | X |
| CRI F-15/NG JAA/737-700/ES/F-15 | Wingtip Position Lights Equivalent Safety with 25.1389(b)(3) | X | X | X |
| CRI F-17/MAX | Leading Edge Flaps Transit - Flight Crew Indication Equivalent Safety with 25.1322(a)(1)(i) | X | X | X |
| CRI F-GEN 9-1 | Minimum Mass Flow of Supplemental Oxygen "Component Qualification" Equivalent Safety with 25.1443(c) | X | X | X |



SECTION 8: 737-8/-9/-8200 - continued

| CRI - ESF | Title/ Equivalent Safety Requirement | -8 | -9 | -8200 |
|------------------|--|-----------|-----------|--------------|
| CRI F-GEN9-3 | Crew Determination of Quantity of Oxygen in Passenger Oxygen System Equivalent Safety with 25.1441(c) | X | X | X |
| CRI G-GEN1 | Instructions for Continued Airworthiness Equivalent Safety with 25.1529, 25.1729, 25 Appendix H | X | X | X |
| CRI J-03/MAX | APU Engine Mount Equivalent Safety with 25.865 | X | X | X |
| CRI F-40 PTC | First Aid Portable Pulse Oxygen System Equivalent Safety with 25.1443(d) | X | X | X |



SECTION 8: 737-8/-9/-8200 - continued

5.4 Reversions

All reversions from the applicable airworthiness standards to earlier standard, as per Part 21.101(b), are listed in the Table A of appendix A.

The following reversions from the applicable airworthiness standards contain additional requirements that can be found in the associated CRI.

| Applicable paragraph | Title/ Reversion | Conditions associated to the reversions are given in the following CRIs | -8 | -9 | -8200 |
|--|--|---|----|----|-------|
| 25.562 | Emergency Landing Dynamic Loads (Partly reversion to JAR 25 Change 12 excluding 25.562. Partly NPA 25C,D, F-314 except for (c)(5) and (c)(6)) | CRI A.11-04 | X | | |
| 25.562 | Emergency Landing Dynamic Loads (Partly reversion to JAR 25 Change 12 excluding 25.562. Partly NPA 25C,D, F-314 except for (c)(5) and (c)(6)) | CRI 9ER/A.11-04 | | X | |
| 25.607(a) | Fasteners Reversion to FAR 25.607(a) Amendment 0 | CRI A. 11-06 | X | X | X |
| 25.783(f) | Doors Reversion to FAR 25.783 Amendment 15 | CRI A. 11-11 | X | X | X |
| 25.785(h)(1), (h)(2) | Direct View and Cabin Attendant Seat Reversion to FAR 25.785 Amendment 32 | CRI A.11-13 | X | X | X |
| 25.1309 | Equipment, Systems and Installations Reversion to FAR 25.1309 Amendment 0 | CRI A. 11-16 | X | X | X |
| 25.775(d) | Windshields and Windows Reversion to FAR 25.775(d) Amendment 0 | CRI A.11-23 | X | X | X |
| 25.21(g)(1), 25.125(b)(2)(ii)(B), 25.143(j), 25.207(e), 25.253(c), and Appendix C | Flight in Icing Conditions Reversion to CS 25.21(g)(1), 25.125(b)(2)(ii)(B), 25.143(j), 25.207(e), 25.253(c), and Appendix C Amendment 2 | B-07/MAX | X | X | X |
| 25.365(e)(1) | Pressurised Compartment loads, Engine disintegration fragments Reversion to FAR 25.365 Amendment 0 | C-03/MAX | X | X | X |



SECTION 8: 737-8/-9/-8200 - continued

| Applicable paragraph | Title/ Reversion | Conditions associated to the reversions are given in the following CRIs | -8 | -9 | -8200 |
|----------------------|---|---|----|----|-------|
| 25.1322 | Flight Crew Alerting Reversion to JAR 25,1322(b) at Amendment 13 | F-14/MAX | X | X | X |
| 25J1141(b)(2), | APU Fuel Shut-Off Valve Indication Reversion to B737-800 CRI J-04, Reversion to FAR 25.1141 Amendment 11 | J-01/MAX | X | X | X |

Note: The Boeing Model 737-8/-9/-8200 was granted an exception per Part 21.101(b) for CS 25.795(c)(2) based on the demonstration and justification that security features were present in the type design. These security features must be in consideration in any subsequent type design change, modification, or repair, to ensure that the level of safety designed into the 737-8/-9/-8200 is maintained. In lieu of the following, compliance to CS 25.795(c)(2), at amendment 11 (737-8), amendment 12 (737-9), and amendment 17 (737-8200) may be shown:

'Modifications that reduce flight critical system separation or adversely impact survivability of systems are not acceptable.'

6. Environmental Protection Requirements:

Noise: ICAO Annex 16, Volume I (Sixth Edition, Amendment 10 for 737-8/-9, Amendment 11-B for 737-8200)

Fuel Venting: ICAO Annex 16, Volume II (Fourth Edition, Amendment 9)

See also TCDSN EASA.IM.A.120

7. Operational Suitability Requirements:

CS-MMEL Initial Issue January 31, 2014
CS-CCD Initial Issue January 31, 2014
CS-FCD Initial Issue January 31, 2014



SECTION 8: 737-8/-9/-8200 - continued

III. Technical Characteristics and Operational Limitations

1. Type Design Definition:

| Model | Boeing Document |
|----------|-----------------|
| 737-8 | D926A006 |
| 737-9 | D926A010 |
| 737-8200 | D926A020-2 |

2. Description:

Low wing jet transport with a conventional tail unit configuration, powered by two high bypass turbofan engines mounted on pylons beneath the wings.

3. Equipment:

The basic required equipment as prescribed in the applicable airworthiness regulations (see Certification Basis) must be installed in the aircraft for certification.

4. Dimensions:

| Model | Fuselage Length | Height | Wingspan with Winglets |
|----------|-----------------------|----------------------|------------------------|
| 737-8 | 39.5 m (129 ft 6 in) | 12.29 m (40 ft 4 in) | 35.92 m (117 ft 10 in) |
| 737-9 | 42.11 m (138 ft 2 in) | 12.29 m (40 ft 4 in) | 35.92 m (117 ft 10 in) |
| 737-8200 | 39.5 m (129 ft 6 in) | 12.29 m (40 ft 4 in) | 35.92 m (117 ft 10 in) |

5. Engines:

Two CFM LEAP-1B Series Engines. Refer to the approved Airplane Flight Manual for engine limitations.

Engine ratings, engine limitations, and all approved models are referred to in: EASA TCDS E.115 "CFM International LEAP-1B Series Engines"

| Engine Configurations | Models | | |
|-----------------------|--------|-------|----------|
| | 737-8 | 737-9 | 737-8200 |
| LEAP-1B25 | X | | X |
| LEAP-1B27 | X | X | X |
| LEAP-1B28 | X | X | X |
| LEAP-1B28B1 | X | X | X |
| LEAP-1B28BBJ1 | X | X | |

6. Auxiliary Power Unit:

Auxiliary Power Unit (APU): Honeywell 131-9 [B]
Limitations: See approved Airplane Flight Manual

7. Propellers: N/A



SECTION 8: 737-8/-9/-8200 - continued

8. Fluids (Fuel, Oil, Additives, Hydraulics):

Eligible Fuels:

Kerosene jet fuels conforming to the Boeing document D6-85140-101, revision C or later FAA approved revision, "Aviation Fuel and Fuel Additives Properties, Composition and Performance Requirements", are authorized for unlimited use with this airplane provided the limitations and requirements specified in the AFM are met. Kerosene jet fuels produced to other specifications and having properties meeting or exceeding the minimum requirements defined in the Boeing document D6-85140-101, revision C or later FAA approved revision, are acceptable for use. The engines will operate satisfactorily with any of the approved fuels or any mixture thereof. Kerosene jet fuels specifications that have been shown to meet the fuel minimum performance and specification requirements as described in the Boeing document D6-85140-101, revision C or later FAA approved revision, are the following:

- Jet A, Jet A-1 as specified in ASTM D1655
- Jet A-1 as specified in UK MoD Def-Stan 91-091
- JP-5 as specified in MIL-DTL-5624
- JP-8 as specified in MIL-DTL-83133

The above list is not exhaustive: other fuel specification/designation (e.g. GOST 10227 [TS-1], GB 6537 [Chinese No. 3 Jet Fuel], etc.) may be used provided the Boeing document D6-85140-101, revision C or later FAA approved revision, requirements are met.

Fuel specifications are often changed and updated. It is the responsibility of the operator to ensure the fuel and any additive that are put in the fuel meet the requirements specified in the Boeing document D6-85140-101, revision C or later FAA approved revision, and the AFM.

The approved fuel additives at the allowable maximum concentrations are listed in the Boeing document D6-85140-101, revision C or later FAA approved revision. A list of tolerated "incidental materials" and respective maximum concentrations allowed is also provided in the same Boeing document D6-85140-101, revision C or later FAA approved revision.

Operation of the CFM LEAP-1B series engines with fuel containing Kathon FP1.5 biocide is prohibited.

The use of any Wide Cut Fuel as defined in the Boeing document D6-85140-101, revision C or later FAA approved revision (e.g. Jet B as specified in ASTM D6615, JP-4 as specified in MIL-DTL-5624) is prohibited.

The maximum tank fuel temperature should not exceed 49°C (120°F).

Tank fuel temperature prior to take-off and inflight must not be less than -43°C (-45°F) or 3°C (5°F) above the fuel freezing point temperature, whichever is higher. The use of Fuel System Icing Inhibitor additives does not change the minimum fuel tank temperature limit.

Eligible Oils: Refer to the applicable associated manuals.

9. Fluid Capacities

Fuel Capacity:

25817 litres (6820 gallons), consisting of two wing tanks, each of 4819 litres (1273 gallons) capacity, and one center tank, capacity 16179 litres (4274 gallons).

Oil Capacity: 19.25 litres useable



SECTION 8: 737-8/-9/-8200 - continued

10. Airspeed Limits: See Airplane Flight Manual.

11. Maximum Operating Altitude: 12,497 m (41,000 ft) pressure altitude

12. Operating Limitations: See Airplane Flight Manual.

12.1 Approved Operations:

The airplane is approved for the following kinds of flight and operation, both day and night, provided the required equipment is installed and approved in accordance with the applicable regulations/specifications:

- Visual (VFR)
- Instrument (IFR)
- Icing Conditions
- Low weather minima (CAT I, II, III operations)
- RVSM
- Gear down dispatch
- Towbarless Towing
- Wet and Contaminated runway operations
- Extended Over-Water
- Narrow Runway

All Weather Capability

The aircraft is qualified to Cat III precision approach and autoland.

12.2 Other Limitations:

Operational Limits

Runway slope – ±3%

Maximum Takeoff and Landing Tailwind Component – 15 knots*

Maximum Operating Altitude – 41,000 feet pressure altitude

10 Minute Takeoff Thrust

* The capability of the airplane has been satisfactorily demonstrated for takeoff and manual and automatic landings with tailwinds up to 15 knots. This finding does not constitute operational approval to conduct take-offs and landings with tailwind components in excess of 10 knots.

13. Maximum Certified Masses: See Airplane Flight Manual.

| Model | Maximum Taxi and Ramp Weight | | Maximum Take-off Weight | | Maximum Landing Weight | | Zero Fuel Weight | |
|----------|------------------------------|--------|-------------------------|--------|------------------------|--------|------------------|--------|
| | lbs. | kg. | lbs. | kg. | lbs. | kg. | lbs. | kg. |
| 737-8 | 182,700 | 82,871 | 182,200 | 82,645 | 152,800 | 69,308 | 145,400 | 65,952 |
| 737-9 | 195,200 | 88,541 | 194,700 | 88,314 | 163,900 | 74,343 | 156,500 | 70,987 |
| 737-8200 | 181,700 | 82,417 | 181,200 | 82,190 | 152,800 | 69,308 | 145,400 | 65,952 |

14. Centre of Gravity Range: See Airplane Flight Manual

15. Datum: See Weights and Balance Manual

16. Mean Aerodynamic Chord (MAC): 3.96m (155.81 in)

17. Levelling Means: See Airplane Flight Manual



SECTION 8: 737-8/-9/-8200 - continued

18. Minimum Flight Crew: Two (Pilot and Co-pilot) for all types of flight

19. Minimum Cabin Crew:

The table below provides the certified Maximum Passenger Seating Capacities (MPS), the corresponding cabin configuration (exit arrangement and modifications) and the associated numbers of cabin crew members used to demonstrate compliance with the evacuation certification requirements of CS 25.803. Additional cabin crew members may be required to comply with other regulatory requirements (e.g., cabin attendant direct view).

| 737-8 Passenger Seating Capacity & Cabin Configuration | Cabin crew |
|---|-------------------|
| From 151 to 189 passengers: (I, III, III, I) exit arrangement | 4 |
| From 101 to 150 passengers: (I, III, III, I) exit arrangement | 3 |
| 100 or fewer passengers: (I, III, III, I) exit arrangement | 2 |

| 737-9 Passenger Seating Capacity & Cabin Configuration | Cabin crew |
|--|-------------------|
| From 216 to 220 passengers: (C, III, III, I, C) exit arrangement | 5 |
| From 201 to 215 passengers: (C, III, III, II, C) exit arrangement | 5 |
| From 151 to 200 passengers: (C, III, III, I, C) or (C, III, III, II, C) exit arrangement | 4 |
| From 151 to 189 passengers: (I, III, III, I) exit arrangement | 4 |
| 150 or fewer passengers: (C, III, III, I, C) or (C, III, III, II, C) exit arrangement | 3 |
| From 101 to 150 passengers: (I, III, III, I) exit arrangement | 3 |
| 100 or fewer passengers: (I, III, III, I) exit arrangement | 2 |

| 737-8200 Passenger Seating Capacity & Cabin Configuration | Cabin crew |
|---|-------------------|
| From 201 to 202 passengers: (C,III,III,II, C) exit arrangement | 5 |
| From 201 to 202 passengers: (C,III,III,III (de-rated Type II), C) attended MED exit arrangement | 5 |
| From 190 to 200 passengers: (C,III,III,III (de-rated Type II), C) attended MED exit arrangement | 4 |
| From 151 to 189 passengers: (I, III, III, I) exit arrangement | 4 |
| From 101 to 150 passengers: (I, III, III, I) exit arrangement | 3 |
| 100 or fewer passengers: (I, III, III, I) exit arrangement | 2 |

Note:

737-8200 only: The total number of passengers and cabin crew member is limited to 207 due to the Environmental Control System ventilation rate per occupant as defined in CS 25.831(a).

20. Maximum Seating Capacity:

| Model | Maximum Number of Passengers Approved for Emergency Evacuation |
|--------------|--|
| 737-8 | 189 passengers with special condition CRI D-15/MAX and NG ESF CRI D-17 applied, otherwise 180 passengers |



SECTION 8: 737-8/-9/-8200 - continued

| | |
|----------|---|
| 737-9 | 220 passengers with (C-III-III-I-C) exit arrangement; 215 passengers with a (C-III-III-II-C) exit arrangement and CRI 9ER/D-20 applied; 189 passengers with a (I-III-III-I) exit arrangement and special condition CRI D-15/MAX and NG ESF CRI D-17 applied, otherwise 180 passengers. |
| 737-8200 | 189 passengers with a (I-III-III-I) exit arrangement and special condition CRI D-15/MAX and NG ESF CRI D-17 applied, otherwise 180 passengers. 202 passengers with a (C-III-III-derated II (III)-C) exit arrangement with flight attendant, and CRI D-28/MAX applied; 202 passengers with a (C-III-III-II-C) exit arrangement and CRI 9ER/D-20 applied; |

Notes:

See interior layout drawing for the maximum passenger capacities approved for each aeroplane delivered.

737-8200 only: The total number of passengers and cabin crew member is limited to 207 due to the Environmental Control System ventilation rate per occupant as defined in CS 25.831(a).

21. Baggage/ Cargo Compartment:

| 737-8 | | |
|------------|-------|--|
| Location | Class | Volume m ³ (ft ³) |
| Front Fwd | C | 19.0 (672) |
| Middle | N/A | N/A |
| Rear Aft | C | 24.6 (869) |
| Underfloor | N/A | N/A |

| 737-9 | | |
|------------|-------|--|
| Location | Class | Volume m ³ (ft ³) |
| Front Fwd | C | 23.2 (818) |
| Middle | N/A | N/A |
| Rear Aft | C | 28.2 (996) |
| Underfloor | N/A | N/A |

| 737-8200 | | |
|------------|-------|--|
| Location | Class | Volume m ³ (ft ³) |
| Front Fwd | C | 19.0 (672) |
| Middle | N/A | N/A |
| Rear Aft | C | 24.6 (869) |
| Underfloor | N/A | N/A |

22. Wheels and Tyres:

Speed Rating: 225 MPH, 235 MPH

| Model | Speed Rating | Nose Assy (Qty 2) Tyre | Wheel | Main Assy (Qty 4) Tyre | Wheel |
|-------|--------------|------------------------|-------|------------------------|-------|
| | | | | | |



SECTION 8: 737-8/-9/-8200 - continued

| | | | | | |
|----------|---------------------|----------------------|----------------|--------------------|-----------------------|
| 737-8 | 225 MPH, 235 MPH | 27 x 7.75R15/12PR | 27 x 7.75 – 15 | H44.5x16.5R21/30PR | HR44.5 x 16.5 – 21 |
| 737-9 | 225 MPH, 235 MPH | 27 x 7.75R15/12PR | 27 x 7.75 – 15 | H44.5x16.5R21/32PR | HR44.5 x 16.5 – 21 |
| 737-8200 | 225 MPH, 235 MPH | 27 x 7.75R15/12PR | 27 x 7.75 – 15 | H44.5x16.5R21/30PR | HR44.5 x 16.5 – 21 |

Refer to Boeing Wheel/Tire/Brake Interchangeability Drawing for further details

23. ETOPS:

The 737-8 and 737-9 have been evaluated in accordance with the type design requirements of CS 25.1535 and found suitable for up to and including 180-minute Extended Operations (ETOPS) when operated and maintained in accordance with Boeing Document No. D044A032, "Model 737 MAX ETOPS Configuration, Maintenance, and Procedures (CMP)". This finding does not constitute approval to conduct ETOPS.

24. Exits:

| B737-8 | Number | Type | Size mm (inches) |
|------------------------------|--------------------------|-------------|------------------------------|
| 1 Main Fwd LH | 1 | Type I | 864W x 1829H (34 x 72) |
| 2 Main Aft LH | 1 | Type I | 762W x 1829H (30 x 72) |
| 3 Service (Fwd, RH, Aft, RH) | 1+1 | Type I | 762W x 1651H (30 x 65, both) |
| 4 Overwing/Emergency left | 2 | Type III | 508W x 914H (20 x 36) |
| 5 Overwing/Emergency right | 2 | Type III | 508W x 914H (20 x 36) |
| 6 Cockpit side window (2) | Flight Crew Emerg. Exits | | 483W x 508H (19 x 20) |

| B737-9 | Number | Type | Size mm (inches) |
|------------------------------|--------------------------|-------------|------------------------------|
| 1 Main Fwd LH | 1 | Type I (C) | 864W x 1829H (34 x 72) |
| 2 Main Aft LH | 1 | Type I (C) | 762W x 1829H (30 x 72) |
| 3 Service (Fwd, RH, Aft, RH) | 1+1 | Type I (C) | 762W x 1651H (30 x 65, both) |
| 4 Overwing/Emergency left | 2 | Type III | 508W x 914H (20 x 36) |
| 5 Overwing/Emergency right | 2 | Type III | 508W x 914H (20 x 36) |
| 6 Mid Emergency Door LH/RH | 1+1 | Type I (II) | 660W x 1295H (26 x 51) |
| 7 Cockpit side window (2) | Flight Crew Emerg. Exits | | 483W x 508H (19 x 20) |

| B737-8200 | Number | Type | Size mm (inches) |
|------------------------------|---------------|------------------------|------------------------------|
| 1 Main Fwd LH | 1 | Type I (C) | 864W x 1829H (34 x 72) |
| 2 Main Aft LH | 1 | Type I (C) | 762W x 1829H (30 x 72) |
| 3 Service (Fwd, RH, Aft, RH) | 1+1 | Type I (C) | 762W x 1651H (30 x 65, both) |
| 4 Overwing/Emergency left | 2 | Type III | 508W x 914H (20 x 36) |
| 5 Overwing/Emergency right | 2 | Type III | 508W x 914H (20 x 36) |
| 6 Mid Emergency Door LH/RH | 1+1 | Type II | 660W x 1321H (26 x 52) |
| 7 Mid Emergency Door LH/RH | 1+1 | Type III (de-rated) | 660W x 1321H (26 x 52) |



SECTION 8: 737-8/-9/-8200 - continued

| | | |
|---------------------------|--------------------------|-----------------------|
| | Type II) | |
| 8 Cockpit side window (2) | Flight Crew Emerg. Exits | 483W x 508H (19 x 20) |

For crew emergency evacuation purposes, the side windows are available on both sides.

25. Fuel Tank Flammability Reduction System (FRS):

The Fuel Tank Flammability Reduction System shall remain installed and operative and can only be dispatched inoperative in accordance with the provisions of the MMEL.

IV. Operating and Service Instructions

1. Airplane Flight Manual (AFM): Boeing Document D631A002

2. Instructions for Continued Airworthiness and Airworthiness Limitations:

| Boeing Document | Title |
|-----------------|---|
| D626A009 | 737-7/8/8200/9/10 Maintenance Review Board (MRB) Report |
| D626A011-9-01 | 737-7/8/8200/9/10 Airworthiness Limitations |
| D626A011-9-02 | 737-7/8/8200/9/10 Airworthiness Limitations – Line No. Specific |
| D626A011-9-03 | 737-7/8/8200/9/10 Certification Maintenance Requirements |
| D626A011-9-04 | 737-7/8/8200/9/10 Special Compliance Items |

3. Service Information:

| Boeing Document | Title |
|-----------------|---|
| D626A011 | 737-7/8/8200/9/10 Maintenance Planning Document (MPD) |
| D633AM101 | Airplane Maintenance Manual |

4. Weight and Balance (WBM):

| Model | Boeing Document |
|-------------|-----------------|
| 737-8/-8200 | D636A080 |
| 737-9 | D737A090 |

5. Universal Airplane Network Security Operator Guidance (UANSOG)

The Boeing Commercial Airplanes Universal Airplane Network Security Operator Guidance, D925W704-04, contains required Instructions for Continued Airworthiness and security guidance that when followed meets compliance requirements of the Network Cybersecurity Special Conditions.

V. Operating Suitability Data (OSD)



SECTION 8: 737-8/-9/-8200 - continued

The Operational Suitability Data elements listed below are approved by the European Union Aviation Safety Agency under the EASA Type Certificate IM.A.120 as per Commission Regulation (EU) 748/2012 as amended by Commission Regulation (EU) No 69/2014. Applicable OSD requirements are detailed in section 8.II.7.

1. Master Minimum Equipment List

- a. The EASA MMEL for the 737-8 and 737-9 is defined in Boeing document D639A001-02, revision 2 dated 25 September 2020, or later approved revisions.
- b. The EASA MMEL for the 737-8200 is defined in Boeing document D639A001-02, revision 3 dated 05 March 2021, or later approved revisions.

2. Flight Crew Data

The Flight Crew Data is defined in Boeing document D626A014, revision A dated 19 February 2021 or later approved revisions.
The Flight Crew Data is required for entry into service by EU operator.

3. Cabin Crew Data

- a. The Cabin Crew Data has been approved as per the defined Operational Suitability Data Certification Basis, namely CS-CCD- Initial Issue, and as demonstrated by the “Boeing Document D611A099 - Operational Suitability Data - Cabin Crew Data, B737NG and B737-8/-9/-8200 MAX, First Issue, Revision D, dated 29 March 2019”, or later approved revisions.
- b. Required for entry into service by EU operator.
- c. For Cabin Crew, the aircraft models: B737-9 MAX without Mid Exit Doors (MED) activated and B737-8 MAX are determined to be the same aircraft type.
- d. For Cabin Crew, the model B737-9 MAX with MED activated is determined to be a variant to the B737-8 MAX model.
- e. For Cabin Crew the model B737-9 MAX “with” or “without” MED activated is determined to be a variant to the aircraft model B737-900ER (with Mid Exit Door (MED) activated), thus, also a variant to the models: B737-600, B737-700, B737-800, B737-900, B737-900ER.
- f. For Cabin Crew, the model B737-8200 MAX is determined to be a variant to the B737-900ER (with MED activated) model.
- g. For Cabin Crew, the models: B737-600, B737-700, B737-800, B737-900, B737-900/ER, B737 MAX-8/-9, and the B737-8200 are variants to the B737-900ER (with MED activated).
- h. For Cabin Crew, the model B737-8200 MAX “with” or “without” MED activated is determined to be a variant to the aircraft model B737-900ER (with Mid Exit Door (MED) activated), thus, also a variant to the models: B737-600, B737-700, B737-800, B737-900, B737-900ER.

VI. Part 26 compliance information

For all variants in this section, compliance with point 26.300(a) of Part 26 is demonstrated by complying with points:

- 26.301 Compliance Plan for (R)TC holders
- 26.302 Fatigue and damage tolerance evaluation
- 26.303 Limit of Validity
- 26.304 Corrosion prevention and control program
- 26.305 Validity of the continuing structural integrity program
- 26.306 Fatigue critical baseline structure



SECTION 8: 737-8/-9/-8200 - continued

- 26.307 Damage tolerance data for existing changes to fatigue critical structure
- 26.308 Damage tolerance data for existing repairs to fatigue critical structure
- 26.309 Repair Evaluation Guidelines

VII. Notes

1. Cabin Interior and Seating Configuration must be approved.
2. 737-8 airplanes modified by Boeing Service Bulletin 737-21-1217 Lower Cabin Altitude (LCA) modification are capable of maintaining a cabin altitude of 6,500 feet in lieu of the standard 8,000 feet when operating at a cruising altitude of 41,000 feet. This modification has been approved for airplanes listed in Boeing Service Bulletin 737-21-1217 Revision 1, dated July 17, 2018, or later approved revision.
737-9 airplanes modified by Boeing Service Bulletin 737-21-1217 Lower Cabin Altitude (LCA) modification are capable of maintaining a cabin altitude of 6,500 feet in lieu of the standard 8,000 feet when operating at a cruising altitude of 41,000 feet. This modification has been approved for airplanes listed in Boeing Service Bulletin 737-21-1217 Revision 4, dated August 14, 2020, or later approved revision.
3. Additional information is provided in FAA Type Certificate Data Sheet A16WE.



SECTION: ADMINISTRATIVE

I. Acronyms and Abbreviations

| | |
|-------|---|
| AFM | Airplane Flight Manual |
| APU | Auxiliary Power Unit |
| AWO | All Weather Operations |
| CAA | Civil Aviation Authority |
| CMR | Certification Maintenance Requirements |
| CRI | Certification Review Item |
| CS | Certification Specification |
| EASA | European Union Aviation Safety Agency |
| EC | European Commission |
| ES(F) | Equivalent Safety (Finding) |
| ETOPS | Extended Range Operations with Two-Engined Aeroplanes |
| EU | European Union |
| EU MS | European Union Member States |
| EWIS | Electrical Wiring Interconnection System |
| FAA | Federal Aviation Administration |
| FAR | Federal Aviation Regulation |
| FRS | Flammibility Reduction Systems |
| HIRF | High Intensity Radiated Field |
| IAA | Irish Aviation Authority |
| ICA | Instructions for Continued Airworthiness |
| ICAO | International Civil Aviation Organization |
| IGW | Increased Gross Weight |
| JAA | Joint Aviation Authorities |
| JAR | Joint Aviation Requirements |
| LBA | Luffahrt-Bundesamt (CAA Germany) |
| MRB | Maintenance Review Board |
| NAA | National Aviation Authority |
| NG | Next Generation |
| NPA | Notice of Proposed Amendment |
| PTC | Post Type Certificate |
| SC | Special Condition |
| TC | Type Certificate |
| TCDS | Type Certificate Data Sheet |
| TCDSN | Type Certificate Data Sheet for Noise |
| TSO | Technical Standards Order |



II.Type Certificate Holder Record

The Boeing Company
P.O. Box 3707
Seattle, WA 98124-2207
United States of America



SECTION: ADMINISTRATIVE – continued

III. Change Record

Starting with issue 07

| Issue | Date | Changes | TC issue |
|----------|------------|--|------------------------|
| Issue 07 | 11/10/2011 | Section 2-7.III.5 (NG): Addition of engine variants Section 2.III.17: Added term “approved” wrt AFM Section 3.II.4: JAR 25.562 added to text CRI D-14 Section 3 II.4, 6.II.4, 7.II.4: CRI PTC/E-10 added Section 7.II.3: Paragraph 4.4 MOCs deleted Section 7.II.4: CRI PTC/D-GEN02 added Section “Administrative” added | Issue 02 07/07/2008 |
| Issue 08 | 03/11/2011 | Section 3.II.4 Removal of the duplicate sentence before CRI PTC/E-10. Section 3.III.24 Added Fuel Tank Flammability Reduction System Requirments Section 4.III.24 Added Fuel Tank Flammability Reduction System Requirments Section 5.III.23 Corrected list to sequential numbers Section 5.III.24 Added Fuel Tank Flammability Reduction System Requirments Section 6.II.4 Removal of the duplicate sentence before CRI PTC/E-10. Section 6.III.23 Corrected list to sequential numbers Section 6.III.24 Added Fuel Tank Flammability Reduction System Requirments Section 7.III.24 Added Fuel Tank Flammability Reduction System Requirments | |
| Issue 09 | 12/07/2012 | Section 1.II.4.and Section 2.II: Introduction of CRI H-01 for ICA on EWIS | |
| Issue 10 | 10/01/2014 | 1 st page: The Boeing Company address Section 1.II.3, 3.II 3 JAA Airworthiness requirements: - Change the title to JAA/EASA Airworthiness Requirements Section 3.II.3 JAA Airworthiness requirements: - Change the title to JAA/EASA Airworthiness Requirements - Identification of applicable paragraphs and CRI associated to each NPA. - Correction of applicable paragraph 25.519(b) instead of 25.X519(b) - For the CRI C-11, removal of affected requirement 25.310(b) - For the CRI D-14, addition of affected requirement JAR 25.813 - Addition of two Special Conditions: CRI F-29 and CRI F-30 Sections 3. III.12; 4.III.12; 5.III.12; 6.III.12; 7.III.12: All weather capability: Reference to the AFM instead of the category. Section 6.II.3 JAA Airworthiness requirements: - Change the title to JAA/EASA Airworthiness Requirements - Identification of applicable paragraphs and CRI associated to each NPA. - Correction of applicable paragraph 25.519(b) instead | |



SECTION: ADMINISTRATIVE – continued

| Issue | Date | Changes | TC issue |
|----------|------------|---|------------------------|
| | | of 25.X519(b) -For the CRI D-14, addition of affected requirement JAR 25.813 -Addition of two Special Conditions: CRI F-29 and CRI F-30 Section 7 II.3 JAA/EASA Airworthiness Requirements -Change the title to JAA/EASA Airworthiness Requirements -For the CRI D-14, addition of affected requirement JAR 25.562 -Addition of two Special Conditions: CRI F-29 and CRI F-30 | |
| Issue 11 | 14/12/2015 | -Editorial changes to page one -OSD implementation in Sections V -Section 1.II.4: Addition of Special Condition CRIs PTC/E-10, E-15 PTC E-16/PTC and F-GEN10 PTC -Section 1.II.6: Addition of Equivalent Safety Finding CRIs F-GEN 9-1, F-GEN9-3 and G-GEN1 -Section 1.III.13: Updated the maximum weight values to incorporate increases that were approved post type validation -Section 1.III.22: Corrected typo “Qty” to “Qty” -Section 2.II: Removed Special Condition CRI H-01 -Section 2.III.9: Corrected “Gall” to “Gallons” -Section 3.II.3.1: Added Reversion CRI A.11-13 -Section 3.II.4: Added Special Conditions CRIs D-GEN02 PTC, E-10, E-16/PTC, PTC F-23, PTC/F-17, PTC/F-18, PTC/F-27, F-31(PTC) , F-GEN10 PTC, G-01 and H-01 -Section 3.II.5: Added Deviation CRI PTC D-22 -Section 3.II.6: Added Equivalent Safety Finding CRIs PTC C-14, PTC/D-21, 9ER/D-21, F-GEN 9-1, F-GEN9-3 and G-GEN1 -Section 3.III.13: Corrected the kilogram value of maximum taxi and ramp weight -Section 4.II.6: Added Equivalent Safety Finding CRIs C-15/PTC, F-01 PTC and F-02 PTC -Section 4.III.13: Updated the maximum taxi and ramp weights to incorporate increases that were approved post type validation. Also corrected the kilogram values of each of the certified masses -Section 5.III.13 Updated the maximum weight values to incorporate increases that were approved post type validation -Section 6.II.4: Added Special Condition CRI E-16/PTC, PTC F-23, PTC/F-27, F-31(PTC) , F-GEN10 PTC and H-01 Section 6.II.5: Added Deviation CRI PTC D-22 -Section 6.II.6: Added Equivalent Safety Finding CRIs PTC C-14, PTC/D-21, 9ER/D-21, F-GEN 9-1, F-GEN9-3 and G-GEN1 -Section 6.III.13: Updated the maximum landing weight values to incorporate increases that were approved post type validation. Corrected the kilogram value of maximum taxi and ramp, take-off and landing weights. | Issue 02 07/07/2008 |



SECTION: ADMINISTRATIVE – continued

| Issue | Date | Changes | TC issue |
|----------|------------|---|------------------------|
| | | <ul style="list-style-type: none"> -Section 7.II.3.1: Corrected the JAR referenced under Reversion CRI A.11-5 from “2571” to “571”. Moved CRIs 9ER/F04 and 9ER/C-21 to present them in sequence -Section 7.II.3.2: inserted CRI PTC/G-02 -Section 7.II.4: Added Special Condition CRIs F-GEN10 PTC, D-GEN01 PTC, D-GEN02 PTC, E-16/PTC, PTC F-23, F-31(PTC) and H-01 -Section 7.II.6: Added Equivalent Safety Finding CRIs C-15/PTC, E-11, F-GEN 9-1, F-GEN9-3, G-GEN1, and 9ER/D-21. Moved several CRIs to present the listing in sequence -Section 7.III.13: Corrected each of the kilogram values | |
| Issue 12 | 27/03/2017 | <ul style="list-style-type: none"> -Section 8 “737-8” added. To be completed with inputs by CVU -Page1: references to B737-8 and Max series added -Section 4.II.3: B737-800 Winglets affected/non-affected area as per letter B-H320-2000-00472 -Sections 3 to 7: applicable OSD requirements detailed in the respective sub-sections II | Issue 02 07/07/2008 |
| Issue 13 | 28/07/2017 | <ul style="list-style-type: none"> -Section 8.III.23 ETOPS completed -OSD data: statement “or later approved revisions” added to the document rev. number if mentioned. -F-GEN-11 CRI added to sections 1.II, 3.II, 6.II and 7.II -clarification about F-GEN10 PTC applicability added in sections 1.II, 3.II, 6.II and 7.II -typos corrected | Issue 02 07/07/2008 |
| Issue 14 | 12/04/2018 | <ul style="list-style-type: none"> - Section 4: split into 4.1 for the B737-800 baseline model and 4.2 for the B737-800 BCF significant major change - Section 2.V OSD requirements explicitly stated Section 8: III.13 Weights corrected (metric values) | Issue 02 07/07/2008 |
| Issue 15 | 13/09/2018 | <ul style="list-style-type: none"> - B737-8 LEAP engines section III.5 amended with – G06 variants. - Minimum Cabin Crew indications added in section III.19 for models -300/-400/-500/-600/-700/-900 and -900ER - FAA postal address updated - Lower Cabin Altitude Notes added in Section VI of B737-700/-800/-900ER/-8 | Issue 02 07/07/2008 |
| Issue 16 | 05/10/2018 | <ul style="list-style-type: none"> - B737-9 Model added in Section 8 - former “Section 9” renumbered to “Section 8” - B737-9 certification basis integrated in Table A of Appendix A | Issue 02 07/07/2008 |
| Issue 17 | 17/10/2018 | <ul style="list-style-type: none"> - B737-9 LEAP engines section III.5 amended with – G06 variants. | Issue 02 07/07/2008 |
| Issue 18 | 24/05/2019 | <ul style="list-style-type: none"> - B737-8/9 certification basis updated with reference to CRI PTC F-30 and PTC F-37 (table 8.II.5.1 and Appendix A) - Section 3.II.4 amended to include F-GEN11 in the 737-700 certification basis | Issue 02 07/07/2008 |
| Issue | Date | Changes | TC issue |



SECTION: ADMINISTRATIVE – continued

| Issue | Date | - Changes | TC issue |
|----------|--------------|--|------------------------|
| Issue 19 | 14 Jun 2019 | - Section 4.2/ III / 5 operating limitations for 737-800 BCF updated. | Issue 02 07/07/2008 |
| Issue 20 | 12 Dec 2019 | - Section 8 II 6 B737-8/9 Fuel Venting and Exhaust Emission Requirements updated. - EASA new logo and footer introduced. | Issue 02 07/07/2008 |
| Issue 21 | 26 Jan 2021 | - Section 1/ II/ 6. CRI G-GEN1 removed. - Section 2/ III/ 6. Honeywell included as APU supplier - Section 8/ III/ 8. Kathon prohibition introduced for LEAP-1B. - Section 8/ V/ 1. And 2. OSD documentation for MAX RTS updated. - Appendix A CRI PTC F-30 removed from 737-8/-9 CRI list. | Issue 02 07/07/2008 |
| Issue 22 | 06 Apr 2021 | - 737-8200 model added in Section 8. - B737-8200 certification basis integrated in Table A of Appendix A. - Section 8/ VI. Note added for 737-8 airplanes modified by Boeing Service Bulletin 737-21-1217 Lower Cabin Altitude (LCA). | Issue 02 07/07/2008 |
| Issue 23 | 26 May 2021 | - Section 8/ II/ 5.2. Deviation E-30 limit delayed to the end of June 2022. | Issue 02 07/07/2008 |
| Issue 24 | 11 June 2021 | - Section 4/ III/ 6. Limitation to 2,000 flight cycles or 1 year removed. | Issue 02 07/07/2008 |
| Issue 25 | 17 Nov 2021 | - Section 8/I/8. 737-9 Certification date modified. - Section 8/ II/ 5.2. Boeing Service Bulleting reference included for Deviation E-30. - Section 8/ III/13. Certified masses updated. - Section 8/ VI. Note added for 737-9 airplanes modified by Boeing Service Bulletin 737-21-1217 Lower Cabin Altitude (LCA). - Section 8 and appendix A references to CRIs and requirements corrected. | Issue 02 07/07/2008 |
| Issue 26 | 10 Jan 2023 | Section 7/II/3.1 Explanatory note for CRI A.11-13 added. Section 8/III/5 LEAP-1B G variants removed. | Issue 02 07/07/2008 |
| Issue 27 | 13 Dec 2024 | Section 1,2 and 8/VI Compliance with Part 26 included. Section 4/III/19 Minimum Cabin Crew data included. Section 8/II/6 Environmental Requirements updated. Section 8/II/7 MMEL Certification Basis corrected. Section 8/III/20 Correction of ESF CRI D-15 designation | Issue 02 07/07/2008 |



SECTION: ADMINISTRATIVE – continued

| | | | |
|----------|---------------|--|------------------------|
| Issue 28 | 16 April 2025 | In first page Boeing address changed. Section 2/III/23 and Section 4/V/6 ETOPS added for 737-800BCF. Section 3/II/3.1 CRI A.11-13 removed. Section 3/III/22, Section 4/III/22, Section 4/V/5 and Section 5/III/22 cargo compartment class changed from D to C. Section 3 737-700, Section 4 737-800, Section 7 737-900ER and Section 8 737Max models IV new Operating and Service Instructions added for UANSOG. | Issue 02 07/07/2008 |
|----------|---------------|--|------------------------|



SECTION: Appendix A – continued

Appendix A
Detailed Certification Basis of the
737-8/-9/-8200

TABLE A – 737-8/-9/-8200 CERTIFICATION BASIS

| CS-25 Section No. | Title (or subparagraph) | 737-8 Amdt | 737-9 Amdt | 737-8200 Amdt | System/Area | Notes |
|-------------------|--|---|------------------|------------------|---|--|
| 25.1 | Applicability | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.2 | Removed [Special retroactive requirements] | N/A | N/A | N/A | | Not applicable |
| 25.20 | Scope | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.21 | Proof of Compliance | 737-8/-9/-8200 Associated CRI: B-07/MAX (Reversion) Note: CS 25 Appendix C is at CRI B-07/MAX. | | | | |
| | 25.21 | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane except as noted below | |
| | 25.21(g) except (g)(1) | | | CS 11 | 737-8200 Airplane | |
| | 25.21(g)(1) | See CRI B-07/MAX | See CRI B-07/MAX | See CRI B-07/MAX | 737-8/-9/-8200 Airplane | |
| 25.23 | Load distribution limits | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.25 | Weight limits | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.27 | Center of gravity limits | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.29 | Empty weight and corresponding center of gravity | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.31 | Removable ballast | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.33 | Propeller speed and pitch limits | N/A | N/A | N/A | | Not applicable |
| 25.101 | General (Performance) | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.103 | Stall speed | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.105 | Take-off | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane except as noted below | Note: CS 25 Appendix C is at CRI B-07/MAX. |
| | 25.105(a)(2) | | | CS 11 | 737-8200 Airplane | |
| 25.107 | Take-off speeds | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.109 | Accelerate-stop distance | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.111 | Take-off path | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane except as noted below | Note: CS 25 Appendix C is at CRI B-07/MAX. |
| | 25.111(c)(5) | | | CS 11 | 737-8200 Airplane | |
| 25.113 | Take-off distance and take-off run | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.115 | Take-off flight path | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.117 | Climb: general | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.119 | Landing climb: All- engines-operating | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane except as noted below | Note: CS 25 Appendix C is at CRI B-07/MAX. |
| | 25.119(b) | | | CS 17 | 737-8200 Airplane | |
| 25.121 | Climb: One engine- inoperative | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane except as noted below | Note: CS 25 Appendix C is at CRI B-07/MAX. |
| | 25.121(b)(2), (c)(2), (d)(2) | | | CS 11 | 737-8200 Airplane | |
| 25.123 | En route flight paths | 737-8/-9/-8200 Associated CRI: B-06/MAX (ESF) Note: CS 25 Appendix C is at CRI B-07/MAX. | | | | |
| | 25.123 | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane except as noted below | |
| | 25.123(b) | | | CS 11 | 737-8200 Airplane | |
| 25.125 | Landing | 737-8/-9/-8200 Associated CRI: B-07/MAX (Reversion) Note: CS 25 Appendix C is at CRI B-07/MAX. | | | | |
| | 25.125 | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane except as noted below | |



SECTION: Appendix A – continued

| CS-25 Section No. | Title (or subparagraph) | 737-8 Amdt | 737-9 Amdt | 737-8200 Amdt | System/Area | Notes |
|-------------------|--|---|-----------------------------------|-----------------------------------|---|---|
| | 25.125(a)(2), (b)(2)(ii)(C) | | | CS 11 | 737-8200 Airplane | |
| | 25.125(b)(2)(ii)(B) | See CRI B-07/MAX | See CRI B-07/MAX | See CRI B-07/MAX | 737-8/-9/-8200 Airplane | |
| 25.143 | General (Controllability and Maneuverability) | 737-8/-9/-8200 Associated CRI: B-07/MAX (Reversion) Note: CS 25 Appendix C is at CRI B-07/MAX. | | | | |
| | 25.143 | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane except as noted below | |
| | 25.143(c) | N/A | N/A | N/A | | Not Applicable |
| | 25.143(i) | | | CS 11 | 737-8200 Airplane | |
| | 25.143(j) | See CRI B-07/MAX | See CRI B-07/MAX | See CRI B-07/MAX | 737-8/-9/-8200 Airplane | |
| | 25.143(k), (l) | | | N/A | | Not applicable |
| 25.145 | Longitudinal control | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.147 | Directional and lateral control | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.149 | Minimum control speed | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.161 | Trim | 737-8/-9/-8200 Associated CRI: B-05/MAX (ESF) | | | | |
| | 25.161 | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.171 | General.(Stability) | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.173 | Static longitudinal stability | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.175 | Demonstration of static longitudinal stability | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.177 | Static directional and lateral stability | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.181 | Dynamic stability | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.201 | Stall demonstration | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.203 | Stall characteristics | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.205 | Removed [Stalls: critical engine inoperative] | N/A | Does not exist | Does not exist | | Not applicable |
| 25.207 | Stall warning | 737-8/-9/-8200 Associated CRI: B-07/MAX (Reversion) Note: CS 25 Appendix C is at CRI B-07/MAX. | | | | |
| | 25.207 | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane except as noted below | |
| | 25.207(e) | CS 2, See CRI B-07/MAX (see note) | CS 2, See CRI B-07/MAX (see note) | CS 2, See CRI B-07/MAX (see note) | 737-8/-9/-8200 Airplane | Note: CS 2 for non-icing aspects and CRI B-07/MAX for flight in icing aspects |
| | 25.207(f), (h), (i) | N/A | N/A | N/A | | Not Applicable |
| 25.231 | Longitudinal stability and control | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.233 | Directional stability and control | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.235 | Taxiing condition | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.237 | Wind velocities | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane except as noted below | Note: CS 25 Appendix C is at CRI B-07/MAX. |
| | 25.237(a)(3)(ii) | | | CS 11 | 737-8200 Airplane | |
| 25.251 | Vibration and buffeting | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.253 | High-speed characteristics | 737-8/-9/-8200 Associated CRI: B-07/MAX (Reversion) Note: CS 25 Appendix C is at CRI B-07/MAX. | | | | |
| | 25.253 | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane except as noted below | |
| | 25.253(c) | See CRI B-07/MAX | See CRI B-07/MAX | See CRI B-07/MAX | 737-8/-9/-8200 Airplane | |
| 25.255 | Out-of-trim characteristics | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.261 | Removed [Flight in rough air] | N/A | N/A | N/A | | Not applicable |



SECTION: Appendix A – continued

| CS-25 Section No. | Title (or subparagraph) | 737-8 Amdt | 737-9 Amdt | 737-8200 Amdt | System/Area | Notes |
|-------------------|---|---|-------------------------------|---------------------------|---|--|
| 25.301 | Loads | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.302 | Interaction of systems and structures | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.303 | Factor of safety | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.305 | Strength and deformation | OP 91/1 only applied to 25.305(d). 737-700 CRI C-05 voluntary elect-to-comply only applied to 25.305(e),(f) for the 737-800 Cert Basis. Neither apply to this exception proposal. | | | | |
| | 25.305 | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.307 | Proof of structure | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.321 | General (Flight Loads) | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.331 | Symmetric Manoeuvring conditions | 737-8/-9/-8200 Associated CRI: C-02/MAX (SC/IM) | | | | |
| | 25.331 | CS 11 with 25.331(c) at CS 13 | CS 12 with 25.331(c) at CS 13 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.333 | Flight Manoeuvring envelope | CS 11 with 25.333(b) at CS 13 | CS 12 with 25.333(b) at CS 13 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.335 | Design airspeeds | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.337 | Limit maneuvering load factors | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.341 | Gust and Turbulence Loads | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.343 | Design fuel and oil loads | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.345 | High lift devices | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.349 | Rolling conditions | 737-8/-9/-8200 Associated CRI: C-02/MAX (SC/IM) | | | | |
| | 25.349 | CS 11 with 25.349(a) at CS 13 | CS 12 with 25.349(a) at CS 13 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.351 | Yaw Manoeuver conditions | 737-8/-9/-8200 Associated CRI: C-02/MAX (SC/IM) | | | | |
| | 25.351 | CS 13 | CS 13 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.361 | Engine and auxiliary power unit torque | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.362 | Engine Failure Loads | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.363 | Side Load on Engine and APU Mounts | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.365 | Pressurized compartment loads | 737-8/-9/-8200 Associated CRIs: C-03/MAX (Reversion) | | | | |
| | 25.365 | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane except as noted below | |
| | 25.365(e)(1) | See CRI C-03/MAX (Note 1) | See CRI C-03/MAX (Note 2) | See CRI C-03/MAX (Note 3) | 737-8/-9/-8200 Airplane | <p>Note 1: 737-800 JAR 25.365 at FAR 0 (per 737-700 CRI A.11-02) and 25.365(e)(1) did not exist at FAR Amdt 25-0.</p> <p>Note 2: 737-900ER JAR 25.365 at FAR 0 (per 737-900 CRI 9ER / A.11-01, 737-900 CRI 9ER/C-19) and 25.365(e)(1) did not exist at FAR Amdt 25-0.</p> <p>Note 3: 737-8 JAR 25.365 at FAR 0 (per 737-700 CRI A.11-02) and 25.365(e)(1) did not exist at FAR Amdt 25-0.</p> |
| 25.367 | Unsymmetrical loads due to engine failure | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.371 | Gyroscopic loads | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.373 | Speed control devices | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.391 | Control surface loads: general | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.393 | Loads parallel to hinge line | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |



SECTION: Appendix A – continued

| CS-25 Section No. | Title (or subparagraph) | 737-8 Amdt | 737-9 Amdt | 737-8200 Amdt | System/Area | Notes |
|-------------------|--|---|-----------------------------------|---------------|--|---|
| 25.395 | Control system | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.397 | Control system loads | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane except as noted below | |
| | 25.397(d) | N/A | N/A | N/A | | Not applicable - 737 does not use side stick controllers |
| 25.399 | Dual control system | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.405 | Secondary control system | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.407 | Trim tab effects | N/A | N/A | N/A | | Not applicable – the tabs are not used to control airplane trim |
| 25.409 | Tabs | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.415 | Ground gust conditions | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.427 | Unsymmetrical loads | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.445 | Outboard fins | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.457 | Wing flaps | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.459 | Special devices | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.471 | General (Ground Loads) | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.473 | Landing load conditions and assumptions | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.477 | Landing gear arrangement | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.479 | Level landing conditions | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.481 | Tail-down landing conditions | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.483 | One- gear landing conditions | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.485 | Side load conditions | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.487 | Rebound landing condition | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.489 | Ground handling conditions | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.491 | Taxi, Takeoff and Landing Roll | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.493 | Braked roll conditions | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.495 | Turning | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.497 | Tail-wheel yawing | N/A | N/A | N/A | | Not applicable |
| 25.499 | Nose-wheel yaw and steering | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.503 | Pivoting | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.507 | Reversed braking | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.509 | Towing loads | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.511 | Ground load: unsymmetrical loads on multiple-wheel units | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.519 | Jacking & Tie-Down Provisions | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.561 | General (Emergency Landing Conditions) | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.562 | Emergency landing dynamic conditions | 737-8/-8200 Associated CRIs: D-15/MAX (SC), D-27/MAX (SC/IM), D-GEN9 (SC) 737-9 Associated CRIs: same as -8 plus 9ER/A.11-04 (NG)(Reversion) <i>Note: Per CRI D-15/MAX (SC), seats must comply with JAR 25.562 Change 13 except 25.562(c)(5),(c)(6); therefore, the requirement is "N/A" for 25.562(c)(5),(c)(6) for Passenger Seats in the 737-8/-9 certification basis.</i> | | | | |
| | 25.562 | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane except as noted below | |
| | 25.562(c)(5), (c)(6) | N/A 737-700 CRI A.11-04 | N/A 737-900ER CRI 9ER/ A.11-04 | | Interiors: (737-8/-9 Only) Passenger Seats | |
| 25.563 | Structural ditching provisions | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.571 | Damage-tolerance and fatigue evaluation of structure. | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |



SECTION: Appendix A – continued

| CS-25 Section No. | Title (or subparagraph) | 737-8 Amdt | 737-9 Amdt | 737-8200 Amdt | System/Area | Notes |
|-------------------|---|---|----------------------------|----------------------------|--|--|
| 25.581 | Lightning protection | 737-8/-9/-8200 Associated CRIs:F-03 (NG)(SC) | | | | |
| | 25.581 | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |
| 25.601 | General (Design and Construction) | 737-8/-9/-8200 Associated CRIs: F-GEN-11 (SC), PTC F-29 (NG) (SC) | | | | |
| | 25.601 | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |
| 25.603 | Materials | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |
| 25.605 | Fabrication methods | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |
| 25.607 | Fasteners | 737-8/-9/-8200 Associated CRIs: A.11-06 (NG) (Reversion) | | | | |
| | 25.607 | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane except as noted below | |
| | 25.607(a) | 737-700 CRI A.11- 06 | 737-700 CRI A.11 -06 | 737-700 CRI A.11 -06 | Systems – Flight Controls: ▪ Aileron Actuator, ▪ Aileron Trim Actuator ▪ Elevator Actuator, ▪ Elevator, Rudder, Stabilizer, Captain Lateral Body and Wing Aileron Cable Runs ▪ Elevator Tab Mechanism ▪ Lateral Feel and Centering Unit ▪ Stabilizer input arm to Elevator Feel Computer | |
| 25.609 | Protection of structure | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |
| 25.611 | Accessibility provisions | | | | | |
| | 25.611 | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane except as noted below | |
| | 25.611(b) | N/A | N/A | N/A | Interiors: EWIS components integral to the following interior design area: ▪ Closets ▪ Galleys ▪ Lavatories ▪ Passenger Seats ▪ Windscreens/Partitions | All design areas comply with the EWIS requirements at CS-25 Amendment 11(-8) or Amendment 12 (-9) or Amendment 17 (-8200) except the noted Interior areas. |
| 25.613 | Material strength properties and Material Design Values | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |
| 25.615 | Removed [Design properties] | N/A | Does not exist | Does not exist | | Not applicable |
| 25.619 | Special factors | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |
| 25.621 | Casting factors | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |
| 25.623 | Bearing factors | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |
| 25.625 | Fitting factors | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |
| 25.629 | Aeroelastic stability requirements | CS 11 | CS 12 | CS 11 | ▪ 737-8/-9/-8200 Airplane | |
| 25.631 | Bird Strike Damage | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |
| 25.651 | Proof of strength | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |
| 25.655 | Installation | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |
| 25.657 | Hinges | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |
| 25.671 | General (Control Systems) | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |
| 25.672 | Stability Augmentation and Automatic and Power-operated Systems | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |
| 25.675 | Stops | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |
| 25.677 | Trim systems | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |
| 25.679 | Control system gust locks | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |
| 25.681 | Limit load static tests | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |



SECTION: Appendix A – continued

| CS-25 Section No. | Title (or subparagraph) | 737-8 Amdt | 737-9 Amdt | 737-8200 Amdt | System/Area | Notes |
|-------------------|--|---------------------------|---------------------------|---------------------------|--|--|
| 25.683 | Operation tests | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.685 | Control system details | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.689 | Cable systems | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.693 | Joints | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.697 | Lift and Drag devices, controls | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.699 | Lift and Drag device indicator | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.701 | Flap and slat interconnection | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.703 | Take-off Warning System | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.721 | General (Landing Gear) | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.723 | Shock absorption tests | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.729 | Retracting mechanism | | | | | |
| | 25.729 | CS 11 | CS 12 | CS 11 | 737-8/-9/-8200 Airplane except as noted below | |
| | 25.729 | | | CS 11 | 737-8200 Airplane | |
| 25.731 | Wheels | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.733 | Tires | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.734 | Protection against wheel and tyre failures | Does not exist | Does not exist | N/A | 737-8200 Airplane | |
| 25.735 | Brakes and braking systems | | | | | |
| | 25.735 | CS 11 | CS 12 | CS 11 | 737-8/-9/-8200 Airplane except as noted below | |
| | 25.735 | JAR 13, JAR 15 (see note) | JAR 14, JAR 15 (see note) | JAR 13, JAR 15 (see note) | Mech/Hyd – Landing Gear Systems: Mechanical Brake Control System including Antiskid/Auto brake | Note: Within the brake control system, only the brake hydraulic system flow limiter and parking brake demonstration is certified to JAR 15. |
| | 25.735(l) | | | N/A | Mech/Hyd – Landing Gear Systems: (737-8200 Only) Brake Temperatures | |
| 25.745 | Nose-wheel steering | | | | 737-8/-9/-8200 Associated CRI: D-04/MAX (SC/MOC) | |
| | 25.745 | CS 11 | CS 12 | CS 11 | 737-8/-9/-8200 Airplane | |
| 25.771 | Pilot compartment | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.772 | Pilot compartment doors | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.773 | Pilot compartment view | | | | | |
| | 25.773 | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane except as noted below | |
| | 25.773(b) | JAR 13 | JAR 15 | JAR 13 | Environmental Control System: Windshield Wipers System | |
| | 25.773(b),(c) | JAR 13 | JAR 15 | JAR 13 | Environmental Control System: Window Heat System | |
| 25.775 | Windshield and windows | | | | 737-8/-9/-8200 Associated CRI: A.11-23 (NG)(Reversion. | |
| | 25.775 | CS 11 | CS 12 | CS 17 | 737-8/-9 Airplane except as noted below | |
| | 25.775(d) | 737-700 CRI A.11-23 | 737-700 CRI A.11-23 | 737-700 CRI A.11-23 | Transparencies: Flight Deck #1 Window Flight Deck #2 Window Flight Deck #3 Window Integrated Door Windows Passenger Window | |
| 25.777 | Cockpit controls | | | | 737-8/-9/-8200 Associated CRI: D-18/MAX (ESF) | |



SECTION: Appendix A – continued

| CS-25 Section No. | Title (or subparagraph) | 737-8 Amdt | 737-9 Amdt | 737-8200 Amdt | System/Area | Notes | |
|-------------------|--|--|--|--|--|---|--|
| | 25.777 | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | | |
| | 25.777(i) | | | N/A | Flight Controls: (737-8200 Only) ▪ Roll and Pitch Equipment and Installation | | |
| 25.779 | Motion and effect of cockpit controls | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | | |
| 25.781 | Cockpit control knob shape | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | | |
| 25.783 | Fuselage Doors | 737-8 Associated CRIs: A.11-11 (NG)(Reversion), D-16 (NG) (ESF) 737-9/-8200 Associated CRIs: same as 737-8 plus 9ER/D-16 (NG) (ESF) | | | | | |
| | 25.783 | CS 11 | CS 12 | CS 17 | ▪ Forward Access Door ▪ Mid-Exit Door (737-8200 only) | | |
| | 25.783 | JAR 13 | JAR 15 | JAR 13 | Doors: ▪ Airstair Door ▪ EE Access Door ▪ Automatic Overwing Exit (AOE) Door ▪ Mid Exit Door (MED) (737-9 only) EE Subsystems: (737-8/-9 only) ▪ PSEU / Fuselage Doors | Note: CRI D-16 (NG)(ESF) applies to JAR 25.783(f) for AOE only. Note: CRI 9ER/D-16 (NG)(ESF) applies to JAR 25.783 for 737-9 MED only. | |
| | 25.783 | N/A | N/A | N/A | Transparencies: ▪ Flight Deck #2 Window | | |
| | 25.783(a),(b),(h) | JAR 13 | JAR 15 | | Interiors: (737-8/-9 only) ▪ Emergency Exits | | |
| | 25.783(b),(e) | | | JAR 13 | EE Subsystems: (737-8200 Only) ▪ PSEU / Fuselage Doors except Mid Exit Door | | |
| | 25.783 except 25.783(f) | JAR 13 | JAR 15 | JAR 13 | Doors: ▪ Forward/Aft Cargo Door ▪ Forward/Aft Entry Door ▪ Forward/Aft Galley Door | | |
| | 25.783(f) | N/A (737-700 CRI A.11-11) (see note) | N/A (737-700 CRI A.11-11) (see note) | N/A (737-700 CRI A.11-11) (see note) | Doors: ▪ Forward/Aft Cargo Door ▪ Forward/Aft Entry Door ▪ Forward/Aft Galley Door | Note: JAR 25.783(f) at Change 10 is N/A at FAR 15 (737-700 CRI A.11-11) | |
| | 25.783(g) | N/A | N/A | N/A | Doors: ▪ External Access Door ▪ Lavatory Service Panel ▪ Water Service Door ▪ Access and Blowout Door ▪ ECS Access Door | | |
| 25.785 | Seats, berths, safety belts, and harnesses | 737-8/-9/-8200 Associated CRI: A.11-13 (NG)(Reversion), D-27/MAX (SC/IM), D-GEN9 (SC) | | | | | |
| | 25.785 | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane except as noted below | | |
| | 25.785(b) | CS 13 | CS 13 | | Interiors: (737-8/-9 Only) ▪ Medical Stretcher | | |



SECTION: Appendix A – continued

| CS-25 Section No. | Title (or subparagraph) | 737-8 Amdt | 737-9 Amdt | 737-8200 Amdt | System/Area | Notes |
|-------------------|--|---|------------|---------------|---|---|
| 25.787 | Stowage compartments | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.789 | Retention of items of mass in passenger and crew compartment and galleys | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.791 | Passenger information signs and placards | 737-8/-9/-8200 Associated CRI: PTC/D-23 (ESF) | | | | |
| 25.791 | | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane except as noted below | |
| 25.791(d) | | | | CS 23 | 737-8200 Airplane | |
| 25.793 | Floor surfaces | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.795 | Security consideration | | | | | |
| 25.795 | | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane except as noted below | |
| 25.795(b)(1) | | N/A | N/A | N/A | 737-8/-9/-8200 Airplane: Security considerations (flight deck smoke protection) | |
| 25.795(c)(2) | | N/A | N/A | N/A | 737-8/-9/-8200 Airplane: Security considerations (survivability of systems) | |
| 25.795(c)(3)(i) | | N/A | N/A | N/A | 737-8/-9/-8200 Airplane | |
| 25.795(c)(3)(iii) | | N/A | N/A | N/A | 737-8/-9 Airplane <u>Interiors:</u> (737-8200 Only) Passenger seats in Deactivated MED Configuration | |
| 25.799 | Removed [Water systems] | N/A | N/A | N/A | | Not applicable |
| 25.801 | Ditching | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.803 | Emergency evacuation | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.807 | Emergency exits | 737-8 Associated CRIs: D-15/MAX (SC), D-17 (NG) (ESF) 737-9/-8200 Associated CRIs: same as 737-8 plus D-28/MAX (ESF) | | | | |
| 25.807 | | JAR 13 OP 93/1 | JAR 15 | CS 17 | 737-8/-9/-8200 Airplane except as noted below | |
| 25.807 | | | | JAR 15 | <u>Interiors:</u> (737-8200 Only) Deactivated MED Configuration | |
| 25.809 | Emergency exit arrangement | | | | | |
| 25.809 | | JAR 13 (see note) | JAR 15 | CS 17 | 737-8/-9/-8200 Airplane except as noted below | Note: JAR 25.809(f) and (h) at Change 13 moved to JAR 25.810(a) and (d) at Change 14 and it is now in CS 25.810(a) and (d) |
| 25.809 | | | | JAR 13 | <u>Doors:</u> (737-8200 Only) Automatic Overwing Exit (AOE) Forward/Aft Entry Door Forward/Aft Galley Door | |
| 25.809(a) | | | | CS 11 | <u>Interiors:</u> (737-8200 Only) Emergency Exits (Flight Deck Windows, Forward / Aft Doors, Overwing) | |
| 25.810 | Emergency egress assist means and escape routes | JAA/737-700/ESF/D-08 applies to CS 25.810(a)(1)(ii) for forward and aft doors. Note: CRI D-08 was issued against JAR 25.809(f)(1)(ii) Change 13, originally. However, to harmonize with the FAA, the same requirement was moved to JAR 25.810(a)(1)(ii) at Change 14 which is now in CS 25.810(a)(1)(ii). | | | | |



SECTION: Appendix A – continued

| CS-25 Section No. | Title (or subparagraph) | 737-8 Amdt | 737-9 Amdt | 737-8200 Amdt | System/Area | Notes |
|-------------------|---|----------------|------------|---------------|--|--|
| | | | | | | 737-8 Associated CRI: D-08 (NG) (ESF) 737-9/-8200 Associated CRI: 9ER/D-08 (NG)(ESF) |
| | 25.810 | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |
| 25.811 | Emergency exit marking | | | | | 737-8/-9/-8200 Associated CRIs: 9ER/D-21 (NG)(ESF) , PTC/D-19 (NG) (ESF) |
| | 25.811 | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |
| 25.812 | Emergency lighting | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |
| 25.813 | Emergency exit access and ease of operation | | | | | OP 93/1 applies to 25.813 introductory paragraph and 25.813(a) and (b) only. 737-8 Associated CRI: D-15/MAX (SC) 737-9/-8200 Associated CRI: same as 737-8 plus 9ER/D-20 (NG)(ESF), D-28/MAX (ESF), D-31/MAX (ESF) |
| | 25.813 | JAR 13 OP 93/1 | JAR 15 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |
| 25.815 | Width of aisle | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |
| 25.817 | Maximum number of seats abreast | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |
| 25.819 | Lower deck service compartments (including galleys) | N/A | N/A | N/A | | Not applicable |
| 25.820 | Lavatory Doors | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |
| 25.831 | Ventilation | | | | | 737-8/-9/-8200 Associated CRI: D-17/MAX (ESF) |
| | 25.831 | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane except as noted below | |
| | 25.831(b),(c) | JAR 13 | JAR 15 | JAR 13 | Environmental Control System: ▪ Advisory Ice Detection System ▪ Cargo Smoke Detection System ▪ Ice/Rain Protection – Air Data Sensor Heat System ▪ Window Heat System ▪ Windshield Wipers System | |
| 25.832 | Cabin ozone concentration | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |
| 25.833 | Combustion Heating systems | N/A | N/A | N/A | | Not applicable |
| 25.841 | Pressurized cabins | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |
| 25.843 | Tests for pressurized cabins | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |
| 25.851 | Fire extinguishers | | | | | |
| | 25.851 | CS 11 | CS 12 | CS17 | ▪ 737-8/-9/-8200 Airplane except as noted below | |
| | 25.851(a) | | CS 11 | | Flight Deck: (737-9 Only) ▪ Miscellaneous/Emergency Equipment ▪ Fire Extinguisher Installation Interiors: (737-9 Only) ▪ Portable Emergency Equipment and Life Line | |
| | 25.851(b)(1), (b)(2) | | | CS 11 | Environmental Control System: (737-8200 Only) ▪ Cargo Fire Suppression System | |
| | 25.851(c) | | N/A | | Flight Deck: (737-9 Only) ▪ Miscellaneous/Emergency Equipment ▪ Fire Extinguisher Installation Interiors: (737-9 Only) ▪ Portable Emergency | |



SECTION: Appendix A – continued

| CS-25 Section No. | Title (or subparagraph) | 737-8 Amdt | 737-9 Amdt | 737-8200 Amdt | System/Area | Notes |
|-------------------|--|------------|------------|---------------|---|----------------|
| | | | | | Equipment and Life Line ▪ Lavatories | |
| 25.853 | Compartment Interiors | | | | 737-8/-9/-8200 Associated CRI: D-GEN02/PTC (SC/MOC) | |
| | 25.853 | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane except as noted below | |
| | 25.853(g) | | | CS 23 | ▪ 737-8200 Airplane | |
| 25.854 | Lavatory fire protection | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |
| 25.855 | Cargo or baggage compartments | | | | 737-8/-9/-8200 Associated CRI: D-17/MAX (ESF) | |
| | 25.855 | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |
| 25.856 | Thermal/acoustic Insulation materials | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |
| 25.857 | Cargo compartment classification | | | | 737-8/-9/-8200 Associated CRI: D-17/MAX (ESF) | |
| | 25.857 | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |
| 25.858 | Cargo or baggage compartment smoke or fire detection systems | | | | 737-8/-9/-8200 Associated CRI: D-17/MAX (ESF) | |
| | 25.858 | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane except as noted below | |
| | 25.858 | JAR 13 | JAR 15 | JAR 13 | Environmental Control System: ▪ Cargo Smoke Detection System | |
| 25.859 | Combustion heater fire protection | N/A | N/A | N/A | | Not applicable |
| 25.863 | Flammable fluid fire protection | | | | 737-8/-9/-8200 Associated CRIs: E-33/MAX (ESF), F-GEN-11 (SC), PTC F-29 (NG) (SC) | |
| | 25.863 | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane except as noted below | |
| | 25.863(a), (b)(3) | JAR 13 | JAR 15 | JAR 13 | Environmental Control System: ▪ Advisory Ice Detection System ▪ Cargo Smoke Detection System ▪ Ice/Rain Protection - Air Data Sensor Heat System ▪ RAM Air System, Inlet and Exhaust Ducts ▪ Window Heat System ▪ Windshield Wipers System | |
| 25.865 | Fire Protection of Flight Controls, Engine Mounts and Other Flight Structure | | | | 737-8/-9/-8200 Associated CRI: J-03/MAX (ESF) | |
| | 25.865 | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |
| 25.867 | Fire protection: other components | | | | 737-8/-9/-8200 Associated CRI: E-24/MAX (ESF) | |
| | 25.867 | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |
| 25.869 | Fire protection: systems | | | | | |
| | 25.869 | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane except as noted below | |
| | 25.869(a)(1) | N/A | JAR 15 | N/A | Environmental Control System: ▪ Advisory Ice Detection System ▪ Cargo Smoke Detection System ▪ Ice/Rain Protection – Air Data Sensor Heat System ▪ RAM Air System, Inlet and Exhaust Ducts | |



SECTION: Appendix A – continued

| CS-25 Section No. | Title (or subparagraph) | 737-8 Amdt | 737-9 Amdt | 737-8200 Amdt | System/Area | Notes | |
|-------------------|--|--|------------|---------------|--|---|--|
| | | | | | <ul style="list-style-type: none"> Window Heat System Windshield Wipers System | | |
| | 25.869(a)(3) | N/A | N/A | N/A | <p>Interiors: EWIS components integral to the following interior design area:</p> <ul style="list-style-type: none"> Closets Galleys Lavatories Passenger Seats Windscreens/Partitions | <p>All design areas comply with the EWIS requirements at CS-25 Amendment 11(-8) or Amendment 12 (-9) or Amendment 17 (-8200) except the noted Interior areas.</p> <p>In lieu of compliance to 25.869(a)(3) and 25.1713, compliance to 25.869(a)(4) [JAR 15] may be shown for the noted areas.</p> | |
| | 25.869(a)(4) | JAR 15 | JAR 15 | JAR 15 | <p>Interiors: EWIS components integral to the following Interiors design area:</p> <ul style="list-style-type: none"> Closets Galleys Lavatories Passenger Seats Windscreens/Partitions | <p>All design areas comply with the EWIS requirements at CS-25 Amendment 11(-8) or Amendment 12 (-9) or Amendment 17 (-8200) except the noted Interior areas.</p> | |
| 25.871 | Leveling means | CS 11 | CS 12 | CS 17 | <ul style="list-style-type: none"> 737-8/-9/-8200 Airplane | | |
| 25.875 | Reinforcement near propellers | N/A | N/A | N/A | | Not applicable | |
| 25.899 | Electrical bonding and protection against static electricity | <p>Note: 25.899 was titled JAR 25X899 at JAR Change 13. It was re-designated to 25.899 at JAR 16. 737-8/-9 Associated CRIs: E-31/MAX (Deviation), F-03 (NG)(SC) 737-8200 Associated CRIs: same as 737-8 except E-31/MAX (Deviation) is not applicable.</p> | | | | | |
| | 25.899 | CS 11 | CS 12 | CS 17 | <ul style="list-style-type: none"> 737-8/-9/-8200 Airplane except as noted below | <p>Note: Deviation E-31/MAX applies to 25.899 (737-8/-9 only)</p> | |
| | 25X899 | JAR 13 | JAR 15 | JAR 13 | <p>Avionics: (737-8/-9 Only)</p> <ul style="list-style-type: none"> Cockpit Voice Recorder (CVR) System <p>Environmental Control System:</p> <ul style="list-style-type: none"> Advisory Ice Detection System Cargo Smoke Detection System Ice/Rain Protection – Air Data Sensor Heat System Ram Air System Inlet and Exhaust Ducts Window Heat System Windshield Wipers System <p>Flight Controls/Flight Deck Instruments:</p> <ul style="list-style-type: none"> Floodlights <p>Mech/Hyd – Landing Gear Systems:</p> <ul style="list-style-type: none"> Mechanical Brake Control System including | | |



SECTION: Appendix A – continued

| CS-25 Section No. | Title (or subparagraph) | 737-8 Amdt | 737-9 Amdt | 737-8200 Amdt | System/Area | Notes |
|-------------------|---|------------|------------|---------------|---|---|
| | | | | | Antiskid/Auto brake | |
| 25.901 | Installation | | | | 737-8/-9 Associated CRIs: E-05/MAX (SC), E-27/MAX (SC/IM), E-29/MAX (ESF), E-30/MAX (Deviation), E-31/MAX (Deviation), E-32/MAX (SC/IM), E-33/MAX (ESF) 737-8200 Associated CRIs: same as 737-8 except E-30/MAX (Deviation) and E-31/MAX (Deviation) are not applicable. | |
| | 25.901 | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | Note: (737-8/-9 Only): Deviation CRI E-30/MAX applies to 25.901(b)(2) and 25.901(c). Deviation CRI E-31/MAX applies to 25.901(c). |
| 25.903 | Engines | | | | 737-8/-9/-8200 Associated CRIs: E-27/MAX (SC/IM), E-32/MAX (SC/IM) | |
| | 25.903 | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.904 | Automatic takeoff thrust control system (ATTCS) | N/A | N/A | N/A | | Not applicable |
| 25.905 | Propellers | N/A | N/A | N/A | | Not applicable |
| 25.907 | Propeller vibration | N/A | N/A | N/A | | Not applicable |
| 25.925 | Propeller clearance | N/A | N/A | N/A | | Not applicable |
| 25.929 | Propeller deicing | N/A | N/A | N/A | | Not applicable |
| 25.933 | Reversing systems | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.934 | Turbojet engine thrust reverser system tests | | | | 737-8/-9/-8200 Associated CRI: E-12/MAX (ESF) | |
| | 25.934 | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.937 | Turbo propeller-drag limiting systems | N/A | N/A | N/A | | Not applicable |
| 25.939 | Turbine engine operating characteristics | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.941 | Inlet, engine, and exhaust compatibility | N/A | N/A | N/A | | Not applicable |
| 25.943 | Negative acceleration | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.945 | Thrust or power augmentation system | N/A | N/A | N/A | | Not applicable |
| 25.951 | General (Fuel System) | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.952 | Fuel system analysis and test | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.953 | Fuel system independence | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.954 | Fuel system lightning protection | | | | 737-8/-9/-8200 Associated CRIs: F-03 (NG) (SC) | |
| | 25.954 | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.955 | Fuel flow | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.957 | Flow between interconnected tanks | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.959 | Unusable fuel supply | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.961 | Fuel system hot weather operation | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.963 | Fuel tanks: general | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane except as noted below | |
| | 25.963(e)(1) | | | CS 11 | Airframe: (737-8200 Only) Wing | |
| 25.965 | Fuel tank tests | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.967 | Fuel tank installations | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.969 | Fuel tank expansion space | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.971 | Fuel tank sump | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.973 | Fuel tank filler connection | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.975 | Fuel tank vents | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.977 | Fuel tank outlet | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.979 | Pressure Fuelling System | | | | 737-8 Associated CRI: E-09 (NG) (ESF) 737-9 Associated CRI: same as 737-8 plus E-36/MAX (deviation) | |
| | 25.979 | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | Note: Deviation E-36/MAX applies to 25.979(b)(2). (737-9 and 737-8200) |



SECTION: Appendix A – continued

| CS-25 Section No. | Title (or subparagraph) | 737-8 Amdt | 737-9 Amdt | 737-8200 Amdt | System/Area | Notes |
|-------------------|--|--|------------|---------------|---------------------------|--|
| 25.981 | Fuel tank ignition prevention | 737-8/-9 Associated CRIs: E-29/MAX (ESF), E-31/MAX (Deviation), E-33/MAX (ESF) 737-8200 Associated CRIs: same as 737-8 except E-31/MAX (Deviation) is not applicable. | | | | |
| | 25.981 | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | Note: Deviation E-31/MAX applies to 25.981(a)(3). (737-8/-9 Only) |
| 25.991 | Fuel pumps | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |
| 25.993 | Fuel system lines and fittings | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |
| 25.994 | Fuel System Components | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |
| 25.995 | Fuel valves | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |
| 25.997 | Fuel strainer or filter | 737-8/-9/-8200 Associated CRI: E-20/MAX (ESF) | | | | |
| | 25.997 | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |
| 25.999 | Fuel system drains | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |
| 25.1001 | Fuel jettisoning system | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |
| 25.1011 | General (Oil System) | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |
| 25.1013 | Oil tank | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |
| 25.1015 | Oil tank tests | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |
| 25.1017 | Oil lines and fittings | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |
| 25.1019 | Oil strainer or filter | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |
| 25.1021 | Oil system drains | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |
| 25.1023 | Oil radiators | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |
| 25.1025 | Oil valves | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |
| 25.1027 | Propeller feathering system | N/A | N/A | N/A | | Not applicable |
| 25.1041 | General (Cooling) | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |
| 25.1043 | Cooling tests | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |
| 25.1045 | Cooling test procedures | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |
| 25.1091 | Air intake | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |
| 25.1093 | Air intake system deicing and anti-icing provisions | 737-8/-9/-8200 Associated CRI: F-11/MAX (SC/IM) | | | | |
| | 25.1093 | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |
| 25.1103 | Air Intake system ducts and air duct systems | 737-8/-9/-8200 Associated CRIs: E-22/MAX (ESF), E-33/MAX (ESF) | | | | |
| | 25.1103 | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |
| 25.1121 | General (Exhaust System) | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |
| 25.1123 | Exhaust piping | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |
| 25.1141 | Powerplant controls: general | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |
| 25.1143 | Engine Controls | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |
| 25.1145 | Ignition switches | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |
| 25.1149 | Propeller speed and pitch controls | N/A | N/A | N/A | | Not applicable |
| 25.1153 | Propeller feathering controls | N/A | N/A | N/A | | Not applicable |
| 25.1155 | Reverse thrust and propeller pitch settings below the flight regime | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |
| 25.1161 | Fuel jettisoning system controls | N/A | N/A | N/A | | Not applicable |
| 25.1163 | Powerplant accessories | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |
| 25.1165 | Engine ignition systems | 737-8/-9/-8200 Associated CRIs: E-22/MAX (ESF) | | | | |
| | 25.1165 | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |
| 25.1167 | Accessory gearboxes | N/A | N/A | N/A | | Not applicable |
| 25.1181 | Designated fire zones: regions included | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |
| 25.1182 | Nacelle areas behind firewalls, and engine pod attaching structures containing flammable fluid lines | 737-8/-9/-8200 Associated CRIs: E-10/MAX (ESF), E-22/MAX (ESF) | | | | |
| | 25.1182 | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |
| 25.1183 | Flammable fluid-carrying components | 737-8/-9/-8200 Associated CRIs: E-10/MAX (ESF), E-22/MAX (ESF) | | | | |
| | 25.1183 | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |



SECTION: Appendix A – continued

| CS-25 Section No. | Title (or subparagraph) | 737-8 Amdt | 737-9 Amdt | 737-8200 Amdt | System/Area | Notes |
|-------------------|--|--|-----------------------------------|---------------|--|---|
| 25.1185 | Flammable fluids | 737-8/-9/-8200 Associated CRI: E-22/MAX (ESF) | | | | |
| | 25.1185 | CS11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |
| 25.1187 | Drainage and ventilation of fire zones | 737-8/-9/-8200 Associated CRI: E-22/MAX (ESF) | | | | |
| | 25.1187 | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |
| 25.1189 | Shutoff means | 737-8/-9/-8200 Associated CRI: E-22/MAX (ESF) | | | | |
| | 25.1189 | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |
| 25.1191 | Firewalls | 737-8/-9/-8200 Associated CRI: E-28/MAX (ESF) | | | | |
| | 25.1191 | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |
| 25.1193 | Cowling and nacelle skin | 737-8/-9 Associated CRIs: E-05/MAX (SC), E-30/MAX (Deviation) 737-8200 Associated CRIs: same as 737-8 except E-30/MAX (Deviation) is not applicable. | | | | |
| | 25.1193 | CS 11 with 25.1193(e)(3) at CS 13 | CS 12 with 25.1193(e)(3) at CS 13 | CS 17 | ▪ 737-8/-9/-8200 Airplane | Note: Deviation E-30/MAX applies to CRI E-05/MAX (ref. 25.1193(f)(3)). (737-8/-9 Only) |
| 25.1195 | Fire extinguisher systems | 737-8/-9/-8200 Associated CRIs: E-22/MAX (ESF), E-32/MAX (SC/IM) | | | | |
| | 25.1195 | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |
| 25.1197 | Fire extinguishing agents | 737-8/-9/-8200 Associated CRI: E-22/MAX (ESF) | | | | |
| | 25.1197 | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |
| 25.1199 | Extinguishing agent containers | 737-8/-9/-8200 Associated CRI: E-22/MAX (ESF) | | | | |
| | 25.1199 | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |
| 25.1201 | Fire extinguishing system materials | 737-8/-9/-8200 Associated CRI: E-22/MAX (ESF) | | | | |
| | 25.1201 | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |
| 25.1203 | Fire-detector system | 737-8/-9/-8200 Associated CRI: E-22/MAX (ESF) | | | | |
| | 25.1203 | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |
| 25.1207 | Compliance | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |
| 25.1301 | Function and installation | 737-8 Associated CRIs: B-05/MAX (ESF), PTC/F-17 (NG)(SC), PTC/F-27 (NG)(SC/IM), PTC F-30 (SC/IM), PTC F-37 (SC/IM) 737-9/-8200 Associated CRIs: same as 737-8 plus 9ER/D-20 (NG)(ESF) | | | | |
| | 25.1301 | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane except as noted below | |
| | 25.1301 | JAR 13 | JAR 15 | JAR 13 | Avionics: <ul style="list-style-type: none"> ▪ Airborne Data Loading System ▪ Air Traffic Control (ATC) ▪ Cockpit Voice Recorder (CVR) System ▪ Communications Management Unit (CMU) System ▪ Flight Deck Audio System ▪ Flight Deck Printer ▪ High Frequency (HF) Communications System ▪ Radio Nav Systems (ADF, DME, ELT, LRRRA, VOR/MB) ▪ Radio Nav Systems (GPS, ILS) - Honeywell ▪ Satellite Communications (SATCOM) System ▪ Selective Call (SELCAL) System ▪ Traffic Collision Avoidance System (TCAS) ▪ Very High Frequency (VHF) Communications System | |



SECTION: Appendix A – continued

| CS-25 Section No. | Title (or subparagraph) | 737-8 Amdt | 737-9 Amdt | 737-8200 Amdt | System/Area | Notes |
|----------------------|----------------------------|---------------|---------------|------------------|--|-------|
| | | | | | <p>Doors:</p> <ul style="list-style-type: none"> ▪ Airstair Door ▪ Automatic Overwing Exit (AOE) Door ▪ EE Access Door ▪ Forward/Aft Cargo Door ▪ Forward/Aft Entry Door ▪ Forward/Aft Galley Door ▪ Mid Exit Door (MED) (-9 only) <p>EE Subsystems:</p> <ul style="list-style-type: none"> ▪ Aural Warning Module / Master Caution ▪ Window Heat <p>Environmental Control System:</p> <ul style="list-style-type: none"> ▪ Advisory Ice Detection System ▪ Cargo Smoke Detection System ▪ Galley Vent System ▪ Ice/Rain Protection – Air Data Sensor Heat System ▪ RAM Air System, Inlet and Exhaust Ducts ▪ Window Heat System ▪ Windshield Wipers System <p>Flight Controls:</p> <ul style="list-style-type: none"> ▪ Standby Compass <p>Flight Controls/Flight Deck Instruments:</p> <ul style="list-style-type: none"> ▪ Floodlights <p>Flight Deck:</p> <ul style="list-style-type: none"> ▪ Air Data System Installations – Angle of Attack (AOA) Vanes ▪ Air Data System Installations – Pitot Probes and Elevator Feel Probes ▪ Air Data System Installation - Static Ports Installation ▪ Air Data System Installations – Total Air Temperature (TAT) Probes ▪ Communications Equipment Installations ▪ Crew Oxygen Installations (737-8/-9 only) ▪ Door – Flight Deck Access System (FDAS) ▪ Flight Deck Observer Seats (737-8/-9 only) ▪ Lighting/Floodlights/Map | |



SECTION: Appendix A – continued

| CS-25 Section No. | Title (or subparagraph) | 737-8 Amdt | 737-9 Amdt | 737-8200 Amdt | System/Area | Notes |
|----------------------|----------------------------|---------------|---------------|------------------|--|-------|
| | | | | | <p>Lights/Utility Lights/Dome Lights/Chart Lights</p> <ul style="list-style-type: none"> ▪ PC Power System (737-8/-9 only) ▪ Pilot Seats (737-8/-9 only) ▪ Standby Compass System Installation ▪ Stowage and Linings – except HUD provisions, ceiling linings, closet lining, and 2nd observer stowage box (737-8/-9 only) <p><u>Miscellaneous/Emergency Equipment</u> (737-8/-9 only) -</p> <ul style="list-style-type: none"> ▪ Ashtray Installation ▪ Checklist holder Installation ▪ Cup Holders Installation ▪ Drain Tubing Installation ▪ Emergency Locator Transmitter (ELT) Installation on P-18 panel ▪ Fire Extinguisher Installation ▪ Flashlights Installation ▪ Life Vests Installation ▪ Protective Breathing Equipment (PBE) Installation ▪ Protective Gloves Installation ▪ Sun visor and roller sunshade installation ▪ Test Receptacle Installation <p><u>Mech/Hyd – Landing Gear Systems:</u></p> <ul style="list-style-type: none"> ▪ Mechanical Brake Control System including Antiskid/Auto brake <p><u>Interiors:</u> (737-8/-9 Only)</p> <ul style="list-style-type: none"> ▪ AC Rails ▪ Attendant Control Panel (ACP) ▪ Attendant Partitions ▪ Attendant Seats ▪ Cabin Interphone ▪ Cabin (Passenger) Telecommunications ▪ Centerline Overhead Stowbox ▪ Class Dividers ▪ Closets ▪ Curtains, Curtain Tracks and Curtain Header, and Class Divider Curtains ▪ Dog-Houses ▪ Door and Doorway Linings/Headers ▪ Emergency Lighting | |



SECTION: Appendix A – continued

| CS-25 Section No. | Title (or subparagraph) | 737-8 Amdt | 737-9 Amdt | 737-8200 Amdt | System/Area | Notes |
|----------------------|---|---------------|---------------|------------------|---|--|
| | | | | | <ul style="list-style-type: none"> ▪ Galleys ▪ General Lighting ▪ In-Flight Entertainment System ▪ Lavatories ▪ Lowered Ceilings ▪ Main Cabin Ceilings ▪ Overhead Stowage Bins ▪ Passenger Address System ▪ Passenger Seats ▪ Passenger Service Units (PSU) and PSU Video Monitors ▪ PC Power System ▪ Portable Emergency Equipment and Life Line ▪ PRAM ▪ Service Outlets ▪ Sidewalls ▪ Stowboxes ▪ Video Control Center ▪ Video Surveillance ▪ Water and Waste Systems ▪ Windscreens/Partitions | |
| | 25.1301 | JAR 14 | JAR 15 | JAR 14 | Avionics: <ul style="list-style-type: none"> ▪ Radio Nav Systems (GLS, GPS, ILS) - Rockwell | |
| | 25.1301(b) | N/A | N/A | N/A | Interiors: EWIS components integral to the following interior design areas: <ul style="list-style-type: none"> ▪ Closets ▪ Galleys ▪ Lavatories ▪ Passenger Seats ▪ Windscreens/Partitions | All design areas comply with the EWIS requirements at CS-25 Amendment 11(-8) or Amendment 12 (-9) or Amendment 17 (-8200) except the noted Interior areas. |
| 25.1302 | Installed Systems and Equipment for use by the flight crew | CS 11 | CS 12 | CS 17 | <ul style="list-style-type: none"> ▪ 737-8/-9/-8200 Airplane | |
| 25.1303 | Flight and navigation instruments | | | | | |
| | 25.1303 | CS 11 | CS 12 | CS 17 | <ul style="list-style-type: none"> ▪ 737-8/-9/-8200 Airplane except as noted below | |
| | 25.1303(a)(3) | JAR 13 | JAR 15 | JAR 13 | Flight Deck: <ul style="list-style-type: none"> ▪ Standby Compass System Installation | |
| 25.1305 | Powerplant instruments 737-8/-9/-8200 Associated CRI: E-20/MAX (ESF) | | | | | |
| | 25.1305 | CS 11 | CS 12 | CS 17 | <ul style="list-style-type: none"> ▪ 737-8/-9/-8200 Airplane | |
| 25.1307 | Miscellaneous equipment | CS 11 | CS 12 | CS 17 | <ul style="list-style-type: none"> ▪ 737-8/-9/-8200 Airplane | 737-8/-9 Associated CRI: PTC F-30 (SC/IM) |
| 25.1309 | Equipment, systems and installations 737-8 Associated CRIs: A.11-16 (NG)(Reversion), B-05/MAX (ESF), D-04/MAX (SC/MOC), D-17/MAX (ESF), E-27/MAX (SC/IM), E-29/MAX (ESF), E-31/MAX (Deviation), F-03(NG) (SC), PTC/F-17 (NG) (SC), PTC/F-27 (NG) (SC/IM), PTC/F-29 (NG) (SC), PTC F-30 (SC/IM), PTC/F-31 (NG)(SC/IM) | | | | | |
| | 737-9 Associated CRIs: same as 737-8 plus 9ER/D-20 (NG)(ESF) | | | | | |



SECTION: Appendix A – continued

| CS-25 Section No. | Title (or subparagraph) | 737-8 Amdt | 737-9 Amdt | 737-8200 Amdt | System/Area | Notes |
|-------------------|--|----------------|------------|----------------|---|--|
| | 737-8200 Associated CRIs: same as 737-9 except E-31/MAX (Deviation) is not applicable. | | | | | |
| 25.1309 | | CS 11 | CS 12 | CS 17 | <ul style="list-style-type: none"> ▪ 737-8/-9/-8200 Airplane except as noted below | Note: Deviation E-31/MAX applies to 25.1309(b)(1) (737-8/-9 only) |
| 25.1309 | | JAR 13 OP 90/1 | JAR 15 | JAR 13 OP 90/1 | <p>Avionics:</p> <ul style="list-style-type: none"> ▪ Airborne Data Loading System ▪ Air Traffic Control (ATC) ▪ Communications Management Unit (CMU) System ▪ Flight Deck Printer ▪ High Frequency (HF) Communications System ▪ Radio Nav Systems (ADF, DME, ELT, LRRRA, VOR/MB) ▪ Radio Nav Systems (GPS, ILS) –Honeywell ▪ Satellite Communications (SATCOM) System ▪ Selective Call (SELCAL) System ▪ Traffic Collision Avoidance System (TCAS) ▪ Very High Frequency (VHF) Communication System <p>Doors:</p> <ul style="list-style-type: none"> ▪ Airstair Door ▪ Automatic Overwing Exit (AOE) Door ▪ EE Access Door ▪ Mid Exit Door (MED) (-9 only) <p>EE Subsystems:</p> <ul style="list-style-type: none"> ▪ Aural Warning Module/Master Caution ▪ Window Heat <p>Environmental Control System:</p> <ul style="list-style-type: none"> ▪ Advisory Ice Detection System ▪ Cargo Smoke Detection System ▪ Ice/Rain Protection – Air Data Sensor Heat System ▪ RAM Air System, Inlet and Exhaust ducts ▪ Window Heat System <p>Flight Controls:</p> <ul style="list-style-type: none"> ▪ Standby Compass <p>Flight Controls/Flight Deck</p> | |



SECTION: Appendix A – continued

| CS-25 Section No. | Title (or subparagraph) | 737-8 Amdt | 737-9 Amdt | 737-8200 Amdt | System/Area | Notes |
|----------------------|----------------------------|---------------|---------------|------------------|--|-------|
| | | | | | <p><u>Instruments:</u></p> <ul style="list-style-type: none"> ▪ Floodlights <p><u>Flight Controls/Flight Deck Instruments:</u></p> <ul style="list-style-type: none"> ▪ Floodlights <p><u>Flight Deck:</u></p> <ul style="list-style-type: none"> ▪ Air Data System Installations – Angle of Attack (AOA) Vanes ▪ Air Data System Installations – Pitot Probes and Elevator Feel Probes ▪ Air Data System Installation - Static Ports Installation ▪ Air Data System Installations – Total Air Temp (TAT) Probes ▪ Communications Equipment Installations ▪ Crew Oxygen Installations (737-8/-9 only) ▪ Door – Flight Deck Access System (FDAS) ▪ Flight Deck Observer Seats (737-8/-9 only) ▪ Lighting/Floodlights/Map Lights/Utility Lights/Dome Lights/Chart Lights ▪ PC Power System (737-8/-9 only) ▪ Pilot Seats (737-8/-9 only) ▪ Standby Compass System Installation <p><u>Miscellaneous/Emergency Equipment:</u> (737-8/-9 only)–</p> <ul style="list-style-type: none"> ▪ Emergency Locator Transmitter (ELT) Installation on P-18 panel ▪ Fire Extinguisher Installation ▪ Flashlights Installation ▪ Protective Breathing Equipment (PBE) Installation ▪ Test Receptacle Installation <p><u>Interiors:</u> (737-8/-9 only)</p> <ul style="list-style-type: none"> ▪ AC Rails ▪ Attendant Control Panel (ACP) ▪ Attendant Partitions ▪ Cabin Interphone ▪ Cabin (Passenger) Telecommunications ▪ Centerline Overhead Stowbox ▪ Class Dividers ▪ Closets | |



SECTION: Appendix A – continued

| CS-25 Section No. | Title (or subparagraph) | 737-8 Amdt | 737-9 Amdt | 737-8200 Amdt | System/Area | Notes |
|----------------------|----------------------------|-----------------------------------|---------------------------|-----------------------------------|---|--|
| | | | | | <ul style="list-style-type: none"> ▪ Door and Doorway Linings/Headers ▪ Emergency Lighting ▪ Galleys ▪ General Lighting ▪ In-Flight Entertainment System ▪ Lavatories ▪ Lowered Ceilings ▪ Main Cabin Ceilings ▪ Overhead Stowage Bins ▪ Passenger Address System ▪ Passenger Seats ▪ Pass Service Units (PSU) and PSU Video Monitors ▪ PC Power System ▪ Portable Emergency Equipment and Life Line ▪ PRAM ▪ Service Outlets ▪ Sidewalls ▪ Video Control Center ▪ Video Surveillance ▪ Water and Waste Systems ▪ Windscreens/Partitions | |
| 25.1309 | | JAR 13 | JAR 15 | JAR 13 | Avionics: <ul style="list-style-type: none"> ▪ Cockpit Voice Recorder (CVR) System | |
| 25.1309 | | JAR 13 | JAR 13 | JAR 13 | Avionics: <ul style="list-style-type: none"> ▪ Flight Deck Audio System | |
| 25.1309 | | JAR 13 OP 90/1, JAR 15 (see note) | JAR 14, JAR 15 (see note) | JAR 13 OP 90/1, JAR 15 (see note) | Mech/Hyd – Landing Gear Systems: <ul style="list-style-type: none"> ▪ Mechanical Brake Control System including Antiskid/Auto brake | Note: Within the brake control system, only the brake hydraulic system flow limiter and parking brake demonstration is certified to JAR 15. |
| 25.1309 | | JAR 14 | JAR 15 | JAR 14 | Avionics: <ul style="list-style-type: none"> ▪ Radio Nav Systems (GLS, GPS, ILS) - Rockwell | |
| 25.1309 | | FAR 0 | FAR 0 | FAR 0 | Avionics: <ul style="list-style-type: none"> ▪ Flight and Ground Crew Call ▪ Flight Interphone ▪ Service Interphone Doors: <ul style="list-style-type: none"> ▪ Forward/Aft Cargo Door ▪ Forward/Aft Entry Door ▪ Forward/Aft Galley Door Environmental Control System: <ul style="list-style-type: none"> ▪ Galley Vent System ▪ Windshield Wipers System | |
| 25.1309(d) | | N/A | N/A | N/A | Interiors: EWIS components integral to the following interior designs: | All design areas comply with the EWIS requirements at CS-25 |



SECTION: Appendix A – continued

| CS-25 Section No. | Title (or subparagraph) | 737-8 Amdt | 737-9 Amdt | 737-8200 Amdt | System/Area | Notes | |
|----------------------|--|---|---------------|------------------|--|--|--|
| | | | | | <ul style="list-style-type: none"> ▪ Closets ▪ Galleys ▪ Lavatories ▪ Passenger Seats ▪ Windscreens/Partitions | Amendment 11(-8) or Amendment 12 (-9) or Amendment 17 (-8200) except the noted Interior areas. | |
| 25.1310 | Power source capacity and distribution | CS 11 | CS 12 | CS 17 | <ul style="list-style-type: none"> ▪ 737-8/-9/-8200 Airplane | | |
| 25.1315 | Negative acceleration | CS 11 | CS 12 | CS 17 | <ul style="list-style-type: none"> ▪ 737-8/-9/-8200 Airplane | | |
| 25.1316 | System lightning protection | 737-8/-9/-8200 Associated CRI: F-03(NG)(SC) | | | | | |
| | 25.1316 | CS 11 | CS 12 | CS 17 | <ul style="list-style-type: none"> ▪ 737-8/-9/-8200 Airplane except as noted below | | |
| | 25.1316(a) | N/A | N/A | N/A | <p>Avionics:</p> <ul style="list-style-type: none"> ▪ Air Data Inertial Reference System (ADIRS) (737-8/-9 Only) ▪ Air Data Inertial Reference System (ADIRS) – (ADIRU, ADM) (737-8200 Only) ▪ Radio Nav Systems (GLS, ILS, LRRRA) ▪ Radio Nav Systems (GPS) (737-8/-9 Only) <p>Flight Controls – Autoflight System: (737-8/-9 Only)</p> <ul style="list-style-type: none"> ▪ Flight Control Computer (FCC) | | |
| | 25.1316 (b) | N/A | JAR 15 | N/A | <p>Avionics:</p> <ul style="list-style-type: none"> ▪ Air Traffic Control (ATC) (737-8/-9 only) ▪ Air Traffic Control (ATC Antenna) (737-8200 only) ▪ Communications Management Unit (CMU) System (737-8/-9 only) ▪ Flight Deck Audio System (737-8/-9 only) ▪ High Frequency (HF) Communications System (737-8/-9 only) ▪ Radio Nav Systems (ADF, DME, VOR/MB) (737-8/-9 only) ▪ Radio Nav Systems, (DME Antenna, VOR/MB Antenna) (737-8200 only) ▪ Traffic Collision Avoidance System (TCAS) (737-8/-9 only) ▪ Traffic Collision Avoidance System (TCAS) Antenna (737-8200 only) ▪ Very High Frequency (VHF) Communications System (737-8/-9 only) ▪ Very High Frequency (VHF) Communications System Antenna (737-8200 only) <p>Environmental Control System:</p> | | |



SECTION: Appendix A – continued

| CS-25 Section No. | Title (or subparagraph) | 737-8 Amdt | 737-9 Amdt | 737-8200 Amdt | System/Area | Notes |
|----------------------|--|----------------|---------------|------------------|--|--|
| | | | | | <ul style="list-style-type: none"> ▪ Cargo Smoke Detection System (737-8/-9 Only) ▪ Ice/Rain Protection – Air Data Sensor Heat System (737-8/-9 Only) ▪ RAM Air System, Inlet and Exhaust Ducts ▪ Window Heat System ▪ Windshield Wipers System <p>Flight Controls/Flight Deck Instruments: (737-8/-9 Only)</p> <ul style="list-style-type: none"> ▪ Integrated Standby Flight Display (ISFD) <p>Flight Deck: (737-8/-9 Only)</p> <ul style="list-style-type: none"> ▪ Crew Oxygen Installations ▪ Door – Flight Deck Access System (FDAS) <p>Mech/Hyd – Landing Gear Systems: (737-8/-9 Only)</p> <ul style="list-style-type: none"> ▪ Mechanical Brake Control System including Antiskid/Auto brake <p>Flight Controls/Flight Deck Instruments: (737-8/-9 only)</p> <ul style="list-style-type: none"> ▪ Integrated Standby Flight Display (ISFD) <p>Flight Deck:</p> <ul style="list-style-type: none"> ▪ Crew Oxygen Installations ▪ Door – Flight Deck Access System (FDAS) (737-8/-9 only) <p>Mech/Hyd – Landing Gear Systems:</p> <ul style="list-style-type: none"> ▪ Mechanical Brake Control System including Antiskid/Auto brake (737-8/-9 only) ▪ Mechanical Brake Control System for Wheel Speed Transducer and Antiskid/Auto brake Control Unit (AACU) (737-8200 only) | |
| | 25.1316(b) | JAR 14 OP 96/1 | JAR 15 | JAR 14 OP 96/1 | <p>Avionics:</p> <ul style="list-style-type: none"> ▪ Flight Management Computer System (FMCS) ▪ Stall Management Yaw Damper (SMYD) System | |
| | 25.1316(b) | N/A | N/A | N/A | <p>Flight Controls – Autoflight System:</p> <ul style="list-style-type: none"> ▪ Integrated Flight System Accessory Unit (IFSAU) | Note: IFSAU under requalification and future revision of TCDS will be requested to remove this exception. |
| 25.1317 | High-Intensity Radiated Fields (HIRF) protection | | | | | Associated CRIs: F-01 (NG)(SC) |



SECTION: Appendix A – continued

| CS-25 Section No. | Title (or subparagraph) | 737-8 Amdt | 737-9 Amdt | 737-8200 Amdt | System/Area | Notes | |
|-------------------|--|---|------------------|------------------|---|--|--|
| | 25.1317 | Does not exist | Does not exist | CS 17 | <ul style="list-style-type: none"> 737-8200 Airplane except as noted below | | |
| | 25.1317(a) | | | N/A | Avionics: (737-8200 Only) <ul style="list-style-type: none"> Air Data Inertial Reference System (ADIRS) – (ADIRU, ADM) Radio Nav Systems (GLS, ILS, LRR) | | |
| | 25.1317(b) | | | N/A (see note) | Avionics: (737-8200 Only) <ul style="list-style-type: none"> Flight Management Computer System (FMCS) Stall Management Yaw Damper (SMYD) System Flight Controls – Autoflight System: (737-8200 Only) <ul style="list-style-type: none"> Integrated Flight Systems Accessory Unit (IFSAU) Mech/Hyd – Landing Gear Systems: (737-8200 Only) <ul style="list-style-type: none"> Mechanical Brake Control System for Wheel Speed Transducer and Antiskid / Autobrake Control Unit (AACU) | Note: IFSAU under requalification and future revision of TCDS will be requested to remove this exception. | |
| | 25.1317(c) | | | N/A | Environmental Control Systems: (737-8200 Only) <ul style="list-style-type: none"> RAM Air System, Inlet and Exhaust Ducts Flight Deck: (737-8200 Only) <ul style="list-style-type: none"> Crew Oxygen Installations | | |
| 25.1321 | Arrangement and visibility | 737-8/-9/-8200 Associated CRI: PTC F-30 (SC/IM) | | | | | |
| | 25.1321 | CS 11 | CS 12 | CS 17 | <ul style="list-style-type: none"> 737-8/-9/-8200 Airplane except as noted below | | |
| | 25.1321(a),(d),(e) | JAR 13 | JAR 15 | JAR 13 | Flight Controls/Flight Deck Instruments: <ul style="list-style-type: none"> Integrated Standby Flight Display (ISFD) | | |
| 25.1322 | Flight Crew Alerting | 737-8/-9/-8200 Associated CRIs: D-04/MAX (SC/MOC), D-17/MAX, F-14/MAX (Reversion), F-17/MAX (ESF), PTC/F-27 (NG)(SC/IM), PTC F-30 (SC/IM) | | | | | |
| | 25.1322 | See CRI F-14/MAX | See CRI F-14/MAX | CS 17 | <ul style="list-style-type: none"> 737-8/-9/-8200 Airplane except as noted below | | |
| | 25.1322(b)(2), (b)(3), (c)(2), (d), (d)(1), (d)(2) | | | See CRI F-14/MAX | <ul style="list-style-type: none"> 737-8200 Airplane | | |
| 25.1323 | Airspeed indicating system | | | | | | |
| | 25.1323 | CS 11 | CS 12 | CS 17 | <ul style="list-style-type: none"> 737-8/-9/-8200 Airplane except as noted below | | |
| | 25.1323(a) | JAR 13 | JAR 15 | JAR 13 | Flight Controls/Flight Deck Instruments: <ul style="list-style-type: none"> Integrated Standby Flight Display (ISFD) | | |
| | 25.1323(i) | | | CS 11 | Avionics: (737-8200 Only) <ul style="list-style-type: none"> Air Data Inertial Reference System (ADIRS) Environmental Control System: (737-8200 Only) | | |



SECTION: Appendix A – continued

| CS-25 Section No. | Title (or subparagraph) | 737-8 Amdt | 737-9 Amdt | 737-8200 Amdt | System/Area | Notes |
|-------------------|--|----------------|----------------|----------------|---|---|
| | | | | | <ul style="list-style-type: none"> Ice/Rain Protection – Air Data Sensor Heat System <p>Flight Deck: (737-8200 Only)</p> <ul style="list-style-type: none"> Air Data System Installations – Pitot Probes and Elevator Feel Probes | |
| 25.1324 | Flight instrument external probes | Does not exist | Does not exist | N/A | <ul style="list-style-type: none"> 737-8200 Airplane | |
| 25.1325 | Static pressure systems | | | | | |
| | 25.1325 | CS 11 | CS 12 | CS 17 | <ul style="list-style-type: none"> 737-8/-9/-8200 Airplane except as noted below | |
| | 25.1325(b) | | | CS 11 | <p>Avionics: (737-8200 Only)</p> <ul style="list-style-type: none"> Air Data Inertial Reference System (ADIRS) <p>Environmental Control System: (737-8200 Only)</p> <ul style="list-style-type: none"> Ice/Rain Protection – Air Data Sensor Heat System <p>Flight Deck:(737-8200 Only)</p> <ul style="list-style-type: none"> Air Data System Installation – Static Ports Installation | |
| | 25.1325(d) | JAR 13 | JAR 15 | JAR 13 | <p>Flight Controls/Flight Deck Instruments:</p> <ul style="list-style-type: none"> Integrated Standby Flight Display (ISFD) | |
| 25.1326 | Pilot heat indication systems | CS 11 | CS 12 | CS 11 | <ul style="list-style-type: none"> 737-8/-9/-8200 Airplane | |
| 25.1327 | Direction Indicator | CS 11 | CS 12 | CS 17 | <ul style="list-style-type: none"> 737-8/-9/-8200 Airplane | At JAR 13, section called Magnetic direction indicator. |
| 25.1328 | Removed [Direction Indicator] | N/A | N/A | N/A | | Not applicable |
| 25.1329 | Flight Guidance system | | | | | |
| | | | | | 737-8/-9/-8200 Associated CRI: PTC/F-27 (NG)(SC/IM) | |
| | 25.1329 | CS 11 | CS 12 | CS 11 | <ul style="list-style-type: none"> 737-8/-9/-8200 Airplane | |
| 25.1331 | Instruments using power supply | | | | | |
| | 25.1331 | CS 11 | CS 12 | CS 17 | <ul style="list-style-type: none"> 737-8/-9/-8200 Airplane except as noted below | |
| | 25.1331(a),(b) | JAR 13 | JAR 15 | JAR 13 | <p>Flight Controls/Flight Deck Instruments:</p> <ul style="list-style-type: none"> Integrated Standby Flight Display (ISFD) | |
| 25.1333 | Instrument systems | CS 11 | CS 12 | CS 17 | <ul style="list-style-type: none"> 737-8/-9/-8200 Airplane | |
| 25.1337 | Powerplant instruments | CS 11 | CS 12 | CS 17 | <ul style="list-style-type: none"> 737-8/-9/-8200 Airplane | |
| 25.1351 | General (Electrical Systems and Equipment) | CS 11 | CS 12 | CS 17 | <ul style="list-style-type: none"> 737-8/-9/-8200 Airplane | |
| 25.1353 | Electrical equipment and installation | | | | | |
| | | | | | OP 90/1 only amended 25.1353(c)(6)(ii), (c)(6)(iii),and(d). OP 90/1 applied to all 25.1353 exceptions. | |
| | | | | | 737-8/-9/-8200 Associated CRIs: F-GEN-11 (SC), PTC F-29 (NG) (SC) | |
| | 25.1353 | CS 11 | CS 12 | CS 17 | <ul style="list-style-type: none"> 737-8/-9/-8200 Airplane except as noted below | |
| | 25.1353(a), (b) | JAR 13 OP 90/1 | JAR 15 | JAR 13 OP 90/1 | <p>Environmental Control System:</p> <ul style="list-style-type: none"> Advisory Ice Detection System Cargo Smoke Detection System | |



SECTION: Appendix A – continued

| CS-25 Section No. | Title (or subparagraph) | 737-8 Amdt | 737-9 Amdt | 737-8200 Amdt | System/Area | Notes |
|-------------------|---|---|----------------|---------------|---|---|
| | | | | | <ul style="list-style-type: none"> ▪ Ice/Rain Protection – Air Data Sensor Heat System ▪ RAM Air System, Inlet and Exhaust Ducts ▪ Window Heat System ▪ Windshield Wipers System | |
| | 25.1353(a), (b), (d) | JAR 13 OP 90/1 | JAR 15 | JAR 15 | <p>Interiors: EWIS components integral to the following interiors designs:</p> <ul style="list-style-type: none"> ▪ Closets ▪ Galleys ▪ Lavatories ▪ Passenger Seats ▪ Windscreens/Partitions | All design areas comply with the EWIS requirements at CS-25 Amendment 11(-8) or Amendment 12 (-9) or Amendment 17 (-8200) except the noted except the noted Interior areas. |
| | 25.1353(b) | N/A | N/A | | <p>Interiors: EWIS components integral to the following interior designs:</p> <ul style="list-style-type: none"> ▪ Closets ▪ Galleys ▪ Lavatories ▪ Passenger Seats ▪ Windscreens/Partitions | All design areas comply with the EWIS requirements at CS-25 Amendment 11(-8) or Amendment 12 (-9) except the noted Interior areas. |
| 25.1355 | Distribution system | CS 11 | CS 12 | CS 17 | <ul style="list-style-type: none"> ▪ 737-8/-9/-8200 Airplane | |
| 25.1357 | Circuit protective devices | CS 11 | CS 12 | CS 17 | <ul style="list-style-type: none"> ▪ 737-8/-9/-8200 Airplane | |
| 25.1359 | Removed [Electrical system fire and smoke protection] | N/A | Does not exist | N/A | | Not applicable |
| 25.1360 | Precautions against injury | JAR 25X1360 was re-designated to 25.1360 at JAR 16; At JAR 13, designated as JAR 25X1360. | | | | |
| | 25.1360 | CS 11 | CS 12 | CS 17 | <ul style="list-style-type: none"> ▪ 737-8/-9/-8200 Airplane except as noted below | |
| | 25X1360 | JAR 13 | JAR 15 | JAR 13 | <p>Environmental Control System:</p> <ul style="list-style-type: none"> ▪ Advisory Ice Detection System ▪ Cargo Smoke Detection System ▪ Ice/Rain Protection - Air Data Sensor Heat System ▪ RAM Air System, Inlet and Exhaust Ducts ▪ Window Heat System ▪ Windshield Wipers System <p>Flight Controls/Flight Deck Instruments:</p> <ul style="list-style-type: none"> ▪ Floodlights <p>Mech/Hyd – Landing Gear Systems:</p> <ul style="list-style-type: none"> ▪ Mechanical Brake Control System including Antiskid/Auto brake | |
| 25.1362 | Electrical supplies for emergency conditions | CS 11 | CS 12 | CS 17 | <ul style="list-style-type: none"> ▪ 737-8/-9/-8200 Airplane | |
| 25.1363 | Electrical system tests | CS 11 | CS 12 | CS 17 | <ul style="list-style-type: none"> ▪ 737-8/-9/-8200 Airplane | |
| 25.1365 | Electrical appliances, motors, and transformers | Introduced at JAR Change 16 | | | | |



SECTION: Appendix A – continued

| CS-25 Section No. | Title (or subparagraph) | 737-8 Amdt | 737-9 Amdt | 737-8200 Amdt | System/Area | Notes |
|----------------------|----------------------------|---------------|---------------|------------------|--|-------|
| | 25.1365 | CS 11 | CS 12 | CS 17 | <ul style="list-style-type: none"> ▪ 737-8/-9/-8200 Airplane except as noted below | |
| | 25.1365(d) | N/A | N/A | N/A | <p>Avionics:</p> <ul style="list-style-type: none"> ▪ Airborne Data Loading System ▪ Air Traffic Control (ATC) ▪ Cockpit Voice Recorder (CVR) System ▪ Communications Management Unit (CMU) System ▪ Flight Deck Audio System ▪ Flight Deck Printer ▪ High Frequency (HF) Communications System ▪ Radio Nav Systems (ADF, DME, GLS, GPS, ILS, LRRRA, VOR/MB) ▪ Satellite Communications (SATCOM) System ▪ Selective Call (SELCAL) System ▪ Traffic Collision Avoidance System (TCAS) ▪ Very High Frequency (VHF) Communications Systems <p>Environmental Control System:</p> <ul style="list-style-type: none"> ▪ Advisory Ice Detection System ▪ RAM Air System, Inlet and Exhaust Ducts ▪ Windshield Wipers System <p>Flight Deck:</p> <ul style="list-style-type: none"> ▪ PC Power System <p>Interiors:</p> <ul style="list-style-type: none"> ▪ Attendant Control Panel (ACP) ▪ Cabin Interphone ▪ Cabin (Passenger) Telecommunications ▪ Closets ▪ Emergency Lighting ▪ General Lighting ▪ Galleys ▪ In-Flight Entertainment System ▪ Lavatories ▪ Passenger Address System ▪ Passenger Seats ▪ PC Power System ▪ PRAM ▪ Service Outlets ▪ Video Control Center (737-8/-9 only) ▪ Video Surveillance | |



SECTION: Appendix A – continued

| CS-25 Section No. | Title (or subparagraph) | 737-8 Amdt | 737-9 Amdt | 737-8200 Amdt | System/Area | Notes |
|-------------------|---|--|----------------|---------------|--|----------------|
| | | | | | <ul style="list-style-type: none"> Water and Waste Systems Windscreens/Partitions <p>Mech/Hyd – Landing Gear Systems:</p> <ul style="list-style-type: none"> Mechanical Brake Control System including Antiskid/Auto Brake | |
| 25.1381 | Instrument light | | | | | |
| | 25.1381 | CS 11 | CS 12 | CS 17 | <ul style="list-style-type: none"> 737-8/-9/-8200 Airplane except as noted below | |
| | 25.1381 | JAR 13 | JAR 15 | JAR 13 | <p>Flight Controls/Flight Deck Instruments:</p> <ul style="list-style-type: none"> Floodlights <p>Flight Deck:</p> <ul style="list-style-type: none"> Door – Flight Deck Access System (FDAS) | |
| | 25.1381(a),(b) | JAR 13 | JAR 15 | JAR 13 | <p>Flight Controls/Flight Deck Instruments:</p> <ul style="list-style-type: none"> Integrated Standby Flight Display (ISFD) | |
| 25.1383 | Landing lights | CS 11 | CS 12 | CS 17 | <ul style="list-style-type: none"> 737-8/-9/-8200 Airplane | |
| 25.1385 | Position light system installation | CS 11 | CS 12 | CS 17 | <ul style="list-style-type: none"> 737-8/-9/-8200 Airplane | |
| 25.1387 | Position light system dihedral angles | CS 11 | CS 12 | CS 17 | <ul style="list-style-type: none"> 737-8/-9/-8200 Airplane | |
| 25.1389 | Position light distribution and intensities | 737-8/-9/-8200 Associated CRI: F-15 (NG) (ESF) | | | | |
| | 25.1389 | CS 11 | CS 12 | CS 17 | <ul style="list-style-type: none"> 737-8/-9/-8200 Airplane | |
| 25.1391 | Minimum intensities in the horizontal plane of forward and rear position lights | CS 11 | CS 12 | CS 17 | <ul style="list-style-type: none"> 737-8/-9/-8200 Airplane | |
| 25.1393 | Minimum intensities in any vertical plane of forward and rear position lights | CS 11 | CS 12 | CS 17 | <ul style="list-style-type: none"> 737-8/-9/-8200 Airplane | |
| 25.1395 | Maximum intensities in overlapping beams of forward and rear position lights | CS 11 | CS 12 | CS 17 | <ul style="list-style-type: none"> 737-8/-9/-8200 Airplane | |
| 25.1397 | Color specifications | CS 11 | CS 12 | CS 17 | <ul style="list-style-type: none"> 737-8/-9/-8200 Airplane | |
| 25.1401 | Anti-collision light system | CS 11 | CS 12 | CS 17 | <ul style="list-style-type: none"> 737-8/-9/-8200 Airplane | |
| 25.1403 | Wing Icing Detection Lights | CS 11 | CS 12 | CS 11 | <ul style="list-style-type: none"> 737-8/-9/-8200 Airplane | |
| 25.1411 | General (Safety Equipment) | 737-8/-9/-8200 Associated CRI: E-11 (NG) (ESF) | | | | |
| | 25.1411 | CS 11 | CS 12 | CS 17 | <ul style="list-style-type: none"> 737-8/-9/-8200 Airplane | |
| 25.1413 | Removed [Safety belts] | N/A | Does not exist | N/A | | Not applicable |
| 25.1415 | Ditching Equipment | CS 11 | CS 12 | CS 17 | <ul style="list-style-type: none"> 737-8/-9/-8200 Airplane | |
| 25.1416 | Removed [Pneumatic de-icer boot system] | N/A | Does not exist | N/A | | Not applicable |
| 25.1419 | Ice protection | Note: CS 25 Appendix C is at CRI B-07/MAX. | | | | |
| | 25.1419 | CS 11 | CS 12 | CS 11 | <ul style="list-style-type: none"> 737-8/-9/-8200 Airplane except as noted below | |
| | 25.1419(e),(f),(g),(h) | N/A | N/A | N/A | <ul style="list-style-type: none"> 737-8/-9/-8200 Airplane | |
| 25.1420 | Supercooled large drop icing conditions | Does not exist | Does not exist | N/A | <ul style="list-style-type: none"> 737-8200 Airplane | |
| 25.1421 | Megaphones | CS 11 | CS 12 | CS 17 | <ul style="list-style-type: none"> 737-8/-9/-8200 Airplane | |
| 25.1423 | Public address system | CS 11 | CS 12 | CS 17 | <ul style="list-style-type: none"> 737-8/-9/-8200 Airplane | |
| 25.1431 | Electronic Equipment | OP 90/1 applies to 25.1431(d) only, JAA/737-700/SC/F-01 affects JAR 25.1431(a). 737-8/-9/-8200 Associated CRIs: F-01 (NG) (SC), PTC/F-17 (NG)(SC), PTC/F-27 (NG)(SC/IM), PTC F-30 (SC/IM) | | | | |
| | 25.1431 | CS 11 | CS 12 | CS 17 | <ul style="list-style-type: none"> 737-8/-9/-8200 Airplane | |



SECTION: Appendix A – continued

| CS-25 Section No. | Title (or subparagraph) | 737-8 Amdt | 737-9 Amdt | 737-8200 Amdt | System/Area | Notes |
|-------------------|--|---------------------------|---------------------------|---------------------------|--|--|
| 25.1433 | Vacuum systems | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.1435 | Hydraulic Systems | | | | | |
| | 25.1435 | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane except as noted below | |
| | 25.1435(a), (b)(2) | JAR 13, JAR 15 (see note) | JAR 13, JAR 15 (see note) | JAR 13, JAR 15 (see note) | Mech/Hyd – Landing Gear Systems: Mechanical Brake Control System including Antiskid/Auto brake | Note: Within the brake control system, only the brake hydraulic system flow limiter and parking brake demonstration is certified to JAR 15. |
| | 25.1435(a), (b)(2) | JAR 13 | JAR 15 | JAR 13 | Systems – Flight Controls: Aileron Actuator Elevator Actuator Elevator Feel Actuator Elevator Feel Computer Elevator Feel Shift Module Elevator/Lateral Autopilot Actuators High Lift System Rudder Actuator Standby Rudder Actuator | |
| 25.1436 | Pneumatic systems – high pressure | | | | 737-8/-9/-8200 Associated CRI: D-18(NG) (ESF) | |
| | 25.1436 | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.1438 | Pressurization and low pressure pneumatic system | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.1439 | Protective breathing equipment | | | | | |
| | 25.1439 | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane except as noted below | |
| | 25.1439(a) | JAR 13 | JAR 15 | | Flight Deck: (737-8/-9 Only) Crew Oxygen Installations Miscellaneous/Emergency Equipment(737-8/-9 only) - Protective Breathing Equipment (PBE) Installation Interiors: 737-8/-9 Only Portable Emergency Equipment and Life Line | |
| 25.1441 | Oxygen equipment and supply | | | | 737-8/-9/-8200 Associated CRI: F-GEN9-3 (ESF) | |
| | 25.1441 | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane except as noted below | |
| | 25.1441(a) | JAR 13 (see note) | JAR 15 | | Flight Deck: (737-8/-9 Only) Crew Oxygen Installations Interiors: (737-8/-9 Only) Door and Doorway Linings/Headers Lavatories Passenger Service Units (PSU) and PSU Video Monitors Portable Emergency Equipment and Life Line | Note: For CS 25.1443 through 25.1453, see specific regulation for amendment level |
| | 25.1441(c) | JAR 13 | JAR 15 | JAR 13 (see note) | Interiors: Door and Doorway Linings/Headers (737-8/-9) | Note: For CS 25.1443 through 25.1453 see specific regulation for |



SECTION: Appendix A – continued

| CS-25 Section No. | Title (or subparagraph) | 737-8 Amdt | 737-9 Amdt | 737-8200 Amdt | System/Area | Notes | |
|-------------------|---|---|---------------------|----------------|--|--|--|
| | | | | | only) ▪ Lavatories (737-8/-9 only) ▪ Passenger Service Units (PSU) and PSU Video Monitors (737-8/-9 only)Oxygen systems (Integral to Areas of the Doorway Linings, Galleys, Lavatories, Passenger Service Units (PSU), and Portable Emergency Equipment) (737-8200 only) | amendment level | |
| 25.1443 | Minimum mass flow of supplemental oxygen | 737-8/-9/-8200 Associated CRIs: F-GEN9-1 (ESF), F-40/PTC (ESF POST-ATC ONLY) | | | | | |
| | 25.1443 | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | | |
| 25.1445 | Equipment standards for the oxygen distributing system | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | | |
| 25.1447 | Equipment standards for oxygen dispensing units | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | | |
| 25.1449 | Means for determining use of oxygen | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | | |
| 25.1450 | Chemical oxygen generators | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | | |
| 25.1451 | Removed [Fire protection for oxygen equipment] | N/A | Does not exist | Does not exist | | Not applicable | |
| 25.1453 | Protection of oxygen equipment from rupture | JAR 13 | JAR 15 | JAR 13 | ▪ 737-8/-9/-8200 Airplane | | |
| 25.1455 | Draining of fluids submit to freezing | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | | |
| 25.1457 | Cockpit voice recorder | 737-8/-9/-8200 Associated CRI: PTC F-37 (SC/IM) | | | | | |
| | 25.1457 | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | | |
| 25.1459 | Flight recorders | 737-8/-9/-8200 Associated CRIs: PTC/F-17 (NG)(SC), PTC/F-27 (NG)(SC/IM), PTC F-30 (SC/IM), PTC F-37 (SC/IM) | | | | | |
| | 25.1459 | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | | |
| 25.1461 | Equipment containing high-energy rotors | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | | |
| 25.1499 | Removed [Domestic Services and Appliances] | N/A | N/A | N/A | | Not applicable | |
| 25.1501 | General (Operating Limitations and Information) | CS 13 | CS 13 | CS 17 | ▪ 737-8/-9/-8200 Airplane | | |
| 25.1503 | Airspeed limitations: general | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | | |
| 25.1505 | Maximum operating limit speed | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | | |
| 25.1507 | Maneuvering speed | CS11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | | |
| 25.1511 | Flap extended speed | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | | |
| 25.1513 | Minimum control speed | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | | |
| 25.1515 | Landing gear speeds | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | | |
| 25.1516 | Other speed limitations | CS 11 (see note) | CS 12 (see note) | CS 17 | ▪ 737-8/-9/-8200 Airplane | No other speed limitations required for the 737-8/-9/-8200 type design | |
| | Note: At JAR 13 this regulation was identified as 25X1516. | | | | | | |
| 25.1517 | Rough Air Speed, VRA | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | | |
| 25.1519 | Weight, center of gravity, and weight distribution | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | | |
| 25.1521 | Powerplant limitations | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | | |
| 25.1523 | Minimum flight crew | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | | |
| 25.1524 | Removed [Systems and equipment limitations] | N/A | N/A | N/A | | Not applicable | |
| 25.1525 | Kinds of operation | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | | |
| 25.1527 | Ambient air temperature and operating altitude | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | | |
| 25.1529 | Instructions for Continued Airworthiness | 737-8/-9/-8200 Associated CRIs: G-GEN1 (ESF), PTC F-29 (NG)(SC) | | | | | |



SECTION: Appendix A – continued

| CS-25 Section No. | Title (or subparagraph) | 737-8 Amdt | 737-9 Amdt | 737-8200 Amdt | System/Area | Notes |
|-------------------|--|--|------------|---------------|--|--|
| | 25.1529 | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.1531 | Maneuvering flight load factors | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.1533 | Additional operating limitations | CS 11 | CS 12 | CS 11 | 737-8/-9/-8200 Airplane | |
| 25.1535 | ETOPS design approval | CS 11 | CS 12 | N/A | 737-8/-9/-8200 Airplane | Not applicable POST-ATC (737-8200 only) |
| 25.1541 | General (Markings and Placards) | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.1543 | Instrument markings: general | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.1545 | Airspeed limitation information | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.1547 | Magnetic direction indicator | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.1549 | Powerplant instruments | 737-8/-9/-8200 Associated CRI: F-07/MAX (ESF) | | | | |
| | 25.1549 | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.1551 | Oil quantity indicator | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.1553 | Fuel quantity indicator | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.1555 | Control markings | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.1557 | Miscellaneous markings and placards | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.1561 | Safety equipment | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.1563 | Airspeed placard | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.1581 | General (Aeroplane Flight Manual) | 737-8/-9/-8200 Associated CRIs: PTC/F-27 (NG)(SC/IM), PTC F-30 (SC/IM) | | | | |
| | 25.1581 | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.1583 | Operating limitations | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.1585 | Operating procedures | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | 737-8/-9 Associated CRI: PTC F-30 (SC/IM) |
| 25.1587 | Performance information | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.1591 | Performance information for operations with contaminated runway surface conditions | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.1593 | Exposure to volcanic cloud hazards | CS 13 | CS 13 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.1701 | Definition | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | |
| 25.1703 | Function and installation: EWIS | Introduced at CS Amdt 5 | | | | |
| | 25.1703 | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane except as noted below | |
| | 25.1703 | N/A | N/A | N/A | Interiors: EWIS components integral to the following design areas only: ▪ Closets ▪ Galleys ▪ Lavatories ▪ Passenger Seats ▪ Windscreens/Partitions | All design areas comply with the EWIS requirements at CS-25 Amendment 11(-8) or Amendment 12 (-9) or Amendment 17 (-8200) except the noted Interior areas. |
| 25.1705 | Systems and functions: EWIS | Introduced at CS Amdt 5 | | | | |
| | 25.1705 | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane except as noted below | |
| | 25.1705 | N/A | N/A | N/A | Interiors: EWIS components integral to the following design areas only: ▪ Closets ▪ Galleys ▪ Lavatories ▪ Passenger Seats ▪ Windscreens/Partitions | All design areas comply with the EWIS requirements at CS-25 Amendment 11(-8) or Amendment 12 (-9) or Amendment 17 (-8200) except the noted Interior areas. |
| 25.1707 | System separation: EWIS | Introduced at CS Amdt 5 | | | | |
| | 25.1707 | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane except as noted below | |



SECTION: Appendix A – continued

| CS-25 Section No. | Title (or subparagraph) | 737-8 Amdt | 737-9 Amdt | 737-8200 Amdt | System/Area | Notes |
|-------------------|--|------------|------------|---------------|---|--|
| | 25.1707 | N/A | N/A | N/A | Interiors: EWIS components integral to the following design areas only: <ul style="list-style-type: none"> ▪ Closets ▪ Galleys ▪ Lavatories ▪ Passenger Seats ▪ Windscreens/Partitions | All design areas comply with the EWIS requirements at CS-25 Amendment 11(-8) or Amendment 12 (-9) or Amendment 17 (-8200) except the noted Interior areas. |
| 25.1709 | System safety: EWIS | | | | | Introduced at CS Amdt 5 |
| | 25.1709 | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane except as noted below | |
| | 25.1709 | N/A | N/A | N/A | Interiors: EWIS components integral to the following design areas only: <ul style="list-style-type: none"> ▪ Closets ▪ Galleys ▪ Lavatories ▪ Passenger Seats ▪ Windscreens/Partitions | All design areas comply with the EWIS requirements at CS-25 Amendment 11(-8) or Amendment 12 (-9) or Amendment 17 (-8200) except the noted Interior areas. |
| 25.1711 | Component identification: EWIS | | | | | Introduced at CS Amdt 5 |
| | 25.1711 | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane except as noted below | |
| | 25.1711 | N/A | N/A | N/A | Interiors: EWIS components integral to the following design areas only: <ul style="list-style-type: none"> ▪ Closets ▪ Galleys ▪ Lavatories ▪ Passenger Seats ▪ Windscreens/Partitions | All design areas comply with the EWIS requirements at CS-25 Amendment 11(-8) or Amendment 12 (-9) or Amendment 17 (-8200) except the noted Interior areas. |
| 25.1713 | Fire protection: EWIS | | | | | Introduced at CS Amdt 5 |
| | 25.1713 | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane except as noted below | |
| | 25.1713 | N/A | N/A | N/A | Interiors: EWIS components integral to the following design areas only: <ul style="list-style-type: none"> ▪ Closets ▪ Galleys ▪ Lavatories ▪ Passenger Seats ▪ Windscreens/Partitions | All design areas comply with the EWIS requirements at CS-25 Amendment 11(-8) or Amendment 12 (-9) or Amendment 17 (-8200) except the noted Interior areas. In lieu of compliance to 25.869(a)(3) and 25.1713, compliance to 25.869(a)(4) [JAR 15] may be shown for the noted areas. |
| 25.1715 | Electrical bonding and protection against static electricity: EWIS | | | | | Introduced at CS Amdt 5 |
| | 25.1715 | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane except as noted below | |
| | 25.1715 | N/A | N/A | N/A | Interiors: EWIS components integral to the following design areas only: <ul style="list-style-type: none"> ▪ Closets ▪ Galleys | All design areas comply with the EWIS requirements at CS-25 Amendment 11(-8) or Amendment 12 (-9) or Amendment 17 (-8200) except the noted Interior |



SECTION: Appendix A – continued

| CS-25 Section No. | Title (or subparagraph) | 737-8 Amdt | 737-9 Amdt | 737-8200 Amdt | System/Area | Notes |
|-------------------|--|------------|------------|---------------|---|--|
| | | | | | <ul style="list-style-type: none"> ▪ Lavatories ▪ Passenger Seats ▪ Windscreens/Partitions | areas. |
| 25.1717 | Circuit protective devices: EWIS | | | | | Introduced at CS Amdt 5 |
| | 25.1717 | CS 11 | CS 12 | CS 17 | <ul style="list-style-type: none"> ▪ 737-8/-9/-8200 Airplane except as noted below | |
| | 25.1717 | N/A | N/A | N/A | <p>Interiors: EWIS components integral to the following design areas only:</p> <ul style="list-style-type: none"> ▪ Closets ▪ Galleys ▪ Lavatories ▪ Passenger Seats ▪ Windscreens/Partitions | All design areas comply with the EWIS requirements at CS-25 Amendment 11(-8) or Amendment 12 (-9) or Amendment 17 (-8200) except the noted Interior areas. |
| 25.1719 | Accessibility provisions: EWIS | | | | | Introduced at CS Amdt 5 |
| | 25.1719 | CS 11 | CS 12 | CS 17 | <ul style="list-style-type: none"> ▪ 737-8/-9/-8200 Airplane except as noted below | |
| | 25.1719 | N/A | N/A | N/A | <p>Interiors: EWIS components integral to the following design areas only:</p> <ul style="list-style-type: none"> ▪ Closets ▪ Galleys ▪ Lavatories ▪ Passenger Seats ▪ Windscreens/Partitions | All design areas comply with the EWIS requirements at CS-25 Amendment 11(-8) or Amendment 12 (-9) or Amendment 17 (-8200) except the noted Interior areas. |
| 25.1721 | Protection of EWIS | | | | | Introduced at CS Amdt 5 |
| | 25.1721 | CS 11 | CS 12 | CS 17 | <ul style="list-style-type: none"> ▪ 737-8/-9/-8200 Airplane except as noted below | |
| | 25.1721 | N/A | N/A | N/A | <p>Interiors: EWIS components integral to the following design areas only:</p> <ul style="list-style-type: none"> ▪ Closets ▪ Galleys ▪ Lavatories ▪ Passenger Seats ▪ Windscreens/Partitions | All design areas comply with the EWIS requirements at CS-25 Amendment 11(-8) or Amendment 12 (-9) or Amendment 17 (-8200) except the noted Interior areas. |
| 25.1723 | Flammable Fluid Protection: EWIS | CS 11 | CS 12 | CS 17 | <ul style="list-style-type: none"> ▪ 737-8/-9/-8200 Airplane | |
| 25.1725 | Powerplants: EWIS | CS 11 | CS 12 | CS 17 | <ul style="list-style-type: none"> ▪ 737-8/-9/-8200 Airplane | |
| 25.1727 | Flammable Fluid Shutoff Means: EWIS | CS 11 | CS 12 | CS 17 | <ul style="list-style-type: none"> ▪ 737-8/-9/-8200 Airplane | |
| 25.1729 | Instructions for Continued Airworthiness: EWIS | | | | | 7-8/-9/-8200 Associated CRIs: G-GEN1 (ESF) |
| | 25.1729 | CS 11 | CS 12 | CS 17 | <ul style="list-style-type: none"> ▪ 737-8/-9/-8200 Airplane except as noted below | |
| | 25.1729 | N/A | N/A | N/A | <p>Interiors: EWIS components integral to the following design areas only:</p> <ul style="list-style-type: none"> ▪ Closets ▪ Galleys ▪ Lavatories ▪ Passenger Seats ▪ Windscreens/Partitions | All design areas comply with the EWIS requirements at CS-25 Amendment 11(-8) or Amendment 12 (-9) or Amendment 17 (-8200) except the noted Interior areas. |
| 25.1731 | Powerplant and APU fire detector system; EWIS | CS 11 | CS 12 | CS 17 | <ul style="list-style-type: none"> ▪ 737-8/-9/-8200 Airplane | |
| 25J901 | Installation | CS 11 | CS 12 | CS 17 | <ul style="list-style-type: none"> ▪ 737-8/-9/-8200 Airplane | 737-800/-900ER JAR |



SECTION: Appendix A – continued

| CS-25 Section No. | Title (or subparagraph) | 737-8 Amdt | 737-9 Amdt | 737-8200 Amdt | System/Area | Notes |
|-------------------|------------------------------------|------------|------------|---------------|---------------------------|--|
| | | | | | | 25A901 |
| 25J903 | Auxiliary power unit. | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | 737-800/-900ER JAR 25A903, 25B903 |
| 25J939 | APU operating characteristics | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | 737-800/-900ER JAR 25A9039 |
| 25J943 | Negative acceleration | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | 737-800/-900ER JAR 25A943 |
| 25J951 | General.(Fuel System) | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | 737-800/-900ER JAR 25B951 |
| 25J952 | Fuel system analysis and test. | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | 737-800/-900ER JAR 25A952 |
| 25J953 | Fuel system independence. | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | 737-800/-900ER JAR 25A953 |
| 25J955 | Fuel flow. | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | 737-800/-900ER JAR 25B955 |
| 25J961 | Fuel system hot weather operation. | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | 737-800/-900ER JAR 25B961 |
| 25J977 | Fuel tank outlet. | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | 737-800/-900ER JAR 25B977 |
| 25J991 | Fuel pumps. | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | 737-800/-900ER JAR 25B991 |
| 25J993 | Fuel system lines and fittings | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | 737-800/-900ER JAR 25A993 |
| 25J994 | Fuel system components | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | 737-800/-900ER JAR 25A994 |
| 25J995 | Fuel valves | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | 737-800/-900ER JAR 25A995 |
| 25J997 | Fuel strainer or filter | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | 737-800/-900ER JAR 25B997 |
| 25A999 | Removed [Fuel system drains] | N/A | N/A | N/A | | Not applicable |
| 25J1011 | Oil system General | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | 737-800/-900ER JAR 25A1011, 25B1011 |
| 25J1017 | Oil lines and fittings | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | 737-800/-900ER JAR 25A1017 |
| 25J1019 | Oil filter | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |
| 25J1021 | Oil system drains | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | 737-800/-900ER JAR 25A1021 |
| 25J1023 | Oil radiators | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | 737-800/-900ER JAR 25A1023 |
| 25J1025 | Oil valves | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | 737-800/-900ER JAR 25A1025 |
| 25J1041 | General (Cooling) | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | 737-800/-900ER JAR 25A1041 |
| 25J1043 | Cooling tests | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | 737-800/-900ER JAR 25A1043 |
| 25J1045 | Cooling test procedures | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | 737-800/-900ER JAR 25A1045 |
| 25J1091 | Air intake | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | 737-800/-900ER JAR 25A1091, 25B1091 |
| 25J1093 | Air intake system icing protection | | | | | 737-800/-900ER JAR 25A1093, 25B1093 737-8/-9/-8200 Associated CRI: F-11/MAX (SC/IM) |
| | 25J1093 | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |
| 25J1103 | Air intake system ducts | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | 737-800/-900ER JAR 25A1103 |
| 25A1105, 25B1105 | Air intake system screens | N/A | N/A | N/A | | Not applicable |
| 25J1106 | Bleed air duct systems | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |
| 25J1121 | General (Exhaust System) | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | 737-800/-900ER JAR |



SECTION: Appendix A – continued

| CS-25 Section No. | Title (or subparagraph) | 737-8 Amdt | 737-9 Amdt | 737-8200 Amdt | System/Area | Notes | |
|-------------------|--|--|-----------------------------------|-------------------|---|---|--|
| | | | | | | 25A1121 | |
| 25J1123 | Exhaust piping | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | 737-800/-900ER JAR 25A1123 | |
| 25J1141 | APU controls | 737-8/-9/-8200 Associated CRIs: J-01/MAX (Reversion) | | | | | |
| | 25J1141 | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane except as noted below | | |
| | 25J1141(b)(2) | See CRI J-01/ MAX | See CRI J-01/ MAX | See CRI J-01/ MAX | Propulsion – APU APU Fuel Shut Off Valve (FSOV) | Note : FAR 25.1141(f) did not exist at Amdt 25-11 (737-700 CRI J-04) | |
| 25J1163 | APU accessories | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | 737-800/-900ER JAR 25A1163, 25B1163 | |
| 25J1165 | APU ignition systems | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | 737-800/-900ER JAR 25B1165 | |
| 25J1181 | Designated fire zone | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | 737-800/-900ER JAR 25A1181 | |
| 25J1183 | Lines, fittings and components | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | 737-800/-900ER JAR 25A1183 | |
| 25J1185 | Flammable fluids | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | 737-800/-900ER JAR 25A1185 | |
| 25J1187 | Drainage and ventilation of fire zones | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | 737-800/-900ER JAR 25A1187 | |
| 25J1189 | Shut-off means | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | 737-800/-900ER JAR 25A1189 | |
| 25J1191 | Firewalls | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | 737-800/-900ER JAR 25A1191 | |
| 25J1193 | APU compartment | CS 11 with 25J1193(e)(3) at CS 13 | CS 12 with 25J1193(e)(3) at CS 13 | CS 17 | 737-8/-9/-8200 Airplane | 737-800/-900ER JAR 25A1193 | |
| 25J1195 | Fire extinguisher systems | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | 737-800/-900ER JAR 25A1195) | |
| 25J1197 | Fire extinguishing agents | CS 11 | CS 12 | CS 17 | 737-8/-9 /-8200Airplane | 737-800/-900ER JAR 25A1197 | |
| 25J1199 | Extinguishing agent containers | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | 737-800/-900ER JAR 25A1199 | |
| 25J1201 | Fire extinguishing system materials | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | 737-800/-900ER JAR 25A1201 | |
| 25J1203 | Fire-detector system | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | 737-800/-900ER JAR 25A1203 | |
| 25J1207 | Compliance | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | 737-800/-900ER JAR 25A1207 | |
| 25J1305 | APU instruments | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | 737-800/-900ER JAR 25A1305, 25B1305 | |
| 25J1337 | APU instruments | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | 737-800/-900ER JAR 25A1337 | |
| 25J1501 | General (Operating Limitations) | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | | |
| 25J1521 | APU limitations | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | 737-800/-900ER JAR 25A1521 | |
| 25J1527 | Ambient air temperature and operating altitude | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | 737-800/-900ER JAR 25A1527 | |
| 25J1549 | APU instruments | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | 737-800/-900ER JAR 25A1549 | |
| 25J1551 | Oil quantity indicator | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | 737-800/-900ER JAR 25A1551 | |
| 25J1557 | Miscellaneous markings and placards | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | | |
| 25J1583 | Operating limitations | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200 Airplane | 737-800/-900ER JAR 25A1583 | |
| Appendix A | Appendix A (Basic dimensions) | CS 11 | CS 12 | CS 17 | 737-8/-9/-8200Airplane | | |



SECTION: Appendix A – continued

| CS-25 Section No. | Title (or subparagraph) | 737-8 Amdt | 737-9 Amdt | 737-8200 Amdt | System/Area | Notes |
|-------------------|--|---|------------------|------------------|--|---|
| Appendix C | Appendix C (Atmospheric Icing Conditions) | 737-8/-9/-8200 Associated CRI: B-07/MAX (Reversion) | | | | |
| | Appendix C | See CRI B-07/MAX | See CRI B-07/MAX | See CRI B-07/MAX | ▪ 737-8/-9/-8200 Airplane | |
| Appendix D | Appendix D (Criteria for determining minimum flight crew) | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |
| Appendix F | Appendix F (Flammability) | 37-8/-9/-8200 Associated CRI: D-GEN02/PTC (SC/MOC) | | | | |
| | Appendix F | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |
| Appendix H | Appendix H (Instructions for Continuing Airworthiness) | 737-8/-9/-8200 Associated CRI: G-GEN1 (ESF) | | | | |
| | Appendix H | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |
| Appendix I | Appendix I (Automatic Takeoff Thrust Control System (ATTCS)) | N/A | N/A | N/A | | Not applicable |
| Appendix J | Appendix J | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |
| Appendix K | Appendix K (Interaction of Systems and Structure) | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |
| Appendix L | Appendix L | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |
| Appendix M | Appendix M (Fuel Tank Flammability Reduction Means (FRM)) | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |
| Appendix N | Appendix N (Fuel Tank Flammability Exposure) | CS 11 | CS 12 | CS 17 | ▪ 737-8/-9/-8200 Airplane | |
| Appendix O | Appendix O (Supercooled Large Drop icing condition) | | | | | |
| | Appendix O | Does not exist | Does not exist | N/A | ▪ 737-8200 Airplane | |
| Appendix P | Appendix P (Mixed phase and ice crystal icing envelope (deep convective clouds)) | Does not exist | Does not exist | N/A | ▪ 737-8200 Airplane | |
| Appendix Q | Appendix Q (Additional airworthiness requirements for approval of a Steep Approach Landing (SAL) capability) | Does not exist | Does not exist | N/A | | Not applicable |
| Appendix R | Appendix R (HIRF Environments and Equipment HIRF Test Levels) | Associated CRIs: F-01 (NG)(SC) | | | | |
| | Appendix R | Does not exist | Does not exist | CS 17 | ▪ 737-8200 Airplane | |
| | Appendix R | | | N/A | Avionics: (737-8200 only) <ul style="list-style-type: none"> ▪ Air Data Inertial Reference System (ADIRS) – (ADIRU, ADM) ▪ Radio Nav Systems (GLS, ILS, LRRRA) | |
| | Appendix R | | | N/A (see note) | Avionics: (737-8200 only) <ul style="list-style-type: none"> ▪ Flight Management Computer System (FMCS) ▪ Stall Management Yaw Damper (SMYD) System Environmental Control System: (737-8200 only) <ul style="list-style-type: none"> ▪ RAM Air System, Inlet and Exhaust Ducts Flight Controls – Autoflight System: (737-8200 only) <ul style="list-style-type: none"> ▪ Integrated Flight Systems Accessory Unit (IFSAU) Flight Deck: (737-8200 only) <ul style="list-style-type: none"> • Crew Oxygen Installations Mech/Hyd – Landing Gear Systems: (737-8200 only) <ul style="list-style-type: none"> ▪ Mechanical Brake Control System for Wheel Speed | Note: IFSAU under requalification and future revision of TCDS will be requested to remove this exception |



SECTION: Appendix A – continued

| CS-25 Section No. | Title (or subparagraph) | 737-8 Amdt | 737-9 Amdt | 737-8200 Amdt | System/Area | Notes |
|----------------------|----------------------------|---------------|---------------|------------------|---|-------|
| | | | | | Transducer and Antiskid / Autobrake Control Unit (AACU) | |

- END -

