



TYPE-CERTIFICATE DATA SHEET

NO. EASA.A.054

for
Stemme S10

Type Certificate Holder

Stemme AG
Flugplatzstrasse F2 Nr. 6-7
15344 Strausberg
Germany

Variants: Stemme S10
 Stemme S10-V
 Stemme S10-VT
 Stemme S12



Table of Content

Table of Content	2
Section A: Stemme S10.....	3
A.I. General	3
A.II. Certification Basis	3
A.III. Technical Characteristics and Operational Limitations	4
A.IV. Operating and Service Instructions	6
A.V. Notes	7
Section B: Stemme S10-V	8
B.I. General	8
B.II. Certification Basis	8
B.III. Technical Characteristics and Operational Limitations	9
B.IV. Operating and Service Instructions	11
B.V. Notes	11
Section C: Stemme S10-VT	13
C.I. General	13
C.II. Certification Basis	13
C.III. Technical Characteristics and Operational Limitations	14
C.IV. Operating and Service Instructions	16
C.V. Notes	16
Section D: Stemme S12.....	17
D.I. General	17
D.II. Certification Basis	17
D.III. Technical Characteristics and Operational Limitations	18
D.IV. Operating and Service Instructions	20
D.V. Notes	20
Administrative section	21



Section A: Stemme S10

A.I. General

1. Data Sheet No.: EASA.A.054
2. a) Type: Stemme S10
b) Variant: Stemme S10
3. Airworthiness Category: Powered Sailplane, JAR 22 - Utility
4. Type Certificate Holder: Stemme AG
Flugplatzstrasse F2 Nr. 6-7
15344 Strausberg
Germany
5. Manufacturer: Stemme GmbH & Co. KG
Gustav-Meyer-Allee 25
13355 Berlin

Stemme GmbH & Co. KG
Flugplatzstrasse F2 Nr. 7
15344 Strausberg

Stemme AG
Flugplatzstrasse F2 Nr. 7
15344 Strausberg

Stemme AG
Flugplatzstrasse F2 Nr. 6-7
15344 Strausberg
6. LBA Certification Application Date: 30. May 1985
7. LBA Type Certification Date: 31. December 1990
8. This TCDS replaces LBA TCDS No. 846

A.II. Certification Basis

1. Certification Basis: Defined by LBA letter I 3-846/85,
dated 12. June 1985
2. Airworthiness Requirements: Joint Airworthiness Requirements for Sailplanes and
Powered Sailplanes (JAR 22), effective on June 27, 1989
(Change 4 of the English Original Issue)
3. Requirements elected to comply: Preliminary Standards for Structural Substantiation of
Sailplane and Powered Sailplane Components Consisting of
Glass or Carbon Fibre Reinforced Plastics, Issue Jan. 1981
Preliminary Standards for the Substantiation of the Electrical
System of Powered Sailplanes, Issue Feb. 1, 1990.
Standards for the Substantiation of the Electrical System of
Powered Sailplanes, Issue September 15, 1992.



Preliminary Standard for the Substantiation of Indirect Drive Shafts in Power Plants of Powered Sailplanes (JAR 22) (with modifications for S10), dated 05.08.1988.
JAR-22.375 from amendment 22/90/1 (Winglets)

- | | |
|--------------------------------|---|
| 4. Special Conditions: | None |
| 5. Exemptions: | None |
| 6. Equivalent Safety Findings: | None |
| 7. Environmental Standards: | ICAO Annex 16, Volume I (for more details see EASA TCDSN A.054) |

A.III. Technical Characteristics and Operational Limitations

- | | |
|--------------------------------|--|
| 1. Type Design Definition: | Records of the documents defining Type Stemme S 10: dated Okt. 27, 1990, LBA approved, with supplement dated Dec.13, 1991, LBA approved.
Document Record STEMME S10, doc. no. A08-10-000, am.-index 02.a, dated Okt. 17, 1994, LBA approved
Record of Service Bulletins and Airworthiness Directives, Doc.No. P150-981001 in the actual revision. |
| 2. Description: | Selflaunching, twin-seat, all composite construction powered sailplane, with the engine mounted in the center fuselage, propeller shaft system and fully foldable, jointed propeller, 3-piece wing, double panel Schempp-Hirth type airbrakes on the upper wing surface, optional winglets (see V.8). Re-tractable main landing gear with brake, T-tail (fixed horiz. stabilizer with elevator) fin and rudder. |
| 3. Equipment: | Min. Equipment:
1 Air speed indicator (up to 300 km/h)
1 Altimeter
1 Magnetic compass
1 RPM indicator
1 Oil pressure indicator
1 Oil temperature indicator
1 Cylinder head temperature indicator
1 Engine hour meter
2 Fuel quantity indicator
Stallwarning indicator
2 4-Point harness (symmetrical)
2 Automatic or manual parachute
or
2 Back cushion (thickness approx. 10 cm / 3.94 in. when compressed), when flying without parachute
Additional Equipment refer to Flight and Operating Manual |
| 4. Dimensions:
Abmessungen: | Span 23.0 m
Spannweite
Wing area 18.74 m ²
Flügelfläche
Length 8.42 m
Länge |



5. Engine
Limbach L 2400 EB1.AD
EASA Type Certificate Data Sheet No. EASA.E.084
Remark:
Former name of the engine: L 2400 EB1.D. See also Service Bulletin no.17 of company Limbach.
- 5.1 Engine Limits:
Maximum Power RPM 3400 rpm
Maximum Continuous Power RPM 3000 rpm
6. Propellers:
Stemme 10AP-N
LBA-Type Certificate Data Sheet 32.100/1 dated Nov. 16th 1990
- 6.1 Propeller diameter: 1610 mm +/- 2 mm
7. Fluids and Fluid capacities:
Wing tank left: 45.00 l
Wing tank right: 45.00 l
Non-usable amount of fuel: 1.5 l
Optional tank capacity 2 x 60 l (see also V. 6)
8. Launching Hooks: None
9. Weak links: None
10. Air Speeds:
Manoeuvring Speed V_A 180 km/h
Never Exceed Speed V_{NE} 270 km/h
- at flap setting $-10^\circ, -5^\circ, 0^\circ$ V_{FE} 270 km/h
- at flap setting $+5^\circ, +10^\circ$ V_{FE} 180 km/h
- at flap setting L ($+16^\circ$) V_{FE} 140 km/h

Maximum permitted speeds
- in rough air V_{RA} 180 km/h
- max gear operating speed V_{LO} 140 km/h
11. Operational Capability:
Approved for VFR-Day.
VFR Night limited to the vicinity (range of glide ratio) of active airfields approved for night flight operations (see V.9)
12. Maximum Masses:
Max. Mass 850 kg
Max. Mass of Non-Lifting Parts 570 kg
13. Centre of Gravity Range:
Schwerpunktsbereich: Datum: Inner wing leading edge, where upper side of fuselage boom placed at slope 1000 : 84

Forward Limit 254 mm aft of datum point
Rearward Limit 420 mm aft of datum point
14. Seating Capacity: 2
15. Lifetime limitations: Refer to Maintenance Manual
16. Deflection of control surfaces: Refer to Maintenance Manual



A.IV. Operating and Service Instructions

1. Flight manual for the powered sailplane type STEMME S10, Issue Oct. 1, 1990, LBA –approved, or later approved revisions.
2. Maintenance Manual for the Powered Sailplane STEMME S10, Issue Oct. 1, 1990, or later approved revisions.
3. Operating and Maintenance Manual for the engine Limbach L 2400 and series.
4. Small Repair Manual (Document A35-10-SMR), Revision 02.a dated October 13th 1997, or later approved revisions.



A.V. Notes

1. Manufacturing is confined to industrial production.
2. All parts exposed to sun radiation – except the areas for markings and registration – must have a white colour surface.
3. For issuance of the Certificate of Airworthiness pertinent to an individual aircraft the Noise Protection Requirements effective on the day of application are applicable.
4. Only to the s/n 10-3 to 10-10 differing operational limits as well as data are defined by Stemme company in modification bulletins LBA-approved, belonging to the individual s/n.
5. The type certification is valid for the s/n: 10-3 up to 10-10 and starting with 10-12.
6. The optional equipment with 2 x 60 l tanks ex works is allowed according to the modification bulletin Stemme A30-92-077, LBA-approved.
7. Conversion from the model Stemme S10 into the model Stemme S10-V is allowed according to the Stemme Service Bulletin A31-10-010, LBA-approved.
8. The optional equipment with winglets is allowed according to the Service Bulletin Stemme A31-10-023, LBA-approved.
9. VFR Night limited to the vicinity (range of glide ratio) of active airfields approved for night flight operations is allowed when the powered sailplane is equipped for this operation according to national rules and Service Bulletin Stemme A31-10-044 LBA-approved and A31-10-072 EASA-approved.



Section B: Stemme S10-V

B.I. General

1. Data Sheet No.: EASA.A.054
2. a) Type: Stemme S10
b) Variant: Stemme S10-V
3. Airworthiness Category: Powered Sailplane, JAR 22 - Utility
4. Type Certificate Holder: Stemme AG
Flugplatzstrasse F2 Nr. 6-7
15344 Strausberg
Germany
5. Manufacturer: Stemme GmbH & Co. KG
Gustav-Meyer-Allee 25
13355 Berlin

Stemme GmbH & Co. KG
Flugplatzstrasse F2 Nr. 7
15344 Strausberg

Stemme AG
Flugplatzstrasse F2 Nr. 7
15344 Strausberg

Stemme AG
Flugplatzstrasse F2 Nr. 6-7
15344 Strausberg
6. LBA Certification Application Date: 03. February 1992
7. LBA Type Certification Date: 16. September 1994
8. This TCDS replaces LBA TCDS No. 846

B.II. Certification Basis

1. Certification Basis: Defined by LBA letter I 414-846/7/94,
dated 21. July 1994
2. Airworthiness Requirements: Joint Airworthiness Requirements for Sailplanes and
Powered Sailplanes (JAR 22), effective on June 27, 1989
(Change 4 of the English Original Issue)
3. Requirements elected to comply: Standards for Structural Substantiation of Sailplane and
Powered Sailplane Components Consisting of Glass or
Carbon Fibre Reinforced Plastics, Issue July. 1991
Preliminary Standards for the Substantiation of the Electrical
System of Powered Sailplanes, Issue Feb. 1, 1990.
Standards for the Substantiation of the Electrical System of
Powered Sailplanes, Issue September 15, 1992.



Preliminary Standard for the Substantiation of Indirect Drive Shafts in Power Plants of Powered Sailplanes (JAR 22) (with modifications for S10), dated 05.08.1988.
NPA 22E-XX (Proposed Amendment to JAR 22 for Variable Pitch Propellers), Issue March 25, 1993.
JAR-22.375 from amendment 22/90/1 (Winglets)

- | | |
|--------------------------------|---|
| 4. Special Conditions: | None |
| 5. Exemptions: | None |
| 6. Equivalent Safety Findings: | None |
| 7. Environmental Standards: | ICAO Annex 16, Volume I (for more details see EASA TCDSN A.054) |

B.III. Technical Characteristics and Operational Limitations

1. Type Design Definition: Document Record No. A08-10-000, am-index 02.a, dated October 17th, 1994 (record of the documents defining Type Stemme S10), LBA approved.
in addition:
Document Record No. A08-10-039, am-index 03.c, dated Sept. 21, 1994 (supplement for Model S 10-V), LBA approved.
Document Record No. A08-10-239, am.-index 02.a, dated Sept. 29, 2003: variant S 10-V with Fix-Pitch Propeller 10AP-F, LBA approved.
Record of Service Bulletins and Airworthiness Directives, Doc.No. P150-981002 in the actual revision.

2. Description: Selflaunching, twin-seat, all composite construction powered sailplane, with the engine mounted in the center fuselage, propeller shaft system and fully foldable, jointed variable pitch propeller CFRP, 3-piece wing, double panel Schempp-Hirth type airbrakes on the upper wing surface, optional winglets (see V.6). Retractable main landing gear with brake, T-tail (fixed horiz. stabilizer with elevator) fin and rudder.



3. Equipment: Min. Equipment:
1 Air speed indicator (up to 300 km/h)
1 Altimeter
1 Magnetic compass
1 RPM indicator
1 Oil pressure indicator
1 Oil temperature indicator
1 Cylinder head temperature indicator
1 Engine hour meter
2 Fuel quantity indicator
Stallwarning indicator
1 Indicator for Takeoff (low pitch) propeller position
2 4-Point harness (symmetrical)
2 Automatic or manual parachute
or
2 Back cushion (thickness approx. 10 cm / 3.94 in. when compressed), when flying without parachute
Additional Equipment refer to Flight and Operating Manual
4. Dimensions:
Abmessungen: Span 23.0 m
Spannweite
Wing area 18.74 m²
Flügelfläche
Length 8.42 m
Länge
5. Engine Limbach L 2400 EB1.AD
EASA Type Certificate Data Sheet EASA.E.084
Remark:
Former name of the engine: L 2400 EB1.D. See also Service Bulletin no.17 of company Limbach.
- 5.1 Engine Limits: Maximum Power RPM 3400 rpm
Maximum Continuous Power RPM 3000 rpm
6. Propellers: Stemme 10AP-F
LBA-Type Certificate Data Sheet 32.100/4 dated Nov. 12th 2003

Stemme 10AP-V
LBA-Type Certificate Data Sheet 32.100/2 dated August 9th 1994
- 6.1 Propeller diameter: Both Propellers 1610 mm +/- 3 mm
7. Fluids and Fluid capacities: Wing tank left: 45.00 l
Wing tank right: 45.00 l
Non-usable amount of fuel: 1.5 l
Optional tank capacity 2 x 60 l (see also V. 5)
8. Launching Hooks: None
9. Weak links: None



- | | | | | |
|-----|--|--|---------------------------|----------|
| 10. | Air Speeds: | Manoeuvring Speed | V _A | 180 km/h |
| | | Never Exceed Speed | V _{NE} | 270 km/h |
| | | - at flap setting -10°, -5°, 0° | V _{FE} | 270 km/h |
| | | - at flap setting +5°, +10° | V _{FE} | 180 km/h |
| | | - at flap setting L (+16°) | V _{FE} | 140 km/h |
| | | Maximum permitted speeds | | |
| | | - in rough air | V _{RA} | 180 km/h |
| | | - max gear operating speed | V _{LO} | 140 km/h |
| 11. | Operational Capability: | Approved for VFR-Day.
VFR Night limited to the vicinity (range of glide ratio) of active airfields approved for night flight operations (see V.8) | | |
| 12. | Maximum Masses: | Max. Mass | | 850 kg |
| | | Max. Mass of Non-Lifting Parts | | 570 kg |
| 13. | Centre of Gravity Range:
Schwerpunktsbereich: | Datum: Inner wing leading edge, where upper side of fuselage boom placed at slope 1000 : 84 | | |
| | | Forward Limit | 254 mm aft of datum point | |
| | | Rearward Limit | 420 mm aft of datum point | |
| 14. | Seating Capacity: | 2 | | |
| 15. | Lifetime limitations: | Refer to Maintenance Manual | | |
| 16. | Deflection of control surfaces: | Refer to Maintenance Manual | | |

B.IV. Operating and Service Instructions

1. Flight manual for the powered sailplane type STEMME S10-V, Issue Sep. 6, 1994, LBA –approved, or later approved revisions.
2. Maintenance Manual for the Powered Sailplane STEMME S10-V, Edition Sep. 6, 1994, or later approved revisions.
3. Operating and Maintenance Manual for the engine Limbach L 2400 and series.
4. Stemme Maintenance Instruction Doc-No: A35-10-067 for Fix Pitch Propeller 10AP-F, actual revision.
5. Small Repair Manual (Document A35-10-SMR), revision 02.a dated October 13th 1997, or later approved revisions.

B.V. Notes

1. Manufacturing is confined to industrial production.
2. All parts exposed to sun radiation – except the areas for markings and registration – must have a white colour surface.



3. For issuance of the Certificate of Airworthiness pertinent to an individual aircraft the Noise Protection Requirements effective on the day of application are applicable.
4. The Variant Certification is effective from Serial No. 14-001 onwards.
5. The optional equipment with 2 x 60 l tanks ex works is allowed according to the modification bulletin Stemme A30-92-077, LBA-approved.
6. The optional equipment with winglets is allowed according to the Service Bulletin Stemme A31-10-023, LBA-approved.
7. The optional equipment of the variant Stemme S10-V with the „Fixed Pitch Propeller“ Stemme 10AP-F is allowed according to the Service Bulletin Stemme A31-10-067, EASA-approved.
8. VFR Night limited to the vicinity (range of glide ratio) of active airfields approved for night flight operations is allowed when the powered sailplane is equipped for this operation according to national rules and Service Bulletin Stemme A31-10-044 LBA-approved and A31-10-072 EASA-approved.



Section C: Stemme S10-VT

C.I. General

1. Data Sheet No.: EASA.A.054
2. a) Type: Stemme S10
b) Variant: Stemme S10-VT
3. Airworthiness Category: Powered Sailplane, JAR 22 - Utility
4. Type Certificate Holder: Stemme AG
Flugplatzstrasse F2 Nr. 6-7
15344 Strausberg
Germany
5. Manufacturer: Stemme GmbH & Co. KG
Flugplatzstrasse F2 Nr. 7
15344 Strausberg

Stemme AG
Flugplatzstrasse F2 Nr. 7
15344 Strausberg

Stemme AG
Flugplatzstrasse F2 Nr. 6-7
15344 Strausberg
6. LBA Certification Application Date: 16. August 1996
7. LBA Type Certification Date: 15. August 1997
8. This TCDS replaces LBA TCDS No. 846

C.II. Certification Basis

1. Certification Basis: Defined by LBA letter I 413-846/97,
dated 14. April 1997
2. Airworthiness Requirements: Joint Airworthiness Requirements for Sailplanes and
Powered Sailplanes (JAR 22), effective on June 27, 1989
(Change 4 of the English Original Issue)
3. Requirements elected to comply: Standards for Structural Substantiation of Sailplane and
Powered Sailplane Components Consisting of Glass or
Carbon Fibre Reinforced Plastics, Issue July. 1991
Standards for the Substantiation of the Electrical System of
Powered Sailplanes, Issue September 15, 1992.
Preliminary Standard for the Substantiation of Indirect
Drive Shafts in Power Plants of Powered Sailplanes (JAR
22) (with modifications for S10), dated 05.08.1988.
NPA 22E-XX (Proposed Amendment to JAR 22 for Variable
Pitch Propellers), Issue March 25, 1993.
JAR-22.375 from amendment 22/90/1 (Winglets)
4. Special Conditions: None



- | | |
|--------------------------------|---|
| 5. Exemptions: | None |
| 6. Equivalent Safety Findings: | None |
| 7. Environmental Standards: | ICAO Annex 16, Volume I (for more details see EASA TCDSN A.054) |

C.III. Technical Characteristics and Operational Limitations

- | | |
|--------------------------------|--|
| 1. Type Design Definition: | Document Record No. A08-11-0, am-index 04.a, dated January 39 th , 1998 (Part 2: record of the documents defining Type Stemme S10-VT), LBA approved.
in addition:
Record of Service Bulletins and Airworthiness Directives, Doc.No. P150-981003 in the actual revision. |
| 2. Description: | Selflaunching, twin-seat, all composite construction powered sailplane, with the liquid cooled, turbocharged engine mounted in the center fuselage, propeller shaft system and fully foldable, jointed variable pitch propeller CFRP, 3-piece wing, double panel Schempp-Hirth type airbrakes on the upper wing surface, optional winglets (see V.6). Retractable main landing gear with brake, T-tail (fixed horiz. stabilizer with elevator) fin and rudder. |
| 3. Equipment: | Min. Equipment:
1 Air speed indicator (up to 300 km/h)
1 Altimeter
1 Magnetic compass
1 RPM indicator
1 Oil pressure indicator
1 Oil temperature indicator
1 Cylinder head temperature indicator
1 Engine hour meter
2 Fuel quantity indicator
Stallwarning indicator
1 Indicator for Takeoff (low pitch) propeller position
2 4-Point harness (symmetrical)
2 Automatic or manual parachute
or
2 Back cushion (thickness approx. 10 cm / 3.94 in. when compressed), when flying without parachute
Additional Equipment refer to Flight and Operating Manual |
| 4. Dimensions:
Abmessungen: | Span 23.0 m
Spannweite
Wing area 18.74 m ²
Flügelfläche
Length 8.42 m
Länge |
| 5. Engine | Rotax 914 F2/S1
LBA-Engine Type Certificate Data Sheet No. 5006,
dated: Aug. 14 th 1997
Remark:
Rotax 914 F2 modified for the use in the Stemme S10-VT |



5.1	Engine Limits:	Maximum Power RPM		5800 rpm
		Maximum Continuous Power RPM		5500 rpm
6.	Propellers:	Stemme 11AP-V		
		LBA-Type Certificate Data Sheet 32.100/3 dated Aug. 05 th 1997		
6.1	Propeller diameter:	1630 mm +/- 3 mm		
7.	Fluids and Fluid capacities:	Wing tank left:		45.00 l
		Wing tank right:		45.00 l
		Non-usable amount of fuel:		1.5 l
		Optional tank capacity 2 x 60 l (see also V. 5)		
8.	Launching Hooks:	None		
9.	Weak links:	None		
10.	Air Speeds:	Manoeuvring Speed	V _A	180 km/h
		Never Exceed Speed	V _{NE}	270 km/h
		- at flap setting -10°, -5°, 0°	V _{FE}	270 km/h
		- at flap setting +5°, +10°	V _{FE}	180 km/h
		- at flap setting L (+16°)	V _{FE}	140 km/h
		Maximum permitted speeds		
		- in rough air	V _{RA}	180 km/h
		- max gear operating speed	V _{LO}	140 km/h
11.	Operational Capability:	Approved for VFR-Day. VFR Night limited to the vicinity (range of glide ratio) of active airfields approved for night flight operations (see V.7)		
12.	Maximum Masses:	Max. Mass		850 kg
		Max. Mass of Non-Lifting Parts		570 kg
13.	Centre of Gravity Range: Schwerpunktsbereich:	Datum: Inner wing leading edge, where upper side of fuselage boom placed at slope 1000 : 84		
		Forward Limit	254 mm aft of datum point	
		Rearward Limit	420 mm aft of datum point	
14.	Seating Capacity:	2		
15.	Lifetime limitations:	Refer to Maintenance Manual		
16.	Deflection of control surfaces:	Refer to Maintenance Manual		



C.IV. Operating and Service Instructions

1. Flight manual for the powered sailplane type STEMME S10-VT, Issue August. 1st, 1997, LBA – approved, or later approved revisions.
2. Maintenance Manual for the Powered Sailplane STEMME S10-VT, Issue January. 01, 1998, or later approved revisions.
3. Operating and Maintenance Manual for the engine see Maintenance Manual for the Powered Sailplane STEMME S10-VT section E.
4. Small Repair Manual (Document A35-10-SMR), revision 02.a dated October 13th 1997, or later approved revisions.

C.V. Notes

1. Manufacturing is confined to industrial production.
2. All parts exposed to sun radiation – except the areas for markings and registration – must have a white colour surface.
3. For issuance of the Certificate of Airworthiness pertinent to an individual aircraft the Noise Protection Requirements effective on the day of application are applicable.
4. The Variant Certification is effective from Serial No. 11-002 onwards.
5. The optional equipment with 2 x 60 l tanks ex works is allowed according to the modification bulletin Stemme A30-92-077, LBA-approved.
6. The optional equipment with winglets is allowed according to the Service Bulletin Stemme A31-10-023, LBA-approved.
7. VFR Night limited to the vicinity (range of glide ratio) of active airfields approved for night flight operations is allowed when the powered sailplane is equipped for this operation according to national rules and Service Bulletin Stemme A31-10-044 LBA-approved and A31-10-072 EASA-approved.
8. The engine ROTAX 914 F2/S1 (STEMME P/N 11AM-M) is a modification on base of a ROTAX 914 F2 or ROTAX 914 F2-01 in accordance with the Technical Specification Doc-No: A26-11AM-M. This modification is a necessary customization of the basic engine for the use within model STEMME S10-VT. Modified engines on base of a ROTAX 914 F2 may only be used for model STEMME S10-VT.



Section D: Stemme S12

D.I. General

1. Data Sheet No.: EASA.A.054
2. a) Type: Stemme S10
b) Variant: Stemme S12
3. Airworthiness Category: Powered Sailplane, JAR 22 - Utility
4. Type Certificate Holder: Stemme AG
Flugplatzstrasse F2 Nr. 6-7
15344 Strausberg
Germany
5. Manufacturer: Stemme AG
Flugplatzstrasse F2 Nr. 7
15344 Strausberg

Stemme AG
Flugplatzstrasse F2 Nr. 6-7
15344 Strausberg
6. EASA Certification Application Date: 6. December 2013

D.II. Certification Basis

1. Certification Basis: Defined in CRI A-1, Dec. 2013, with Amendments
2. Airworthiness Requirements: CS-22 (initial Version) 14. November 2003
3. Requirements elected to comply: Standards for Structural Substantiation of Sailplane and Powered Sailplane Components Consisting of Glass or Carbon Fibre Reinforced Plastics, Issue July. 1991
Standards for the Substantiation of the Electrical System of Powered Sailplanes, Issue September 15, 1992.
4. Special Conditions: EASA SC A.22.1-01 Increased mass up to 900 kg
Preliminary Standards for the Substantiation of Indirect Drive Shafts in Powered Plants of Powered Sailplanes (JAR22) (with modification for S10), dated 05.08.1988.
CRI F-01 Autopilot Installations on Board of Powered Sailplanes. Use of a "non TSO" 2-axis auto pilot system (as an option).
5. Exemptions: None
6. Equivalent Safety Findings: CS-VLA 725 Limit drop tests
CS-VLA 726 Ground load dynamic tests
CS-VLA 727 Reserve energy absorption
CS-VLA 1309 Equipment, systems, installations
7. Environmental Standards: ICAO Annex 16, Volume I (for more details see EASA TCDSN A.054)



D.III. Technical Characteristics and Operational Limitations

1. Type Design Definition: Document Record No. L150-912.005 Rev.00
In addition:
Record of Service Bulletins and Airworthiness Directives, Doc.No. P150-981004 in the actual revision.
2. Description: Self-launching, twin-seat, all composite construction powered sailplane, with a liquid cooled, turbo-charged engine mounted in the center fuselage, propeller shaft system and fully foldable, jointed variable pitch propeller CFRP, 5-piece wing, double panel Schempp-Hirth type airbrakes on the upper wing surface, Retractable main landing gear with brake, T-tail (fixed horiz. stabilizer with elevator) fin and rudder.
3. Equipment: Min. Equipment:
1 Air speed indicator (up to 300 km/h)
1 Altimeter
1 Magnetic compass
1 RPM indicator*
1 Oil pressure indicator*
1 Oil temperature indicator*
1 Cylinder head temperature indicator*
1 Engine hour meter
2 Fuel quantity indicator*
1 Indicator for Takeoff (low pitch) propeller position
1 Indicator for the trim position
1 Indicator for Low fuel
1 Alternator warning light
1 Outside air temperature gauge, if flown with waterballast in the fin*
2 4-Point harness (symmetrical)
2 Automatic or manual parachute
or
2 Back cushion (thickness approx. 10 cm / 3.94 in. when compressed), when flying without parachute

* These instruments can be included in the digital engine monitoring GARMIN G3X Touch system (see Note 7).

Additional Equipment refer to Flight and Operating Manual

4. Dimensions:
Abmessungen:
- | | |
|--------------|------------------------------------|
| Span | 25.0 / 21.7 / 21.4 m |
| Spannweite | |
| Wing area | 19.95 / 18.6 / 18.5 m ² |
| Flügelfläche | |
| Length | 8.42 m |
| Länge | |



5. Engine Engine Rotax 914 F2/S1 (P/N 11AM-M) according to Technical Specification Doc-No: A26-11AM-M Rev 08.a*
- Clutch (P/N: 12AK) according to Assembly drawing Doc.-No.: A12-12AK Rev 01.a* and Parts List Doc.-No.: A21-12AK Rev 01.a*
- Drive System (P/N: 11AS) according to Assembly Drawing Doc.-No.: A12-11AS Rev 03.a* and Parts List Doc.-No.: A21-11AS Rev 02.a*
- Propeller Gear (P/N: 11AG) according to Technical Specification Doc.-No.: A26-11AG Rev 11.a*
- * or later approved revisions.
- 5.1 Engine Limits: Maximum Power RPM 5800 rpm
Maximum Continuous Power RPM 5500 rpm
6. Propellers: Stemme 11AP-V
LBA-Type Certificate Data Sheet 32.100/3 dated Aug. 05th 1997
- 6.1 Propeller diameter: 1630 mm +/- 3 mm
7. Fluids and Fluid capacities: Wing tank left: 60.00 l
Wing tank right: 60.00 l
Non-usable amount of fuel: 0.52 l
8. Launching Hooks: None
9. Weak links: None
10. Air Speeds: Manoeuvring Speed V_A 180 km/h
Never Exceed Speed V_{NE} 270 km/h
- at flap setting $-10^\circ, -5^\circ, 0^\circ$ V_{FE} 270 km/h
- at flap setting $+5^\circ, +10^\circ$ V_{FE} 180 km/h
- at flap setting L ($+16^\circ$) V_{FE} 140 km/h
- Maximum permitted speeds
- in rough air V_{RA} 180 km/h
- max gear operating speed V_{LO} 140 km/h
11. Operational Capability: Approved for VFR-Day.
12. Maximum Masses: Max. Mass 900 kg
Max. Mass of Non-Lifting Parts 610 kg



13. Centre of Gravity Range: Schwerpunktsbereich: Datum: Inner wing leading edge, where upper side of fuselage boom placed at slope 1000 : 54
- | | |
|----------------|---------------------------|
| Forward Limit | 265 mm aft of datum point |
| Rearward Limit | 420 mm aft of datum point |
14. Seating Capacity: 2
15. Lifetime limitations: Refer to Maintenance Manual
16. Deflection of control surfaces: Refer to Maintenance Manual

D.IV. Operating and Service Instructions

1. Flight manual for the powered sailplane Stemme S12, Edition L400-912810 Rev.00; 01/2016, EASA-approved, or later approved revisions.
2. Maintenance Manual Powered Sailplane, Stemme S12, Edition L500-912820 Rev.00; 01/2016, EASA –approved, or later approved revisions.
3. Operating and Maintenance Manual for the engine see Maintenance Manual for the Powered Sailplane, STEMME S12 section 3.
4. Small Repair Manual (Document P520-901502), issue April 2017, or later approved revisions.

D.V. Notes

1. Manufacturing is confined to industrial production.
2. All parts exposed to sun radiation – except the areas for markings and registration – must have a white colour surface.
3. For issuance of the Certificate of Airworthiness pertinent to an individual aircraft the Noise Protection Requirements effective on the day of application are applicable.
4. The Variant Certification is effective from Serial No. 12-002 onwards.
5. Optional use of a non ETSO 2 axis autopilot (Dynon) is included into the certification of the Stemme S12, all wing spans (25 m, 21.7 m and 21.4 m).
6. The engine ROTAX 914 F2/S1 (STEMME P/N 11AM-M) is a modification on base of a ROTAX 914 F2 or ROTAX 914 F2-01 in accordance with the Technical Specification Doc-No: A26-11AM-M. This modification is a necessary customization of the basic engine for the use within model STEMME S12. For the use within the model STEMME S12 the modification must be based on a ROTAX 914 F2-01.
Modified engines on base of a ROTAX 914 F2 may only be used for model STEMME S12.
7. Optional use of a non ETSO 2 axis autopilot and digital engine monitoring (GARMIN G3X) is included into the certification of the Stemme S12, all wing spans (25 m, 21.7 m and 21.4 m).



Administrative section

I. Acronyms

N/A

II. Type Certificate Holder Record

Stemme AG
Flugplatzstrasse F2 Nr. 6-7
15344 Strausberg
Germany

III. Change Record

Issue	Date	Changes
01	16 September 2005	Initial Issue
02	19 December 2014	Change of name of TC-Holder
03	14 March 2016	Certification of Variant Stemme S12; Section D added Editorial changes
04	20 October 2017	Changes to referenced manuals for Stemme S10 series
05	12 February 2019	Approval of 21.7 m wingspan for Stemme S10 variant Stemme S12; additional manufacturer address; editorial changes; Engine TCDS references (LBA->EASA)
06	17 May 2019	Approval of GARMIN G3X Touch System for Stemme S10 variant Stemme S12, editorial changes chapter C and D

