



European Aviation Safety Agency

EASA

**TYPE CERTIFICATE
DATA SHEET**

EASA.A.027

ZLIN Z 42 Series

Type Certificate Holder:

ZLIN AIRCRAFT a.s.
Letiště 1887
765 02 Otrokovice
CZECH REPUBLIC

For models: Z 42 M, Z 42 MU, Z 142, Z 142 C, Z 242 L

Issue 7: 25 April 2016

CONTENT

SECTION A: Z 42

- AI. General
- AII. Certification Basis
- AIII. Technical Characteristics and Operational Limitations
- AIV. Operating and Service Instructions
- AV. Notes

SECTION B: Z 42 M

- BI. General
- BII. Certification Basis
- BIII. Technical Characteristics and Operational Limitations
- BIV. Operating and Service Instructions
- BV. Notes

SECTION C: Z 42 MU

- CI. General
- CII. Certification Basis
- CIII. Technical Characteristics and Operational Limitations
- CIV. Operating and Service Instructions
- CV. Notes

SECTION D: Z 142

- DI. General
- DII. Certification Basis
- DIII. Technical Characteristics and Operational Limitations
- DIV. Operating and Service Instructions
- DV. Notes

SECTION E: Z 142 C

- EI. General
- EII. Certification Basis
- EIII. Technical Characteristics and Operational Limitations
- EIV. Operating and Service Instructions
- EV. Notes

SECTION F: Z 242 L

- FI. General
- FII. Certification Basis
- FIII. Technical Characteristics and Operational Limitations
- FIV. Operating and Service Instructions
- FV. Notes

ADMINISTRATIVE SECTION

- I. Acronyms
- II. Type Certificate Holder Record
- III. Change Record

SECTION A: Z 42

AI. General

1. a) Type: Z 42
b) Model: ---
2. Airworthiness category: Aerobatic (A) (see Note 2)
Utility (U) (see Note 2)
Normal (N) (see Note 2)
3. Type Certificate Holder: ZLIN AIRCRAFT a.s.
Letiště 1887
765 02 Otrokovice
CZECH REPUBLIC
4. Manufacturer: Moravan, n.p.
Letiště 1578
765 81 Otrokovice
CZECHOSLOVAKIA
S/N: 0001-0010; 0015-0026; 0028-0047
5. Certification Application Date: ---
6. CAA Cz Type Certificate Date: September 07, 1970
7. EASA Type Certificate Date: 22-Mar-2007 (reissue, EASA)

The EASA Type Certificate replaces the CAA CZ Type Certificate No. 70 – 05.

II. Certification Basis

1. Reference Date for determining the applicable requirements: ---
2. (Reserved)
3. (Reserved)
4. Airworthiness Requirements: FAR PART 23, Amdt 23-6 (including)
5. Requirements elected to comply: None
6. EASA Special Conditions: None
7. EASA Exemptions: None
8. EASA Equivalent Safety Findings: § 23.177(a)(2) – Good controllability around longitudinal axis of the aircraft.
§ 23.613(c); § 23.615 – Used materials and results of calculation are sufficiently satisfactory (they are in compliance with ČSN and specifications effective for aeronautical industry).

Z 42

§ 23.955 – The fuel flow is closed with battery stopcock and is higher by 50 % than the consumption at start.

§ 23.991(b) – Failure of low-pressure fuel pump is extremely improbable.

§ 23.1013(e); § 23.1019 – The screen area at oil tank outlet is several times larger than the outlet pipe union section.

§ 23.1183(-) - The hoses materials safety is proved by operation experience.

§ 23.1323 – Aerodynamical repair is on safe side; the speed reached at the cruising power of engine is lower than the speed at which already occurs undesirable distortion.

9. EASA Environmental Standards: ICAO Annex 16/I, Chapter 6

AIII. Technical Characteristics and Operational Limitations

1. Type Design Definition: The specification list of Aircraft Z 42, No. S-Z42.0000.
2. Description: The Z 42 aircraft is two-seat, low wing, single-engine, cantilever monoplane.
3. Equipment: Approved equipment list is stated in document Technický popis a návod k obsluze letounu Z 42, Chapter 5".
4. Dimensions:

Span:	9.11 m
Length:	7.07 m
Height:	2.69 m
Wing Area:	13.15 m ²
5. Engine:
 - 5.1 Model: M 137 A
 - 5.2 Type Certificate: EASA approved (CAA CZ TC No. 69-01) (see Note 3)
 - 5.3 Limitations:

Max. Take-off power (5 min.)	
max. Power	133 kW (180 HP)
max. Engine speed	2 750 RPM
max. Consumption	61 l/h
max. Manifold pressure	100 ± 2 kPa
Max. Continuous power	
max. Power	118 kW (160 HP)
max. Engine speed	2 680 RPM
max. Consumption	52 l/h
max. Manifold pressure	95 ± 2 kPa
Max. Cruising power	
max. Power	103 kW (140 HP)
max. Engine speed	2 580 RPM
max. Consumption	43 l/h
max. Manifold pressure	87 kPa

6. Load factors:
- | | |
|------------|----------------|
| Category A | +6.0 g, -3.5 g |
| Category U | +4.4 g, -2.5 g |
| Category N | +3.8 g, -1.5 g |
7. Propellers:
- 7.1.1 Model: Z42.6411
- 7.1.2 Type Certificate: EASA approved (CAA CZ TC No. 70-06) (see Note 4)
- 7.1.3 Number of blades: 2
- 7.1.4 Diameter: 2 050 mm
- 7.1.5 Sense of Rotation: Anticlockwise in flight direction
- or
- 7.2.1 Model: Z42.6413 (towing)
- 7.2.2 Type Certificate: EASA approved (EASA.P.176 replacing CAA CZ TC No. 70-07) (see Note 5)
- 7.2.3 Number of blades: 2
- 7.2.4 Diameter: 2 050 mm
- 7.2.5 Sense of Rotation: Anticlockwise in flight direction
8. Fluids:
- 8.1 Fuel: Non-ethylated aviation gasoline with min. 72 octanes. Application of ethylated fuels is only permitted in case that the T.E.L. content does not exceed the value of 0.06% vol.
- LBZ 72
- LBZ 78
- LBE 80
- LBE 87
- Shell 80
- ESSO 80
- AVGAS 100 LL
(DEFENCE STANDARD 91/90, ASTM D910)
- 8.2 Oil: Mineral oils are recommended for engine operation with min. kinematic viscosity of 20 cSt at 100°C, whose percentual carbon residue does not exceed the value of 0.4.
- MS 20
- Aeroshell W100
- Aeroshell W120 (in tropical climates)
- 8.3 Coolant: None

9. Fluid capacities:

9.1 Fuel:	Total:	130 litres
	Usable:	127 litres
	2 x 65 litres in main tanks	
9.2 Oil:	Minimum 7 liters - Maximum 12 liters	
9.3 Coolant system capacity:	None	

10. Air Speeds:

Never Exceed Speed Limit	V _{NE}	315 km/h CAS
Normal Operating Speed	V _{NO}	226 km/h CAS
Design Manoeuvring Speed Limit	V _A	
Category A		260 km/h CAS
Category U		230 km/h CAS
Category N		227 km/h CAS
Maximum Flaps Extended Speed Limit	V _{FEE}	185 km/h CAS

11. Maximum Operating Altitude:

Category A	5 000 m
Category U	4 350 m
Category N	4 050 m

12. All-weather Operations Capability: The aircraft is approved for VFR Day flights.

13. Maximum Weights:

Max. Take-off and Landing weight:	
Category A	840 kg
Category U	920 kg
Category N	970 kg
Max. Variable Load:	
Category A, U, N	200 kg

14. Centre of Gravity Range:

21,8 % – 26,5 % MAC
M.A.C. is 1 460 mm; 0 % M.A.C. is 300 mm aft reference datum.

15. Datum:

The rear part of firewall; from it are measured, for purpose of assignation of Gravity Centre, all lateral dimensions.

16. Control Surface Deflections:

Elevator deflection	up	30° ± 1°
	down	27° + 1°
Rudder deflection	right and left	30° ± 2°
Ailerons deflection	up	21° ± 1°
	down	17° ± 1°
Wing flaps positions	retracted	0°
	take-off	14° ± 1°
	landing	37° ± 1°

17. Levelling Means:

Levelling points on left and right side of airplane fuselage to be levelled. Measurement plane to be min. 600 mm below.

- | | |
|---|--|
| 18. Minimum Flight Crew: | 1 (Pilot) |
| 19. Maximum Passenger Seating Capacity: | 2 (including crew) |
| 20. (Reserved) | |
| 21. Baggage/Cargo Compartments: | Max. 20 kg. |
| 22. Wheels and Tyres: | Wheels of main gear K 22-0100-7 with tyre Barum 420 x 150 model 2 or
Wheel of nose gear K 23-0000-7 with tyre Barum 350 x 135 |

AIV. Operating and Service Instructions

1. Flight Manual:
 - In Czech language Letová příručka letounu Z 42,
Initial issue 1971 or later approved revisions

2. Technical Manual:
 - In Czech language Technický popis a návod k obsluze letounu ZLIN 42,
Initial issue 1971 or later approved revisions

3. Repair Manual:
 - In Czech language Opravárenská příručka letounů Z 42, Z 42 M, Z 42 MU,
Initial issue 1978 or later approved revisions

4. Catalogue of Spare Parts:
 - In Russian, Czech, German Katalog ZLIN 42,
and English language *Initial issue 1971 or later approved revisions*

5. Table of Dimensions, Limits and Clearances:
 - In Czech, German and English language
Album rozměrů, tolerancí a vůlí Z 42, Z 42 M, Z 43
Album der Abmessungen, der Toleranz und Spielangaben
Z 42, Z 42 M, Z 43
Table of Dimensions, Limits and Clearances Z 42, Z 42 M,
Z 43,
Initial issue 1976 or later approved revisions

AV. Notes

- Note 1: The Z 42 aircraft have been converted by the aircraft manufacturer to the models:
Z 42 M S/N: 0006
Z 42 MU S/N: 0003-0004; 0007-0008; 0010; 0015; 0017-0026; 0028-0045;
0047
- Note 2: For operation of the airplane in other than the Normal Category, compliance with the applicable parts of Mandatory Service Bulletins Z42/55a and Z42/56a or later revision of each is required.
- Note 3: The EASA type certification standard includes that of CAA Cz TCDS No. 69-01 based on individual EU member state acceptance or certification of this standard prior to 28 September 2003. Other standards confirming to TC/TCDS standards certificated by individual EU member state prior to 28 September 2003 are also acceptable.
- Note 4: The EASA type certification standard includes that of CAA Cz TCDS No. 70-06 based on individual EU member state acceptance or certification of this standard prior to 28 September 2003. Other standards confirming to TC/TCDS standards certificated by individual EU member state prior to 28 September 2003 are also acceptable.
- Note 5: The EASA type certification standard includes that of CAA Cz TCDS No. 70-07 based on individual EU member state acceptance or certification of this standard prior to 28 September 2003. Other standards confirming to TC/TCDS standards certificated by individual EU member state prior to 28 September 2003 are also acceptable.

The EASA TC EASA.P.176 issued to Ales Kremen on 19 August 2010 replaced the Czech TC.

SECTION B: Z 42 M

BI. General

1. a) Type: Z 42
b) Model: Z 42 M
2. Airworthiness category: Aerobatic (A) (see Note 2)
Utility (U) (see Note 2)
Normal (N) (see Note 2)
3. Type Certificate Holder: ZLIN AIRCRAFT a.s.
Letiště 1887
765 02 Otrokovice
CZECH REPUBLIC
4. Manufacturer: Moravan, n.p.
Letiště 1578
765 81 Otrokovice
CZECHOSLOVAKIA
S/N: 0048; 0060-0190
5. Certification Application Date: ---
6. CAA Cz Type Certificate Date: October 30, 1973
7. EASA Type Certificate Date: 21-Mar-2007 (reissue, EASA)

The EASA Type Certificate replaces the CAA CZ Type Certificate No. 73-06.

BII. Certification Basis

1. Reference Date for determining the applicable requirements: ---
2. (Reserved)
3. (Reserved)
4. Airworthiness Requirements: FAR PART 23, Amdt 23-13 (including)
5. Requirements elected to comply: None
6. EASA Special Conditions: None
7. EASA Exemptions: None
8. EASA Equivalent Safety Findings: § 23.33 – In the Flight manual is a notice – limitation of revolutions of the propeller is met in normal category at maximal flight weight up to a height of 600 m MSA.
§ 23.177(a)(2) – Sufficient controllability in critical regimes of flight.

Z 42 M

§ 23.613(c); § 23.615 – Used materials and calculation results are convenient.

§ 23.955 – The fuel flow is higher than the consumption at take-off regime.

§ 23.991(b) – The engine is equipped with a high-pressure pump connected with a low-pressure pump to one aggregate, the low-pressure pump breakdown is extremely improbable.

§ 23.1013(e); § 23.1019 – The screen area at oil tank outlet is several times larger than the outlet pipe union section.

§ 23.1183(-) - The hoses material safety is verified by experiences from operation.

§ 23.1323 – At the speeds over 200 km/h, there is made a correction on the safe side.

§ 23.1389(b); §23.1391; §23.1393; §23.1395; §23.1397; § 23.1401 – Landing lights, anti-collision lights are convenient with respect to the night flights exclusiveness.

9. EASA Environmental Standards: ICAO Annex 16/I, Chapter 6

BIII. Technical Characteristics and Operational Limitations

1. Type Design Definition: The specification list of Aircraft Z 42 M, No. S-M42.0000.
2. Description: The Z 42 M aircraft is two-seat, low wing, single-engine, and cantilever monoplane.
3. Equipment: Approved equipment list is stated in document Technical manual of the ZLIN Z 42M Aircraft, Chapter 4.
4. Dimensions:

Span:	9.11 m
Length:	7.07 m
Height:	2.69 m
Wing Area:	13.15 m ²
5. Engine:
 - 5.1. Model: M137 AZ
 - 5.2. Type Certificate: EASA approved (CAA CZ TC No. 69-01) (see Note 3)
 - 5.3 Limitations:

Max. Take-off power (5 min.)	
max. Power	133 kW (180 HP)
max. Engine speed	2 750 RPM
max. Consumption	61 l/h
max. Manifold pressure	100 ± 2 kPa
Max. Continuous power	
max. Power	118 kW (160 HP)
max. Engine speed	2 680 RPM
max. Consumption	52 l/h
max. Manifold pressure	95 ± 2 kPa

Z 42 M

Max. Cruising power:

max. Power	103 kW (140 HP)
max. Engine speed	2 580 RPM
max. Consumption	43 l/h
max. Manifold pressure	87 kPa

6. Load factors:
- | | |
|------------|----------------|
| Category A | +6.0 g, -3.5 g |
| Category U | +5.0 g, -3.2 g |
| Category N | +3.8 g, -1.5 g |
7. Propeller:
- 7.1 Model: V 503 A
- 7.2 Type Certificate: EASA approved (CAA CZ TC No. 69-02) (see Note 4)
- 7.3 Number of blades: 2
- 7.4 Diameter: 2 000 mm
- 7.5 Sense of Rotation: Anticlockwise in flight direction.
8. Fluids:
- 8.1 Fuel: Non-ethylated aviation gasoline, with min. 72 octanes. Application of ethylated fuels is only permitted in case that the T.E.L. content does not exceed the value of 0.06% vol.
- LBZ 72
- LBZ 78
- LBE 80
- LBE 87
- Shell 80
- ESSO 80
- AVGAS 100 LL
(DEFENCE STANDARD 91/90, ASTM D910)
- 8.2 Oil: AERO SHELL 100 (a mineral oil) or equivalent – is recommended for running-in (max. up to 50 hours).
- AERO SHELL W 100 or equivalent – is recommended for after-running-in operation in temperate climatic area.
- AERO SHELL W 120 or equivalent – is recommended for after-running-in operation in tropical area.
- AERO SHELL W 80 or AERO SHELL W 65 or equivalent – is recommended for after-running-in operation during winter or in polar area.
- 8.3 Coolant: None
9. Fluid capacities:

9.1 Fuel:	Total:		130 litres
	Usable:		127 litres
	2 x 65 litres in main tanks		
9.2 Oil:	Minimum 7 liters – Maximum 12 liters		
9.3 Coolant system capacity:	None		
10. Air Speeds:	Never Exceed Speed Limit	V _{NE}	315 km/h CAS
	Normal Operating Speed Limit	V _{NO}	226 km/h CAS
	Design Manoeuvring Speed Limit	V _A	
	Category A,U		270 km/h CAS
	Category N		220 km/h CAS
	Maximum Flaps Extended Speed Limit	V _{FEE}	185 km/h CAS
	Maximum Speed Limit for flicked figures		
	Category A		160 km/h CAS
11. Maximum Operating Altitude:	Category A, U		4 250 m
	Category N		3 800 m
12. All-weather Operations Capability:	The aircraft is approved for VFR Day flights.		
13. Maximum Weights:	Max. Take-off and Landing weight:		
	Category A, U		920 kg
	Category N		970 kg
	Max. Variable Load:		200 kg
14. Centre of Gravity Range:	19 % – 27 % MAC M.A.C. is 1 460 mm; 0 % M.A.C. is 300 mm aft reference datum.		
15. Datum:	The rear part of firewall; from it are measured, for purpose of assignation of Gravity Centre, all lateral dimensions.		
16. Control surface deflections:	Elevator deflection	up down	34° + 0°, -1° 27° + 1°
	Rudder deflection	right and left	30° ± 2°
	Ailerons deflection	up down	21° ± 1° 17° ± 1°
	Wing flaps positions	retracted take-off landing	0° 14° ± 1° 37° ± 1°
17. Levelling Means:	Levelling points on left and right side of airplane fuselage to be levelled. Measurement plane to be min. 600 mm below.		
18. Minimum Flight Crew:	1 (Pilot)		
19. Maximum Passenger Seating	2 (including crew)		

Z 42 M

Capacity:

20. (Reserved)

21. Baggage/Cargo Compartments: Max. 20 kg

22. Wheels and Tires: Wheels of main gear K 22-0100-7 with tyre
Barum 420 x 150 model 2 or
Wheels of main gear K 22-3100-7 with tyre
Mitas 420 x 150 model 2 or Goodyear 6.00-6.5.
Wheel of nose gear K 23-0000-7 with tyre
Barum 350 x 135, or
Wheel of nose gear K 51-1100-7 with tyre
Mitas 350 x 135 or Goodyear 5.00-5..

Z 42 M

BIV. Operating and Service Instructions

1. Flight Manual:
 - In Czech language Letová příručka Z 42 M,
Initial issue September 1977 or later approved revisions
 - In English language Flight Manual of the ZLIN 42 M Aircraft,
Initial issue 1978 or later approved revisions
 - In German language Flughandbuch ZLIN 42 M,
Initial issue 1978 or later approved revisions
2. Technical Manual:
 - In Czech language Technický popis a návod k obsluze letounu Z 42 M,
Initial issue October 1977 or later approved revisions
 - In English language Technical Manual of the ZLIN 42 M Aircraft,
Initial issue April 1973 or later approved revisions
3. Repair Manual:
 - In Czech language Opravárenská příručka letounů Z 42, Z 42 M, Z 42 MU,
Initial issue 1978 or later approved revisions
4. Catalogue of Spare Parts:
 - In Russian, Czech, German and English language
Katalog náhradních dílů Z 42 M,
Initial issue or later approved revisions
5. Table of Dimensions, Limits and Clearances:
 - In Czech, German and English language
Album rozměrů, tolerancí a vůlí Z 42, Z 42 M, Z 43,
Album der Abmessungen, der Toleranz und Spielangaben
Z 42, Z 42 M, Z 43
Table of Dimensions, Limits and Clearances Z 42, Z 42 M,
Z 43,
Initial issue 1976 or later approved revisions
6. Manual for Operation:
 - In Czech language
Doc. No. 232.071 Příručka pro provoz letounů Z 42 M, Z 42 MU bez
generálních oprav draku část 1 a 2, prohlídka A, B, C,
Initial issue 30.1.1997 or later approved revisions
 - In English language
Doc. No. 232.071 Manual for operation of Z 42 M, Z 42 MU aircraft
without airframe overhaul, Part 1, Part 2, revision A, B, C,
Initial issue 30.1.1997 or later approved revisions
7. Instruments and Aggregates:
 - In Czech language
Doc. No. PRA.081.1 Přístroje a agregáty, použité na letounech Z 42 M, Z 42 MU
Z 142 a Z 43,
Initial issue 10.1.2012 or later approved revisions

BV. Notes

- Note 1: The Z 42 M aircraft have been converted by the manufacturer to the models:
Z 42 MU S/N: 0048
- Note 2: For operation of the airplane in other than the Normal Category, compliance with the applicable parts of Mandatory Service Bulletins Z42/54a, Z42/55a and Z42/56a or later revision of each is required.
- Note 3: The EASA type certification standard includes that of CAA CZ TCDS No. 69-01 based on individual EU member state acceptance or certification of this standard prior to 28 September 2003. Other standards confirming to TC/TCDS standards certificated by individual EU member state prior to 28 September 2003 are also acceptable.
- Note 4: The EASA type certification standard includes that of CAA CZ TCDS No. 69-02 based on individual EU member state acceptance or certification of this standard prior to 28 September 2003. Other standards confirming to TC/TCDS standards certificated by individual EU member state prior to 28 September 2003 are also acceptable.

SECTION C: Z 42 MU

CI. General

1. a) Type: Z 42
b) Model: Z 42 MU
2. Airworthiness category: Utility (U) (see Note 3)
Normal (N) (see Note 3)
3. Type Certificate Holder: ZLIN AIRCRAFT a.s.
Letiště 1887
765 02 Otrokovice
CZECH REPUBLIC
4. Manufacturer: Moravan, n.p.
Letiště 1578
765 81 Otrokovice
CZECHOSLOVAKIA
S/N: 0011-0014; 0027; 0049-0059
5. Certification Application Date: ---
6. CAA Cz Type Certificate Date: 01-Feb-1974
7. EASA Type Certificate Date: 22-Mar-2007 (reissue, EASA)

The EASA Type Certificate replaces the CAA CZ Type Certificate No. 73-06.

CII. Certification Basis

1. Reference Date for determining the applicable requirements: ---
2. (Reserved)
3. (Reserved)
4. Airworthiness Requirements: FAR PART 23, Amdt 23-13 (including)
5. Requirements elected to comply: None
6. EASA Special Conditions: None
7. EASA Exemptions: None
8. EASA Equivalent Safety Findings: § 23.33 – In the Flight manual is a notice – limitation of revolutions of the propeller is met in normal category at maximal flight weight up to a height of 600 m MSA.
§ 23.177(a)(2) – Sufficient controllability in critical regimes of flight.

§ 23.613(c); § 23.615 – Used materials and calculation results are convenient.

§ 23.955 – The fuel flow is higher than the consumption at take-off regime.

§ 23.991(b) – The engine is equipped with a high-pressure pump connected with a low-pressure pump to one aggregate, the low-pressure pump breakdown is extremely improbable.

§ 23.1013(e); § 23.1019 – The screen area at oil tank outlet is several times larger than the outlet pipe union section.

§ 23.1183(-) - The hoses material safety is verified by experiences from operation.

§ 23.1323 – At the speeds over 200 km/h, there is made a correction on the safe side.

§ 23.1389(b); §23.1391; §23.1393; §23.1395; §23.1397; § 23.1401 – Landing lights, anti-collision lights are convenient with respect to the night flights exclusiveness.

9. EASA Environmental Standards: ICAO Annex 16/I, Chapter 6

CIII. Technical Characteristics and Operational Limitations

1. Type Design Definition: The specification list of Aircraft Z 42 MU, No. S-MU42.0000.

2. Description: The Z 42 MU aircraft is two-seat, low wing, single-engine, and cantilever monoplane.

3. Equipment: Approved equipment list is stated in Flight manual for the ZLIN Z 42MU Aircraft, Chapter 4.

4. Dimensions:

Span:	9.11 m
Length:	7.07 m
Height:	2.69 m
Wing Area:	13.15 m ²

5. Engine:

5.1.1 Model: M 137 A

5.1.2 Type Certificate: EASA approved (CAA CZ TC No. 69-01) (see Note 4)

5.1.3 Limitations:

Max. Take-off power (5 min.)	
max. Power	133 kW (180 HP)
max. Engine speed	2 750 RPM
max. Consumption	61 l/h
max. Manifold pressure	100 ± 2 kPa
Max. Continuous power	
max. Power	118 kW (160 HP)
max. Engine speed	2 680 RPM
max. Consumption	52 l/h
max. Manifold pressure	95 ± 2 kPa

Max. Cruising power

Z 42 MU

max. Power	103 kW (140 HP)
max. Engine speed	2 580 RPM
max. Consumption	43 l/h
max. Manifold pressure	87 kPa

or

- 5.2.1 Model: M 137 AZ
- 5.2.2 Type Certificate: EASA approved (CAA CZ TC No. 69-01) (see Note 4)
- 5.2.3 Limitations:
- | | |
|------------------------------|-----------------|
| Max. Take-off power (5 min.) | |
| max. Power | 133 kW (180 HP) |
| max. Engine speed | 2 750 RPM |
| max. Consumption | 61 l/h |
| max. Manifold pressure | 100 ± 2 kPa |
| Max. Continuous power | |
| max. Power | 118 kW (160 HP) |
| max. Engine speed | 2 680 RPM |
| max. Consumption | 52 l/h |
| max. Manifold pressure | 95 ± 2 kPa |
| Max. Cruising power | |
| max. Power | 103 kW (140 HP) |
| max. Engine speed | 2 580 RPM |
| max. Consumption | 43 l/h |
| max. Manifold pressure | 87 kPa |
6. Load factors: Category U +5.0 g, -3.2 g
Category N +3.8 g, -1.5 g
7. Propeller:
- 7.1 Model: V 503 A
- 7.2 Type Certificate: EASA approved (CAA CZ TC No. 69-02) (see Note 5)
- 7.3 Number of blades: 2
- 7.4 Diameter: 2 000 mm
- 7.5 Sense of Rotation: Anticlockwise in flight direction.
8. Fluids:
- 8.1 Fuel: Non-ethylated aviation gasoline, with min. 72 octanes.
Application of ethylated fuels is only permitted in case the T.E.L. content does not exceed the value of 0.06% vol.
- LBZ 72
LBZ 78
LBE 80
LBE 87
Shell 80
- ESSO 80
AVGAS 100 LL

Z 42 MU

(DEFENCE STANDARD 91/90, ASTM D910)

- 8.2 Oil: AERO SHELL 100 (a mineral oil) or equivalent – is recommended for running-in (max. up to 50 hours).
AERO SHELL W 100 or equivalent – is recommended for after-running-in operation in temperate climatic area.
AERO SHELL W 120 or equivalent – is recommended for after-running-in operation in tropical area.
AERO SHELL W 80 or AERO SHELL W 65 or equivalent – is recommended for after-running-in operation during winter or in polar area.
- 8.3 Coolant: None
9. Fluid capacities:
- 9.1 Fuel: Total: 130 litres
Usable: 127 litres
2 x 65 litres in main tanks
- 9.2 Oil: Minimum 7 litres – Maximum 12 litres
- 9.3 Coolant system capacity: None
10. Air Speeds:
- | | | |
|------------------------------------|-----|--------------|
| Never Exceed Speed Limit | VNE | 315 km/h CAS |
| Normal Operating Speed Limit | VNO | 226 km/h CAS |
| Design Manoeuvring Speed Limit | VA | |
| Category U | | 270 km/h CAS |
| Category N | | 220 km/h CAS |
| Maximum Flaps Extended Speed Limit | VFE | 185 km/h CAS |
11. Maximum Operating Altitude: Category U 4 250 m
Category N 3 800 m
12. All-weather Operations Capability: The aircraft is approved for VFR Day flights.
13. Maximum Weights: Max. Take-off and Landing weight:
Category U 920 kg
Category N 970 kg
Max. Variable Load:
Category U, N 200 kg
14. Centre of Gravity Range: 19 % – 27 % MAC
M.A.C. is 1 460 mm; 0 % M.A.C. is 300 mm aft reference datum.
15. Datum: The rear part of firewall; from it are measured, for pu *Z 42 MU* assignation of Gravity Centre, all lateral dimensions.

- | | | | |
|---|---|----------------|--------------------------------------|
| 16. Control surface deflections: | Elevator deflection | up | $34^{\circ} + 0^{\circ}, -1^{\circ}$ |
| | | down | $27^{\circ} + 1^{\circ}$ |
| | Rudder deflection | right and left | $30^{\circ} \pm 2^{\circ}$ |
| | Ailerons deflection | up | $21^{\circ} \pm 1^{\circ}$ |
| | | down | $17^{\circ} \pm 1^{\circ}$ |
| 17. Levelling Means: | Wing flaps positions | retracted | 0° |
| | | take-off | $14^{\circ} \pm 1^{\circ}$ |
| | | landing | $37^{\circ} \pm 1^{\circ}$ |
| 18. Minimum Flight Crew: | Levelling points on left and right side of airplane fuselage to be levelled. Measurement plane to be min. 600 mm below. | | |
| 19. Maximum Passenger Seating Capacity: | 1 (Pilot) | | |
| 20. (Reserved) | 2 (including crew) | | |
| 21. Baggage/Cargo Compartments: | Max. 20 kg | | |
| 22. Wheels and Tires: | Wheels of main gear K 22-0100-7 with tyre Barum 420 x 150 model 2 or
Wheels of main gear K 22-3100-7 with tyre Mitas 420 x 150 model 2 or Goodyear 6.00-6.5.
Wheel of nose gear K 23-0000-7 with tyre Barum 350 x 135, or
Wheel of nose gear K 51-1100-7 with tyre Mitas 350 x 135 or Goodyear 5.00-5. | | |

Z 42 MU

CIV. Operating and Service Instructions

1. Flight Manual:
 - In Czech language Letová příručka Z 42 MU,
Initial issue March 1975 or later approved revisions
 - In English language Flight Manual ZLIN 42 MU,
Initial issue 1974 or later approved revisions
 - In German language Flugzeugbetriebshandbuch ZLIN 42 MU,
Initial issue March 1974 or later approved revisions
2. Technical Manual:
 - In Czech language Technický popis a návod k obsluze letounu Z 42 MU,
Initial issue April 1975 or later approved revisions
 - In English language Technical Manual ZLIN 42 MU,
Initial issue April 1974 or later approved revisions
3. Repair Manual:
 - In Czech language Opravárenská příručka letounů Z 42, Z 42 M, Z 42 MU,
Initial issue 1978 or later approved revisions
4. Catalogue Supplement:
 - In Czech, German and English language
ZLIN 42 MU – Dodatek ke katalogu Z 42
ZLIN 42 MU – Nachtrag zum Katalog Z 42
ZLIN 42 MU – Supplement of the Z 42 Catalogue
Initial issue January 1974 or later approved revisions
5. Table of Dimensions, Limits and Clearances:
 - In Czech, German and English language
Album rozměrů, tolerancí a vůlí Z 42, Z 42 M, Z 42 MU, Z 43,
Album der Abmessungen, der Toleranz und Spielangaben
Z 42, Z 42 M, Z 43,
Table of Dimensions, Limits and Clearances Z 42, Z 42 M,
Z 43,
Initial issue 1976 or later approved revisions
6. Manual for Operation:
 - In Czech language
Doc. No. 232.071
Příručka pro provoz letounů Z 42 M, Z 42 MU
bez generálních oprav draku část 1 a 2, prohlídka A, B, C
Initial issue 30.1.1997 or later approved revisions
 - In English language
Doc. No. 232.071
Manual for operation of Z 42 M, Z 42 MU aircraft
without airframe overhaul, Part 1, Part 2, revision A, B, C,
Initial issue 30.1.1997 or later approved revisions
7. Instruments and Aggregates:
 - In Czech language
Doc. No. PRA. 081.1
Přístroje a agregáty, použité na letounech Z 42 M, Z 42 MU,
Z 142 a Z 43,
Initial issue 10.1.2012 or later approved revisions

CV. Notes

- Note 1: Model has been approved under original Czech CAA Type Certificate No. 73-06 dated November 30, 1973, Supplement No. 1 dated February 01, 1974.
- Note 2: The Z 42 MU aircraft have been converted by the aircraft manufacturer to the models: Z 42 M S/N: 0011; 0027
- Note 3: For operation of the airplane in other than the Normal Category, compliance with the applicable parts of Mandatory Service Bulletins Z42/54a, Z42/55a and Z42/56a or later revision of each is required.
- Note 4: The EASA type certification standard includes that of CAA Cz TCDS No. 69-01 based on individual EU member state acceptance or certification of this standard prior to 28 September 2003. Other standards confirming to TC/TCDS standards certificated by individual EU member state prior to 28 September 2003 are also acceptable.
- Note 5: The EASA type certification standard includes that of CAA Cz TCDS No. 69-02 based on individual EU member state acceptance or certification of this standard prior to 28 September 2003. Other standards confirming to TC/TCDS standards certificated by individual EU member state prior to 28 September 2003 are also acceptable.

SECTION D: Z 142

DI. General

1. a) Type: Z 42
b) Model: Z 142
2. Airworthiness category: Aerobatic (A) (see Note 2)
Utility (U) (see Note 2)
Normal (N) (see Note 2)
3. Type Certificate Holder: ZLIN AIRCRAFT a.s.
Letiště 1887
765 02 Otrokovice
CZECH REPUBLIC
4. Manufacturer: Moravan, n.p.
Letiště 1578
765 81 Otrokovice
CZECHOSLOVAKIA
S/N: 0201-0460

Moravan, k.p.
Letiště 1578
765 81 Otrokovice
CZECHOSLOVAKIA
S/N: 0461-0524

MORAVAN a.s.
Letiště 1578
765 81 Otrokovice
CZECH REPUBLIC
S/N: 0525-0540
5. Certification Application Date: November 22, 1977
6. CAA Cz Type Certificate Date: January 28, 1980
7. EASA Type Certificate Date: 22-Mar-2007 (reissue, EASA)

The EASA Type Certificate replaces the CAA CZ Type Certificate No. 80-01.

DII. Certification Basis

1. Reference Date for determining the applicable requirements: ---
2. (Reserved)
3. (Reserved)
4. Airworthiness Requirements: FAR PART 23, Amdt 23-13 (including)
5. Requirements elected to comply: None
6. EASA Special Conditions: None

7. EASA Exemptions: None
8. EASA Equivalent Safety Findings: § 23.177 (a)(2), (3) – Ample controllability of the airplane in specified conditions.
§ 23.1013(e) – The level of safety is retained with the multiple area of the strainer surface.
§ 23.1183(a) – The safety of hose materials is proved by experience in operation.
§ 23. 1323 – At the speeds above 240 km/hr, the accomplished correction is on the safe side.
§ 23.1383(a); § 23.1389(b); § 23.1391; § 23.1393; § 23.1395; § 23.1401 – The measurement of light intensity and of colour shade of position and anti-collision lights has not been performed.
It is permitted with respect to the fact that night flights are prevailingly of training character and are performed in a determined area.
9. EASA Environmental Standards: ICAO Annex 16/I, Chapter 10
FAR PART 36, App. G

DIII. Technical Characteristics and Operational Limitations

1. Type Design Definition: The specification list of Aircraft Z 142 No. S-Z142.0001.
2. Description: The Z 142 aircraft is two-seat, single-engine, low wing cantilever monoplane.
3. Equipment: Approved equipment list is stated in document Flight manual of the ZLIN Z 142 aircraft, Chapter 6.
4. Dimensions:
- | | |
|------------|----------------------|
| Span: | 9.160 m |
| Length: | 7.330 m |
| Height: | 2.750 m |
| Wing Area: | 13.15 m ² |
5. Engine:
- 5.1 Model: M 337 AK
- 5.2 Type Certificate: EASA approved (CAA CZ No. 94-06) (see Note 3)
- 5.3 Limitations:
- | | |
|------------------------|-----------------|
| Max. Take-off power | |
| max. Power | 154 kW (210 HP) |
| max. Engine speed | 2 750 RPM |
| max. Consumption | 61 l/h |
| max. Manifold pressure | 118 kPa |

	Continuous power	
	max. Power	125 kW (170 HP)
	max. Engine speed	2 600 RPM
	max. Consumption	56 l/h
	max. Manifold pressure	98 kPa
	Cruising power	
	max. Power	103 kW (140 HP)
	max. Engine speed	2 400 RPM
	max. Consumption	42 l/h
	max. Manifold pressure	90 kPa
6.	Load factors:	
	Category A	+6.0 g -3.5 g
	Category U	+5.0 g -3.0 g
	Category N	+3.8 g -1.5 g
7.	Propeller:	
	7.1 Model:	V 500 A
	7.2 Type Certificate:	EASA approved (CAA CZ TC No. 73-03) (see Note 4)
	7.3 Number of blades:	2
	7.4 Diameter:	2 000 mm
	7.5 Sense of Rotation:	Anticlockwise in flight direction
8.	Fluids:	
	8.1 Fuel:	LBZ 78 SHELL 80 ESSO 80 (TEO max. 0.06 % volume) Grade 100/130 (TEO max. 0.06 % volume) AVGAS 100 LL (DEFENCE STANDARD 91/90, ASTM D910)AVGAS 100L (gr. 100/130)
	8.2 Oil:	AERO SHELL 100 (a mineral oil) or equivalent – is recommended for running-in (max. up to 50 hours). AERO SHELL W 100 or equivalent – is recommended for after-running-in operation in temperate climatic area. AERO SHELL W 120 or equivalent – is recommended for after-running-in operation in tropical area. AERO SHELL W 65 or equivalent – is recommended for after-running-in operation during winter or in polar area.
	8.3 Coolant:	None
9.	Fluid capacities:	
	9.1 Fuel:	Total: Category A: 125 litres Category N: 225 litres
	Usable: Category A:	122 litres

Z 142

	Category N:		220 litres	
			2 x 60 litres in main tanks	
			2 x 50 litres in auxiliary wing tip tanks	
			1 x 5 litres in aerobatic tank	
9.2 Oil:	Minimum 7 litres – Maximum 12 litres			
9.3 Coolant system capacity:	None			
10. Air Speeds:	Never Exceed Speed Limit	V _{NE}		
	Category A, U		333 km/h IAS	
	Category N		332 km/h IAS	
	Normal Operating Speed Limit	V _{NO}		
	Category A, U		273 km/h IAS	
	Category N		272 km/h IAS	
	Design Manoeuvring Speed Limit	V _A		
	Category A		284 km/h IAS	
	Category U		264 km/h IAS	
	Category N		235 km/h IAS	
	Maximum Flaps Extended Speed Limit	V _F E		
	Category A, U		189 km/h IAS	
	Category N		188 km/h IAS	
11. Maximum Operating Altitude:	Category A		5 000 m	
	Category U		4 700 m	
	Category N		4 300 m	
12. All-weather Operations Capability:	The aircraft is approved for VFR Day flights.			
13. Maximum Weights:	Max. Take-off and Landing weight:			
	Category A		970 kg	
	Category U		1 020 kg	
	Category N			
	– Take-off weight		1 090 kg	
	– Landing weight		1 050 kg	
	Max. Variable Load:			
	Category A		240 kg	
	Category U		290 kg	
	Category N		360 kg	
14. Centre of Gravity Range:	20 % – 26 % MAC M.A.C. is 1 460 mm; 0 % M.A.C. is 300 mm aft reference datum.			
15. Datum:	The rear part of firewall; from it are measured, for purpose of assignation of Gravity Centre, all lateral dimensions.			
16. Control surface deflections:	Elevator deflection	up	34° + 0°; - 1°	
		down	31° + 1°	
	Rudder deflection	right and left	30° ± 2°	
	Ailerons deflection	up	21° ± 1°	Z 142
		down	17° ± 1°	

Wing flaps positions	retracted	0°
	take-off	14° ± 1°
	landing	37° ± 1°

17. Levelling Means: Levelling points on left and right side of airplane fuselage to be levelled. Measurement plane to be min. 600 mm below.
18. Minimum Flight Crew: 1 (Pilot)
19. Maximum Passenger Seating Capacity: 2 (including crew)
20. (Reserved)
21. Baggage/Cargo Compartments: Max. 20 kg.
22. Wheels and Tyres: Wheels of main gear K 22-0100-7 with tyre Barum 420 x 150 model 2 or
Wheels of main gear K 22-3100-7 with tyre Mitas 420 x 150 model 2 or Goodyear 6.00-6.5.
Wheel of nose gear K 23-0000-7 with tyre Barum 350 x 135, or
Wheel of nose gear K 51-1100-7 with tyre Mitas 350 x 135 or Goodyear 5.00-5.

DIV. Operating and Service Instructions

1. Flight Manual:
 - In Czech language *Letová příručka Z 142,
Initial issue 1982 or later approved revisions*
 - In English language *Flight Manual of the ZLIN 142 Aircraft,
Initial issue 1989 or later approved revisions*
 - In German language *Flughandbuch ZLIN 142,
Initial issue 1982 or later approved revisions*

2. Technical Manual:
 - In Czech language *Technický popis pro letoun ZLIN 142,
Initial issue 1988 or later approved revisions*
 - In English language *Technical Manual Z 142,
Initial issue 1990 or later approved revisions*

3. Repair Manual:
 - In Czech language *Oprávérenská příručka letounu ZLIN 142,
Initial issue 1988 or later approved revisions*

4. Catalogue of Spare Parts:
 - In Czech and English language *Katalog náhradních dílů Z 142
Catalogue of Spare Parts Z 142
Initial issue September 2010 or later approved revisions*

5. Table of Dimensions, Limits and Clearances:
 - In Russian, Czech, German and English language *Album rozměrů, tolerancí a vůlí Z 142
Album der Abmessungen, der Toleranz und Spielangabe
Z 142
Table of Dimensions, Limits and Clearance Z 142
Initial issue 1982 or later approved revisions*

6. Manual for Operation:
 - In Czech language *Příručka pro provoz letounu Z 142 bez generálních
Doc. No. Z002.071 oprav draku část 1, část 2, prohlídka A, B, C
Initial issue 1.6.1996 or later approved revisions*
 - In English language *Manual for Operation of Z 142 Aircraft without
Doc. No. Z002.071 airframe overhaul Part 1, Part 2, Revision A, B, C
Initial issue 1.6.1996 or later approved revisions*

7. Instruments and Aggregates:
 - In Czech language *Přístroje a agregáty, použité na letounech Z 42 M, Z 42 MU
Doc. No. PRA. 081.1 Z 142 a Z 43,
Initial issue 10.1.2012 or later approved revisions*

DV. Notes

- Note 1: Following Z 142 aircraft have been converted by the aircraft manufacturers to the models: Z 142 C S/N: 0524, 0535
- Note 2: For operation of the airplane in other than the Normal Category, compliance with the applicable parts of Mandatory Service Bulletins Z142/53a, Z142/54a and Z142/55a or later revision of each is required.
- Note 3: The EASA type certification standard includes that of CAA CZ TCDS No. 94-06 based on individual EU member state acceptance or certification of this standard prior to 28 September 2003. Other standards confirming to TC/TCDS standards certificated by individual EU member state prior to 28 September 2003 are also acceptable.
- Note 4: The EASA type certification standard includes that of CAA CZ TCDS No. 73-03 based on individual EU member state acceptance or certification of this standard prior to 28 September 2003. Other standards confirming to TC/TCDS standards certificated by individual EU member state prior to 28 September 2003 are also acceptable.

SECTION E: Z 142 C

EI. General

1. a) Type: Z 42
b) Model: Z 142 C
2. Airworthiness category: Aerobatic (A) (see Note 2)
Utility (U) (see Note 2)
Normal (N) (see Note 2)
3. Type Certificate Holder: ZLIN AIRCRAFT a.s.
Letiště 1887
765 02 Otrokovice
CZECH REPUBLIC
4. Manufacturer: Moravan a.s.
Letiště 1578
765 81 Otrokovice
CZECH REPUBLIC
S/N: 0541-0568

MORAVAN – AEROPLANES, a.s.
Letiště 1578
765 81 Otrokovice
CZECH REPUBLIC
S/N: 0569-0572
5. Application Date: ---
6. CAA CZ Type Certificate Date: July 18, 1991
7. EASA Type Certificate Date: 22-Mar-2007 (reissue, EASA)

The EASA Type Certificate replaces the CAA CZ Type Certificate No. 80-01.

EII. Certification Basis

1. Reference Date for determining the applicable requirements: ---
2. (Reserved)
3. (Reserved)
4. Airworthiness Requirements: FAR PART 23, Amdt 23-20 (including)
5. Requirements elected to comply: None
6. EASA Special Conditions: None
7. EASA Exemptions: None

8. EASA Equivalent Safety Findings: § 23.177 (a)(2), (3) – Ample controllability of the airplane in specified conditions.
§ 23.1013(e); § 23.1019(b) – The active strainer input area is thirty-times larger than the critical outlet section. The strainer blocking has never occurred during operation. Dangerous blocking is prevented by scheduled inspection periods. The airplane is provided with a duplicate oil pressure checking system.
§ 23.1323 – At the speeds above 240 km/h, the accomplished correction is on the safe side.
9. EASA Environmental Standards: ICAO Annex 16/I, Chapter 10
FAR PART 36, App. G

EIII. Technical Characteristics and Operational Limitations

1. Type Design Definition: The specification list of Aircraft Z 142 C No. S-C142.0000.
2. Description: The Z 142 C aircraft is two-seat, single-engine, low wing cantilever monoplane.
3. Equipment: Approval equipment list is stated in document Flight manual of the ZLIN Z 142C aircraft, Chapter 6.
4. Dimensions:
- | | |
|------------|----------------------|
| Span: | 9.160 m |
| Length: | 7.330 m |
| Height: | 2.750 m |
| Wing Area: | 13.15 m ² |
5. Engine:
- 5.1 Model: M 337 AK
- 5.2 Type Certificate: EASA approved (CAA CZ TC No. 94-06) (see Note 3)
- 5.3 Limitations:
- | | |
|------------------------|------------------|
| Max. Take-off power | |
| max. Power | 154 kW, (210 HP) |
| max. Engine speed | 2 750 RPM |
| max. Manifold pressure | 118 kPa |
| Continuous power | |
| max. Power | 125 kW, (170 HP) |
| max. Engine speed | 2 600 RPM |
| max. Manifold pressure | 98 kPa |
| Cruising power | |
| max. Power | 103 kW, (140 HP) |
| max. Engine speed | 2 400 RPM |
| max. Manifold pressure | 90 kPa |
6. Load factors:
- | | |
|------------|----------------|
| Category A | +6.0 g, -3.5 g |
| Category U | +5.0 g, -3.0 g |
| Category N | +3.8 g, -1.5 g |

7. Propeller:
- 7.1 Model: V 500 A
- 7.2 Type Certificate: EASA approved (CAA CZ TC No. 73-03) (see Note 4)
- 7.3 Number of blades: 2
- 7.4 Diameter: 2 000 mm
- 7.5 Sense of Rotation: Anticlockwise in flight direction.
8. Fluids:
- 8.1 Fuel: LBZ 78
SHELL 80
ESSO 80 (TEO max. 0.06 % volume)
Grade 100/130 (TEO max. 0.06 % volume)
AVGAS 100 LL
(DEFENCE STANDARD 91/90, ASTM D910)
- 8.2 Oil: AERO SHELL 100 (a mineral oil) or equivalent – is recommended for running-in (max. up to 50 hours).
AERO SHELL W 100 or equivalent – is recommended for after-running-in operation in temperate climatic area.
AERO SHELL W 120 or equivalent – is recommended for after-running-in operation in tropical area.
AERO SHELL W 65 or equivalent – is recommended for after-running-in operation during winter or in polar area.
- 8.3 Coolant: None
9. Fluid capacities:
- 9.1 Fuel: Total: for category A: 125 litres
for category N: 225 litres
Usable: for category A: 122 litres
for category N: 220 litres
2 x 60 litres in main tanks
2 x 50 litres in auxiliary wing tip tanks
1 x 5 litres in aerobatic tank
- 9.2 Oil: Minimum 7 litres – Maximum 12 litres
- 9.3 Coolant system capacity: None
10. Air Speeds: Never Exceed Speed Limit V_{NE}
Category A, U 333 km/h IAS
Category N 332 km/h IAS

	Normal Operating Speed Limit	V _{NO}	
	Category A, U		273 km/h IAS
	Category N		272 km/h IAS
	Design Manoeuvring Speed Limit	V _A	
	Category A		284 km/h IAS
	Category U		264 km/h IAS
	Category N		235 km/h IAS
	Maximum Flaps Extended Speed Limit	V _F E	
	Category A, U		189 km/h IAS
	Category N		188 km/h IAS
11. Maximum Operating Altitude:	Category A		4 750 m
	Category U		4 500 m
	Category N		4 300 m
12. All-weather Operations Capability:	The aircraft is approved for VFR Day and Night flights. IFR, not icing conditions.		
13. Maximum Weights:	Max. Take-off and Landing weight:		
	Category A		970 kg
	Category U		1 020 kg
	Category N		
	- Take-off weight		1 090 kg
	- Landing weight		1 050 kg
	Max. Variable Load:		
	Category A, U, N		200 kg
14. Centre of Gravity Range:	20 % – 26 % MAC M.A.C. is 1 460 mm; 0 % M.A.C. is 300 mm aft reference datum.		
15. Datum:	The rear part of firewall; from it are measured, for purpose of assignation of Gravity Centre, all lateral dimensions.		
16. Control surface deflections:	Elevator deflection	up	34° + 0°; - 1°
		down	31° + 1°
	Rudder deflection	right and left	30° ± 2°
	Ailerons deflection	up	21° ± 1°
		down	17° ± 1°
	Wing flaps positions	retracted	0°
		take-off	14° ± 1°
		landing	37° ± 1°
17. Levelling Means:	Levelling points on left and right side of airplane fuselage to be levelled. Measurement plane to be min. 600 mm below.		
18. Minimum Flight Crew:	1 (Pilot)		
19. Maximum Passenger Seating Capacity:	2 (including crew)		
20. (Reserved)			

21. Baggage/Cargo Compartments: Max. 20 kg
22. Wheels and Tyres:
Wheels of main gear K 22-0100-7 with tyre
Barum 420 x 150 model 2 or
Wheels of main gear K 22-3100-7 with tyre
Mitas 420 x 150 model 2 or Goodyear 6.00-6.5.

Wheel of nose gear K 23-0000-7 with tyre
Barum 350 x 135, or
Wheel of nose gear K 51-1100-7 with tyre
Mitas 350 x 135 or Goodyear 5.00-5

EIV. Operating and Service Instructions

1. Flight Manual:
 - In English language Flight Manual of the Z 142 C Aircraft,
Initial issue October 21, 1991 or later approved revisions

2. Maintenance Manual:
 - In Czech language Návod pro údržbu pro letoun ZLIN 142 C, část II,
Initial issue 1.11.1993 or later approved revisions

 - In English language Maintenance Manual of the Z 142 C Aircraft Vol. I,
Initial issue 15.7.1991 or later approved revisions

Maintenance Manual of the Z 142 C Aircraft Vol. II,
Initial issue November 1, 1993 or later approved revisions

3. Catalogue of spare parts:
 - In Czech, English and German language
Katalog náhradních dílů Z 142 C
Catalogue of spare parts Z 142 C
Katalog der Ersatzteile Z 142 C
Initial issue 1994 or later approved revisions

4. Table of dimensions, limits and clearances:
 - In Czech, English and German language
Album rozměrů, tolerancí a vůlí ZLIN 142 C - Z 142 C-AF
Table of dimensions, limits and clearances ZLIN 142 C -
Z 142 C-AF
Album der Abmessungen, der Toleranz – und spielanlagen
ZLIN 142 C - Z 142 C-AF
Initial issue or later approved revisions

EV. Notes

- Note 1: The Z 142 C aircraft have been converted by the aircraft manufacturer to the models:
Z 242 L S/N: 0541
- Note 2: For operation of the airplane in other than the Normal Category, compliance with the applicable parts of Mandatory Service Bulletins Z142C/30a, Z142C/31a and Z142C/32a or later revision of each is required.
- Note 3: The EASA type certification standard includes that of CAA CZ TCDS No. 94-06 based on individual EU member state acceptance or certification of this standard prior to 28 September 2003. Other standards confirming to TC/TCDS standards certificated by individual EU member state prior to 28 September 2003 are also acceptable.
- Note 4: The EASA type certification standard includes that of CAA CZ TCDS No. 73-03 based on individual EU member state acceptance or certification of this standard prior to 28 September 2003. Other standards confirming to TC/TCDS standards certificated by individual EU member state prior to 28 September 2003 are also acceptable.

SECTION F: Z 242 L

FI. General

1. a) Type: Z 42
b) Model: Z 242 L

2. Airworthiness category: Aerobatic (A) (see Note 1)
Utility (U) (see Note 1)
Normal (N) (see Note 1)

3. Type Certificate Holder: ZLIN AIRCRAFT a.s.
Letiště 1887
765 02 Otrokovice
CZECH REPUBLIC

4. Manufacturer: Moravan a.s.
Letiště 1578
765 81 Otrokovice
CZECH REPUBLIC
S/N: 0651-0730

MORAVAN - AEROPLANES a.s.
Letiště 1578
765 81 Otrokovice
CZECH REPUBLIC
S/N: 0731-0769, except S/N 0768

Moravan Aviation s.r.o.
Letiště 1578
765 81 Otrokovice
CZECH REPUBLIC
S/N: 0770-0789

ZLIN AIRCRAFT a.s.
Letiště 1887
765 02 Otrokovice
CZECH REPUBLIC
S/N: 0768 and from S/N 0790 and up

5. Certification Application Date: February 13, 1989

6. CAA CZ Type Certificate Date: April 22, 1992

7. EASA Type Certificate Date: 01-Feb-2005 (reissue, EASA)

The EASA Type Certificate replaces the CAA CZ Type Certificate No. 92-03

FII. Certification Basis

1. Reference Date for determining the applicable requirements: February 13, 1989

2. (Reserved)

3. (Reserved)
4. Airworthiness Requirement: FAR PART 23, Amdt. 23-36 (including)
5. Requirements elected to comply: None
6. EASA Special Conditions: None
7. EASA Exemptions: None
8. EASA Equivalent Safety Findings: § 23.177(a)(2), (3), Exception to verbal fulfilment. An equivalent safety is provided.
9. EASA Environmental Standards: ICAO Annex 16/I, Chapter 10
FAR PART 36, App. G (Amdt. 36-20)

FIII. Technical Characteristics and Operational Limitations

1. Type Design Definition: The specification list of Aircraft Z 242 L No. S-L242.0000; the specification drawing No. L242.0000
2. Description: The Z 242 L aircraft is two-seat, low wing, single-engine, cantilever monoplane.
3. Equipment: Master equipment list is stated in document Flight manual of the ZLIN Z 242 L aircraft, Chapter 6.
4. Dimensions:

Span:	9.340 m
Length:	6.940 m
Height:	2.950 m
Wing Area:	13.860 m ²
5. Engine:
 - 5.1 Model: TEXTRON Lycoming AEIO-360-A1B6
 - 5.2 Type Certificate: EASA approved (FAA TC No. 1E10) (see Note 2)
 - 5.3 Limitations:

Max. Continuous power (MT)	
max. Power	149 kW
max. Engine speed	2 700 RPM
max. Consumption	61 l/h
max. Manifold pressure	101 kPa
Cruising (75 % MC)	
max. Power	112 kW
max. Engine speed	2 450 RPM
max. Consumption	46.5 l/h
max. Manifold pressure	82 kPa
Cruising (65 % MC)	
max. Power	97 kW
max. Engine speed	2 350 RPM
max. Consumption	36 l/h
max. Manifold pressure	78 kPa

6. Load factors:
- | | |
|------------|----------------|
| Category A | +6.0 g, -3.5 g |
| Category U | +5.0 g, -3.0 g |
| Category N | +3.8 g, -1.5 g |
7. Propellers:
- 7.1.1 Model: MTV-9-B-C/C-188-18a
- 7.1.2 Type Certificate: EASA approved (LBA TC No. 32.130/65) (see Note 3)
- 7.1.3 Number of blades: 3
- 7.1.4 Diameter: 1 880 mm
- 7.1.5 Sense of Rotation: Clockwise in flight direction
- or
- 7.2.1 Model: HC-C3YR-4BF/FC6890
- 7.2.2 Type Certificate: EASA approved (FAA TC No. P25EA) (see Note 4)
- 7.2.3 Number of blades: 3
- 7.2.4 Diameter: 1 780 mm
- 7.2.5 Sense of Rotation: Clockwise in flight direction.
8. Fluids:
- 8.1 Fuel: Aviation gasoline 100L, 100LL or BL 95
(see service instruction of Engine manufacturer)
- 8.2 Oil: See Airplane flight manual
- 8.3 Coolant: None
9. Fluid capacities:
- 9.1 Fuel:
- | | |
|---------------------|------------|
| Total: Category A: | 120 litres |
| Category N: | 230 litres |
| Usable: Category A: | 117 litres |
| Category N: | 225 litres |
- 2 x 60 litres in main tanks
2 x 55 litres in auxiliary wing tip tanks
- 9.2 Oil: Minimum 4 litres – Maximum 8 litres
- 9.3 Coolant system capacity: None

10. Air Speeds:
- | | | |
|--|------------------|--------------|
| Never Exceed Speed Limit | V _{NE} | 319 km/h IAS |
| Normal Operating Speed Limit | V _{NO} | 250 km/h IAS |
| Design Manoeuvring Speed Limit | V _A | |
| Category A | | 265 km/h IAS |
| Category U | | 248 km/h IAS |
| Category N | | 224 km/h IAS |
| Maximum Flaps Extended Speed Limit | V _{FEE} | 184 km/h IAS |
| Maximum Permissible Snap Manoeuvre Speed Limit | | |
| Category A | | 175 km/h IAS |
11. Maximum Operating Altitude:
- | | |
|------------|---------|
| Category A | 4 800 m |
| Category U | 4 600 m |
| Category N | 4 500 m |
12. All-weather Operations Capability: VFR Day and Night, IFR, not in icing conditions
13. Maximum Weights:
- | | |
|-------------------------|----------|
| Maximum Take-off Weight | |
| Category A | 970 kg |
| Category U | 1 020 kg |
| Category N | 1 090 kg |
| Maximum Landing Weight | |
| Category A | 970 kg |
| Category U | 1 020 kg |
| Category N | 1 050 kg |
| Maximum Variable Load | |
| Category A | 240 kg |
| Category U | 290 kg |
| Category N | 360 kg |
14. Centre of Gravity Range: 19 % ÷ 26 % MAC
M.A.C. is 1 504 mm; 0 % M.A.C. is 368.4 mm aft reference datum.
15. Datum: The rear part of firewall; from it are measured, for purpose of assignation of Gravity Centre, all lateral dimensions.
16. Control Surface Deflections:
- | | | |
|----------------------|----------------|----------------|
| Elevator deflection | up | 34° + 0°; - 1° |
| | down | 31° + 1°; - 0° |
| Rudder deflection | right and left | 30° ± 2° |
| Ailerons deflection | up | 21° ± 1° |
| | down | 17° ± 1° |
| Wing flaps positions | retracted | 0° |
| | take-off | 14° ± 1° |
| | landing | 37° ± 1° |
17. Levelling Means: Levelling points on left and right side of airplane fuselage to be levelled. Measurement plane to be min. 600 mm below.
18. Minimum Flight Crew: 1 (Pilot)

19. Maximum Passenger Seating Capacity: 2 (including crew)
20. (Reserved)
21. Baggage/Cargo Compartments: Max. 20 kg (for category Normal)
22. Wheels and Tyres: Wheels of main gear K 22-0100-7 with tyre Barum 420 x 150 model 2 or
Wheels of main gear K 22-3100-7 with tyre Mitas 420 x 150 model 2 or Goodyear 6.00-6.5.
Wheel of nose gear K 23-0000-7 with tyre Barum 350 x 135, or
Wheel of nose gear K 51-1100-7 with tyre Mitas 350 x 135 or Goodyear 5.00-5

FIV. Operating and Service Instructions

1. Flight Manual:
 - In Czech language
Doc. No. 003.011.1
Letová příručka pro letoun ZLIN Z 242 L
Initial issue 20.3.2011 or later approved revisions
 - In English language
Doc. No. 003.012.1
Flight Manual of the ZLIN Z 242 L Aircraft
Initial issue 20.3.2011 or later approved revisions
2. Maintenance Manual:
 - In Czech language
Doc. No. 003.021.1
Návod pro údržbu letounu Z 242 L - část I,
Initial issue 1.3.1996 or later approved revisions
 - Doc. No. 003.031.1
Návod pro údržbu letounu Z 242 L - část II,
Initial issue 1.5.1997 or later approved revisions
 - In English language
Doc. No. 003.022.1
Maintenance Manual of the Z 242 L Aircraft - Vol. I
Initial issue Mar 1, 1996 or later approved revisions
 - Doc. No. 003.032.1
Maintenance Manual of the Z 242 L Aircraft - Vol. II
Initial issue May 1, 1998 or later approved revisions
3. Table of dimensions, limits and clearances:
 - In Czech English and German language
Doc. No. 003.050
Album rozměrů, tolerancí a vůlí Z 242 L
Table of dimensions, limits and clearances Z 242 L
Album der abmessungen, der toleranz-und
spielangaben Z 242 L,
Initial issue 1996 or later approved revisions
4. Illustrated parts catalog:
 - In Czech and English language
Doc. No. 003.040.4
Katalog náhradních dílů letounu Z 242 L
Illustrated parts catalog Z 242 L,
Initial issue April 2014 or later approved revisions

FV. Notes:

- Note 1: For operation of the airplane in other than the Normal Category, compliance with the applicable parts of Mandatory Service Bulletins Z242L/49a, Z242L/51a and Z242L/52a or later revision of each is required.
- Note 2: The EASA type certification standard includes that of FAA TCDS No. 1E10 based on individual EU member state acceptance or certification of this standard prior to 28 September 2003. Other standards confirming to TC/TCDS standards certificated by individual EU member state prior to 28 September 2003 are also acceptable.
- Note 3: The EASA type certification standard includes that of LBA TCDS No. 32.130/65 based on individual EU member state acceptance or certification of this standard prior to 28 September 2003. Other standards confirming to TC/TCDS standards certificated by individual EU member state prior to 28 September 2003 are also acceptable.
- Note 4: The EASA type certification standard includes that of FAA TCDS No. P25EA based on individual EU member state acceptance or certification of this standard prior to 28 September 2003. Other standards confirming to TC/TCDS standards certificated by individual EU member state prior to 28 September 2003 are also acceptable.

ADMINISTRATIVE SECTION

I Acronyms
N/A

II Type Certificate Holder Record:

Current:

ZLIN AIRCRAFT a.s.
Letiště 1887
765 02 Otrokovice
CZECH REPUBLIC

Former:

Moravan, n.p.
Letiště 1578
765 81 Otrokovice
CZECHOSLOVAKIA

Moravan, k.p.
Letiště 1578
765 81 Otrokovice
CZECHOSLOVAKIA

Moravan a.s.
Letiště 1578
765 81 Otrokovice
CZECH REPUBLIC

MORAVAN-AEROPLANES a.s.
Letiště 1578
765 81 Otrokovice
CZECH REPUBLIC

Moravan Aviation s.r.o.
Letiště 1578
765 81 Otrokovice
CZECH REPUBLIC

III Change Record

Issue	Date	Changes
Issue 1	04-Feb-2005	Transfer of ZLIN Z 242 L Type Design to EASA
Issue 2	23-Mar-2007	Transfer of ZLIN Z 42 as basic Type Design under this TC / TCDS Transfer of ZLIN Z 42 M, Z 42 MU, Z 142, and Z 142 C
Issue 3	24-Aug-2009	Change of Company's Name
Issue 4	23-July 2010	Editorial corrections Revision into standard EASA TCDS format
Issue 5	25-Aug-2010	Change to the reference to the TC of the Z-42.6413 propeller which =was issued with TC EASA.P.176 on 19 August 2010.
Issue 6	02-Nov-2010	Corrections to Section F, Z-242 L, serial numbers manufactured by each company and the removal of certain serial numbers of airframes that were used solely for testing purposes.
Issue 7	25 April-2016	Editorial and formal correction Revision of actual accompanying documentation