



---

# TYPE-CERTIFICATE DATA SHEET

NO. EASA.A.637

**for**  
P2012

**Type Certificate Holder**  
Costruzioni Aeronautiche TECNAM SPA

Via S. D'acquisto, 62  
80042 Boscotrecase (Na)  
ITALIA

For models: P2012 Traveller



Intentionally left blank



## CONTENT

<b>SECTION A: P2012 TRAVELLER .....</b>	<b>4</b>
<b>A.I. General .....</b>	<b>4</b>
<b>A.II. EASA Certification Basis.....</b>	<b>4</b>
<b>A.III. Technical Characteristics and Operational Limitations .....</b>	<b>5</b>
<b>A.IV. Operating and Service Instructions .....</b>	<b>8</b>
<b>A.V. Notes.....</b>	<b>8</b>
<b>SECTION ADMINISTRATIVE .....</b>	<b>9</b>
<b>I. Acronyms &amp; Abbreviations.....</b>	<b>9</b>
<b>II. Type Certificate Holder Record.....</b>	<b>9</b>
<b>III. Change Record .....</b>	<b>9</b>



## **SECTION A: P2012 TRAVELLER**

### **A.I. General**

1. Type/ Model/ Variant	
1.1 Type	P2012
1.2 Model	P2012 Traveller
1.3 Variant	-----
2. Airworthiness Category	CS-23 Normal Category
3. Manufacturer	Costruzioni Aeronautiche TECNAM SPA. Via S. D'acquisto, 62 80042 Boscotrecase (NA) ITALIA
4. EASA Type Certification	
Application Date	29 November 2015
6. State of Design Authority Type	
Certificate Date	N/A
7. EASA Type Certification Date	19 December 2018

### **A.II. EASA Certification Basis**

1. Reference Date for determining the applicable requirements	19 December 2015
2. Airworthiness Requirements	EASA CS-23 amdt. 4 dated 15 July 2015.
3. Special Conditions	SC-C23.div01 Human Factors –Integrated Avionic System (CRI B-52); SC-F23.1353-02 Lithium battery installation (CRI F 58); SC-CS-23.1305 Fuel low level annunciation means (CRI E-060); SC-CS-23.803 Emergency evacuation for Air Medical service (CRI-D-103), see note 7;
4. Exemptions	None
5. (Reserved) Deviations	None
6. Equivalent Safety Findings	None
7. Requirements elected to comply:	CS-23 Amdt.4 § 783(d)(e) CS-23 Amdt.4 § 803(a) CS-23 Amdt.4 § 807(d) CS-23 Amdt.4 § 811(b) CS-23 Amdt.4 § 813(a) CS-23 Amdt.4 § 853(d) FAR 23.856
8. Environmental Protection	Refer to TCDSN EASA.A.637;



### **A.III. Technical Characteristics and Operational Limitations**

1. Type Design Definition	C. A. Tecnam Aircraft P2012 report "Type design definition" 2012/003 1 <sup>st</sup> ed. and later revision		
2. Description	Twin engine, 11 seats, high wing airplane, aluminium construction, fixed tricycle landing gear.		
3. Equipment	Equipment list, Doc. 2012/100 AFM Section 6 latest issue		
4. Dimensions:	Span	14.0 m	(45.9 ft)
	Length	11.8 m	(38.7 ft)
	Height	4.4 m	(14.4 ft)
	Wing Area	25.4 m <sup>2</sup>	(273 sqft)
5. Engine			
5.1. Model	No.2 Lycoming TEO-540-C1A		
5.2 Type Certificate	EASA TCDS n° IM.E.119 dated 12 December 2018		
5.3 Limitations	Max continuous power 280 kW (375HP) at 2575 RPM Other engine's limitations are listed in doc. No. 2012/100 "AFM", Section 2		
6. Load factors			
6.1Basic		Flap UP	Flap DOWN
	Positive	+3.44 g	+2.0 g
	Negative	-1.37g	0.0 g
7. Propeller			
7.1 Model	No.2 MT Propeller MTV-14-B-C-F/CF195-30 ( ) (see note 1)		
7.2 Type Certificate	EASA TCDS n° P.017		
7.3 Number of blades	4		
7.4 Diameter	1950 mm		
7.5 Sense of Rotation	Clockwise (pilot's view)		
8. Fluids			
8.1 Fuel	AVGAS 100LL (ASTM D910) (see Lycoming SI-1070)		
8.2 Oil	Lubricant specifications and grade are detailed into the Lycoming SI-1014.		
9. Fluid capacities			
9.1 Fuel	Total:	750 litres	(198.1 US Gallon)
	Usable:	728 litres	(192.3 US Gallon)
9.2 Oil	Maximum oil capacity:	11.3 litres	(12.0 qts)
	Minimum:	3.8 litres	(4.0 qts)



## 10. Airspeeds (Basic)

Design Maneuvering Speed $V_A$ :	141 KIAS (142 KCAS)
Flap Extended Speed $V_{FE}$ :	119 KIAS (119 KCAS) <i>LND</i> 124 KIAS (125 KCAS) <i>TO</i>
Minimum Control Speed $V_{MC}$ :	70 KIAS (76 KCAS) <i>TO</i> 67 KIAS (73 KCAS) <i>LND</i>
Cruising Speed $V_{NO}$ :	176 KIAS (175 KCAS) <small>(up to 15000ft)</small>
Cruising Speed $V_{NO}$ (see note 9):	161 KIAS (161 KCAS) @19500ft
Never Exceed Speed $V_{NE}$ :	223 KIAS (219 KCAS) <small>(up to 15000ft)</small>
Never Exceed Speed $V_{NE}$ (see note 9):	204 KIAS (202 KCAS) @19500ft

### 10.1 Airspeeds (Optional) see note 5:

Design Maneuvering Speed $V_A$ :	143 KIAS (143 KCAS)
Flap Extended Speed $V_{FE}$ :	120 KIAS (120 KCAS) <i>LND</i> 126 KIAS (127 KCAS) <i>TO</i>
Minimum Control Speed $V_{MC}$ :	71 KIAS (77 KCAS) <i>TO</i> 68 KIAS (74 KCAS) <i>LND</i>
Cruising Speed $V_{NO}$ :	178 KIAS (177 KCAS) <small>(up to 15000ft)</small>
Cruising Speed $V_{NO}$ (see note 9):	161 KIAS (161 KCAS) @19500ft
Never Exceed Speed $V_{NE}$ :	226 KIAS (222 KCAS) <small>(up to 15000ft)</small>
Never Exceed Speed $V_{NE}$ (see note 9):	205 KIAS (202 KCAS) @19500ft

11. Maximum Operating Altitude: 19500 ft (see note 8)

## 12. Approved Operations Capability

Day/Night-VFR, IFR

Flight into expected or actual icing conditions is allowed only if Ice Protection system (MOD2012/002) is installed.

Flight into expected or actual icing conditions is forbidden if stall warning device (MOD2012/022) is installed

## 13. Maximum Masses (Basic)

Take-off	3600 kg	(7936 lb)
Landing	3600 kg	(7936 lb)

### 13.1 Maximum Masses (Optional) see note 5:

Take-off	3680 kg	(8113 lb)
Landing	3630 kg	(8003 lb)

## 14. Centre of Gravity Range

Forward limit:  
0.367 m (18.0 % MAC) behind Datum up to 3000Kg



	0.441 m	(22.0 % MAC) behind Datum at MTOW:3600Kg
	0.450 m	(22.5 % MAC) behind Datum at MTOW:3680Kg(see note 5).
	Straight line variation between indicated points.	
	Rear limit:	
	0.606 m	(31.0 % MAC) behind Datum
	MAC is 1.839m (72.4 in)	
15. Datum	Vertical plane tangent to wing leading edge	
16. Control surface deflections	Elevator: $23^{\circ}\pm 2^{\circ}$ to pitch up / $13^{\circ}\pm 2^{\circ}$ to pitch down Elevator Trim Tab: $-8 \pm 2^{\circ}$ upward / $-21^{\circ}\pm 2^{\circ}$ downward Elevator Trim Tab: $-6 \pm 4^{\circ}$ upward / $-23^{\circ}\pm 4^{\circ}$ downward (see note 5). Aileron: $20^{\circ}\pm 2^{\circ}$ upward / $15^{\circ}\pm 2^{\circ}$ downward Aileron Trim Tab: $30^{\circ}\pm 2^{\circ}$ upward / $28^{\circ}\pm 2^{\circ}$ downward Rudder: $22^{\circ}\pm 2^{\circ}$ left / $22^{\circ}\pm 2^{\circ}$ right Rudder Trim Tab: $6^{\circ}\pm 2^{\circ}$ left / $6^{\circ}\pm 2^{\circ}$ right Flaps: $0^{\circ}$ Fully Retracted/ $15^{\circ}\pm 2^{\circ}$ TO / $30^{\circ}\pm 2^{\circ}$ Fully Extended	
17. Levelling Means	Seat support tracks (see AFM, 2012/100, Sect.6 for the procedure)	
18. Minimum Flight Crew	1 (Pilot)	
19. Maximum Passenger Seating Capacity	9 (see note 6)	
20. Baggage/ Cargo Compartments	Max. allowable Loads: Front 103 kg (227 lb) Location 3.316m (10,88 ft) fwd of datum Rear 239Kg (527 lb) Location 3.518m (11,54 ft) aft of datum	
21. Wheels and Tyres	Nose Wheel Tyre Size	6.00-6
	Main Wheel Tyre Size	6.50-10
22. Serial Numbers Eligible:	S/N 002 and subsequent;	



#### **A.IV. Operating and Service Instructions**

- |                                |  |
|--------------------------------|--|
| 1. Flight Manual               | Doc. No 2012/100 "Aircraft Flight Manual" Issue. 1 or latest issue.              |
| 2. Maintenance Manual          | Doc. No 2012/101 "Aircraft Maintenance Manual" Issue. 1 or latest issue          |
| 3. Illustrated Parts Catalogue | Doc. No 2012/103 "Aircraft Illustrated Parts Catalogue" Issue. 1 or latest issue |
| 4. Instruments and aggregates: | Doc. No 2012/101 "Aircraft Maintenance Manual" Issue. 1 or latest issue          |

#### **A.V. Notes**

**Note 1:** As per Manufacturer TCDS, propellers with designation having a "small" letter in the place of the brackets (for example "MTV-14-B-C-F/CF 195-30x") may be installed since it does not affect interchangeability. A capital letter in the place of the bracket (for example MTV-14-B-C-F/CF 195-30X) may not be installed according to propeller TCDS since it may affect interchangeability

**Note 2:** Fuel Combustion Heater change (MOD2012/008) is approved as per EASA approval No. 10069738

**Note 3:** Until the completion of the Fatigue Test, the A/C is life limited as listed in Section 04 of the AMM.

**Note 4:** The following P2012 Optional Equipment are approved within Type of investigation process

##### P2012 Optional Equipment

ID	System Description
MOD2012/001	Autopilot System
MOD2012/002	TKS FIKI system Ice protection system
MOD2012/003	Flight Management System keyboard
MOD2012/004	Weather radar
MOD2012/005	TAS unit
MOD2012/006	Satellite data-link
MOD2012/007	Iridium data-link
MOD2012/009	Air Conditioning

**Note 5:** When MOD 2012/017 (EASA approval 10073218) "MTOW increment up to 3680kg" is installed

**Note 6:** the maximum passenger seating capacity is limited when MOD2012/098 (EASA approval 10074612) "SMP configuration" is installed, refer to details reported in No.2012/100 "AFM Supplement S-15, Section 2".

**Note 7:** When MOD 2012/027 (EASA approval 10075149) "P2012 MedEvac configuration" is installed

**Note 8:** For Flight operation above 13000ft the maximum seating capacity is reduced to 4 occupants and oxygen operational requirements must be met by operators, refer to details reported in No.2012/100 "AFM Supplement S-20, approved as per MOD 2012/020 (EASA approval 10076658) "Max operating altitude at 19500ft".

**Note 9:** Airspeed value linearly reducing from 15000ft to 19500ft





## **SECTION ADMINISTRATIVE**

### **I. Acronyms & Abbreviations**

AFM – Aircraft Flight Manual  
 AMM – Aircraft Maintenance Manual  
 CRI – Certification Review Item  
 CS – Certification Specification  
 EASA – European Union Aviation Safety Agency  
 ICAO – International Civil Aviation Organization  
 IPC – Illustrated Part Catalogue  
 KCAS – Knots Calibrated Air Speed  
 KOEL – Kind of Operations Equipment List  
 MAC – Mean Aerodynamic Chord  
 MTOW – Maximum Take-Off Weight  
 VFR – Visual Flight Rules

### **II. Type Certificate Holder Record**

<b>TC Holder</b>	<b>Period</b>
Costruzioni Aeronautiche TECNAM S.P.A. Via S. D'acquisto, 62 80062 Boscotrecase (NA), ITALY	Effective

### **III. Change Record**

<b>Issue</b>	<b>Date</b>	<b>Changes</b>	<b>TC Issue No. &amp; Date</b>
01	19 November 2018	Initial Issue	EASA.A.637
02	29 April 2019	MOD2012/008 Approval (EASA N. 10069738) and typos error removal	/
03	29 May 2019	MOD2012/022 Approval (EASA N. 10070098) and Company business address update	/
04	27 December 2019	Updated propeller and engine information (field A.III (5.1 and 7.1). Amended note 1	/
05	06 May 2020	MOD 2012/017 (EASA N.10073218) is added	/
06	20 October 2020	MOD 2012/098 (EASA N.10074612) (SMP) is added	/
07	14 December 2020	Updated certification basis (filed 3 and 8 in A.II) and added MOD 2012/027 (EASA N. 10075149)	/
08	16 June 2021	Update maximum operating altitude and airspeeds in accordance with MOD2012/020 (EASA approval 10076658)	

-END-

