

EDDY DISSIPATION RATE (EDR) UPLINK DEMONSTRATION AND CAPACITY AND EFFICIENCY BENEFITS QUANTIFICATION

**Eldridge Frazier
WTIC Program Engineer
202-267-2790
Eldridge.Frazier@faa.gov**

October 29, 2015



FAA/Delta Air Lines EDR Uplink Demo

August 2013 – July 2014

- Proof of Concept demonstration FAA and Delta Airlines
- 1-year flight demonstration period
- Goals:
 - ✦ Assess the feasibility of flight crews using electronics flight bag to display turbulence observation (Eddy Dissipation Rate-EDR) and forecast (Graphical Turbulence Guidance-GTG) information in cockpit
 - ✦ Identify and address human factors considerations
 - ✦ Quantify NAS efficiency and capacity benefits from the provision of GTG / EDR information to flight crews




Hypothesis

- Temporal and spatial relevant turbulence information in the cockpit will enhance cabin safety, reduce unnecessary pilot initiated altitude diversions, and improve the capacity and efficiency of the NAS
 - ✦ **Better cabin management**
 - ✦ **Reduce excessive fuel burn**
 - ✦ Reduce unnecessary reallocation of airspace
- } Demonstration Effort

EDR Uplink Demonstration

- 80 Line Check Pilots
- 300 Aircraft \cong 14.5 M Objective Reports
- 40,000+ Flights
- Web Viewer Application
 - ✦ Turbulence reports overlaid on turbulence forecast
 - ✦ Tablet in the cockpit
 - ✦ WiFi in the aircraft
- Acceptance amongst the participating pilots was outstanding

Turbulence Viewer Application




FAA

NextGEN


Turbulence Viewer Application

Smoother Ride Selection



Turbulence Viewer Application

Cabin Management on Approach



FAA

NextGEN

Turbulence Decision Making Factors During Demonstration

- Pre-Flight – All available sources
- En-route Altitude Changes
 - ✦ Source
 - ATC “Chat Room” 17%
 - Turbulence Viewer 81%
 - ✦ Flights off Optimum Altitude 28%
- Additional benefits
 - ✦ Reduced Radio Calls 44%
 - ✦ Decreased Workloads 37%
 - ATC / Pilots

EDR Uplink Capacity and Efficiency Benefits Assessment

Hypothesis

- Temporal and spatial relevant turbulence information in the cockpit will enhance cabin safety, reduce unnecessary pilot initiated altitude diversions, and improve the capacity and efficiency of the NAS
 - ✦ Better cabin management
 - ✦ Reduce excessive fuel burn
 - ✦ **Reduce unnecessary reallocation of airspace**
- } Quantification Effort

Demonstration Data Collection Periods


- **Baseline period** (October 2012 – June 2013)
 - Baseline data used to establish pre-demonstration and pre-viewer flight crew behaviors in / around areas of clear-air turbulence (e.g., not convectively-induced)
- **Demonstration period** (August 2013 – July 2014)
 - All Delta Air Lines EDR reporting flights
- **Demonstration period with viewer** (August 2013 – July 2014)
 - Delta Air Line flights with viewer
 - Delta Air Line flights submitting questionnaires
 - Subset of Demonstration Period as a whole
 - Includes key questionnaire data submitted by pilots regarding usability of and advantages / disadvantages of viewer tool
- Data collected throughout the Baseline and Demonstration periods included:
 - EDR
 - PIREPs
 - GTG (Analysis/Forecast)
 - Convective Weather Diagnostic Data
 - Aircraft Data (equipment, altitude, etc.)
 - Flight Track Data (actual vs. planned)



Modeling Airspace Utility Benefits

Using Dynamic Airspace Routing Tool (DART)

- Dynamic Airspace Routing Tool (DART) – a weather-aware “superfast-time” NAS simulation model – has ability to:
 - Generate most-economical reroutes using weather diagnostic/forecast blend (including EDR/GTG)
 - Combine reroutes and/or ground delays (and cancellations where needed)
 - Apply user-specified cost parameters for benefits analysis, reroute strategies, and risk tolerance factors
 - Apply actual and simulated Traffic Management Initiatives (TMI) within the modeling environment



Completed NAS simulations for a 6-month period:


- January - June 2014
- ~1,400 simulations
- Separated results by region
- Categorized days by varying coverage of turbulence

- Vertical deviations modeled to account for altitude changes in vicinity of Clear Air Turbulence
 - **Sector MAP values driving factor** in evaluating airspace availability in NAS simulation given turbulence encounters / actions
 - MAP values (i.e., capacity) decreased as result of weather
 - Objective findings applied to ½ impacted sectors
 - In this manner, airspace capacity is a factor contributing to delays

Objective Data Analysis Findings

- Definitions for flights established and re-established at cruise (above FL280) to better isolate altitude changes as a result of experienced turbulence
- Differences between Baseline, Demonstration, and Demo-with-viewer indicated:
 - Flights with viewer tended to not change altitude as much as those without viewer
 - Flights with viewer changed altitude less frequently when encountering higher EDR turbulence values

EDR Equipped Flights Encountering Turbulence



~6% decrease in altitude changes when encountering EDR>0 for all flights reporting EDR

- Potential benefits exist where flights remain on altitude by comparing overall percentages of EDR reporting flights
- Comparing overall %'s of altitude changes when reporting a non-0 turbulence:
 - ~45% Baseline
 - ~43% EDR Demonstration
 - ~39% with viewer



FAA



Results Summary

Baseline/Demo vs. Viewer Equipped

- Primary operational impact identified as a result of EDR/GTG information in cockpit is a reduction in altitude changes prior to or during a turbulence encounter

Sample High-level **Objective** Findings

Comparing overall percentages:

- ~6% **decrease in altitude changes** when encountering EDR >0 for all flights reporting EDR

Higher tolerance for higher EDR ranges

- Reduction in altitude changes in the higher EDR range
 - e.g., 14% increase in flights remaining at altitude for higher EDR ranges (≥ 0.1)



Benefits

1) Reduction in fuel burn / emissions

- Frequency of altitude change

2) Reduction in ATC workload

- Communications
- Sector changes
- Flight amendments
- Requests for ride reports

3) Capacity utilization efficiency

- Reduction in ATM actions
- Reduction in NAS Delay

- **Subjective** response data collected throughout demonstration period via viewer questionnaire
- 77 Line Check Airmen (815 reports) on subset of Delta fleet using tablet device reported:
 - 79% reported decisions were influenced by “viewer”
 - 64% reported that the “viewer” was primary driver for altitude change decision
 - 53% reported radio calls were reduced as a result of using viewer



FAA

Next**GEN**

Simulating and Measuring Effects of Capacity Degradation

- DART computes arrival delay (sum of multiple components) per flight:

- 1) **Ground Delays:**

- Departure delay due to departure airport capacity constraints with/without weather
 - Departure delays due to TMIs
 - Departure delay due to airspace capacity constraints (simulator will not send an aircraft into an overloaded sector)

- 2) **Airborne Delays:**

- Airborne delay due to airborne reroutes
 - Arrival delay due to sequencing and spacing on approach to destination airport

- Two key metrics were used to evaluate benefits of turbulence information in cockpit:

- + **Total Arrival Delay**

- Ground Delays + Airborne Delays
 - Sums ASQP flights only
 - DART output is daily average Total Arrival Delay per day


- + **Daily Airspace Capacity Delay Savings**

- Component of Total Arrival Delay
 - Average difference between the “Departure delay due to airspace capacity constraints with/without weather” for baseline runs and simulated benefits

Turbulence Capacity Utilization Benefits Results

Capacity-Related Benefits

- Metrics for baseline period compared to increased sector usage
 - Simulations identified previously underutilized sectors in increments identified in study (i.e., baseline sectors identified as impacted and thus 'avoided' by flights)
 - DART simulated results for Low, High, and All turbulence coverage days



- Simulation results indicate a modest increase in both metrics when additional % of sectors are utilized
- Results increase to ~118 hours of capacity delay savings per day due to increased sector usage
- Following factors applied to estimated cost savings:

Economic Impact Category
Direct Operating Cost, On-Ground, At-Gate
Direct Operating Cost, airborne
Passenger Value of Time

Cost Associated with Air Traffic Impact

(from: FAA, 2014: Economic Information for Investment Analysis, Prepared for Operations Research / ATO-F)

Average Daily Simulated Savings	6% Sector Usage Increase	25% Sector Usage Increase	50% Sector Usage Increase
TOTAL Daily Cost Savings Estimate	\$190,000	\$600,000	\$1.1 M
TOTAL Annual Cost Savings Estimate	\$69 M	\$219 M	\$414 M

Estimating ATC Workload Benefits

Associated with Improved Turbulence Awareness in Cockpit

AOC, ATC,
ATM
Productivity
Benefits

Benefits per Center per Day
(min/max minutes)

Center	Simulated Benefits Based on Objective Data
ZMA	8 / 15
ZAU	8 / 14
ZLA	7 / 13
ZFW	7 / 12
ZHU	6 / 12
ZSE	5 / 8
ZJX	4 / 8
ZOA	4 / 8
ZTL	4 / 7
ZDV	4 / 7
ZAB	4 / 6
ZID	4 / 6
ZNY	4 / 6
ZDC	3 / 6
ZOB	3 / 5
ZKC	2 / 4
ZME	2 / 4
ZMP	2 / 4
ZBW	2 / 3
ZLC	1 / 2

- Simulated reductions from baseline in altitude changes per Center applied to ATC workload times per:
 - TRB published report on Air Traffic Controller Staffing in the En Route Domain
- Task times associated with a flight transitioning from one altitude to another are approximately 14.6 seconds
 - Used as 'minimum' ATC task time
- When a traffic separation situation occurs, the task time increases to approximately 27.6 seconds
 - Used as conservative 'maximum' ATC task time - could be cumulative with minimum time



WTIC EDR Uplink Demonstration

Conclusions

- Objective analysis identified positive behavior as a result of turbulence information in cockpit
- Objective analysis results were applied in simulation environment to translate reductions in altitude changes to fuel burn/emissions, ATC workload, and capacity savings
- Simulation environment evaluated benefits as result of additional reductions in changes in altitude
- Conclusions
 - + Number of flights changing altitude for low turbulence significantly reduced
 - + Reduction in flights changing altitude results in reduced controller workload
 - + Sector capacities were maintained
 - + Arrival delays were reduced
- Additional benefits from turbulence information in cockpit could further reduce unnecessary changes in altitude through:
 - + Pilot and turbulence impact training
 - + Recognition of product benefits and risks
 - + Aircraft specific EDR thresholds
 - + Aircraft cabin management as related to specific EDR thresholds

Questions ?



FAA

Next**GEN**